STIEBEL ELTRON

Specialist information
01 | 2026

Inform comprehensively
Install uncomplicated

Overview of products 2026



EN

Explanation of symbols


Group supply


Individual supply


Central supply


Floorstanding installation


Oversink installation


Undersink installation


Indoor installation


Outdoor installation


Portable


Fully wired


Permanent connection


Pressurised / unvented


Non-pressurised / vented


Boiling water (approx. 100 °C)


High temperature (approx. 85 °C)


Average temperature (approx. 60 °C)


Low temperature (approx. 50 °C)


High flow rate


Average flow rate


Low flow rate


Radiator


Underfloor heating


Heat source – air


Heat source – ground


Heat source – water


DHW cylinder integrated


Buffer cylinder integrated


Instantaneous water cylinder integrated


Ventilation heating


Central ventilation


Decentralised ventilation


Heat recovery


Moisture recovery


Dehumidify


Heating


Cooling


Heating circuit, thermostatic mixing


Heating circuit, electronic mixing


Electric reheating


Domestic hot water

Manual filling

Automatic filling

IR radiant heat

Convection

Fan

Integrated control unit

Self-limiting

UV-resistant

Mastic asphalt

Infloor installation

Quiet

Short drying time

Normal drying time

2i technology

3i technology

4i technology

Anti-drip

Thermostop

Profi-Rapid

Profi-Direct

High efficiency

Extremely quiet

C-PLUS technology

● | ■ New | Discontinued

Prices

With the publication of this printed version, all previous versions become invalid. This version is only intended for use by wholesalers, specialist trade shops and qualified contractors. Duplication and/or transmission is therefore not permitted.
This printed version is not intended for consumers. Deliveries are made in accordance with our general terms of delivery and payment. The binding basis for the use and installation of the appliances are the printed documents included with the appliances, as well as the relevant regulations.
The latest technical values can be found on our homepage at www.stiebel-eltron.com

Complete table of contents

Table of contents

› Alphabetic directory
› Product range directory
› Successor directory

Domestic hot water

› Comfort instantaneous water heater 6
› Remote controls for comfort instantaneous water heaters 24
› Compact instantaneous water heaters, 3-phase 28
› Compact instantaneous water heaters, 1-phase 38
› Mini instantaneous water heaters 46
› Accessories for instantaneous water heaters 52
› Small water heaters, non-pressurised 56
› Small water heaters, pressurised 62
› Accessories for small water heaters, pressurised 72
› Wall mounted cylinder 78
› Accessories for wall mounted cylinders 92
› Floor mounted cylinder 96
› Accessories for floor mounted cylinders, pressurised 106
› Compact DHW heat pumps 116
› DHW heat pump accessories 128
› Water filter 134

Heat pumps

› Air source heat pumps, outdoor installation – inverter 152
› Air source heat pumps, outdoor installation – Fixspeed 216
› Accessories for air source heat pumps installed outdoors 232
› Air source heat pumps, indoor installation – inverter 254
› Accessories for air source heat pumps installed indoors 268
› Ground source heat pumps – inverter 278
› Ground source heat pumps – Fixspeed 308
› Accessories for ground source heat pumps 320
› Control units 332
› Hydraulic modules 340
› Accessories for hydraulic modules 342
› Integral cylinder 344
› Accessories for integral cylinders 352
› DHW cylinder 356
› Accessories for DHW cylinders 360
› Instantaneous water cylinder 362
› Accessories for instantaneous water cylinders 366
› Buffer cylinder 368
› Accessories for buffer cylinders 376
› Additional accessories 382
› Heat pump accessories 386

Ventilation

› Central ventilation units 404
› Accessories, central ventilation units 426
› Distribution system for integral and central ventilation 448
› Decentralised ventilation in residential buildings 474
› Accessories for decentralised ventilation in residential buildings 482
› Decentralised ventilation in non-residential buildings 488
› Accessories for decentralised ventilation in non-residential buildings 522

Room heating

› Storage heaters 532
› Accessories for storage heaters 534
› Convectors 538
› Rapid heater 546
› Infrared wall mounted radiant heater 550

Hand dryer

› Hand dryer, high speed 554

Service

› Engineering 560

Complete table of contents

Tables of contents	
Instantaneous water heater	1
DHW cylinder	53
DHW heat pumps	111
Water pumps and filters	131
Air source heat pumps	147
Ground source and water source heat pumps	273
Accessories for heat pumps and cylinders	329
Central ventilation	401
Decentralised ventilation	471
Storage heaters	529
Direct heating	535
Hand dryer	551
Service	557

	Type	Order no.	Page
	A		
	AF PT	235997	326, 336
●	AGC-CB.1	207733	234
●	AGC-CW.1	207734	235
●	AHP-BH 8.8	207902	353
●	AHP-BS.1	207894	232
●	AHP-CB.1	207735	233
●	AHP-CM 2	208660	247
●	AHP-CM 3	208040	247
●	AHP-CM 4	208009	247
●	AHP-CM 5	208010	247
●	AHP-CM 6	208011	247
●	AHP-CS.1	207723	248
●	AHP-CW.1	207736	233
●	AHP-DS 0.8	207738	238
●	AHP-DT.1	207731	232
●	AHP-FH 25-0.4	207724	239
●	AHP-FW 25-0.4	208863	239
●	AHP-GC.1	207732	234
	AHP-PH	207742	327
●	AHP-PS.1	208668	389
●	AHP-PS.2	208669	389
●	AHP-PS.3	208670	389
●	AHP-SB.1	207711	241
●	AHP-SC.1	207737	237
●	AHP-SW.1	207712	241
●	AHP-TB 420	207727	240
●	AHP-TB 710	207728	240
	AHP-TC	207744	327
●	AHP-TW 420	207730	240
●	AHP-TW 710	207710	240
●	AHP-WB.1	207713	242
●	AHP-WB.2	208679	242
●	AHP-WB.3	208680	242
●	AHP-WM.1	207891	235
●	AHP-WO.1	207715	243
●	AHP-WU.1	207716	243
●	AHP-WU.2	207717	244
●	AHP-WW.1	208658	242
●	AHP-WW.2	208681	242
●	AHP-WW.3	208682	242
●	AHS-SI 200	207721	246
	AS-HM Trend	233750	342
	AS-WP 1	233622	248
	AS-WP 2	233623	248
	ASL-HM	232806	342
	AVF 6	165341	336
	AWG 160 R	234505	128
	AWG 560 H-GL	232956	268
	AWG 560 H-SR	233837	268
	AWG 80	207743	326
●	AWM-CB.1	207892	236
●	AWM-CW.1	207893	237
●	AWU-HS 10	207720	245
●	AWU-HS 2.5	207718	245
●	AWU-HS 5	207719	245
	Activated carbon block 13“ (EX)	230877	135
	B		
	B21	076102	107
	B28	076103	107
	BBI 5-I	205877	376
	BF 80	205090	378
	BF 80 Set	231884	378
	BGC 2/60	232030	107, 382
	BGC 6 kW 500 mm ET	003769	107, 382
	BGC/45	075115	107, 382
	BS LSWP 160-4 AL	234108	130
	C		
	CDT 180	204642	352
	CK 20 Premium	237835	546
	CK 20 Trend LCD	236653	547
	CNS 100 Trend M	203640	541
	CNS 200 Trend M	203642	541
	CNS 2000 Plus LCD Move	207060	542
	CNS 50 Trend M	203638	541
	CNS-B 2000 Plus LCD Move	207068	542
	CON 10 Premium	237831	538
	CON 15 Premium	237832	538
	CON 20 Premium	237833	538
	CON 30 Premium	237834	538
	CON 5 Premium	237830	538
	CWM 1000 M-F	204453	543
	CWM 1000 P	200256	539
■	CWM 1500 M-F	204454	543
	CWM 1500 P	200257	539
	CWM 2000 M-F	204455	543
	CWM 2000 P	200258	539
■	CWM 2500 M-F	204456	543
	CWM 2500 P	200259	539
	CWM 3000 M-F	204457	543
	CWM 3000 P	200260	539
	CWM 500 P	200254	539
■	CWM 750 M-F	204452	543
	CWM 750 P	200255	539
	D		
	DCE 11/13	230770	30
	DCE 11/13 H	232792	32
	DCE 11/13 H + MEKD	205967	34
	DCE 11/13 RC	230771	28
	DCE-C 10/12 Trend	238149	42
	DCE-C 6/8 Trend	238148	42
	DCE-S 10/12 Plus	238154	40
	DCE-S 6/8 Plus	238153	40
	DCE-X 10/12 Premium	238159	38
	DCE-X 6/8 Premium	238158	38
	DEL 18/21/24 Plus	236739	10
	DEL 27 Plus	236740	10
	DHB-E 11/13 LCD	236743	14
	DHB-E 18 LCD 25A	236744	14
	DHB-E 18/21/24 LCD	236745	14
	DHB-E 27 LCD	236746	14
	DHE 18/21/24	202656	6
	DHE 27	202657	6
	DMV/ZH 1	074371	108
	DWS1	221382	321
	E		
	EIL 3 Plus	200138	48
	EIL 3 Premium	200134	46

Type	Order no.	Page
EIL 3 Trend	200142	50
EIL 4 Plus	200139	48
EIL 4 Premium	200135	46
EIL 6 Plus	200140	48
EIL 6 Premium	200136	46
EIL 7 Plus	200141	48
EIL 7 Premium	200137	46
EM 33-87	201715	323
EMW	202062	324
ESH 10 O-N Trend	201393	58
ESH 10 O-N Trend +A	201395	59
ESH 10 O-P Plus	201398	68
ESH 10 U-N Trend	201391	56
ESH 10 U-N Trend +A	201392	57
ESH 10 U-P Plus	201397	66
ESH 5 O-N Trend	201388	58
ESH 5 O-N Trend+A	201389	59
ESH 5 U-N Trend	201386	56
ESH 5 U-N Trend +A	201387	57
ET SBP	003711	377
F		
FCR 21/120 E	071331	106, 382
FCR 21/60	071330	106, 382
FCR 28/120	071332	106, 382
FCR 28/120 CrNi	234503	106, 383
FCR 28/120 E	000694	106, 382
FCR 28/180	071333	106, 383
FCR 28/180 E	000695	106, 383
FEB 2.0	205018	428
FEB 2.1	206612	428
FEG	201767	325
FET	234723	335
FEZ	185358	429
FFB 4 EU	234478	24
FFB 4 Set EU	238930	24
FMK EPA 12-2 W450/600	206597	436
FMK EPM1 55-2 W450/600	206596	435
FMK F7-10 ZUL dez. 300	206209	527
FMK F7-10 ZUL dez. 800/870	206205	527
FMK F7-2 130/135	238925	432
FMK F7-2 180	234208	433
FMK F7-2 70	227660	434
FMK F7-2 ZUL dez. 300	206208	527
FMK F7-2 ZUL dez. 800/870	206204	527
FMK M5-10 ABL dez. 300	206207	527
FMK M5-10 ABL dez. 800/870	206203	527
FMK M5-2 130/135	238924	431
FMK M5-2 180	234148	433
FMK M5-2 ABL dez. 300	206206	527
FMK M5-2 ABL dez. 800/870	206202	527
FMS EPMC 65-10 W450/600	206610	435
FMS G3-10 70	222446	434
FMS G3-5 LA 60	201455	479
FMS G4-10 130/135	238923	431
FMS G4-10 180	234147	432
FS-WP 22	233511	388
FS-WP 28	233512	388
FSHP-L45	202779	398

Type	Order no.	Page
H		
HDB-E 11/13 Trend	204208	20
HDB-E 18/21/24 Trend	204209	20
● HDB-E 27 Trend	204210	20
HG Set 33-87	201716	324
HM Trend	232805	340
HMS Trend	233826	340
HPA-O 05.1 CS Premium	202666	189, 192
● HPA-O 05.2 Plus HC 230	207429	152, 158
● HPA-O 05.2 Plus HC 230 + HM Trend	208407	174
● HPA-O 05.2 Plus HC 230 + HMS Trend	208728	175
● HPA-O 05.2 Plus HC 230 + HSBC 200	208560	166
● HPA-O 05.2 Plus HC 230 + HSBC 200 S	208718	168, 169
● HPA-O 05.2 Plus HC 230 + HSBC 300	208564	171, 172
● HPA-O 05.2 W Plus HC 230	208431	159, 165
● HPA-O 05.2 W Plus HC 230 + HM Trend	208414	174, 175
● HPA-O 05.2 W Plus HC 230 + HMS Trend	208731	176
● HPA-O 05.2 W Plus HC 230 + HSBC 200	208576	167, 168
● HPA-O 05.2 W Plus HC 230 + HSBC 200 S	208721	170
● HPA-O 05.2 W Plus HC 230 + HSBC 300	208396	172, 173
HPA-O 07.1 CS Premium	202668	189, 192
● HPA-O 07.2 Plus HC 230	207430	152, 158
● HPA-O 07.2 Plus HC 230 + HM Trend	208218	174
● HPA-O 07.2 Plus HC 230 + HMS Trend	208729	175
● HPA-O 07.2 Plus HC 230 + HSBC 200	207962	166
● HPA-O 07.2 Plus HC 230 + HSBC 200 S	208719	168, 169
● HPA-O 07.2 Plus HC 230 + HSBC 300	207966	171, 172
● HPA-O 07.2 Trend HC 230	207420	177, 183
● HPA-O 07.2 Trend HC 230 + HM Trend	208405	187
● HPA-O 07.2 Trend HC 230 + HMS Trend	208725	188
● HPA-O 07.2 Trend HC 230 + HSBC 200	208558	184
● HPA-O 07.2 Trend HC 230 + HSBC 200 S	208736	185
● HPA-O 07.2 Trend HC 230 + HSBC 300	208562	186
● HPA-O 07.2 W Plus HC 230	208432	159, 165
● HPA-O 07.2 W Plus HC 230 + HM Trend	208415	174, 175
● HPA-O 07.2 W Plus HC 230 + HMS Trend	208732	176
● HPA-O 07.2 W Plus HC 230 + HSBC 200	208392	167, 168
● HPA-O 07.2 W Plus HC 230 + HSBC 200 S	208722	170
● HPA-O 07.2 W Plus HC 230 + HSBC 300	208397	172, 173
HPA-O 10 C Premium	238979	199, 202
HPA-O 10 Premium	238978	195, 197
● HPA-O 10.2 Plus HC 230	207432	152, 158
● HPA-O 10.2 Plus HC 230 + HM Trend	208408	174
● HPA-O 10.2 Plus HC 230 + HMS Trend	208730	175
● HPA-O 10.2 Plus HC 230 + HSBC 200	208561	166
● HPA-O 10.2 Plus HC 230 + HSBC 200 S	208720	168, 169
● HPA-O 10.2 Plus HC 230 + HSBC 300	208565	171, 172
● HPA-O 10.2 Plus HC 400	207433	152, 158
● HPA-O 10.2 Plus HC 400 + HM Trend	208219	174
● HPA-O 10.2 Plus HC 400 + HSBC 200	207961	166
● HPA-O 10.2 Plus HC 400 + HSBC 300	207967	171, 172
● HPA-O 10.2 Trend HC 230	207422	177, 183
● HPA-O 10.2 Trend HC 230 + HM Trend	208221	187
● HPA-O 10.2 Trend HC 230 + HMS Trend	208726	188
● HPA-O 10.2 Trend HC 230 + HSBC 200	207959	184
● HPA-O 10.2 Trend HC 230 + HSBC 200 S	208716	185
● HPA-O 10.2 Trend HC 230 + HSBC 300	207964	186
● HPA-O 10.2 W Plus HC 230	208433	159, 165
● HPA-O 10.2 W Plus HC 230 + HM Trend	208416	174, 175

	Type	Order no.	Page
●	HPA-O 10.2 W Plus HC 230 + HMS Trend	208733	176
●	HPA-O 10.2 W Plus HC 230 + HSBC 200	208393	167, 168
●	HPA-O 10.2 W Plus HC 230 + HSBC 200 S	208723	170
●	HPA-O 10.2 W Plus HC 230 + HSBC 300	208398	172, 173
●	HPA-O 10.2 W Plus HC 400	208434	159, 165
●	HPA-O 10.2 W Plus HC 400 + HM Trend	208417	174, 175
●	HPA-O 10.2 W Plus HC 400 + HSBC 200	208394	167, 168
●	HPA-O 10.2 W Plus HC 400 + HSBC 300	208399	172, 173
	HPA-O 13 C Premium	238983	199, 202
	HPA-O 13 CS Premium	238981	199, 202
	HPA-O 13 Premium	238982	195, 197
	HPA-O 13 S Premium	238980	195, 197
●	HPA-O 13.2 Plus HC 400	207435	152, 158
●	HPA-O 13.2 Plus HC 400 + HM Trend	208220	174
●	HPA-O 13.2 Plus HC 400 + HSBC 200	207963	166
●	HPA-O 13.2 Plus HC 400 + HSBC 300	207968	171, 172
●	HPA-O 13.2 Trend HC 230	207424	177, 183
●	HPA-O 13.2 Trend HC 230 + HM Trend	208406	187
●	HPA-O 13.2 Trend HC 230 + HMS Trend	208727	188
●	HPA-O 13.2 Trend HC 230 + HSBC 200	208559	184
●	HPA-O 13.2 Trend HC 230 + HSBC 200 S	208717	185
●	HPA-O 13.2 Trend HC 230 + HSBC 300	208563	186
●	HPA-O 13.2 Trend HC 400	207425	177, 183
●	HPA-O 13.2 Trend HC 400 + HM Trend	208222	187
●	HPA-O 13.2 Trend HC 400 + HSBC 200	207960	184
●	HPA-O 13.2 Trend HC 400 + HSBC 300	207965	186
●	HPA-O 13.2 W Plus HC 400	208435	159, 165
●	HPA-O 13.2 W Plus HC 400 + HM Trend	208418	174, 175
●	HPA-O 13.2 W Plus HC 400 + HSBC 200	208395	167, 168
●	HPA-O 13.2 W Plus HC 400 + HSBC 300	208400	172, 173
●	HPA-O 17.2 Trend HC 400	207426	177, 183
	HPA-O 3 CS Plus compact D Set 1.1	204282	210
	HPA-O 4 CS Plus		205, 207
	HPA-O 4 CS Plus flex Set	239052	208
	HPA-O 4 CS Plus flex Set S	238989	208
	HPA-O 6 CS Plus		205, 207
	HPA-O 6 CS Plus compact D Set 1.1	204275	210
	HPA-O 6 CS Plus compact D Set S 1.1	204279	210
	HPA-O 6 CS Plus compact Set 1.1	204269	209
	HPA-O 6 CS Plus compact Set S 1.1	204272	209
	HPA-O 6 CS Plus flex Set	239053	208
	HPA-O 6 CS Plus flex Set S	238990	208
	HPA-O 8 CS Plus		205, 207
	HPA-O 8 CS Plus compact D Set 1.1	204276	210
	HPA-O 8 CS Plus compact D Set S 1.1	204280	210
	HPA-O 8 CS Plus compact Set 1.1	204270	209
	HPA-O 8 CS Plus compact Set S 1.1	204273	209
	HPA-O 8 CS Plus flex Set	239054	208
	HPA-O 8 CS Plus flex Set S	238991	208
	HPG-I 04 CS Premium	202627	293, 296
	HPG-I 04 DCS Premium	202632	282, 285
	HPG-I 04 DS Premium	202622	278, 281
	HPG-I 04 S Premium	202617	297, 300
	HPG-I 06 CS Premium	202628	293, 296
	HPG-I 06 DCS Premium	202633	282, 285
	HPG-I 06 DS Premium	202623	278, 281
	HPG-I 06 S Premium	202618	297, 300
	HPG-I 08 CS Premium	202629	293, 296
	HPG-I 08 DCS Premium	202634	282, 285

Type	Order no.	Page
HPG-I 08 DS Premium	202624	278, 281
HPG-I 08 S Premium	202619	297, 300
HPG-I 12 CS Premium	202630	293, 296
HPG-I 12 DCS Premium	202635	282, 285
HPG-I 12 DS Premium	202625	278, 281
HPG-I 12 S Premium	202620	297, 300
HPG-I 15 CS Premium	202631	293, 296
HPG-I 15 DCS Premium	202636	282, 285
HPG-I 15 DS Premium	202626	278, 281
HPG-I 15 S Premium	202621	297, 300
HSBB 180 Plus	202926	349
HSBB 180 S Plus	203084	349
HSBC 180 Plus	202927	348
HSBC 180 S Plus	203082	348
HSBC 200	233510	346
HSBC 200 L	236684	347
HSBC 200 S	234801	346
HSBC 3-HKM	238825	352
HSBC 300 L cool	238826	345
HSBC 300 cool	203801	344
HSBC-HKM	234648	352
● HUV 1.1	208004	393
● HUV 2.1	208320	393
HUV 65	227425	393
HUV 80	227426	393
HZB-1	232978	251
HZB-2	232979	251
HZEA	230013	394
HZEN	230031	395
I		
● ISG Connect	206780	334
ISG web	229336	334
IW 120	229339	550
K		
KWG 125	239139	469
L		
LA 100 A	205771	476
LA 100 G-A	205906	478
LA 100 G-U	205878	477
LA 100 G-UB	206247	477
LA 100 U	205772	476
LA 100 UB	205773	476
LA 100 VE	205907	478
LLB AWG 315 L	232341	269
LLB AWG 560 L	232342	269
LR 1-A	001786	52
LSK 70 E	227046	427
LSWP 160-4 AL	234022	129
LSWP 315-2 SG Set	238565	270
LSWP 560-3 SG	201721	270
LSWP 560-4 S	234647	270
LTM TL HUMIDITY	237126	482
LTM dezent 300 BA VA 320 B	237627	523
LTM dezent 300 BA VA 320 W	237628	523
LTM dezent 300 ULB-90	237626	522
LTM dezent 300 Z-PSS	237671	522
LTM dezent 600/800 Z-PSS	237672	522
LTM dezent APD BT	237644	483
LTM dezent BA VA 410 B	237629	523

Type	Order no.	Page
LTM dezent BA VA 410 W	237633	523
LTM dezent BACnet Web - Ethernet	237646	526
LTM dezent C-PSS	237673	522
LTM dezent CO2	237649	525
LTM dezent FMS F9-1	237668	527
LTM dezent Modbus RS 485 IF	237648	526
LTM dezent RWA	237674	522
LTM dezent ULB-90	237634	522
LTM dezent VOC	237658	524
LUS 221/301	236899	129
LVE A	205366	452
LVE BF 45	231121	448
LVE BF 90	231122	448
LVE BH 90-D	206252	449
LVE KF	231113	453
LVE M	231112	451
LVE RA	231117	451
LVE RP 20	231111	448
LVE TB 75	207077	450
LVE WDA 125	205364	453
LVE YS	239126	452
LVE Ü 180	231120	449
LVE Ü 90	233032	450
LVE ÜB-O	235913	451
LVE ÜB-U	235912	451
LVE-LVS WDA 125	205368	454
LVS A 2-75	205365	458
LVS AS 75	223318	461
LVS DA 75-125-2	236423	460
LVS M 75	224897	459
LVS RP 75-50	235059	455
LVS RP 90-25	223320	455
LVS RS 75	207074	455
LVS VT 14	205558	456
LVS VTS 6	201456	456
LVS VTS 9	234493	456
LVS WDA 125-2-75	205367	458
LVS-MSV-SB	232117	460
LVS-MSV-SBA	232118	461
LWF AVM 125	227924	468
LWF DR 125-1 EPP	239231	464
LWF DR 160-1 EPP	239232	464
LWF DRB 125-45 EPP	239234	465
LWF DRB 125-90 EPP	239233	465
LWF DRB 160-45 EPP	239236	465
LWF DRB 160-90 EPP	239235	465
LWF DRM 125 EPP	239237	465
LWF DRM 160 EPP	239238	465
LWF F 125 - 5	159334	464
LWF F 160 - 5	159332	464
LWF KB 10	227948	468
LWF LB 10m	159348	467
LWF M 125	159299	462
LWF N 160	159320	463
LWF RS 160 M - 125 N	207509	463
LWF S 160 - 0,9	159346	466
LWF SE 125	207073	467
LWF SK 315 - 0,6	202933	466
LWF T 160 - 160	159323	462

Type	Order no.	Page
LWF W 100 VA - 60	231104	479
LWF ZVM 125	230163	469
LWTF 180/280	236420	426
LWTF W450/600	359304	426
LWZ 130	237805	420, 421
LWZ 130 Enthalpie	237806	422, 423
LWZ 180	232361	412
LWZ 180 Enthalpie	236646	415
LWZ 280	232362	412
LWZ 280 Enthalpie	236647	415
LWZ 70 E	233851	417, 419
M		
MAG 12	235218	322
MAG 18	235219	322
MAG 25	235220	322
MAG 50	235221	322
MEG 30	161696	322
MFS-WP 28	235234	388
P		
PEB 11	202693	18
PEB 18/21/24	206210	18
PEO 18/21/24	233991	12
PER 18/21/24	233990	8
PEY 18/21/24	233993	16
PK 10	229286	271
PSH 100 Classic	235962	85
PSH 100 Trend	232083	83
PSH 100 Universal EL	231153	82
PSH 120 Classic	235963	85
PSH 120 Trend	232084	83
PSH 120 Universal EL	231649	82
PSH 120 WE-H	236239	90
PSH 120 WE-L	236232	88
PSH 120 WE-R	236233	88
PSH 150 Classic	235964	85
PSH 150 Trend	232085	83
PSH 150 Universal EL	231154	82
PSH 150 WE-H	236240	90
PSH 150 WE-L	236234	88
PSH 150 WE-R	236235	88
PSH 200 Classic	235965	85
PSH 200 Trend	232086	83
PSH 200 WE-H	236241	90
PSH 200 WE-L	236236	88
PSH 200 WE-R	236237	88
PSH 30 Trend	232080	83
PSH 30 Universal EL	231150	82
PSH 50 Classic	235960	85
PSH 50 Trend	232081	83
PSH 50 Universal EL	231151	82
PSH 80 Classic	235961	85
PSH 80 Trend	232082	83
PSH 80 Universal EL	231152	82
PSH 80 WE-H	236238	90
PSH 80 WE-L	236230	88
PSH 80 WE-R	236231	88
Planning of ventilation technology, 3D	240592	560
R		
RTA-S2	231061	534

Alphabetic directory

Type	Order no.	Page
S		
SAP-O DN 560	003478	269
SB 1002 AC	071282	103
SB 302 S	185354	102
SB 402 S	185355	102
SB 602 AC	071554	103
SBB 1000 WP SOL	235908	357
SBB 301 WP	221360	356
SBB 302 WP	221361	356
SBB 401 WP SOL	221362	356
SBB 501 WP SOL	227534	356
SBB 600 WP SOL	235906	357
SBB 800 WP SOL	235907	357
SBP 100 classic	235200	368
SBP 1000 E	227564	372
SBP 1000 E SOL	227566	372
SBP 1000 E cool	227588	373
SBP 1010 E	236569	372
SBP 1010 E cool	236570	373
SBP 1500 E	227565	372
SBP 1500 E SOL	227567	372
SBP 1500 E cool	227589	373
SBP 200 Plus cool	205295	368
SBP 400 Plus cool	205296	368
SBP 700 E	185459	370
SBP 700 E SOL	185460	370
SBS 1001 W	229982	362
SBS 1001 W SOL	229986	362
SBS 1501 W	229983	362
SBS 1501 W SOL	229987	362
SBS 601 W	229980	362
SBS 601 W SOL	229984	362
SBS 801 W	229981	362
SBS 801 W SOL	229985	362
SD 25-1 E	232965	396
SD 25-1 G	232976	395
SD 25-1 KE	232974	397
SD 25-2 GE	233828	395
SD 25-2.5 GE	232971	395
SD 32-0.6 G	201710	395
SD 32-1 E	232968	396
SD 32-1 G	232977	396
SD 32-1 KE	232975	397
SD 32-2 GE	233831	396
SD 40-0.8 G	201711	396
SD 50-1 E	232972	396
SD DN25-1 E	074415	396
SD DN32-1 E	074414	396
SDB 40-0.8 G	201713	323
SDB 50-0.8 G	201714	323
SH 100 S electronic	073050	80
SH 120 S electronic	073051	80
SH 150 S electronic	073052	80
SH 30 S electronic	073047	80
SH 50 S electronic	073048	80
SH 80 S electronic	073049	80
SHC 10	233747	64
SHC 15	234337	64
SHD 100 S	073060	86
SHD 30 S	073059	86
SHF 2000	200175	532
SHF 3000	200176	532
SHF 4000	200177	532
SHF 5000	200178	532
SHF 6000	200179	532
SHF 7000	200180	532
SHO AC 1000 12 kW	001415	100
SHO AC 1000 9/18 kW	003353	100
SHO AC 600 6/12 kW	003352	100
SHO AC 600 7,5 kW	001414	100
SHP-F 220 Premium	238630	116
SHP-F 300 Premium	238631	116
SHP-F 300 X Premium	238632	116
■ SHP-I 200 Plus	204474	124
■ SHP-I 300 H Plus	204478	124
■ SHP-I 300 Plus	204476	124
SHP-O 200 Plus	204472	120
● SHP-O 201 Premium	207264	122
SHP-O 300 Plus	204473	120
● SHP-O 301 Premium	207265	122
SHU 10 SLi	229473	62
SHU 5 SLi	222151	62
SHW 200 ACE	070074	98
SHW 200 S	182120	96
SHW 300 ACE	070075	98
SHW 300 S	182121	96
SHW 400 ACE	070076	98
SHW 400 S	182122	96
SHZ 100 LCD	231254	78
SHZ 120 LCD	231255	78
SHZ 150 LCD	231256	78
SHZ 30 LCD	231251	78
SHZ 50 LCD	231252	78
SHZ 80 LCD	231253	78
SILVER GAC & MINERAL BALLS 13“ (EX)	239935	137
SK 1	232964	250
SK 2	236693	250
● SNOW (EX)	206462	144
● SNOW DUAL FILTER CARTRIDGE (EX)	206463	140
● SNOW PRO (EX)	207812	145
● SNOW PRO DUAL FILTER CARTRIDGE (EX)	207813	142
● SNOW PRO RO FILTER CARTRIDGE (EX)	207814	143
● SNOW RO FILTER CARTRIDGE (EX)	206461	141
SP VLR 70 RF COARSE 30 G2-4	239562	484
SP VLR 70 RF COARSE 60 G4-4	239575	484
SP VLR 70 RF EPM1 50 F7-4	239577	484
SP VLR 70 RF EPM10 50 M5-4	239576	485
SRT 2	230764	73, 92
ST GP 1/2“	073945	73, 92
ST GP 3/4“	073946	73, 92
STB-FB	233711	399
STD 315-1 Plus	204784	356
STD 420-1 Plus	204785	356
STD 520-1 Plus	204786	356
STH 210 C Plus	205369	369
STH 415 C Plus	205370	369
STH 720 Plus	203765	371
STH 720-1 Plus	203766	371

Type	Order no.	Page
SV 1/2 6 bar	074373	109
SV 3/4 10 bar	074375	109
SV 3/4 6 bar	074374	109
SV DS 25	003713	397
SV DS 32	070692	397
SVMT	073499	72
Sediment Filter 13“ (EX)	230875	134
Stiebel House ACB cartridge (EX)	239934	139
Stiebel House PS cartridge (EX)	239933	138
T		
TAF PT 2m	235996	325, 335
TAF PT 5m	235995	325, 335
TF 6	165342	337
U		
ULTRONIC Plus	205632	555
ULTRONIC Premium	205633	554
UP 25-60-180	056899	386
UP 25/1-8 PCV	205285	389
UP 25/7.5 PCV	201620	389
UP 30/1-10 PCV	205288	389
UP 30/1-8 PCV	205286	389
UP 40/1-8 E	206633	389
UP 50/1-12 E	206636	389
UPF 30/1-8 E	232532	320
UPF 40/1-8 E	227413	320
UPF 50/1-12 E	227414	320
UPZ	233719	386
Ultrafiltration 13“ (EX)	230879	136
V		
VLR 70 L Trend EN	201458	474
VLR 70 L Trend EU	203133	474
VLR 70 S Trend EN	200002	474
VLR 70-2 CU	239570	482
VLR 70-4 CU	239571	482
VLR 70-8 CU	239572	482
VRC-W 400	203636	410
VRC-W 400 E	203637	410
VRC-W 450 E Premium	204941	407, 409
VRC-W 450 Premium	204940	404, 406
VRC-W 600 E Premium	204715	407, 409
VRC-W 600 Premium	204714	404, 406
VRL-C 300 D Premium	204142	512, 514
VRL-C 300 D Trend	204143	516, 518
VRL-C 300 G Premium	204140	504, 506
VRL-C 300 G Trend	204141	508, 510
VRL-C 870 D Premium	204134	496, 498
VRL-C 870 D Trend	204135	500, 502
VRL-C 870 G Premium	204132	488, 490
VRL-C 870 G Trend	204133	492, 494
W		
WDH 1000 SBB	235911	360
WDH 1000 SBP	231929	379
WDH 1000 cool	231921	379
WDH 1001 SBS	231927	366
WDH 1010 SBP	201662	379
WDH 1500 SBP	231930	379
WDH 1500 cool	231922	379
WDH 1501 SBS	231928	366
WDH 600 SBB	235909	360
WDH 601 SBS	231925	366
WDH 800 SBB	235910	360
WDH 801 SBS	231926	366
WDS 1000	236078	110
WDS 1002	236080	110
WDS 600	236077	110
WDS 602	236079	110
WG 160	205559	470
WG 200	205560	470
WK 1.1	238686	249
WK 2	234722	249
WK 3	208702	238
WLAN VRC .1	206611	430
WPE	234725	333
WPE-I 05 H 400 Plus	205828	310
WPE-I 05 HW 400 Plus	205834	308
WPE-I 07 H 400 Plus	205829	310
WPE-I 07 HW 400 Plus	205835	308
WPE-I 07.1 Plus H 230	207183	289, 291
WPE-I 07.1 Plus H 400	207177	289, 291
WPE-I 07.1 Plus HW 230	207185	286, 288
WPE-I 07.1 Plus HW 400	207180	286, 288
WPE-I 10 H 400 Plus	205831	310
WPE-I 10 HW 400 Plus	205836	308
WPE-I 12.1 Plus H 230	207184	289, 291
WPE-I 12.1 Plus H 400	207178	289, 291
WPE-I 12.1 Plus HW 230	207186	286, 288
WPE-I 12.1 Plus HW 400	207181	286, 288
WPE-I 13 H 400 Plus	205832	310
WPE-I 17 H 400 Plus	205833	310
WPE-I 17.1 Plus H 400	207179	289, 291
WPE-I 33 H 400 Premium	201412	301, 304
WPE-I 44 H 400 Premium	201413	301, 304
WPE-I 59 H 400 Premium	201414	301, 304
WPE-I 87 H 400 Premium	201415	301, 304
WPF 20	233003	312, 314
WPF 27	233004	312, 314
WPF 27 HT	233009	316, 318
WPF 35	233005	312, 314
WPF 40	233006	312, 314
WPF 52	233007	312, 314
WPF 66	233008	312, 314
WPHW 25	221135	394
WPKI 5-I	205875	376
WPKI 6-I	205876	377
WPKI-HK DN 25	206627	390
WPKI-HKM 230 DN 25	206631	391
WPKI-HKM 24 DN 32	206628	391
WPKI-HKM 24 DN 40	206632	391
WPKI-HKM E 24	206300	390
WPKI-HKV 2	206638	392
WPKI-HKV 3	206637	392
WPL 13 E	227756	219, 223
WPL 17 ICS classic	236376	254, 256
WPL 18 E	227757	219, 223
WPL 18 cool	223401	225, 229
WPL 19 A Set	236412	211, 213
WPL 19 I Set	235193	258, 260
WPL 19 IK Set	235878	262, 264

Type	Order no.	Page
WPL 23 E	227758	219, 223
WPL 23 cool	223402	225, 229
WPL 24 A Set	236413	211, 213
WPL 24 I Set	235194	258, 260
WPL 24 IK Set	235879	262, 264
WPL 47 Set A	228836	216, 218
WPL 57 Set A	228837	216, 218
WPM Connect International	207709	333
WPM international	236000	332
WPRB	074233	383
WPSB 308 E	222375	320
WPSF	233307	321
WRV 32	232628	360
WRV 40	232629	360
WT 30	071091	387
WT 40	229338	387
WVT-G3/8	070558	72
WWK 222	231209	118
WWK 222 H	233209	118
WWK 302	231211	118
WWK 302 H	232905	118
Z		
ZH 1	074370	108, 128
ZLA 100-H	205830	477
ZLVS O 75-10	236421	459
ZLVS O 90-10	236422	459
ZLVS VTÜ 75-90	234494	457
ZLWZ 4 S	234866	429
ZLWZ VHR 70 E	236038	427
ZSA 315	236934	268
ZVK WPL 13/18/23 A	074413	251
ZVK WPL 13/18/23 I	074412	271
ZVRL-C CU	204144	524
ZW 1 1/4	230312	366

Comfort instantaneous water heater

Full electronic control		
Type	**Order no.**	**Page**
DHE 18/21/24	202656	6
DHE 27	202657	6
PER 18/21/24	233990	8
Electronic closed-loop control		
Type	**Order no.**	**Page**
DEL 18/21/24 Plus	236739	10
DEL 27 Plus	236740	10
PEO 18/21/24	233991	12
DHB-E 11/13 LCD	236743	14
DHB-E 18 LCD 25A	236744	14
DHB-E 18/21/24 LCD	236745	14
DHB-E 27 LCD	236746	14
PEY 18/21/24	233993	16
Electronic open-loop control		
Type	**Order no.**	**Page**
PEB 11	202693	18
PEB 18/21/24	206210	18
HDB-E 11/13 Trend	204208	20
HDB-E 18/21/24 Trend	204209	20
HDB-E 27 Trend	204210	20

Remote controls for comfort instantaneous water heaters

Wireless remote controls		
Type	**Order no.**	**Page**
FFB 4 Set EU	238930	24
FFB 4 EU	234478	24

Compact instantaneous water heaters, 3-phase

Electronic closed-loop control		
Type	**Order no.**	**Page**
DCE 11/13 RC	230771	28
DCE 11/13	230770	30
DCE 11/13 H	232792	32
DCE 11/13 H + MEKD	205967	34

Compact instantaneous water heaters, 1-phase

Full electronic control		
Type	**Order no.**	**Page**
DCE-X 6/8 Premium	238158	38
DCE-X 10/12 Premium	238159	38
Electronic closed-loop control		
Type	**Order no.**	**Page**
DCE-S 6/8 Plus	238153	40
DCE-S 10/12 Plus	238154	40
Electronic open-loop control		
Type	**Order no.**	**Page**
DCE-C 6/8 Trend	238148	42
DCE-C 10/12 Trend	238149	42

Mini instantaneous water heaters

Electronic closed-loop control		
Type	**Order no.**	**Page**
EIL 3 Premium	200134	46
EIL 4 Premium	200135	46
EIL 6 Premium	200136	46
EIL 7 Premium	200137	46
Hydraulic control, pressurised		
Type	**Order no.**	**Page**
EIL 3 Plus	200138	48
EIL 4 Plus	200139	48
EIL 6 Plus	200140	48
EIL 7 Plus	200141	48
Hydraulic control, non-pressurised		
Type	**Order no.**	**Page**
EIL 3 Trend	200142	50

Accessories for instantaneous water heaters

Accessories for comfort and compact instantaneous water heaters		
Type	**Order no.**	**Page**
LR 1-A	001786	52

Small water heaters, non-pressurised

Undersink		
Type	**Order no.**	**Page**
ESH 5 U-N Trend	201386	56
ESH 10 U-N Trend	201391	56
ESH 5 U-N Trend +A	201387	57
ESH 10 U-N Trend +A	201392	57
Oversink		
Type	**Order no.**	**Page**
ESH 5 O-N Trend	201388	58
ESH 10 O-N Trend	201393	58
ESH 5 O-N Trend+A	201389	59
ESH 10 O-N Trend +A	201395	59

Small water heaters, pressurised

Undersink		
Type	**Order no.**	**Page**
SHU 5 SLi	222151	62
SHU 10 SLi	229473	62
SHC 10	233747	64
SHC 15	234337	64
ESH 10 U-P Plus	201397	66
Oversink		
Type	**Order no.**	**Page**
ESH 10 O-P Plus	201398	68

Accessories for small water heaters, pressurised

Accessories		
Type	**Order no.**	**Page**
SVMT	073499	72
WVT-G3/8	070558	72
SRT 2	230764	73
ST GP 1/2“	073945	73
ST GP 3/4“	073946	73

Wall mounted cylinder

Pressurised		
Type	**Order no.**	**Page**
SHZ 30 LCD	231251	78
SHZ 50 LCD	231252	78
SHZ 80 LCD	231253	78
SHZ 100 LCD	231254	78
SHZ 120 LCD	231255	78
SHZ 150 LCD	231256	78
SH 30 S electronic	073047	80
SH 50 S electronic	073048	80
SH 80 S electronic	073049	80
SH 100 S electronic	073050	80
SH 120 S electronic	073051	80
SH 150 S electronic	073052	80
PSH 30 Universal EL	231150	82
PSH 50 Universal EL	231151	82
PSH 80 Universal EL	231152	82
PSH 100 Universal EL	231153	82
PSH 120 Universal EL	231649	82
PSH 150 Universal EL	231154	82
PSH 30 Trend	232080	83
PSH 50 Trend	232081	83
PSH 80 Trend	232082	83
PSH 100 Trend	232083	83
PSH 120 Trend	232084	83
PSH 150 Trend	232085	83
PSH 200 Trend	232086	83
PSH 50 Classic	235960	85
PSH 80 Classic	235961	85
PSH 100 Classic	235962	85
PSH 120 Classic	235963	85
PSH 150 Classic	235964	85
PSH 200 Classic	235965	85
Instantaneous water cylinder operation		
Type	**Order no.**	**Page**
SHD 30 S	073059	86
SHD 100 S	073060	86
With tubular indirect coil		
Type	**Order no.**	**Page**
PSH 80 WE-L	236230	88
PSH 80 WE-R	236231	88
PSH 120 WE-L	236232	88
PSH 120 WE-R	236233	88
PSH 150 WE-L	236234	88
PSH 150 WE-R	236235	88
PSH 200 WE-L	236236	88
PSH 200 WE-R	236237	88
PSH 80 WE-H	236238	90
PSH 120 WE-H	236239	90
PSH 150 WE-H	236240	90
PSH 200 WE-H	236241	90

Accessories for wall mounted cylinders

Safety assemblies		
Type	**Order no.**	**Page**
SRT 2	230764	73
ST GP 1/2“	073945	73
ST GP 3/4“	073946	73

Floor mounted cylinder

Electric floor mounted cylinders, pressurised		
Type	**Order no.**	**Page**
SHW 200 S	182120	96
SHW 300 S	182121	96
SHW 400 S	182122	96
SHW 200 ACE	070074	98
SHW 300 ACE	070075	98
SHW 400 ACE	070076	98
SHO AC 600 6/12 kW	003352	100
SHO AC 600 7,5 kW	001414	100
SHO AC 1000 9/18 kW	003353	100
SHO AC 1000 12 kW	001415	100
Floor mounted combi cylinders, pressurised		
Type	**Order no.**	**Page**
SB 302 S	185354	102
SB 402 S	185355	102
SB 602 AC	071554	103
SB 1002 AC	071282	103

Accessories for floor mounted cylinders, pressurised

Electric threaded immersion heaters and flanged immersion heaters		
Type	**Order no.**	**Page**
FCR 21/60	071330	106
FCR 21/120 E	071331	106
FCR 28/120	071332	106
FCR 28/120 E	000694	106
FCR 28/120 CrNi	234503	106
FCR 28/180	071333	106
FCR 28/180 E	000695	106
BGC 6 kW 500 mm ET	003769	107
BGC/45	075115	107
BGC 2/60	232030	107
B21	076102	107
B28	076103	107
Safety assemblies		
Type	**Order no.**	**Page**
ZH 1	074370	108
DMV/ZH 1	074371	108
SV 3/4 6 bar	074374	109

SV 3/4 10 bar	074375	109
SV 1/2 6 bar	074373	109
Thermal insulation		
Type	**Order no.**	**Page**
WDS 600	236077	110
WDS 602	236079	110
WDS 1000	236078	110
WDS 1002	236080	110

Compact DHW heat pumps

Floorstanding		
Type	**Order no.**	**Page**
SHP-F 300 X Premium	238632	116
SHP-F 300 Premium	238631	116
SHP-F 220 Premium	238630	116
WWK 302	231211	118
WWK 302 H	232905	118
WWK 222 H	233209	118
WWK 222	231209	118
SHP-O 300 Plus	204473	120
SHP-O 200 Plus	204472	120
SHP-O 301 Premium	207265	122
SHP-O 201 Premium	207264	122
SHP-I 300 H Plus	204478	124
SHP-I 300 Plus	204476	124
SHP-I 200 Plus	204474	124

DHW heat pump accessories

Installation accessories		
Type	**Order no.**	**Page**
ZH 1	074370	128
AWG 160 R	234505	128
LUS 221/301	236899	129
LSWP 160-4 AL	234022	129
BS LSWP 160-4 AL	234108	130

Water filter

Filter cartridges		
Type	**Order no.**	**Page**
Sediment Filter 13“ (EX)	230875	134
Activated carbon block 13“ (EX)	230877	135
Ultrafiltration 13“ (EX)	230879	136
SILVER GAC & MINERAL BALLS 13“ (EX)	239935	137
Stiebel House PS cartridge (EX)	239933	138
Stiebel House ACB cartridge (EX)	239934	139
SNOW DUAL FILTER CARTRIDGE (EX)	206463	140
SNOW RO FILTER CARTRIDGE (EX)	206461	141
SNOW PRO DUAL FILTER CARTRIDGE (EX)	207813	142
SNOW PRO RO FILTER CARTRIDGE (EX)	207814	143
Drinking water filter		
Type	**Order no.**	**Page**
SNOW (EX)	206462	144
SNOW PRO (EX)	207812	145

Air source heat pumps, outdoor installation – inverter

Inverter		
Type	**Order no.**	**Page**
HPA-O 05.2 Plus HC 230	207429	152
HPA-O 07.2 Plus HC 230	207430	152
HPA-O 10.2 Plus HC 230	207432	152
HPA-O 10.2 Plus HC 400	207433	152
HPA-O 13.2 Plus HC 400	207435	152
HPA-O 05.2 W Plus HC 230	208431	159
HPA-O 07.2 W Plus HC 230	208432	159
HPA-O 10.2 W Plus HC 230	208433	159
HPA-O 10.2 W Plus HC 400	208434	159
HPA-O 13.2 W Plus HC 400	208435	159
HPA-O 05.2 Plus HC 230 + HSBC 200	208560	166
HPA-O 07.2 Plus HC 230 + HSBC 200	207962	166
HPA-O 10.2 Plus HC 230 + HSBC 200	208561	166
HPA-O 10.2 Plus HC 400 + HSBC 200	207961	166
HPA-O 13.2 Plus HC 400 + HSBC 200	207963	166
HPA-O 05.2 W Plus HC 230 + HSBC 200	208576	167
HPA-O 07.2 W Plus HC 230 + HSBC 200	208392	167
HPA-O 10.2 W Plus HC 230 + HSBC 200	208393	167
HPA-O 10.2 W Plus HC 400 + HSBC 200	208394	167
HPA-O 13.2 W Plus HC 400 + HSBC 200	208395	167
HPA-O 05.2 Plus HC 230 + HSBC 200 S	208718	168
HPA-O 07.2 Plus HC 230 + HSBC 200 S	208719	168
HPA-O 10.2 Plus HC 230 + HSBC 200 S	208720	168
HPA-O 10.2 W Plus HC 230 + HSBC 200 S	208723	170
HPA-O 05.2 W Plus HC 230 + HSBC 200 S	208721	170
HPA-O 07.2 W Plus HC 230 + HSBC 200 S	208722	170
HPA-O 05.2 Plus HC 230 + HSBC 300	208564	171
HPA-O 07.2 Plus HC 230 + HSBC 300	207966	171
HPA-O 10.2 Plus HC 230 + HSBC 300	208565	171
HPA-O 10.2 Plus HC 400 + HSBC 300	207967	171
HPA-O 13.2 Plus HC 400 + HSBC 300	207968	171
HPA-O 05.2 W Plus HC 230 + HSBC 300	208396	172
HPA-O 07.2 W Plus HC 230 + HSBC 300	208397	172
HPA-O 10.2 W Plus HC 230 + HSBC 300	208398	172
HPA-O 10.2 W Plus HC 400 + HSBC 300	208399	172
HPA-O 13.2 W Plus HC 400 + HSBC 300	208400	172
HPA-O 05.2 Plus HC 230 + HM Trend	208407	174
HPA-O 07.2 Plus HC 230 + HM Trend	208218	174
HPA-O 10.2 Plus HC 230 + HM Trend	208408	174
HPA-O 10.2 Plus HC 400 + HM Trend	208219	174
HPA-O 13.2 Plus HC 400 + HM Trend	208220	174
HPA-O 05.2 W Plus HC 230 + HM Trend	208414	174
HPA-O 07.2 W Plus HC 230 + HM Trend	208415	174
HPA-O 10.2 W Plus HC 230 + HM Trend	208416	174
HPA-O 10.2 W Plus HC 400 + HM Trend	208417	174
HPA-O 13.2 W Plus HC 400 + HM Trend	208418	174
HPA-O 05.2 Plus HC 230 + HMS Trend	208728	175
HPA-O 07.2 Plus HC 230 + HMS Trend	208729	175
HPA-O 10.2 Plus HC 230 + HMS Trend	208730	175
HPA-O 10.2 W Plus HC 230 + HMS Trend	208733	176
HPA-O 05.2 W Plus HC 230 + HMS Trend	208731	176
HPA-O 07.2 W Plus HC 230 + HMS Trend	208732	176
HPA-O 07.2 Trend HC 230	207420	177
HPA-O 10.2 Trend HC 230	207422	177
HPA-O 13.2 Trend HC 230	207424	177

HPA-O 13.2 Trend HC 400	207425	177
HPA-O 17.2 Trend HC 400	207426	177
HPA-O 07.2 Trend HC 230 + HSBC 200	208558	184
HPA-O 10.2 Trend HC 230 + HSBC 200	207959	184
HPA-O 13.2 Trend HC 230 + HSBC 200	208559	184
HPA-O 13.2 Trend HC 400 + HSBC 200	207960	184
HPA-O 07.2 Trend HC 230 + HSBC 200 S	208736	185
HPA-O 10.2 Trend HC 230 + HSBC 200 S	208716	185
HPA-O 13.2 Trend HC 230 + HSBC 200 S	208717	185
HPA-O 07.2 Trend HC 230 + HSBC 300	208562	186
HPA-O 10.2 Trend HC 230 + HSBC 300	207964	186
HPA-O 13.2 Trend HC 230 + HSBC 300	208563	186
HPA-O 13.2 Trend HC 400 + HSBC 300	207965	186
HPA-O 07.2 Trend HC 230 + HM Trend	208405	187
HPA-O 10.2 Trend HC 230 + HM Trend	208221	187
HPA-O 13.2 Trend HC 230 + HM Trend	208406	187
HPA-O 13.2 Trend HC 400 + HM Trend	208222	187
HPA-O 07.2 Trend HC 230 + HMS Trend	208725	188
HPA-O 10.2 Trend HC 230 + HMS Trend	208726	188
HPA-O 13.2 Trend HC 230 + HMS Trend	208727	188
HPA-O 05.1 CS Premium	202666	189
HPA-O 07.1 CS Premium	202668	189
HPA-O 10 Premium	238978	195
HPA-O 13 Premium	238982	195
HPA-O 13 S Premium	238980	195
HPA-O 10 C Premium	238979	199
HPA-O 13 CS Premium	238981	199
HPA-O 13 C Premium	238983	199
HPA-O 4 CS Plus		207
HPA-O 6 CS Plus		207
HPA-O 8 CS Plus		207
HPA-O 4 CS Plus flex Set	239052	208
HPA-O 4 CS Plus flex Set S	238989	208
HPA-O 6 CS Plus flex Set	239053	208
HPA-O 6 CS Plus flex Set S	238990	208
HPA-O 8 CS Plus flex Set	239054	208
HPA-O 8 CS Plus flex Set S	238991	208
HPA-O 6 CS Plus compact Set 1.1	204269	209
HPA-O 6 CS Plus compact Set S 1.1	204272	209
HPA-O 8 CS Plus compact Set 1.1	204270	209
HPA-O 8 CS Plus compact Set S 1.1	204273	209
HPA-O 3 CS Plus compact D Set 1.1	204282	210
HPA-O 6 CS Plus compact D Set 1.1	204275	210
HPA-O 6 CS Plus compact D Set S 1.1	204279	210
HPA-O 8 CS Plus compact D Set 1.1	204276	210
HPA-O 8 CS Plus compact D Set S 1.1	204280	210
WPL 19 A Set	236412	211
WPL 24 A Set	236413	211

Air source heat pumps, outdoor installation – Fixspeed

Fixspeed		
Type	**Order no.**	**Page**
WPL 57 Set A	228837	216
WPL 47 Set A	228836	218
WPL 13 E	227756	219
WPL 18 E	227757	219
WPL 23 E	227758	219
WPL 18 cool	223401	225
WPL 23 cool	223402	229

Accessories for air source heat pumps installed outdoors

Installation accessories		
Type	**Order no.**	**Page**
AHP-DT.1	207731	232
AHP-BS.1	207894	232
AHP-CB.1	207735	233
AHP-CW.1	207736	233
AHP-GC.1	207732	234
AGC-CB.1	207733	234
AGC-CW.1	207734	235
AHP-WM.1	207891	235
AWM-CB.1	207892	236
AWM-CW.1	207893	237
AHP-SC.1	207737	237
WK 3	208702	238
AHP-DS 0.8	207738	238
AHP-FH 25-0.4	207724	239
AHP-FW 25-0.4	208863	239
AHP-TB 420	207727	240
AHP-TB 710	207728	240
AHP-TW 420	207730	240
AHP-TW 710	207710	240
AHP-SB.1	207711	241
AHP-SW.1	207712	241
AHP-WB.1	207713	242
AHP-WB.2	208679	242
AHP-WB.3	208680	242
AHP-WW.1	208658	242
AHP-WW.2	208681	242
AHP-WW.3	208682	242
AHP-WO.1	207715	243
AHP-WU.1	207716	243
AHP-WU.2	207717	244
AWU-HS 2.5	207718	245
AWU-HS 5	207719	245
AWU-HS 10	207720	245
AHS-SI 200	207721	246
AHP-CM 2	208660	247
AHP-CM 3	208040	247
AHP-CM 4	208009	247
AHP-CM 5	208010	247
AHP-CM 6	208011	247
AHP-CS.1	207723	248
AS-WP 1	233622	248
AS-WP 2	233623	248
WK 2	234722	249
WK 1.1	238686	249
SK 1	232964	250
SK 2	236693	250
HZB-1	232978	251
HZB-2	232979	251
ZVK WPL 13/18/23 A	074413	251

Air source heat pumps, indoor installation – inverter

Inverter		
Type	**Order no.**	**Page**
WPL 17 ICS classic	236376	254
WPL 19 I Set	235193	258
WPL 24 I Set	235194	258
WPL 19 IK Set	235878	264
WPL 24 IK Set	235879	264

Accessories for air source heat pumps installed indoors

Accessories		
Type	**Order no.**	**Page**
ZSA 315	236934	268
AWG 560 H-SR	233837	268
AWG 560 H-GL	232956	268
LLB AWG 315 L	232341	269
LLB AWG 560 L	232342	269
SAP-O DN 560	003478	269
LSWP 560-3 SG	201721	270
LSWP 560-4 S	234647	270
LSWP 315-2 SG Set	238565	270
PK 10	229286	271
ZVK WPL 13/18/23 I	074412	271

Ground source heat pumps – inverter

Inverter		
Type	**Order no.**	**Page**
HPG-I 04 DS Premium	202622	278
HPG-I 06 DS Premium	202623	278
HPG-I 08 DS Premium	202624	278
HPG-I 12 DS Premium	202625	278
HPG-I 15 DS Premium	202626	278
HPG-I 04 DCS Premium	202632	282
HPG-I 06 DCS Premium	202633	282
HPG-I 08 DCS Premium	202634	282
HPG-I 12 DCS Premium	202635	282
HPG-I 15 DCS Premium	202636	282
WPE-I 07.1 Plus HW 400	207180	286
WPE-I 12.1 Plus HW 400	207181	286
WPE-I 07.1 Plus HW 230	207185	286
WPE-I 12.1 Plus HW 230	207186	286
WPE-I 07.1 Plus H 230	207183	289
WPE-I 12.1 Plus H 230	207184	289
WPE-I 07.1 Plus H 400	207177	289
WPE-I 12.1 Plus H 400	207178	289
WPE-I 17.1 Plus H 400	207179	289
HPG-I 04 CS Premium	202627	293
HPG-I 06 CS Premium	202628	293
HPG-I 08 CS Premium	202629	293
HPG-I 12 CS Premium	202630	293
HPG-I 15 CS Premium	202631	293
HPG-I 04 S Premium	202617	297
HPG-I 06 S Premium	202618	297
HPG-I 08 S Premium	202619	297
HPG-I 12 S Premium	202620	297
HPG-I 15 S Premium	202621	297
WPE-I 33 H 400 Premium	201412	304
WPE-I 44 H 400 Premium	201413	304
WPE-I 59 H 400 Premium	201414	304
WPE-I 87 H 400 Premium	201415	304

Ground source heat pumps – Fixspeed

Fixspeed		
Type	**Order no.**	**Page**
WPE-I 05 HW 400 Plus	205834	308
WPE-I 07 HW 400 Plus	205835	308
WPE-I 10 HW 400 Plus	205836	308
WPE-I 05 H 400 Plus	205828	310
WPE-I 07 H 400 Plus	205829	310
WPE-I 10 H 400 Plus	205831	310
WPE-I 13 H 400 Plus	205832	310
WPE-I 17 H 400 Plus	205833	310
WPF 20	233003	312
WPF 27	233004	312
WPF 35	233005	312
WPF 40	233006	312
WPF 52	233007	312
WPF 66	233008	312
WPF 27 HT	233009	316

Accessories for ground source heat pumps

Accessories		
Type	**Order no.**	**Page**
UPF 50/1-12 E	227414	320
UPF 30/1-8 E	232532	320
UPF 40/1-8 E	227413	320
WPSB 308 E	222375	320
WPSF	233307	321
DWS1	221382	321
MAG 12	235218	322
MAG 18	235219	322
MAG 25	235220	322
MAG 50	235221	322
MEG 30	161696	322
SDB 40-0.8 G	201713	323
SDB 50-0.8 G	201714	323
EM 33-87	201715	323
EMW	202062	324
HG Set 33-87	201716	324
FEG	201767	325
TAF PT 5m	235995	325
TAF PT 2m	235996	325
AF PT	235997	326
AWG 80	207743	326
AHP-TC	207744	327
AHP-PH	207742	327

Control units

Controller		
Type	**Order no.**	**Page**
WPM international	236000	332
WPM Connect International	207709	333
WPE	234725	333
Connectivity		
Type	**Order no.**	**Page**
ISG Connect	206780	334
ISG web	229336	334
Controller accessories		
Type	**Order no.**	**Page**
FET	234723	335
TAF PT 5m	235995	335
TAF PT 2m	235996	335
AF PT	235997	336
AVF 6	165341	336
TF 6	165342	337

Hydraulic modules

Mono mode		
Type	**Order no.**	**Page**
HM Trend	232805	340
HMS Trend	233826	340

Accessories for hydraulic modules

Accessories		
Type	**Order no.**	**Page**
ASL-HM	232806	342
AS-HM Trend	233750	342

Integral cylinder

With integral buffer cylinder		
Type	**Order no.**	**Page**
HSBC 300 cool	203801	344
HSBC 300 L cool	238826	345
HSBC 200	233510	346
HSBC 200 S	234801	346
HSBC 200 L	236684	347
HSBC 180 Plus	202927	348
HSBC 180 S Plus	203082	348
Without integral buffer cylinder		
Type	**Order no.**	**Page**
HSBB 180 Plus	202926	349
HSBB 180 S Plus	203084	349

Accessories for integral cylinders

Accessories		
Type	**Order no.**	**Page**
HSBC-HKM	234648	352
HSBC 3-HKM	238825	352
CDT 180	204642	352
AHP-BH 8.8	207902	353

DHW cylinder

DHW cylinder		
Type	**Order no.**	**Page**
SBB 301 WP	221360	356
SBB 302 WP	221361	356
SBB 401 WP SOL	221362	356
SBB 501 WP SOL	227534	356
STD 315-1 Plus	204784	356
STD 420-1 Plus	204785	356
STD 520-1 Plus	204786	356
SBB 1000 WP SOL	235908	357
SBB 600 WP SOL	235906	357
SBB 800 WP SOL	235907	357

Accessories for DHW cylinders

Accessories		
Type	**Order no.**	**Page**
WRV 32	232628	360
WRV 40	232629	360
WDH 600 SBB	235909	360
WDH 800 SBB	235910	360
WDH 1000 SBB	235911	360

Instantaneous water cylinder

Instantaneous water cylinder		
Type	**Order no.**	**Page**
SBS 601 W	229980	362
SBS 601 W SOL	229984	362
SBS 801 W	229981	362
SBS 801 W SOL	229985	362
SBS 1001 W	229982	362
SBS 1001 W SOL	229986	362
SBS 1501 W	229983	362
SBS 1501 W SOL	229987	362

Accessories for instantaneous water cylinders

Accessories		
Type	**Order no.**	**Page**
WDH 601 SBS	231925	366
WDH 801 SBS	231926	366
WDH 1001 SBS	231927	366
WDH 1501 SBS	231928	366
ZW 1 1/4	230312	366

Buffer cylinder

Buffer cylinder		
Type	**Order no.**	**Page**
SBP 100 classic	235200	368

SBP 200 Plus cool	205295	368
SBP 400 Plus cool	205296	368
STH 210 C Plus	205369	369
STH 415 C Plus	205370	369
SBP 700 E	185459	370
SBP 700 E SOL	185460	370
STH 720 Plus	203765	371
STH 720-1 Plus	203766	371
SBP 1000 E	227564	372
SBP 1000 E SOL	227566	372
SBP 1010 E	236569	372
SBP 1500 E	227565	372
SBP 1500 E SOL	227567	372
SBP 1000 E cool	227588	373
SBP 1010 E cool	236570	373
SBP 1500 E cool	227589	373

Accessories for buffer cylinders

Accessories		
Type	**Order no.**	**Page**
WPKI 5-I	205875	376
BBI 5-I	205877	376
WPKI 6-I	205876	377
ET SBP	003711	377
BF 80 Set	231884	378
BF 80	205090	378
WDH 1010 SBP	201662	379
WDH 1000 SBP	231929	379
WDH 1500 SBP	231930	379
WDH 1000 cool	231921	379
WDH 1500 cool	231922	379

Additional accessories

Electric threaded immersion heaters and flanged immersion heaters		
Type	**Order no.**	**Page**
BGC 2/60	232030	382
BGC 6 kW 500 mm ET	003769	382
BGC/45	075115	382
FCR 21/60	071330	382
FCR 21/120 E	071331	382
FCR 28/120	071332	382
FCR 28/120 E	000694	382
FCR 28/120 CrNi	234503	383
FCR 28/180	071333	383
FCR 28/180 E	000695	383
WPRB	074233	383

Heat pump accessories

DHW heating		
Type	**Order no.**	**Page**
UPZ	233719	386
UP 25-60-180	056899	386
WT 30	071091	387
WT 40	229338	387

Heating system hydraulics		
Type	**Order no.**	**Page**
FS-WP 22	233511	388
FS-WP 28	233512	388
MFS-WP 28	235234	388
AHP-PS.1	208668	389
AHP-PS.2	208669	389
AHP-PS.3	208670	389
UP 25/7.5 PCV	201620	389
UP 25/1-8 PCV	205285	389
UP 30/1-8 PCV	205286	389
UP 30/1-10 PCV	205288	389
UP 40/1-8 E	206633	389
UP 50/1-12 E	206636	389
WPKI-HK DN 25	206627	390
WPKI-HKM E 24	206300	390
WPKI-HKM 24 DN 32	206628	391
WPKI-HKM 24 DN 40	206632	391
WPKI-HKM 230 DN 25	206631	391
WPKI-HKV 2	206638	392
WPKI-HKV 3	206637	392
HUV 65	227425	393
HUV 80	227426	393
HUV 1.1	208004	393
HUV 2.1	208320	393
WPHW 25	221135	394
HZEA	230013	394
HZEN	230031	395
SD 25-1 G	232976	395
SD 25-2 GE	233828	395
SD 25-2.5 GE	232971	395
SD 32-0.6 G	201710	395
SD 32-1 G	232977	396
SD 32-2 GE	233831	396
SD 40-0.8 G	201711	396
SD DN25-1 E	074415	396
SD 25-1 E	232965	396
SD 32-1 E	232968	396
SD DN32-1 E	074414	396
SD 50-1 E	232972	396
SD 25-1 KE	232974	397
SD 32-1 KE	232975	397
SV DS 25	003713	397
SV DS 32	070692	397
FSHP-L45	202779	398
Additional accessories		
Type	**Order no.**	**Page**
STB-FB	233711	399

Central ventilation units

Supply and extract air with heat recovery, wall mounting		
Type	**Order no.**	**Page**
VRC-W 450 Premium	204940	404
VRC-W 600 Premium	204714	404
VRC-W 450 E Premium	204941	407
VRC-W 600 E Premium	204715	407
VRC-W 400	203636	410
VRC-W 400 E	203637	410

LWZ 180	232361	412
LWZ 280	232362	412
LWZ 180 Enthalpie	236646	415
LWZ 280 Enthalpie	236647	415
LWZ 70 E	233851	417
Supply and extract air with heat recovery, ceiling mounting		
Type	**Order no.**	**Page**
LWZ 130	237805	420
LWZ 130 Enthalpie	237806	422

Accessories, central ventilation units

Accessories		
Type	**Order no.**	**Page**
LWTF 180/280	236420	426
LWTF W450/600	359304	426
ZLWZ VHR 70 E	236038	427
LSK 70 E	227046	427
Controllers		
Type	**Order no.**	**Page**
FEB 2.0	205018	428
FEB 2.1	206612	428
FEZ	185358	429
ZLWZ 4 S	234866	429
WLAN VRC .1	206611	430
Filter		
Type	**Order no.**	**Page**
FMS G4-10 130/135	238923	431
FMK M5-2 130/135	238924	431
FMK F7-2 130/135	238925	432
FMS G4-10 180	234147	432
FMK M5-2 180	234148	433
FMK F7-2 180	234208	433
FMS G3-10 70	222446	434
FMK F7-2 70	227660	434
FMS EPMC 65-10 W450/600	206610	435
FMK EPM1 55-2 W450/600	206596	435
FMK EPA 12-2 W450/600	206597	436

Distribution system for integral and central ventilation

LVE onfloor		
Type	**Order no.**	**Page**
LVE RP 20	231111	448
LVE BF 45	231121	448
LVE BF 90	231122	448
LVE BH 90-D	206252	449
LVE Ü 180	231120	449
LVE Ü 90	233032	450
LVE TB 75	207077	450
LVE ÜB-O	235913	451
LVE ÜB-U	235912	451
LVE M	231112	451
LVE RA	231117	451
LVE YS	239126	452
LVE A	205366	452
LVE KF	231113	453
LVE WDA 125	205364	453
LVE-LVS WDA 125	205368	454
LVS infloor		
Type	**Order no.**	**Page**
LVS RP 75-50	235059	455
LVS RP 90-25	223320	455
LVS RS 75	207074	455
LVS VTS 6	201456	456
LVS VTS 9	234493	456
LVS VT 14	205558	456
ZLVS VTÜ 75-90	234494	457
LVS WDA 125-2-75	205367	458
LVS A 2-75	205365	458
LVS M 75	224897	459
ZLVS O 75-10	236421	459
ZLVS O 90-10	236422	459
LVS DA 75-125-2	236423	460
LVS-MSV-SB	232117	460
LVS-MSV-SBA	232118	461
LVS AS 75	223318	461
LWF system		
Type	**Order no.**	**Page**
LWF T 160 - 160	159323	462
LWF M 125	159299	462
LWF N 160	159320	463
LWF RS 160 M - 125 N	207509	463
LWF F 125 - 5	159334	464
LWF F 160 - 5	159332	464
LWF DR 125-1 EPP	239231	464
LWF DR 160-1 EPP	239232	464
LWF DRB 125-45 EPP	239234	465
LWF DRB 125-90 EPP	239233	465
LWF DRB 160-45 EPP	239236	465
LWF DRB 160-90 EPP	239235	465
LWF DRM 125 EPP	239237	465
LWF DRM 160 EPP	239238	465
LWF S 160 - 0,9	159346	466
LWF SK 315 - 0,6	202933	466
LWF SE 125	207073	467
LWF LB 10m	159348	467
LWF KB 10	227948	468
LWF AVM 125	227924	468
LWF ZVM 125	230163	469
KWG 125	239139	469
WG 160	205559	470
WG 200	205560	470

Decentralised ventilation in residential buildings

Supply and extract air with heat recovery		
Type	**Order no.**	**Page**
VLR 70 S Trend EN	200002	474
VLR 70 L Trend EN	201458	474
VLR 70 L Trend EU	203133	474
Extract air without heat recovery		
Type	**Order no.**	**Page**
LA 100 A	205771	476

LA 100 U	205772	476
LA 100 UB	205773	476
ZLA 100-H	205830	477
LA 100 G-U	205878	477
LA 100 G-UB	206247	477
LA 100 G-A	205906	478
LA 100 VE	205907	478
LWF W 100 VA - 60	231104	479
FMS G3-5 LA 60	201455	479

Accessories for decentralised ventilation in residential buildings

Accessories for controllers		
Type	**Order no.**	**Page**
VLR 70-2 CU	239570	482
VLR 70-4 CU	239571	482
VLR 70-8 CU	239572	482
LTM TL HUMIDITY	237126	482
LTM dezent APD BT	237644	483
Filter		
Type	**Order no.**	**Page**
SP VLR 70 RF COARSE 30 G2-4	239562	484
SP VLR 70 RF EPM1 50 F7-4	239577	484
SP VLR 70 RF COARSE 60 G4-4	239575	484
SP VLR 70 RF EPM10 50 M5-4	239576	485

Decentralised ventilation in non-residential buildings

Supply and extract air with heat recovery		
Type	**Order no.**	**Page**
VRL-C 870 G Premium	204132	488
VRL-C 870 G Trend	204133	492
VRL-C 870 D Premium	204134	498
VRL-C 870 D Trend	204135	500
VRL-C 300 G Premium	204140	504
VRL-C 300 G Trend	204141	508
VRL-C 300 D Premium	204142	512
VRL-C 300 D Trend	204143	516

Accessories for decentralised ventilation in non-residential buildings

Installation accessories		
Type	**Order no.**	**Page**
LTM dezent 300 ULB-90	237626	522
LTM dezent ULB-90	237634	522
LTM dezent 300 Z-PSS	237671	522
LTM dezent 600/800 Z-PSS	237672	522
LTM dezent C-PSS	237673	522
LTM dezent RWA	237674	522
Wall terminal		
Type	**Order no.**	**Page**
LTM dezent 300 BA VA 320 B	237627	523
LTM dezent 300 BA VA 320 W	237628	523
LTM dezent BA VA 410 B	237629	523
LTM dezent BA VA 410 W	237633	523

Controllers and sensors		
Type	**Order no.**	**Page**
ZVRL-C CU	204144	524
LTM dezent VOC	237658	524
LTM dezent CO2	237649	525
Supplementary accessories		
Type	**Order no.**	**Page**
LTM dezent BACnet Web - Ethernet	237646	526
LTM dezent Modbus RS 485 IF	237648	526
Filter		
Type	**Order no.**	**Page**
LTM dezent FMS F9-1	237668	527
FMK M5-2 ABL dez. 800/870	206202	527
FMK M5-10 ABL dez. 800/870	206203	527
FMK F7-2 ZUL dez. 800/870	206204	527
FMK F7-10 ZUL dez. 800/870	206205	527
FMK M5-2 ABL dez. 300	206206	527
FMK M5-10 ABL dez. 300	206207	527
FMK F7-2 ZUL dez. 300	206208	527
FMK F7-10 ZUL dez. 300	206209	527

Storage heaters

Standard storage heater		
Type	**Order no.**	**Page**
SHF 2000	200175	532
SHF 3000	200176	532
SHF 4000	200177	532
SHF 5000	200178	532
SHF 6000	200179	532
SHF 7000	200180	532

Accessories for storage heaters

Control units		
Type	**Order no.**	**Page**
RTA-S2	231061	534

Convectors

Wall installation		
Type	**Order no.**	**Page**
CON 5 Premium	237830	538
CON 10 Premium	237831	538
CON 15 Premium	237832	538
CON 20 Premium	237833	538
CON 30 Premium	237834	538
CWM 500 P	200254	539
CWM 750 P	200255	539
CWM 1000 P	200256	539
CWM 1500 P	200257	539
CWM 2000 P	200258	539
CWM 2500 P	200259	539
CWM 3000 P	200260	539
CNS 50 Trend M	203638	541
CNS 100 Trend M	203640	541
CNS 200 Trend M	203642	541

Floorstanding appliances		
Type	**Order no.**	**Page**
CNS 2000 Plus LCD Move	207060	542
CNS-B 2000 Plus LCD Move	207068	542
CWM 750 M-F	204452	543
CWM 1000 M-F	204453	543
CWM 1500 M-F	204454	543
CWM 2000 M-F	204455	543
CWM 2500 M-F	204456	543
CWM 3000 M-F	204457	543

Rapid heater

Wall installation		
Type	**Order no.**	**Page**
CK 20 Premium	237835	546
CK 20 Trend LCD	236653	547

Infrared wall mounted radiant heater

Indoor		
Type	**Order no.**	**Page**
IW 120	229339	550

Hand dryer, high speed

High speed		
Type	**Order no.**	**Page**
ULTRONIC Premium	205633	554
ULTRONIC Plus	205632	555

Engineering

Engineering services		
Type	**Order no.**	**Page**
Planning of ventilation technology, 3D	240592	560

Comfort instantaneous water heater

Electronic open-loop control							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				PEB 11	202693	01.2026	18
				PEB 18/21/24	206210	01.2026	18
				HDB-E 27 Trend	204210	01.2026	20

Compact DHW heat pumps

Floorstanding							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				SHP-O 301 Premium	207265	11.2025	122
				SHP-O 201 Premium	207264	11.2025	122
SHP-I 200 Plus	204474	06.2026	124				
SHP-I 300 H Plus	204478	06.2026	124				
SHP-I 300 Plus	204476	06.2026	124				

Water filter

Filter cartridges							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				SNOW DUAL FILTER CARTRIDGE (EX)	206463	01.2026	140
				SNOW RO FILTER CARTRIDGE (EX)	206461	01.2026	141
				SNOW PRO DUAL FILTER CARTRIDGE (EX)	207813	01.2026	142
				SNOW PRO RO FILTER CARTRIDGE (EX)	207814	01.2026	143
Drinking water filter							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				SNOW (EX)	206462	01.2026	144
				SNOW PRO (EX)	207812	01.2026	145

Air source heat pumps, outdoor installation – inverter

Inverter							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				HPA-O 10.2 Plus HC 230	207432	02.2026	158
				HPA-O 13.2 Plus HC 400	207435	01.2026	158
				HPA-O 05.2 Plus HC 230	207429	02.2026	158
				HPA-O 10.2 Plus HC 400	207433	01.2026	158
				HPA-O 07.2 Plus HC 230	207430	01.2026	158
				HPA-O 05.2 W Plus HC 230	208431	02.2026	165
				HPA-O 10.2 W Plus HC 400	208434	01.2026	165
				HPA-O 13.2 W Plus HC 400	208435	01.2026	165
				HPA-O 07.2 W Plus HC 230	208432	01.2026	165
				HPA-O 10.2 W Plus HC 230	208433	02.2026	165
				HPA-O 05.2 Plus HC 230 + HSBC 200	208560	02.2026	166
				HPA-O 10.2 Plus HC 230 + HSBC 200	208561	02.2026	166
				HPA-O 10.2 Plus HC 400 + HSBC 200	207961	01.2026	166
				HPA-O 13.2 Plus HC 400 + HSBC 200	207963	01.2026	166
				HPA-O 07.2 Plus HC 230 + HSBC 200	207962	01.2026	166
				HPA-O 13.2 W Plus HC 400 + HSBC 200	208395	01.2026	168
				HPA-O 07.2 W Plus HC 230 + HSBC 200	208392	01.2026	168
				HPA-O 05.2 W Plus HC 230 + HSBC 200	208576	02.2026	168
				HPA-O 10.2 W Plus HC 400 + HSBC 200	208394	01.2026	168
				HPA-O 10.2 W Plus HC 230 + HSBC 200	208393	02.2026	168
				HPA-O 07.2 Plus HC 230 + HSBC 200 S	208719	02.2026	169
				HPA-O 05.2 Plus HC 230 + HSBC 200 S	208718	02.2026	169
				HPA-O 10.2 Plus HC 230 + HSBC 200 S	208720	02.2026	169
				HPA-O 05.2 W Plus HC 230 + HSBC 200 S	208721	02.2026	170
				HPA-O 07.2 W Plus HC 230 + HSBC 200 S	208722	02.2026	170
				HPA-O 10.2 W Plus HC 230 + HSBC 200 S	208723	02.2026	170
				HPA-O 10.2 Plus HC 230 + HSBC 300	208565	02.2026	172
				HPA-O 10.2 Plus HC 400 + HSBC 300	207967	01.2026	172
				HPA-O 07.2 Plus HC 230 + HSBC 300	207966	01.2026	172
				HPA-O 05.2 Plus HC 230 + HSBC 300	208564	02.2026	172
				HPA-O 13.2 Plus HC 400 + HSBC 300	207968	01.2026	172

				HPA-O 10.2 W Plus HC 230 + HSBC 300	208398	02.2026	173
				HPA-O 07.2 W Plus HC 230 + HSBC 300	208397	01.2026	173
				HPA-O 10.2 W Plus HC 400 + HSBC 300	208399	01.2026	173
				HPA-O 05.2 W Plus HC 230 + HSBC 300	208396	02.2026	173
				HPA-O 13.2 W Plus HC 400 + HSBC 300	208400	01.2026	173
				HPA-O 05.2 Plus HC 230 + HM Trend	208407	02.2026	174
				HPA-O 07.2 Plus HC 230 + HM Trend	208218	01.2026	174
				HPA-O 10.2 Plus HC 230 + HM Trend	208408	02.2026	174
				HPA-O 13.2 Plus HC 400 + HM Trend	208220	01.2026	174
				HPA-O 10.2 Plus HC 400 + HM Trend	208219	01.2026	174
				HPA-O 10.2 Plus HC 230 + HMS Trend	208730	02.2026	175
				HPA-O 10.2 W Plus HC 230 + HM Trend	208416	02.2026	175
				HPA-O 05.2 W Plus HC 230 + HM Trend	208414	02.2026	175
				HPA-O 10.2 W Plus HC 400 + HM Trend	208417	01.2026	175
				HPA-O 05.2 Plus HC 230 + HMS Trend	208728	02.2026	175
				HPA-O 07.2 Plus HC 230 + HMS Trend	208729	02.2026	175
				HPA-O 07.2 W Plus HC 230 + HM Trend	208415	01.2026	175
				HPA-O 13.2 W Plus HC 400 + HM Trend	208418	01.2026	175
				HPA-O 10.2 W Plus HC 230 + HMS Trend	208733	02.2026	176
				HPA-O 05.2 W Plus HC 230 + HMS Trend	208731	02.2026	176
				HPA-O 07.2 W Plus HC 230 + HMS Trend	208732	02.2026	176
				HPA-O 17.2 Trend HC 400	207426	02.2026	183
				HPA-O 07.2 Trend HC 230	207420	02.2026	183
				HPA-O 13.2 Trend HC 230	207424	02.2026	183
				HPA-O 10.2 Trend HC 230	207422	01.2026	183
				HPA-O 13.2 Trend HC 400	207425	01.2026	183
				HPA-O 10.2 Trend HC 230 + HSBC 200	207959	01.2026	184
				HPA-O 07.2 Trend HC 230 + HSBC 200	208558	02.2026	184
				HPA-O 13.2 Trend HC 400 + HSBC 200	207960	01.2026	184
				HPA-O 13.2 Trend HC 230 + HSBC 200	208559	02.2026	184
				HPA-O 07.2 Trend HC 230 + HSBC 200 S	208736	02.2026	185
				HPA-O 10.2 Trend HC 230 + HSBC 200 S	208716	02.2026	185
				HPA-O 13.2 Trend HC 230 + HSBC 200 S	208717	02.2026	185
				HPA-O 13.2 Trend HC 230 + HSBC 300	208563	02.2026	186
				HPA-O 10.2 Trend HC 230 + HSBC 300	207964	01.2026	186
				HPA-O 07.2 Trend HC 230 + HSBC 300	208562	02.2026	186
				HPA-O 13.2 Trend HC 400 + HSBC 300	207965	01.2026	186
				HPA-O 10.2 Trend HC 230 + HM Trend	208221	01.2026	187
				HPA-O 07.2 Trend HC 230 + HM Trend	208405	02.2026	187
				HPA-O 13.2 Trend HC 400 + HM Trend	208222	01.2026	187
				HPA-O 13.2 Trend HC 230 + HM Trend	208406	02.2026	187
				HPA-O 13.2 Trend HC 230 + HMS Trend	208727	02.2026	188
				HPA-O 07.2 Trend HC 230 + HMS Trend	208725	02.2026	188
				HPA-O 10.2 Trend HC 230 + HMS Trend	208726	02.2026	188

Accessories for air source heat pumps installed outdoors

Installation accessories							
Phase out	**Order no.**	**Available until**	**Page**	**Start**	**Product number**	**Available from**	**Page**
				AHP-BS.1	207894	01.2026	232

				AHP-DT.1	207731	01.2026	232
				AHP-CB.1	207735	01.2026	233
				AHP-CW.1	207736	01.2026	233
				AHP-GC.1	207732	01.2026	234
				AGC-CB.1	207733	01.2026	234
				AHP-WM.1	207891	01.2026	235
				AGC-CW.1	207734	01.2026	235
				AWM-CB.1	207892	01.2026	236
				AHP-SC.1	207737	01.2026	237
				AWM-CW.1	207893	01.2026	237
				AHP-DS 0.8	207738	01.2026	238
				WK 3	208702	01.2026	238
				AHP-FW 25-0.4	208863	01.2026	239
				AHP-FH 25-0.4	207724	01.2026	239
				AHP-TB 710	207728	01.2026	240
				AHP-TW 710	207710	01.2026	240
				AHP-TW 420	207730	01.2026	240
				AHP-TB 420	207727	01.2026	240
				AHP-SB.1	207711	01.2026	241
				AHP-SW.1	207712	01.2026	241
				AHP-WB.3	208680	01.2026	242
				AHP-WW.1	208658	01.2026	242
				AHP-WB.2	208679	01.2026	242
				AHP-WW.3	208682	01.2026	242
				AHP-WB.1	207713	01.2026	242
				AHP-WW.2	208681	01.2026	242
				AHP-WU.1	207716	01.2026	243
				AHP-WO.1	207715	01.2026	243
				AHP-WU.2	207717	01.2026	244
				AWU-HS 10	207720	01.2026	245
				AWU-HS 5	207719	01.2026	245
				AWU-HS 2.5	207718	01.2026	245
				AHS-SI 200	207721	01.2026	246
				AHP-CM 5	208010	01.2026	247
				AHP-CM 2	208660	01.2026	247
				AHP-CM 3	208040	01.2026	247
				AHP-CM 4	208009	01.2026	247
				AHP-CM 6	208011	01.2026	247
				AHP-CS.1	207723	01.2026	248

Ground source heat pumps – inverter

Inverter							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				WPE-I 17.1 Plus H 400	207179	03.2026	289

Control units

Controller							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				WPM Connect International	207709	07.2026	333
Connectivity							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				ISG Connect	206780	01.2026	334

Accessories for integral cylinders

Accessories							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				AHP-BH 8.8	207902	01.2026	353

Heat pump accessories

Heating system hydraulics							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
				AHP-PS.2	208669	01.2026	389
				AHP-PS.1	208668	01.2026	389
				AHP-PS.3	208670	01.2026	389
				HUV 1.1	208004	01.2026	393
				HUV 2.1	208320	01.2026	393

Convectors


Floorstanding appliances							
Phase out	Order no.	Available until	Page	Start	Product number	Available from	Page
CWM 1500 M-F	204454	06.2026	543				
CWM 750 M-F	204452	06.2026	543				
CWM 2500 M-F	204456	06.2026	543				

Comfort instantaneous water heater		5
Remote controls for comfort instantaneous water heaters		23
Compact instantaneous water heaters, 3-phase		27
Compact instantaneous water heaters, 1-phase		37
Mini instantaneous water heaters		45


Application areas

Rated output: Please note the rated output and fuse protection when selecting an instantaneous water heater

Starting flow rate: Please note the starting flow rate of the instantaneous water heater when selecting your fitting



Application areas



Application areas

Full electronic control
- **DHE** 6
- **PER** 8

Electronic closed-loop control
- **DEL Plus** 10
- **PEO** 12
- **DHB-E LCD** 14
- **PEY** 16

Electronic open-loop control
- **PEB** 18
- **HDB-E Trend** 20

DHE



DHE 18/21/24

Benefits

- Easy operation via large, illuminated multifunction display
- The temperature can be permanently restricted by the installer to 55, 50 or 43 °C; the temperature can be further restricted by the user (childproofing)
- Quick temperature selection with two memory buttons
- Greater convenience when installed undersink, since the appliance cover and the programming unit can be turned the other way up
- Suitable for reheating preheated water
- Safe operation thanks to extensive range of convenience and safety functions
- Quick installation with Profi-Rapid, the innovative installation concept
- Consumption indicator for transparent costs
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 202656)

Application • This comfort instantaneous water heater can supply DHW to multiple draw-off points, e.g. simultaneous supply to the bathroom and kitchen. • The unvented, pressure-tested appliance can be combined with all commercially available pressure taps.

Convenience features • The fully electronically controlled instantaneous water heater ensures accurate temperature delivery at all times thanks to electronic flow rate control. • The temperature can be variably and digitally adjusted in 0.5 °C increments using a rotary selector. • The backlit multifunction display not only shows the set temperature, but also various other values such as current power consumption, energy consumption, flow rate and time. Status and service information is also displayed. • The ECO button and two memory buttons for rapid call-up of programmed preferred temperatures ensure efficiency and convenience. • Four wellness shower programs and automated bath filling provide a high level of hot water convenience. • The LED indicator warns against scalding if the water temperature exceeds 43 °C, or if the temperature of preheated water is unexpectedly high. • The current inlet temperature is shown in the lower section. • The temperature limit can be set individually and used as anti-scalding protection. • An optional convenient remote control is available as an accessory.

Efficiency • The appliance achieves energy and water savings of up to 30 % through full electronic output control with 4i technology. Three sensors and an additional motorised valve ensure that the set temperature is achieved to the exact degree at all times. Only the amount of energy actually required for this is expended; there is no need to add cold water at the tap, which leads to very high energy efficiency. • An additional feature is the individually selectable ECO mode for particularly economical operation. • The information about energy and water consumption encourages economical usage. • The instantaneous water heater is suitable for operation with preheated water.

Installation • With undersink installation, the appliance cover and programming unit can be turned the other way up for a high level of operating convenience. • The improved PROFI-RAPID installation system is integrated for fast installation. Common instantaneous water heaters are quick to replace. • Wall mounting is very simple thanks to the universal mounting rail. Suitable for commonly used fixing points; any unevenness in the wall and drill hole discrepancies are easily compensated for. • For quick and universal water connection, the appliance features an enlarged installation area with pivoting cold water inlet, threaded water fittings and twin nipple connections. • It is suitable for flush and surface mounting, with 3-way shut-off valves. • The appliance can be connected to plastic pipework as long as the manufacturer's instructions are followed. • The mains connection is also quick and easy. It can be made from above or below, with an integral cable insertion aid.

Service: • Simplified fault analysis through integral LED diagnostic traffic light and fault memory which can be called up on the display. • The complete internal assembly can be removed with just one hand movement, if required.

Safety • The quick-action bare wire heating system is suitable for hard and soft water. • The electronic safety concept operates with air detection. • Permanent anti-scalding protection is set by an installer.





		DHE 18/21/24	DHE 27
Part number		**202656**	**202657**
Specification			
Rated voltage	V	400	400
Rated voltage 1	V	380	380
Rated voltage 2	V	400	400
Rated voltage 3	V	415	
Rated output	kW	18/21/24	27
Rated output 1	kW	16,2/19/21,7	24,4

next page >

		DHE 18/21/24	DHE 27
Rated output 2	kW	18/21/24	27
Rated output 3	kW	19,4/22,6/25,8	
Rated current	A	29/31/35	39
Rated current 1	A	27,6/29,5/33,3	37,1
Rated current 2	A	29/31/35	39
Rated current 3	A	30,1/32,2/36,3	
Fuse protection	A	32/32/35	40
Fuse protection 1	A	32/32/35	40
Fuse protection 2	A	32/32/35	40
Fuse protection 3	A	32/32/40	
Frequency	Hz	50/60	50/-
Frequency 1	Hz	50/60	50/-
Frequency 2	Hz	50/60	50/-
Frequency 3	Hz	50/-	
Phases		3/PE	3/PE
Conductivity σ15 ≤	µS/cm	1111	1111
Resistivity ρ15 ≥	Ω cm	900	900
Switch-on water flow rate	l/min	>2,5	>2,55
IP rating		IP25	IP25
Temperature setting	°C	20-60	20-60
Colour		white	white
Height	mm	466	466
Width	mm	225	225
Depth	mm	116	116
Weight	kg	3.10	3.10
Energy efficiency class A+ -> F		A	A

Recommended accessories			
Part number		**234478**	**234478**
Type		FFB 4 EU	FFB 4 EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters
Part number		**238930**	**238930**
Type		FFB 4 Set EU	FFB 4 Set EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters

PER



PER 18/21/24

Benefits

- Very high temperature convenience with this fully electronic instantaneous water heater
- Consistent outlet temperatures regardless of fluctuations in pressure, inlet temperature or voltage
- Accurate temperature selection and easy-to-read LCD screen with 2-colour backlighting
- Very high shower convenience thanks to quick-acting control electronics
- Precise water temperature at maximum flow rate thanks to processor-controlled motorised valve
- Suitable for reheating water up to 60 °C, e.g. from solar thermal systems
- Multifunction display with backlighting
- Display of temperature, flow rate, energy consumption or time
- Two individually adjustable temperatures can be called up via memory buttons
- Convenience functions: ECO button, automatic water volume control, shower program
- Energy saving operation with ECO function
- Electronic air bubble detection
- Effective bare wire heating system

Application • This fully electronically controlled comfort instantaneous water heater supplies DHW conveniently and energy efficiently to multiple draw-off points, for example the bathroom and the kitchen. • This unvented, pressure-tested appliance can be used with preheated water from a solar thermal system or heat pump and with all commercially available pressure taps.

Convenience features • The temperature can be set to the exact degree via the 2-colour backlit digital multifunction display. The temperature, flow rate, energy consumption and time are easy to read. • The preferred temperature can be easily set to suit individual needs via two memory buttons. • The ECO button, automatic water volume control and the shower program offer additional operating convenience. • Accurate temperature delivery at all times with demand-dependent flow rate thanks to processor-controlled motorised valve. • Buttons allow one-off selection of the required temperature for the next draw-off.

Efficiency • With the individually selectable ECO mode, particularly energy efficient operation is possible. • The accurate temperature delivery at all times and precise flow rate further increase the overall efficiency of the instantaneous water heater.

Installation • All commercially available unvented taps can be connected easily. • Installation is facilitated by the separate mounting plate and quick-release toggle. The installation template is included in the standard delivery. • Easy mains connection, either from above or below. • The appliance cover can be removed from the front with no screws. • Undersink installation is possible with the correct accessories.

Safety • The quick-action bare wire heating system is suitable for hard and soft water. • The multi stage safety concept detects air bubbles in the system and automatically deactivates the appliance if the pressure is too high.

		PER 18/21/24
Part number		**233990**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	18/21/24
Rated output 1	kW	16,2/19/21,7
Rated output 2	kW	18/21/24
Rated output 3	kW	19,4/22,6/25,8
Rated current	A	29/31/35
Rated current 1	A	27,6/29,5/33,3
Rated current 2	A	29/31/35
Rated current 3	A	30,1/32,2/36,3
Fuse protection	A	32/32/35
Fuse protection 1	A	32/32/35
Fuse protection 2	A	32/32/35
Fuse protection 3	A	32/32/40
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE

next page >

		PER 18/21/24
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1000
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	770
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	1000
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1300
Switch-on water flow rate	l/min	>2,5
Temperature setting	°C	30-60
Colour		white
Height	mm	485
Width	mm	226
Depth	mm	93
Weight	kg	3.80
Energy efficiency class A+ -> F		A

Incl. wireless remote control (Product: 233990)

DEL Plus



DEL 18/21/24 Plus

Benefits

- Maximum energy efficiency and accurate temperature delivery with 3i technology and electronic closed-loop control
- High hot water convenience and energy savings thanks to three-stage ECO mode with flow rate limitation
- No fixed flow limiter in the cold water inlet
- Illuminated multifunction display
- The temperature can be permanently restricted by the installer to 55, 50 or 43 °C; the temperature can be further restricted by the user (childproofing)
- Quick installation with PROFI-RAPID
- Suitable for preheated water up to 55 °C with reheating and up to a maximum of 70 °C without reheating.
- Greater convenience when installed undersink, since the appliance cover and the programming unit can be turned the other way up
- Quick temperature selection with two memory buttons
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 236739)

Application • This comfort instantaneous water heater with electronic closed-loop control achieves accurate temperature delivery up the maximum output. • The unvented, pressure-tested appliance supplies DHW conveniently and energy efficiently to multiple draw-off points, for example the bathroom and the kitchen. • It is suitable for all commercially available pressure taps. • Highly convenient undersink installation, since the appliance cover and the programming unit can be turned the other way up.

Convenience features • Set temperature, current power consumption, and status and service information are easy to read on the backlit multifunction display. • The preferred temperature can be variably and digitally adjusted via a rotary selector. For showers, the temperature can be adjusted in very precise 0.5 °C increments. • Memory function for two programmable preferred temperatures. • An LED indicator warns of scalding at temperatures above 43 °C, as well as in the case of unexpectedly high outlet temperatures due to preheated water. • Individually adjustable childproofing provides additional safety by limiting the maximum temperature.

Efficiency • Energy and water savings of up to 30 % through electronic output control. • 3i technology with three sensors ensures that the set temperature is reached. This saves a lot of energy, because there is no need to add cold water at the tap. • The individually selectable, three-level ECO mode replaces the fixed flow limiter and ensures particularly energy efficient operation.

Installation • The PROFI-RAPID installation system is used for quick installation. All common instantaneous water heaters are easy to replace. • The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is also suitable for commonly used fixing points. • Fast, universal water connection thanks to the enlarged installation area with pivoting cold water inlet. • Threaded water fittings and twin nipple connections for easy replacement. • Surface-mounted or flush-mounted installation. • Suitable for plastic pipes (observe manufacturer's instructions). • Easy mains connection, either from above or below. • Cable insertion aid.

Service • Fast fault analysis through LED diagnostic traffic light and fault memory which can be called up on the display. • Internal assembly can be removed with just one hand movement.

Safety • Quick-action bare wire heating system, suitable for hard and soft water. • Electronic safety concept detects air bubbles in the system. • To permanently limit the outlet temperature of the water, an installer can set anti-scalding protection.

		DEL 18/21/24 Plus	DEL 27 Plus
Part number		**236739**	**236740**
Specification			
Rated voltage	V	400	400
Rated voltage 1	V	380	380
Rated voltage 2	V	400	400
Rated voltage 3	V	415	
Rated output	kW	18/21/24	27
Rated output 1	kW	16,2/19/21,7	24,4
Rated output 2	kW	18/21/24	27
Rated output 3	kW	19,4/22,6/25,8	
Rated current	A	29/31/35	39

next page >

		DEL 18/21/24 Plus	DEL 27 Plus
Rated current 1	A	27,6/29,5/33,3	37,1
Rated current 2	A	29/31/35	39
Rated current 3	A	30,1/32,2/36,3	
Fuse protection	A	32/32/35	40
Fuse protection 1	A	32/32/35	40
Fuse protection 2	A	32/32/35	40
Fuse protection 3	A	32/32/40	
Frequency	Hz	50/60	50/-
Frequency 1	Hz	50/60	50/-
Frequency 2	Hz	50/60	50/-
Frequency 3	Hz	50/-	
Phases		3/PE	3/PE
Conductivity σ15 ≤	µS/cm	1111	1111
Resistivity ρ15 ≥	Ω cm	900	900
Switch-on water flow rate	l/min	>2,5	>2,5
IP rating		IP25	IP25
Temperature setting	°C	20-60	20-60
Colour		white	white
Height	mm	466	466
Width	mm	225	225
Depth	mm	116	116
Weight	kg	3.10	3.10
Energy efficiency class A+ -> F		A	A

Recommended accessories			
Part number		**234478**	**234478**
Type		FFB 4 EU	FFB 4 EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters
Part number		**238930**	**238930**
Type		FFB 4 Set EU	FFB 4 Set EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters

PEO



PEO 18/21/24

Benefits
- Electronic instantaneous water heater for optimum temperature convenience
- Consistent outlet temperatures regardless of fluctuations in pressure, inlet temperature or voltage
- Temperature selection to the exact degree with easy-to-read LCD screen
- Two-colour backlighting (blue/red)
- Very high shower convenience thanks to quick-acting control electronics
- Integral diagnostic system
- Electronic air bubble detection
- Effective bare wire heating system
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 233991)

Application • This comfort instantaneous water heater is suitable for DHW supply to multiple draw-off points. • The unvented, pressure-tested appliance can be combined with commercially available pressure taps.

Convenience features • Electronic closed-loop control allows precise temperature selection. • The appliance is equipped with an easy-to-read, 2-colour LCD screen. The display also acts as visual anti-scalding protection: at temperatures above 43 °C, the colour changes from blue to red.

Efficiency • Accurate temperature delivery is made possible by electronic closed-loop control. • The instantaneous water heater is suitable for preheated water from solar thermal and heat pump systems.

Installation • Easy installation thanks to separate mounting plate and twist lock. An installation template is included in the standard delivery. • The appliance cover is removed from the front with no screws. • The mains connection is made from above or below via a permanent connection. • Undersink installation is possible with the appropriate accessories. • Integral diagnostic system.

Safety • The bare wire heating system is suitable for hard and soft water. • The multi stage safety concept includes a safety high pressure switch and an electronic air detection system.

		PEO 18/21/24
Part number		**233991**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	18/21/24
Rated output 1	kW	16,2/19/21,7
Rated output 2	kW	18/21/24
Rated output 3	kW	19,4/22,6/25,8
Rated current	A	29/31/35
Rated current 1	A	27,6/29,5/33,3
Rated current 2	A	29/31/35
Rated current 3	A	30,1/32,2/36,3
Fuse protection	A	32/32/35
Fuse protection 1	A	32/32/35
Fuse protection 2	A	32/32/35
Fuse protection 3	A	32/32/40
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1000

next page >

		PEO 18/21/24
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	770
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	1000
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1300
Switch-on water flow rate	l/min	>2,5
IP rating		IP25
Temperature setting	°C	30-60
Colour		white
Height	mm	485
Width	mm	226
Depth	mm	93
Weight	kg	3.60
Energy efficiency class A+ -> F		A

DHB-E LCD



DHB-E 11/13 LCD

Benefits

- Maximum energy efficiency and accurate temperature delivery with 3i technology and electronic closed-loop control
- Temperature shown on the LCD screen
- Precise temperature selection via rotary selector
- Suitable for preheated water up to 55 °C with reheating and up to a maximum of 70 °C without reheating.
- Greater convenience when installed undersink, since the appliance cover and the programming unit can be turned the other way up
- Quick installation with PROFI-RAPID
- High safety level as anti-scalding protection can be permanently activated
- Wide selection of models
- Optimum solution for the kitchen sink, with selectable 11 or 13.5 kW output (Product: 236743)
- Suitable for system with 25 A fuse protection (Product: 236744)
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 236745)

Application • This comfort instantaneous water heater supplies DHW simultaneously to multiple draw-off points, for example the bathroom and the kitchen. • The sealed, pressure-tested appliance can be combined with all commercially available pressure taps.

Convenience features • The instantaneous water heater with electronic closed-loop control ensures accurate temperature delivery up to the maximum output. • The temperature is variably and digitally adjusted via a rotary selector and displayed on the LCD screen. • An optional convenient remote control can be added. • To ensure highly convenient undersink installation, both the appliance cover and the programming unit can be turned the other way up.

Efficiency • The appliance ensures energy and water savings of up to 30 % through electronic output control with 3i technology. 3 sensors ensure that the set temperature is achieved to the exact degree up to the output limit. For this, only the amount of energy actually required is expended. There is no need to add cold water at the tap, which leads to very good energy efficiency. • The appliance is suitable for preheated water.

Installation • Quick and easy installation with the improved PROFI-RAPID installation system. Straightforward replacement for all standard instantaneous water heaters. For fast wall mounting, a universal mounting rail is provided, which is suitable for commonly used fixing points, and also compensates for any unevenness in the wall and drill hole discrepancies. • Fast, universal water connection thanks to enlarged installation area with pivoting cold water inlet and threaded water fittings. • Twin nipple connections for easy replacement. • Option of flush or surface mounting with 3-way shut-off. The instantaneous water heater can be connected to plastic pipework; the manufacturer's instructions must be observed. • Easy mains connection from above or below; a cable insertion aid is provided.

Service • Fast fault analysis with integral LED diagnostic traffic light. • The internal assembly can be removed with just one hand movement.

Safety • The quick-action bare wire heating system is suitable for hard and soft water. • The electronic safety concept is equipped with air detection. • Anti-scalding protection is set by an installer, and permanently limits the water outlet temperature.

		DHB-E 11/13 LCD	DHB-E 18 LCD 25A	DHB-E 18/21/24 LCD	DHB-E 27 LCD
Part number		**236743**	**236744**	**236745**	**236746**
Specification					
Rated voltage	V	400	400	400	400
Rated voltage 1	V	380	380	380	380
Rated voltage 2	V	400	400	400	400
Rated voltage 3	V	415	415	415	
Rated output	kW	11/13,5	18	18/21/24	27
Rated output 1	kW	9,9/12,2	16,2	16,2/19/21,7	24,4
Rated output 2	kW	11/13,5	18	18/21/24	27
Rated output 3	kW	11,8/14,5	19,4	19,4/22,6/25,8	
Rated current	A	17,5/19,5	26	29/31/35	39
Rated current 1	A	16,6/18,5	24,7	27,6/29,5/33,3	37,1
Rated current 2	A	17,5/19,5	26	29/31/35	39
Rated current 3	A	18,2/20	27	30,1/32,2/36,3	

next page >

		DHB-E 11/13 LCD	DHB-E 18 LCD 25A	DHB-E 18/21/24 LCD	DHB-E 27 LCD
Fuse protection	A	20	25	32/32/35	40
Fuse protection 1	A	20	25	32/32/35	40
Fuse protection 2	A	20	25	32/32/35	40
Fuse protection 3	A	20	32	32/32/40	
Frequency	Hz	50/60	50/60	50/60	50/-
Frequency 1	Hz	50/60	50/60	50/60	50/-
Frequency 2	Hz	50/60	50/60	50/60	50/-
Frequency 3	Hz	50/-	50/-	50/-	
Phases		3/PE	3/PE	3/PE	3/PE
Conductivity σ15 ≤	µS/cm	1111	1111	1111	1111
Resistivity ρ15 ≥	Ω cm	900	900	900	900
Switch-on water flow rate	l/min	>2,5	>2,5	>2,5	>2,5
IP rating		IP25	IP25	IP25	IP25
Temperature setting	°C	20-60	20-60	20-60	20-60
Colour		white	white	white	white
Height	mm	466	466	466	466
Width	mm	225	225	225	225
Depth	mm	116	116	116	116
Weight	kg	2.80	2.90	2.90	2.90
Energy efficiency class A+ -> F		A	A	A	A
Recommended accessories					
Part number		**234478**	**234478**	**234478**	**234478**
Type		FFB 4 EU	FFB 4 EU	FFB 4 EU	FFB 4 EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters
Part number		**238930**	**238930**	**238930**	**238930**
Type		FFB 4 Set EU	FFB 4 Set EU	FFB 4 Set EU	FFB 4 Set EU
Description		Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters	Wireless remote control for electronic instantaneous water heaters

PEY



PEY 18/21/24

Benefits
- Accurate temperature delivery up to the output limit with electronic closed-loop control
- Consistent outlet temperatures regardless of fluctuations in pressure, inlet temperature or voltage
- Temperature setting 30 °C - 60 °C
- Highly stable temperatures are ensured by the quick-acting control electronics
- Electronic air bubble detection
- Effective bare wire heating system
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 233993)

Application • This comfort instantaneous water heater with electronic closed-loop control supplies DHW conveniently and energy efficiently to multiple draw-off points, for example the bathroom and the kitchen. • The unvented, pressure-tested appliance can be connected to all commercially available pressure taps. • The instantaneous water heater can be operated with preheated water from solar thermal systems or heat pumps.

Convenience features • The instantaneous water heater has a rapid control PCB and an integral diagnostic system. • Variable temperature selection is carried out via a rotary selector with analogue scale.

Efficiency • Energy saving operation is possible thanks to accurate temperature delivery.

Installation • Easy connection to all commercially available unvented taps. • Installation is greatly facilitated by the separate mounting plate and the twist lock. The installation template is included in the standard delivery. • The appliance is connected from above or below via a permanent electrical connection. • The appliance cover is removed from the front with no screws. • Undersink installation is possible with the correct accessories.

Service • A diagnostic system is integrated for fast fault analysis.

Safety • The bare wire heating system is suitable for hard and soft water. • The multi stage safety concept detects air bubbles in the system and automatically deactivates the appliance if the pressure is too high.

		PEY 18/21/24
Part number		**233993**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	18/21/24
Rated output 1	kW	16,2/19/21,7
Rated output 2	kW	18/21/24
Rated output 3	kW	19,4/22,6/25,8
Rated current	A	29/31/35
Rated current 1	A	27,6/29,5/33,3
Rated current 2	A	29/31/35
Rated current 3	A	30,1/32,2/36,3
Fuse protection	A	32/32/35
Fuse protection 1	A	32/32/35
Fuse protection 2	A	32/32/35
Fuse protection 3	A	32/32/40
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1000

next page >

		PEY 18/21/24
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	833
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	770
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	1000
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1200
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1300
Switch-on water flow rate	l/min	>3
Temperature setting	°C	30-60
Colour		white
Height	mm	485
Width	mm	226
Depth	mm	93
Weight	kg	3.60
Energy efficiency class A+ -> F		A

PEB

PEB 11

Benefits
- Good energy efficiency thanks to electronic control
- DHW is constantly available at 55 °C
- Preferred temperatures achieved by manually adding cold water
- Multi stage safety concept with electronic air bubble detection system
- Effective bare wire heating system
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 206210)

Application • This comfort instantaneous water heater supplies DHW simultaneously to multiple draw-off points, for example the bathroom and the kitchen. • The sealed, pressure-tested appliance can be used with all commercially available pressure taps.

Convenience features • The electronically controlled instantaneous water heater supplies DHW at a generally constant temperature up to the maximum output. • The temperature is preset to 55 °C; cold water is added as required to achieve the preferred temperature.

Efficiency • Energy saving operation is possible even with fluctuating water pressure or cold water inlet temperature. • The generally constant temperature of the DHW is ensured by the fast control electronics, which positively influences the efficiency of the system.

Installation • Straightforward connection to all commercially available taps. • Straightforward installation is ensured by the separate mounting plate with twist lock. An installation template is included in the standard delivery. • The power supply is via a permanent connection from above or below. • The appliance cover can be removed from the front without needing to undo any screws.

Safety • The quick and effective bare wire heating system is suitable for hard or soft water. • The multi stage safety concept comprises a safety pressure limiter and electronic air detection.

		PEB 11	PEB 18/21/24
		NEW	NEW
Part number		**202693**	**206210**
Specification			
Rated voltage	V	400	400
Rated voltage 1	V	380	380
Rated voltage 2	V	400	400
Rated output	kW	11	18/21/24
Rated output 1	kW	10,1	16,2/19/21,7
Rated output 2	kW	11	18/21/24
Rated current	A	16	29/31/35
Rated current 1	A	15,4	27,6/29,5/33,3
Rated current 2	A	16	29/31/35
Fuse protection	A	16	32/32/35
Fuse protection 1	A	16	32/32/35
Fuse protection 2	A	16	32/32/35
Frequency	Hz	50/60	50/60
Frequency 1	Hz	50/60	50/60
Frequency 2	Hz	50/60	50/60
Phases		3/PE	3/PE
Conductivity σ15 ≤	µS/cm	909	909
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	µS/cm	910	
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm		900
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm		900
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm		1000
Resistivity ρ15 ≥	Ω cm	1100	1100
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	Ω cm	1100	
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm		1200

next page >

		PEB 11	PEB 18/21/24
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm		1200
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm		1300
Switch-on water flow rate	l/min	>2,3	2,3
IP rating		IP25	IP25
Temperature setting	°C	55	55
Colour		white	white
Height	mm	485	485
Width	mm	226	226
Depth	mm	93	93
Weight	kg	3.50	3.50
Energy efficiency class A+ -> F		A	A

HDB-E Trend



HDB-E 11/13 Trend

Benefits

- Stable delivery of preferred temperature due to electronic open-loop control with two sensors (2i technology).
- Temperature is fixed by the installer. Anti-scalding protection.
- Flexibility during installation thanks to four appliance variants: 11/13 kW (selectable), 18 kW 25 A, 18/21/24 kW (selectable), 27 kW
- Multi stage electronic safety concept with air bubble detection and high limit safety cut-out.
- Horizontal installation is possible. The HDB E Trend can also be installed in suspended ceilings.
- Preinstalled flow limiter maintains highly stable temperatures even in winter when cold water temperature is low
- Quick and easy installation thanks to the Profi-Rapid installation system.
- Optimum solution for the kitchen sink, with selectable 11 or 13.5 kW output (Product: 204208)
- Highly flexible installation thanks to selectable appliance output – 18/21/24 kW in a single appliance (Product: 204209)

Application • This instantaneous water heater also supplies DHW conveniently and energy efficiently to multiple draw-off points, for example in the bathroom or kitchen. • The unvented, pressure-tested appliance is combined with commercially available pressure taps.

Convenience features • Precise DHW temperature to the output limit thanks to 2i technology. • The required DHW temperature can be set by a qualified contractor on the appliance via a 4-stage pin strip.

Efficiency • 2i technology with 2 sensors ensures that the preset temperature is reached up to the output limit. For this, only the amount of energy actually required is expended, which leads to higher energy efficiency.

Installation • Very quick installation with the improved PROFI-RAPID installation system. Standard instantaneous water heaters can be easily replaced. The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies and is designed to match commonly used fixing points. • Fast, universal water connection is ensured thanks to the enlarged installation area with pivoting cold water inlet. Replacement is straightforward thanks to the threaded water connections and the twin nipple connections. • The 3-way ball shut-off valve enables flush-mounted or surface-mounted installation. • The appliance can also be connected to plastic pipework as long as the pipe manufacturer's instructions are followed. • Straightforward mains connection, either from above or below. A cable insertion aid is provided.

Service • An LED diagnostic traffic light is built in for fast fault analysis. • The internal assembly can be removed with just one hand movement.

Safety • The quick-action bare wire heating system is suitable for hard and soft water. • The electronic safety concept is equipped with air detection. • A qualified contractor can permanently limit the water outlet temperature for anti-scalding protection or childproofing.

		HDB-E 11/13 Trend	HDB-E 18/21/24 Trend	HDB-E 27 Trend
				NEW
Part number		**204208**	**204209**	**204210**
Specification				
Rated voltage	V	400	400	400
Rated voltage 1	V	380	380	380
Rated voltage 2	V	400	400	400
Rated output	kW	11/13,5	18/21/24	27
Rated output 1	kW	9,9/12,2	16,2/19/21,7	24,4
Rated output 2	kW	11/13,5	18/21/24	27
Rated current	A	17,5/19,5	29/31/35	39
Rated current 1	A	16,6/18,5	27,6/29,5/33,3	37,1
Rated current 2	A	17,5/19,5	29/31/35	39
Fuse protection	A	20	32/32/35	40
Fuse protection 1	A	20	32/32/35	40
Fuse protection 2	A	20	32/32/35	40
Frequency	Hz	50/60	50/60	50/-
Frequency 1	Hz	50/60	50/60	50/-
Frequency 2	Hz	50/60	50/60	50/-

next page >

		HDB-E 11/13 Trend	HDB-E 18/21/24 Trend	HDB-E 27 Trend
Phases		3/PE	3/PE	3/PE
Conductivity σ15 ≤	µS/cm	1111	1111	1111
Resistivity ρ15 ≥	Ω cm	900	900	900
Switch-on water flow rate	l/min	>2,5	>2,5	>2,5
IP rating		IP25	IP25	IP25
Temperature setting	°C	35, 43, 50, 55 (400V)	35, 43, 50, 55 (400V)	35, 43, 50, 55 (400V)
Colour		white	white	white
Height	mm	466	466	466
Width	mm	225	225	225
Depth	mm	105	105	105
Weight	kg	2.80	2.90	2.90
Energy efficiency class A+ -> F		A	A	A

Wireless remote controls
Accessories 24

FFB 4



FFB 4 Set EU

Benefits
- Additional wireless remote control with large LCD screen
- Variable temperature selection from 20 °C to 60 °C
- FFB 4 Set EU incl. wireless adaptor as basic equipment (Product: 238930)
- FFB 4 EU as second or additional wireless remote control (Product: 234478)

Description • These comfort instantaneous water heaters can be operated very conveniently with the wireless remote control. The remote control can also be used in the shower. A wall mounting bracket is included in the standard delivery. • Preferred temperatures can be set very easily using the plus and minus buttons or the programmable memory buttons. • The large LCD screen is easy to read. • Power save mode ensures an extended battery service life.

		FFB 4 Set EU	FFB 4 EU
Part number		**238930**	**234478**
Specification			
IP rating		IP X7	IP X7
Width	mm	65	65
Height	mm	132	132
Depth	mm	18,5	18,5

Battery and wall mounting bracket included in the standard delivery.

Application areas

Rated output: Please note the rated output and fuse protection when selecting an instantaneous water heater

Starting flow rate: Please note the starting flow rate of the instantaneous water heater when selecting your fitting



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	l/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE 11/13 RC													■			■																										
																	■																									



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	l/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE 11/13													■			■																										
																	■																									



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	l/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE 11/13 H													■			■																										
																	■																									

Electronic closed-loop control

DCE 11/13 RC	28
DCE 11/13	30
DCE 11/13 H	32
DCE 11/13 H + MEKD	34

DCE 11/13 RC



DCE 11/13 RC

Benefits

- Exceptionally slimline, compact design
- Especially comfortable thanks to electronic power control with 3i technology
- Standard delivery includes wireless remote control with two memory buttons
- Quick installation with PROFI-RAPID
- Multi stage electronic safety concept
- Undersink installation
- Selectable connected load 11 kW or 13.5 kW

Application • This instantaneous water heater with electronic closed-loop control takes up very little space in the kitchen due to its compact design. The appliance is uniquely flat thanks to its low installation depth, making it ideal for space saving installation under the kitchen sink. • In commercial settings, it is suitable for cleaning rooms or sanitary facilities with multiple hand washbasins. • International: With high inlet temperatures, the instantaneous water heater is also suitable for showers.

Convenience features • 3i technology ensures accurate preferred temperature delivery up to the output limit. • The water is heated fast by the bare wire heating system. Electronic open-loop control keeps the preferred temperature constant up to the output limit. • The preferred temperature is set to the exact degree via the wireless remote control. • The connected load can be easily selected on the appliance.

Efficiency • 3i technology ensures energy and water savings of up to 30 % through electronic output control. Three sensors ensure that the set temperature is achieved to the exact degree up to the output limit. Energy savings are further assured by the appliance only using the amount of energy it actually requires. There is no need to add cold water at the tap, which additionally enhances the overall efficiency. • The instantaneous water heater is suitable for operation with preheated water. • Water is heated directly at the draw-off point, which prevents thermal losses in the cylinder or pipework.

Installation • Quick and easy installation using the improved PROFI-RAPID installation system. • The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is also suitable for commonly used fixing points. • Easy and secure wall mounting thanks to direct fitting through the appliance back panel. • Fast, universal water connection from above through external 3/8“ connections. Can be installed with a non-pressurised or pressure-tested tap and with plastic pipework. • Easy mains connection as the power cable is prepared for permanent connection as standard; the cable is included in the standard delivery. Upward cable routing avoids cabling in visible lower areas. • An installer can adjust the output to suit individual needs. • A rapid fault analysis is enabled by the LED diagnostic traffic light. • For installation, the appliance cover and internal assembly can be completely removed from the back panel without tools.

Safety • The bare wire heating system is suitable for hard and soft water. • A qualified contractor can activate anti-scalding protection in order to permanently limit the water outlet temperature. • The multi stage electronic safety concept comprises a high limit temperature switch, sensor controlled monitoring of heating element temperature, and air bubble detection.

		DCE 11/13 RC
Part number		**230771**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	11,2/13,5
Rated output 1	kW	10,1/12,2
Rated output 2	kW	11,2/13,5
Rated output 3	kW	12,1/14,5
Rated current	A	18,7/19,5
Rated current 1	A	17,8/18,5
Rated current 2	A	18,7/19,5
Rated current 3	A	19,4/20,2

next page >

		DCE 11/13 RC
Fuse protection	A	16/20
Fuse protection 1	A	16/20
Fuse protection 2	A	16/20
Fuse protection 3	A	20/20
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	909
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1100
Switch-on water flow rate	l/min	>2,5
IP rating		IP24
Temperature setting	°C	20-60
Colour		white
Height	mm	293
Width	mm	188
Depth	mm	85
Weight	kg	2.40
Energy efficiency class A+ -> F		A

Wireless remote control, power cable, tee and flexible pressure connection hose included in standard delivery.

DCE 11/13



DCE 11/13

Benefits
- Exceptionally slimline, compact design
- Especially comfortable thanks to electronic power control with 3i technology
- Quick installation with PROFI-RAPID
- Undersink installation
- Multi stage electronic safety concept
- Selectable connected load 11 kW or 13.5 kW

Application • This instantaneous water heater with electronic closed-loop control needs very little space due to its compact design. The appliance is uniquely flat thanks to its low installation depth, making it ideal for space saving installation under a washbasin or kitchen sink. • In commercial settings, it is suitable for cleaning rooms or sanitary facilities with multiple hand washbasins. • International: with high inlet temperatures, also suitable for showers.

Convenience features • 3i technology ensures accurate preferred temperature delivery up to the output limit. • The water is heated fast by the bare wire heating system. Electronic open-loop control keeps the preferred temperature constant up to the output limit. It is variably adjusted by means of the rotary selector. • The connected load can be easily selected on the appliance.

Efficiency • 3i technology ensures energy and water savings of up to 30 % through electronic output control. Three sensors ensure that the set temperature is achieved to the exact degree up to the output limit. • Adding cold water at the tap is not necessary, as only the required energy is used. This further improves the overall efficiency of the appliance. • The instantaneous water heater can be operated with preheated water. • Water is heated directly at the draw-off point, which prevents thermal losses in the cylinder or pipework.

Installation • Quick and easy installation using the improved PROFI-RAPID installation system. • The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is also suitable for commonly used fixing points. • Straightforward, stable wall mounting: direct fitting through the appliance back panel enables easy compensation for any wall unevenness. • Fast, universal water connection from above through external 3/8“ connections. Installation with a non-pressurised or pressure-tested tap; connection to plastic pipework is also possible. • Easy mains connection as the power cable is prepared for permanent connection as standard; the cable is included in the standard delivery. Upward cable routing avoids cabling in visible lower areas. • An installer can adjust the output to suit individual needs. • Fast fault analysis with LED diagnostic traffic light. • For installation, the appliance cover and entire internal assembly can be separated from the back panel without tools.

Safety • The bare wire heating system is suitable for hard and soft water. • An installer can activate anti-scalding protection, which permanently limits the water outlet temperature. • The multi stage electronic safety concept comprises a high limit temperature switch, sensor controlled monitoring of heating element temperature, and air bubble detection.

		DCE 11/13
Part number		**230770**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	11,2/13,5
Rated output 1	kW	10,1/12,2
Rated output 2	kW	11,2/13,5
Rated output 3	kW	12,1/14,5
Rated current	A	18,7/19,5
Rated current 1	A	17,8/18,5
Rated current 2	A	18,7/19,5
Rated current 3	A	19,4/20,2
Fuse protection	A	16/20
Fuse protection 1	A	16/20
Fuse protection 2	A	16/20

next page >

		DCE 11/13
Fuse protection 3	A	20/20
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	909
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1100
Switch-on water flow rate	l/min	>2,5
IP rating		IP24
Temperature setting	°C	20 - 60
Colour		white
Height	mm	293
Width	mm	188
Depth	mm	99
Weight	kg	2.10
Energy efficiency class A+ -> F		A

Standard delivery: Power cable, tee and flexible pressure connection hose.

DCE 11/13 H



DCE 11/13 H

Benefits
- Exceptionally slimline, compact design
- Especially comfortable thanks to electronic power control with 3i technology
- Quick installation with PROFI-RAPID
- Oversink installation
- Multi stage electronic safety concept
- With power cable as standard
- Variable temperature selection via rotary selector

Application • This instantaneous water heater with electronic open-loop control needs very little space due to its compact design. Thanks to its exceptionally flat installation depth, this appliance is ideal for space saving oversink installation, e.g. for the kitchen sink. • In commercial settings, the instantaneous water heater is suitable for sinks in cleaning rooms. • Internationally, the appliance can also be used for showers if there are high inlet temperatures.

Convenience features • 3i technology with three sensors ensures that the preferred temperature is achieved to the exact degree up to the output limit. • The water is heated fast by the bare wire heating system. Electronic open-loop control keeps the preferred temperature constant. • The preferred temperature is set manually via a rotary selector.

Efficiency • 3i technology ensures energy and water savings of up to 30 % through electronic output control. Energy savings are further assured by the appliance only using the amount of energy it actually requires. There is no need to add cold water at the tap, which additionally enhances the overall efficiency of the appliance. • Water is heated directly at the draw-off point, which prevents thermal losses in the cylinder or pipework. • The instantaneous water heater is suitable for operation with preheated water.

Installation • Quick installation is made possible with the improved PROFI-RAPID installation system. • The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is also suitable for commonly used fixing points. • Straightforward, stable wall mounting: direct fitting through the appliance back panel enables easy compensation for any wall unevenness and drill hole discrepancies. • Quick, universal water connection from below through external G 1/2 A connections. Installation with a non-pressurised or pressure-tested tap. • Easy mains connection as the power cable is prepared for permanent connection as standard; the cable is included in the standard delivery. Upward cable routing avoids cabling in visible lower areas. • An installer can adjust the output to suit individual needs. • An LED diagnostic traffic light is integrated to be able to analyse faults quickly. • For installation, the appliance cover and internal assembly can be completely removed from the back panel without tools.

Safety • The bare wire heating system is suitable for hard and soft water. • To permanently limit the outlet temperature of the water, an installer can activate anti-scalding protection. • The multi stage electronic safety concept comprises a high limit temperature switch, sensor controlled monitoring of the heating element temperature, and detection of air bubbles in the system.

		DCE 11/13 H
Part number		**232792**
Specification		
Rated voltage	V	400
Rated voltage 1	V	380
Rated voltage 2	V	400
Rated voltage 3	V	415
Rated output	kW	11,2/13,5
Rated output 1	kW	10,1/12,2
Rated output 2	kW	11,2/13,5
Rated output 3	kW	12,1/14,5
Rated current	A	18,7/19,5
Rated current 1	A	17,8/18,5
Rated current 2	A	18,7/19,5
Rated current 3	A	19,4/20,2
Fuse protection	A	16/20
Fuse protection 1	A	16/20
Fuse protection 2	A	16/20

next page >

		DCE 11/13 H
Fuse protection 3	A	20/20
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/-
Phases		3/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 415 V)	µS/cm	1111
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 380 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 400 V)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold >25 °C and 415 V)	µS/cm	909
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 415 V)	Ω cm	900
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 380 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 400 V)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold >25 °C and 415 V)	Ω cm	1100
Switch-on water flow rate	l/min	>2,5
IP rating		IP24
Temperature setting	°C	20-60
Colour		white
Height	mm	293
Width	mm	188
Depth	mm	99
Weight	kg	2.20
Energy efficiency class A+ -> F		A

DCE 11/13 H + MEKD



Benefits
- Compact instantaneous water heater and special MEKD wall mounted tap in one packing unit
- Optimum complete package for supplying one kitchen sink or one utility sink

Description • DHW set with electronic compact instantaneous water heater DCE 11/13 H for oversink installation, with mono lever wall mounted tap for kitchen or utility sinks.

DCE 11/13 H + MEKD

		DCE 11/13 H + MEKD
Part number		**205967**

Set components		DCE 11/13 H + MEKD
1	Type	DCE 11/13
	Qty	1
		Compact instantaneous water heater with electronic closed-loop control
	Page	30

Application areas

Rated output: Please note the rated output and fuse protection when selecting an instantaneous water heater

Starting flow rate: Please note the starting flow rate of the instantaneous water heater when selecting your fitting



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	L/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE-X 6/8 Premium																																										
DCE-X 10/12 Premium																																										



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	L/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE-S 6/8 Plus																																										
DCE-S 10/12 Plus																																										



	kW	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
	L/min	1,0	1,1	1,2	1,3	1,4	1,5	1,6	1,7	1,8	1,9	2,0	2,1	2,2	2,3	2,4	2,5	2,6	2,7	2,8	2,9	3,0	3,1	3,2	3,3	3,4	3,5	3,6	3,7	3,8	3,9	4,0	4,1	4,2	4,3	4,4	4,5	4,6	4,7	4,8	4,9	5,0
DCE-C 6/8 Trend																																										
DCE-C 10/12 Trend																																										

Full electronic control
DCE-X Premium 38
Electronic closed-loop control
DCE-S Plus 40
Electronic open-loop control
DCE-C Trend 42

DCE-X Premium



DCE-X 6/8 Premium

Benefits

- Easy operation via large, illuminated multifunction display
- Energy saving operation with ECO function
- Fully transparent costs thanks to water and power consumption indicator
- High quality design | Made in Germany
- Quick temperature selection with two memory buttons
- Safe operation thanks to extensive range of convenience and safety functions
- Quick installation with PROFI-RAPID
- Selectable output – can be adjusted internally
- Suitable for preheated water up to 55 °C with reheating and up to a maximum of 70 °C without reheating.
- Instant hot water thanks to rapid and maintenance-free bare wire heating system

Application • This space saving compact instantaneous water heater ensures the supply of DHW even to multiple draw-off points – for example a shower, kitchen sink and washbasin. In commercial settings, cleaning rooms or multiple washbasins in sanitary facilities can be supplied. The unvented, pressure-tested appliance can be connected to all commercially available taps.

Convenience features • The fully electronically controlled compact instantaneous water heater ensures accurate temperature delivery at all times thanks to the electronic flow rate control. • The temperatures are variably and digitally adjusted in very precise 0.5 °C increments. • The large multifunction display with white backlighting not only shows the set temperature but also provides information on the current power consumption, energy consumption, flow rate and time. Status and service information is also displayed. • The instantaneous water heater provides a memory function for 2 programmable preferred temperatures as well as a wide range of comfort functions, including various wellness programs and automated bath filling. • The individually adjustable temperature limiting function can be used for anti-scalding protection and childproofing. • An LED indicator provides information about heating operation. • The keypad lock protects the appliance against unintentional adjustment.

Efficiency • The appliance ensures energy and water savings of up to 30 % through fully electronic output control with 4i technology. Three sensors and an additional motorised valve ensure that the set temperature is achieved to the exact degree at all times. Only the amount of energy actually required is expended; there is no need to add cold water at the tap. As there are no thermal losses in the cylinder or pipework either, the instantaneous water heater is impressively efficient. Also contributing to this efficiency is the individually selectable ECO mode. • The current water and power consumption can be displayed. • The appliance is suitable for operation with preheated water from solar thermal and heat pump systems.

Installation • Quick and easy installation with the PROFI-RAPID installation system. • Straightforward, stable wall mounting: direct fitting through the appliance back panel enables easy compensation for any wall unevenness and drill hole discrepancies. • Fast universal water connection using 1/2“ connections. The brass water connections at the bottom enable straightforward surface mounting. Optional accessories are available for flush mounting with non-visible water connections. • Fitting to plastic pipework is also possible (follow the manufacturer‘s instructions). • Easy and flexible electrical connection at the top or bottom when flush mounting and at the bottom or sides when surface mounting. • The appliance cover can be easily opened using a central screw. • The entire inner assembly can be detached from the back panel. • Fast fault analysis with LED diagnostic traffic light.

Safety • The temperature can be permanently limited by an installer to suit individual needs. • The bare wire heating system is suitable for hard and soft water. • Multi stage electronic safety concept with air detection.

		DCE-X 6/8 Premium	DCE-X 10/12 Premium
Part number		**238158**	**238159**
Specification			
Rated voltage	V	220	220
Rated voltage 1	V	220	220
Rated voltage 2	V	230	230
Rated voltage 3	V	240	240
Rated output	kW	6.0/8.0	10.0/12.0
Rated output 1	kW	6.0/8.0	10.0/12.0
Rated output 2	kW	6.6/8.7	11.0/13.1
Rated output 3	kW	7.2/9.6	12.0/14.3
Rated current	A	27.3/36.4	45.5/54.5

next page >

		DCE-X 6/8 Premium	DCE-X 10/12 Premium
Rated current 1	A	27.3/36.4	45.5/54.5
Rated current 2	A	28.5/38.0	47.8/57.0
Rated current 3	A	30.0/40.0	50.0/59.5
Fuse protection	A	30/40	50/60
Fuse protection 1	A	30/40	50/60
Fuse protection 2	A	30/40	50/60
Fuse protection 3	A	30/40	50/60
Frequency	Hz	50/60	50/60
Frequency 1	Hz	50/60	50/60
Frequency 2	Hz	50/60	50/60
Frequency 3	Hz	50/60	50/60
Phases		1/N/PE	1/N/PE
Conductivity σ15 ≤	µS/cm	910	910
Resistivity ρ15 ≥	Ω cm	1100	1100
Switch-on water flow rate	l/min	1.3	1.3
IP rating		IP25	IP25
Temperature setting	°C	Off, 20 - 60	Off, 20 - 60
Colour		white	white
Height	mm	372	372
Width	mm	217	217
Depth	mm	109	109
Weight	kg	2.50	2.50
Energy efficiency class A+ -> F		A	A

DCE-S Plus



DCE-S 6/8 Plus

Benefits
- Degree-accurate desired temperature with 3i technology and electronic control
- High quality design | Made in Germany
- Quick installation with PROFI-RAPID
- Selectable output – can be adjusted internally
- Suitable for preheated water up to 55 °C with reheating and up to a maximum of 70 °C without reheating.
- Variable temperature selection via rotary selector
- High safety level as anti-scalding protection can be permanently activated
- Instant hot water thanks to rapid and maintenance-free bare wire heating system

Application • This compact instantaneous water heater supplies several draw-off points with DHW, for example for the shower and kitchen sink. In commercial settings, water can be supplied to cleaning rooms or multiple washbasins in sanitary facilities. The unvented, pressure-tested appliance can be connected to all commercially available taps.

Convenience features • The instantaneous water heater with electronic closed-loop control ensures accurate preferred temperature delivery up to the maximum output. It can be variably adjusted via a manual rotary selector on the appliance.

Efficiency • The 3i technology ensures energy and water savings of up to 30 % through electronic output control. • Energy savings are further assured as only the amount of energy actually required is used. • Furthermore, thermal losses in the cylinder and pipework are prevented as the water is heated directly at the draw-off point. • Cold water does not need to be added to achieve the preferred temperature, thereby improving the overall efficiency of the appliance. • The compact instantaneous water heater is suitable for operation with preheated water from solar thermal systems or heat pumps.

Installation • Quick and easy installation is ensured with the improved PROFI-RAPID installation system. Direct fitting through the appliance back panel enables easy compensation of any unevenness in the wall and drill hole discrepancies. • Fast, universal water connection from above is facilitated through the 1/2“ connections. The brass water connections at the bottom enable straightforward surface mounting. Optional accessories are available for flush mounting with non-visible water connections. • Fitting to plastic pipework is also possible if the manufacturer‘s instructions are followed. • Simple and flexible mains connection, which is made from below or above in the case of flush-mounted installation. With surface-mounted installation, connection is possible from below or from the side. • The appliance cover can be easily opened using a central screw. • The entire inner assembly can be detached from the back panel. • Rapid fault analysis is assured with the integral LED diagnostic traffic light.

Safety • The temperature can be limited by an installer to suit individual needs. • The bare wire heating system is suitable for hard and soft water. • Multi stage electronic safety concept with high limit safety cut-out and air detection.

		DCE-S 6/8 Plus	DCE-S 10/12 Plus
Part number		**238153**	**238154**
Specification			
Rated voltage	V	220	220
Rated voltage 1	V	220	220
Rated voltage 2	V	230	230
Rated voltage 3	V	240	240
Rated output	kW	6.0/8.0	10.0/12.0
Rated output 1	kW	6.0/8.0	10.0/12.0
Rated output 2	kW	6.6/8.7	11.0/13.1
Rated output 3	kW	7.2/9.6	12.0/14.3
Rated current	A	27.3/36.4	45.5/54.5
Rated current 1	A	27.3/36.4	45.5/54.5
Rated current 2	A	28.5/38.0	47.8/57.0
Rated current 3	A	30.0/40.0	50.0/59.5
Fuse protection	A	30/40	50/60
Fuse protection 1	A	30/40	50/60
Fuse protection 2	A	30/40	50/60

next page >

		DCE-S 6/8 Plus	DCE-S 10/12 Plus
Fuse protection 3	A	30/40	50/60
Frequency	Hz	50/60	50/60
Frequency 1	Hz	50/60	50/60
Frequency 2	Hz	50/60	50/60
Frequency 3	Hz	50/60	50/60
Phases		1/N/PE	1/N/PE
Conductivity σ15 ≤	µS/cm	910	910
Resistivity ρ15 ≥	Ω cm	1100	1100
Switch-on water flow rate	l/min	1.3	1.3
IP rating		IP25	IP25
Temperature setting	°C	20-60	20-60
Colour		white	white
Height	mm	372	372
Width	mm	217	217
Depth	mm	109	109
Weight	kg	2.50	2.50
Energy efficiency class A+ -> F		A	A

DCE-C Trend



DCE-C 6/8 Trend

Benefits
- Constant desired temperature with 2i technology and electronic control
- Quick installation with PROFI-RAPID
- Selectable output – can be adjusted internally
- High quality design | Made in Germany
- Suitable for preheated water up to 55 °C with reheating and up to a maximum of 70 °C without reheating.
- Permanently set DHW temperature – preferred temperature with cold water added at the tap
- Instant hot water thanks to rapid and maintenance-free bare wire heating system

Application • This compact instantaneous water heater with electronic open-loop control ensures the supply of DHW to multiple draw-off points – for example shower and kitchen sink or washstand and washbasin. In commercial settings, water can be supplied to cleaning rooms or multiple washbasins in sanitary facilities. The unvented, pressure-tested appliance can be connected to all commercially available taps.

Convenience features • The appliance supplies DHW at a constant fixed temperature up to the maximum output. • For the preferred temperature, cold water is mixed in at the tap.

Efficiency • Electronic output control with 2i technology, including two sensors which ensure that the preset temperature level is reached up to the output limit. For this, only the amount of energy actually required is expended. Furthermore, the water is heated directly at the draw-off point, which prevents thermal losses in the cylinder and pipework, thereby improving energy efficiency. • The instantaneous water heater is suitable for preheated water from solar thermal and heat pump systems.

Installation • Fast wall mounting with the improved PROFI-RAPID installation system. Direct fitting through the appliance back panel enables easy compensation of drill hole discrepancies. • The appliance cover is opened with a central screw. • For fast, universal water connection, 1/2“ brass water connections are integrated, located at the bottom for surface mounting. Flush mounting for non-visible water connections is possible with optional accessories. • Fitting to plastic pipework is also possible if the manufacturer‘s instructions are followed. • Easy and flexible mains connection at the top or bottom when flush mounting and at the bottom or sides when surface mounting. • The selectable output can be set internally. • An LED diagnostic traffic light is integrated for fast fault analysis. • The internal assembly can be completely removed with no back panel.

Safety • The bare wire heating system is suitable for hard and soft water. • Multi stage electronic safety concept with air detection.

		DCE-C 6/8 Trend	DCE-C 10/12 Trend
Part number		**238148**	**238149**
Specification			
Rated voltage	V	220	220
Rated voltage 1	V	220	220
Rated voltage 2	V	230	230
Rated output	kW	6.0/8.0	10.0/12.0
Rated output 1	kW	6.0/8.0	10.0/12.0
Rated output 2	kW	6.6/8.7	11.0/13.1
Rated current	A	27.3/36.4	45.5/54.5
Rated current 1	A	27.3/36.4	45.5/54.5
Rated current 2	A	28.5/38.0	47.8/57.0
Rated current 3	A		50.0/59.5
Fuse protection	A	30/40	50/60
Fuse protection 1	A	30/40	50/60
Fuse protection 2	A	30/40	50/60
Frequency	Hz	50/60	50/60
Frequency 1	Hz	50/60	50/60
Frequency 2	Hz	50/60	50/60
Frequency 3	Hz		50/60
Phases		1/N/PE	1/N/PE


next page >


		DCE-C 6/8 Trend	DCE-C 10/12 Trend
Conductivity σ15 ≤	µS/cm	910	910
Resistivity ρ15 ≥	Ω cm	1100	1100
Switch-on water flow rate	l/min	1.3	1,3
IP rating		IP25	IP25
Temperature setting	°C	55	55
Colour		white	white
Height	mm	372	372
Width	mm	217	217
Depth	mm	97	97
Weight	kg	2.50	2.50
Energy efficiency class A+ -> F		A	A


Application areas

Rated output: Please note the rated output and fuse protection when selecting an instantaneous water heater

Starting flow rate: Please note the starting flow rate of the instantaneous water heater when selecting your fitting







Electronic closed-loop control
EIL Premium 46
Hydraulic control, pressurised
EIL Plus 48
Hydraulic control, non-pressurised
EIL Trend 50

EIL Premium



EIL 3 Premium

Benefits
- Suitable for oversink and undersink installation with a single appliance
- Can be operated with pressurised and non-pressurised taps
- Accurate temperature delivery up to the maximum output
- Internal permanent set temperature for childproofing and anti-scalding protection
- Special aerator for perfect flow pattern
- Mini instantaneous water heater with electronic closed-loop control for a hand washbasin
- Maintenance-free bare wire heating system
- 3.5 kW version comes with standard plug (Product: 200134)

Application • This mini instantaneous water heater with electronic closed-loop control supplies DHW reliably and efficiently to one washbasin. • With higher inlet temperatures, the appliance is also suitable for showers. • The appliance can be used with either a pressure-tested or a non-pressurised tap.

Convenience features • The mini instantaneous water heater has a control PCB and an outlet temperature sensor. The flow rate can be limited internally. • Preferred temperatures are accurately delivered up to the maximum output and the temperature can be variably limited internally thanks to the temperature scale. • The special aerator ensures a perfect water flow pattern and is fitted with an integral flow rate controller. • In the case of high inlet temperatures, anti-scalding protection automatically activates and adjusts the output.

Efficiency • Thermal losses in the cylinder and pipework are prevented, as instantaneous water heaters heat the water directly at the draw-off point, which saves water and energy. • Electronic output control for energy and water saving operation additionally improves efficiency. • In conjunction with the outlet temperature sensor, the control PCB ensures that the set temperature is achieved to the exact degree. For this, only the amount of energy actually required is expended; there is no need to add cold water at the tap. • The appliance is suitable for preheated water from solar thermal systems or heat pumps.

Installation • The appliance is secured at 2 points, and the back panel serves as a drilling template, if required. • Fast, universal water connection with external metal water fittings. • Simple mains connection as the power cable is prepared for permanent connection as standard. • An LED diagnostic traffic light is integrated for fast fault analysis.

Safety • The maintenance-free bare wire heating system is suitable for hard and soft water. • The safety system monitors the temperature electronically. The appliance switches off automatically in the event of overpressure.

		EIL 3 Premium	EIL 4 Premium	EIL 6 Premium	EIL 7 Premium
Part number		**200134**	**200135**	**200136**	**200137**
Specification					
Rated voltage	V	230	230	230	400
Rated voltage 1	V	200	200	200	380
Rated voltage 2	V	220	220	220	400
Rated voltage 3	V	230	230	230	
Rated voltage 4	V	240	240	240	
Rated output	kW	3,53	4,4	5,7	6,5
Rated output 1	kW	2,7	3,3	4,3	5,9
Rated output 2	kW	3,2	4,0	5,2	6,5
Rated output 3	kW	3,53	4,4	5,7	
Rated output 4	kW	3,8	4,8	6,2	
Rated current	A	15,2	19,1	24,7	16,3
Rated current 1	A	13,3	16,7	21,6	15,5
Rated current 2	A	14,5	18,2	23,6	16,3
Rated current 3	A	15,2	19,1	24,7	
Rated current 4	A	15,8	20,0	25,8	
Fuse protection	A	16	20	25	20
Fuse protection 1	A	16	20	25	16
Fuse protection 2	A	16	20	25	20
Fuse protection 3	A	16	20	25	
Fuse protection 4	A	16	20	32	
Frequency	Hz	50/60	50/60	50/60	50/-
Frequency 1	Hz	50/60	50/60	50/60	50/-
Frequency 2	Hz	50/60	50/60	50/60	50/-
Frequency 3	Hz	50/60	50/60	50/60	

next page >

		EIL 3 Premium	EIL 4 Premium	EIL 6 Premium	EIL 7 Premium
Frequency 4	Hz	50/60	50/60	50/60	
Phases		1/N/PE	1/N/PE	1/N/PE	2/PE
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	µS/cm	1000	1000	1000	1000
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	770	770	770	770
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	Ω cm	1000	1000	1000	1000
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1300	1300	1300	1300
Switch-on water flow rate	l/min	>1,5	>1.8	>2,2	>2.2
IP rating		IP25	IP25	IP25	IP25
Temperature setting	°C	30 – 50	30 – 50	30 – 50	30 – 50
Colour		white	white	white	white
Height	mm	143	143	143	143
Width	mm	190	190	190	190
Depth	mm	82	82	82	82
Weight	kg	1.50	1.50	1.50	1.50
Energy efficiency class A+ -> F		A	A	A	A

EIL Plus



EIL 3 Plus

Benefits

- Mini instantaneous water heater with hydraulic control for a hand washbasin
- Can be operated with pressurised and non-pressurised taps
- For undersink installation
- Special aerator for perfect flow pattern
- Maintenance-free bare wire heating system
- 3.5 kW version comes with standard plug (Product: 200138)

Application • This hydraulically controlled mini instantaneous water heater supplies DHW reliably and efficiently to one washbasin. • The unvented, pressure-tested appliance is suitable for all commercially available pressure taps.

Convenience features • The appliance has a flow switch and automatically controls the flow rate. • Preferred temperatures are delivered with near constant accuracy up to the maximum output by mixing at the tap. • The system hydraulically controls the heating output in a single stage, subject to the flow rate. • A special aerator ensures a perfect water flow pattern. • The integral flow controller can be easily fitted in existing taps.

Efficiency • The instantaneous water heater heats the water directly at the draw-off point, saving water and energy by preventing thermal losses in the cylinder or pipework.

Installation • The appliance is secured at 2 points, and the back panel serves as a drilling template, if required. • Fast, universal water connection with external metal water fittings. • Simple mains connection as the power cable is prepared for permanent connection as standard.

Safety • The bare wire heating system is suitable for hard and soft water. • The appliance switches off automatically in the event of overpressure.

		EIL 3 Plus	EIL 4 Plus	EIL 6 Plus	EIL 7 Plus
Part number		**200138**	**200139**	**200140**	**200141**
Specification					
Rated voltage	V	230	230	230	400
Rated voltage 1	V	200	200	200	380
Rated voltage 2	V	220	220	220	400
Rated voltage 3	V	230	230	230	415
Rated voltage 4	V	240	240	240	
Rated output	kW	3,53	4,4	5,7	6,5
Rated output 1	kW	2,7	3,3	4,3	5,9
Rated output 2	kW	3,2	4,0	5,2	6,5
Rated output 3	kW	3,53	4,4	5,7	7,0
Rated output 4	kW	3,8	4,8	6,2	
Rated current	A	15,2	19,1	24,7	16,3
Rated current 1	A	13,3	16,7	21,6	15,5
Rated current 2	A	14,5	18,2	23,6	16,3
Rated current 3	A	15,2	19,1	24,7	16,9
Rated current 4	A	15,8	20	25,8	
Fuse protection	A	16	20	25	20
Fuse protection 1	A	16	20	25	16
Fuse protection 2	A	16	20	25	20
Fuse protection 3	A	16	20	25	20
Fuse protection 4	A	16	20	32	
Frequency	Hz	50/60	50/60	50/60	50
Frequency 1	Hz	50/60	50/60	50/60	50/60
Frequency 2	Hz	50/60	50/60	50/60	50/60
Frequency 3	Hz	50/60	50/60	50/60	50/-
Frequency 4	Hz	50/60	50/60	50/60	
Phases		1/N/PE	1/N/PE	1/N/PE	2/PE
Conductivity σ15 ≤	µS/cm	909	909	909	909
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	µS/cm	909	909	909	909
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	909	909	909	909
Resistivity ρ15 ≥	Ω cm	1100	1100	1100	1100

next page >

		EIL 3 Plus	EIL 4 Plus	EIL 6 Plus	EIL 7 Plus
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	Ω cm	1100	1100	1100	1100
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1100	1100	1100	1100
Water connection		G 3/8 A	G 3/8 A	G 3/8 A	G 3/8 A
Switch-on water flow rate	l/min	> 1,6	> 2,0	> 2,6	>2,6
IP rating		IP25	IP25	IP25	IP25
Colour		white	white	white	white
Height	mm	143	143	143	143
Width	mm	190	190	190	190
Depth	mm	82	82	82	82
Weight	kg	1.40	1.40	1.40	1.40
Energy efficiency class A+ -> F		A	A	A	A

EIL Trend



EIL 3 Trend

Benefits
- Mini instantaneous water heater with hydraulic control for a hand washbasin
- Operation with non-pressurised tap
- Suitable for oversink and undersink installation with a single appliance
- Special aerator for perfect flow pattern
- Maintenance-free bare wire heating system
- 3.5 kW version comes with standard plug (Product: 200142)

Application • This hydraulically controlled mini instantaneous water heater supplies DHW to one washbasin. • The appliance is for oversink or undersink installation and is suitable for all commercially available non-pressurised taps.

Convenience features • The mini instantaneous water heater is equipped with a flow switch and the appliance hydraulically controls the heating output in a single stage, subject to the flow rate. • Preferred temperatures are delivered with near constant accuracy up to the maximum output by mixing in cold water at the tap. • The appliance hydraulically controls the heating output in a single stage, subject to the flow rate. • The standard delivery includes a special aerator that ensures an optimum water flow pattern and that is equipped with an integral flow rate controller.

Efficiency • The mini instantaneous water heater heats the water directly at the draw-off point, which saves water and energy by preventing thermal losses in the cylinder and pipework.

Installation • The appliance is secured at 2 points, and the back panel serves as a drilling template, if required. Fast, universal water connection with external metal water fittings. • Simple mains connection as the power cable is prepared for permanent connection as standard.

Safety • The bare wire heating system is suitable for hard and soft water. • The appliance switches off automatically in the event of overpressure.

		EIL 3 Trend
Part number		**200142**
Specification		
Rated voltage	V	230
Rated voltage 1	V	200
Rated voltage 2	V	220
Rated voltage 3	V	230
Rated voltage 4	V	240
Rated output	kW	3,53
Rated output 1	kW	2,7
Rated output 2	kW	3,2
Rated output 3	kW	3,53
Rated output 4	kW	3,8
Rated current	A	15,2
Rated current 1	A	13,3
Rated current 2	A	14,5
Rated current 3	A	15,2
Rated current 4	A	15,8
Fuse protection	A	16
Fuse protection 1	A	16
Fuse protection 2	A	16
Fuse protection 3	A	16
Fuse protection 4	A	16
Frequency	Hz	50/60
Frequency 1	Hz	50/60
Frequency 2	Hz	50/60
Frequency 3	Hz	50/60
Frequency 4	Hz	50/60
Phases		1/N/PE
Conductivity σ15 ≤	µS/cm	909
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	µS/cm	909
Conductivity σ15 ≤ (at ϑcold > 25 °C)	µS/cm	909
Resistivity ρ15 ≥	Ω cm	1100

next page >

		EIL 3 Trend
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	Ω cm	1100
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	Ω cm	1100
Water connection		G 3/8 A
Switch-on water flow rate	l/min	> 1,0
IP rating		IP25
Colour		white
Height	mm	143
Width	mm	190
Depth	mm	82
Weight	kg	1.40

Accessories for comfort and compact instantaneous water heaters

LR 1-A



LR 1-A

Benefits

- Load shedding relay for priority control
- Installed dimension = one horizontal pitch as defined by DIN 43880

Description • This load shedding relay for priority control is used, for example, in conjunction with electric storage heaters or to mutually interlock two instantaneous water heaters. • The installed dimension corresponds to one horizontal pitch according to DIN 43880.


		LR 1-A
Part number		**001786**
Specification		
Installation type		DIN rail
Breaking capacity	A	1

Small water heaters, non-pressurised		55
Small water heaters, pressurised		61
Accessories for small water heaters, pressurised		71
Wall mounted cylinder		77
Accessories for wall mounted cylinders		91
Floor mounted cylinder		95
Accessories for floor mounted cylinders, pressurised		105


Application areas

Nominal capacity









Undersink
- **ESH U-N Trend** 56
- **ESH U-N Trend +A** 57

Oversink
- **ESH O-N Trend** 58
- **ESH O-N Trend +A** 59

ESH U-N Trend



ESH 5 U-N Trend

Benefits
- Rapid supply of domestic hot water with no waiting, thanks to non-pressurised operation
- Variable temperature selection
- High limit safety cut-out resettable by disconnecting the mains plug
- Power cable with standard plug
- Operation with non-pressurised tap

Application • These non-pressurised, vented small water heaters provide an energy saving and efficient supply of warm or hot water to individual draw-off points, for example a washbasin or the kitchen sink. • The appliances for undersink installation can be connected to all commercially available non-pressurised taps.

Convenience features • The preferred temperature can be variably adjusted. • The heat-up phase is visually indicated. • Large quantities of DHW can be drawn off thanks to the special geometry of the heating element.

Installation • The PROFI-RAPID installation system enables very fast installation. The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is suitable for commonly used fixing points. • The connecting cable comes fitted with a standard plug. Any excess cable can be housed in the practical cable storage compartment in the appliance back panel.

Safety • The robust copper tubular heater ensures a long service life. • Safe commissioning thanks to resettable high limit safety cut-out.

		ESH 5 U-N Trend	ESH 10 U-N Trend
Part number		**201386**	**201391**
Specification			
Rated output 1	kW	2	2
Power supply		1/N/PE	1/N/PE
Rated voltage 1	V	230	230
Rated current 1	A	8,7	8.7
Frequency	Hz	50-60	50-60
Energy efficiency class A+ -> F		A	A
Standby energy consumption/24 h at 65 °C	kWh	0.25	0.32
Nominal capacity	l	5	10
Mixed water amount at 40 °C	l	9,3	19
Temperature setting range	°C	35 – 85	35 – 85
Version		Small water heater	Small water heater
Type		non-pressurised	non-pressurised
Installation type		Undersink	Undersink
With tap		-	-
Colour		white	white
Operation		manual	manual
Temperature limit		•	•
IP rating		IP24 D	IP24 D
Height	mm	415	506
Width	mm	252	296
Depth	mm	233	276
Weight	kg	3.10	5.00

Installation template (Product: 201386)

ESH U-N Trend +A



ESH 5 U-N Trend +A

Description • DHW sets consisting of ESH 5 U-N Trend or ESH 10 U-N Trend and a non-pressurised, vented mono lever mixer tap.

		ESH 5 U-N Trend +A	ESH 10 U-N Trend +A
Part number		**201387**	**201392**

Set components		**ESH 5 U-N Trend +A**	**ESH 10 U-N Trend +A**
1	Type	ESH 5 U-N Trend	ESH 10 U-N Trend
	Qty	1	1
		Small water heater, non-pressurised, undersink	Small water heater, non-pressurised, undersink
	Page	56	56

ESH 5 U-N Trend (Product: 201387)
Mono lever mixer tap (Product: 201387)
ESH 10 U-N Trend (Product: 201392)
Mono lever mixer tap (Product: 201392)

Oversink

ESH O-N Trend



ESH 5 O-N Trend

Benefits

- Rapid supply of domestic hot water with no waiting, thanks to non-pressurised operation
- Variable temperature selection
- High limit safety cut-out resettable by disconnecting the mains plug
- Power cable with standard plug
- Operation with non-pressurised tap

Application • These non-pressurised, vented small water heaters are suitable for DHW supply to individual draw-off points, e.g. to a sink in the utility room or kitchen. • The non-pressurised appliances for oversink installation are combined with a non-pressurised tap.

Convenience features • The temperature is variably adjusted via a rotary selector. • The special geometry of the heating element means that large amounts of DHW can be drawn off. • The heat-up phase is visually indicated.

Installation • The PROFI-RAPID installation system ensures quick and straightforward installation. The commonly used fixing points facilitate replacement. Simple wall mounting with the universal mounting rail; an installation template is included in the standard delivery. • Power cable with standard plug.

Safety • The robust copper tubular heater ensures a long service life. • The resettable high limit safety cut-out ensures safe commissioning.

		ESH 5 O-N Trend	ESH 10 O-N Trend
Part number		**201388**	**201393**
Specification			
Rated output 1	kW	2	
Power supply		1/N/PE	1/N/PE
Rated voltage 1	V	230	230
Rated current 1	A	8,7	8.7
Frequency	Hz	50-60	50-60
Energy efficiency class A+ -> F		A	A
Standby energy consumption/24 h at 65 °C	kWh	0.25	0.31
Nominal capacity	l	5	10
Mixed water amount at 40 °C	l	9,3	19
Temperature setting range	°C	35 - 85	35 - 85
Version		Small water heater	Small water heater
Type		non-pressurised	non-pressurised
Installation type		Oversink	Oversink
With tap		-	-
Colour		white	white
Operation		manual	manual
Temperature limit		•	•
IP rating		IP24 D	IP24 D
Height	mm	415	506
Width	mm	252	296
Depth	mm	233	276
Weight	kg	3.10	5.00

Installation template (Product: 201388)

ESH O-N Trend +A



ESH 5 O-N Trend+A

Description • DHW sets consisting of ESH 5 O-N Trend or ESH 10 O-N Trend with non-pressurised, vented mono lever mixer tap.

		ESH 5 O-N Trend+A	ESH 10 O-N Trend +A
Part number		**201389**	**201395**

Set components		**ESH 5 O-N Trend+A**	**ESH 10 O-N Trend +A**
1	Type	ESH 5 O-N Trend	ESH 10 O-N Trend
	Qty	1	1
		Small water heater, non-pressurised, oversink	Small water heater, non-pressurised, oversink
	Page	58	58

Design and technical features as ESH 5 O-N Trend or ESH 10 O-N Trend with non-pressurised mono lever mixer tap in one complete package.
ESH 5 O-N Trend (Product: 201389)
Mono lever mixer tap (Product: 201389)
ESH 10 O-N Trend (Product: 201395)
Mono lever mixer tap (Product: 201395)

Application areas

Nominal capacity



	L	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SHU 5 SLi							■	■														
SHU 10 SLi												■	■									



	L	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SHC 10												■	■									
SHC 15																	■	■				

	L	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ESH 10 U-P Plus												■	■									

	L	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ESH 10 O-P Plus												■	■									

Undersink
- **SHU SLi** 62
- **SHC Stiebel** 64
- **ESH U-P Plus** 66

Oversink
- **ESH O-P Plus** 68

SHU SLi



SHU 5 SLi

Benefits
- Plug-in appliance for electrical connection to any standard safety socket
- Quick DHW heating without delay
- Matching safety assemblies as accessories
- Low energy losses thanks to high grade thermal insulation

Application • These small water heaters supply DHW to multiple draw-off points, e.g. the washbasin in the bathroom and the kitchen sink. • The pressure-tested, unvented appliances can be connected to all commercially available unvented taps.

Convenience features • The energy saving thermostop function prevents unwanted heating of the mixer tap. • The temperature can be variably adjusted between 35 °C and 85 °C via a rotary selector on the appliance. It can also be limited mechanically in four stages. • The heat-up phase is signalled by an indicator lamp.

Efficiency • The water is heated directly at the draw-off point, which prevents thermal losses in the cylinder or pipework. • For low energy losses, the polypropylene inner cylinder is equipped with high quality EPS thermal insulation. • The sensor is immersed directly in the water for fast and accurate temperature capture.

Installation • Straightforward replacement for all standard small water heaters. • The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is also suitable for commonly used fixing points. • The metal threaded water fittings enable secure replacement. • The standard delivery includes a prepared power cable for standard plugs or a permanent connection. Any excess power cable is housed in the cable storage compartment in the appliance back panel.

Safety • The appliance is splashproof. • For a long service life, the small water heater has a robust copper tubular heater with a low surface load. • The resettable high limit safety cut-out ensures safe commissioning of 1 kW and 2 kW appliances. • The mechanical temperature limit can be set in two stages for anti-scalding protection.

		SHU 5 SLi	SHU 10 SLi
Part number		**222151**	**229473**
Specification			
Rated output 1	kW	1.8	1.8
Rated output 2	kW	2.0	2.0
Rated output 3	kW	2.2	2.2
Power supply		1/N/PE	1/N/PE
Rated voltage 1	V	220	220
Rated voltage 2	V	230	230
Rated voltage 3	V	240	240
Rated current 1	A	8.3	8.3
Rated current 2	A	8.7	8.7
Rated current 3	A	9.1	9.1
Fuse protection 2	A	10	10
Frequency	Hz	50-60	50-60
Energy efficiency class A+ -> F		A	A
Standby energy consumption/24 h at 65 °C	kWh	0.29	0.36
Nominal capacity	l	5	10
Mixed water amount at 40 °C	l	10	19
Temperature setting range	°C	35 - 82	35 - 82
Version		Small water heater	Small water heater
Type		pressurised	pressurised
Installation type		Undersink	Undersink
With tap		-	-
Colour		white	white
Cable length	m	0.6	1
Operation		manual	manual
Temperature limit		•	•
IP rating		IP24 D	IP24 D
Height	mm	421	504
Width	mm	263	295
Depth	mm	230	275
Weight	kg	5.20	7.60

next page >

		SHU 5 SLi	SHU 10 SLi
Required accessories			
Part number		**070558**	**070558**
Type		WVT-G3/8	WVT-G3/8
Description		Tee	Tee
Part number		**073499**	**073499**
Type		SVMT	SVMT
Description		Safety assembly for small water heater, pressure-tested, undersink	Safety assembly for small water heater, pressure-tested, undersink

Installation template (Product: 222151) , 229473)

Undersink

SHC Stiebel



SHC 10

Benefits

- Supplies multiple draw-off points via a pressurised connection
- Enamelled pressure-tested steel inner cylinder
- Frost protection setting
- Quick and easy installation

Application • These small water heaters supply multiple draw-off points that have a low DHW demand. • The pressure-tested, unvented appliances can be combined with commercially available pressure taps • They are suitable for undersink installation; they can only be installed with the appropriate safety valve.

Convenience features • The small water heaters offer tailored solutions for decentralised group supply. They heat the water directly at the draw-off point, which prevents energy, water and circulation losses caused by long pipe runs. • The temperature is variably adjusted by means of a rotary selector. • The temperature controller uses a sensor installed directly in the water. • Low energy losses are ensured by the high grade EPS thermal insulation. • The appliance has a 2-stage temperature limit and an automatic frost protection setting. • A visual display indicates when the appliance is heating up.

Installation • Quick and easy wall mounting, a universal mounting rail is included in the standard delivery as well as the installation template. • Secure water connection thanks to metal threaded water fittings. Suitable safety valves are available as accessories.

Safety • Robust copper tubular heater with low surface load. • The pressure-tested steel inner cylinder is equipped with a protective magnesium anode. • Resettable high limit safety cut-out reset button. • The temperature can be limited mechanically in two stages to provide anti-scalding protection and childproofing. • The appliance is splash-proof to protection rating IP 24.

		SHC 10	SHC 15
Part number		**233747**	**234337**
Specification			
Rated output 1	kW	1.4	1.4
Rated output 2	kW	1,5	1.5
Rated output 3	kW	1.6	1.6
Power supply		1/N/PE	1/N/PE
Rated voltage 1	V	220	220
Rated voltage 2	V	230	230
Rated voltage 3	V	240	240
Rated current 1	A	6,2	6.2
Rated current 2	A	6.5	6.5
Rated current 3	A	6.8	6.8
Fuse protection 2	A	10	10
Frequency	Hz	50-60	50-60
Energy efficiency class A+ -> F		A	A
Standby energy consumption/24 h at 65 °C	kWh	0.48	0.49
Nominal capacity	l	10	15
Mixed water amount at 40 °C	l	15,3	23
Mixed water amount at 40 °C (15 °C/60 °C)	l	15,3	23
Temperature setting range	°C	30 - 65	30 - 65
Version		Small water heater	Small water heater
Type		pressurised	pressurised
Installation type		Undersink	Undersink
With tap		-	-
Inner cylinder material		Steel, enamelled	Steel, enamelled
Colour		white	white
Cable length	m	1	1
Operation		manual	manual
Temperature limit		•	•

next page >

Undersink

		SHC 10	SHC 15
IP rating		IP24 D	IP24 D
Height	mm	430	452
Width	mm	280	320
Depth	mm	270	318
Weight	kg	7.20	9.00

Required accessories			
Part number		**073499**	**073499**
Type		SVMT	SVMT
Description		Safety assembly for small water heater, pressure-tested, undersink	Safety assembly for small water heater, pressure-tested, undersink

ESH U-P Plus



ESH 10 U-P Plus

Benefits
- Supplies multiple draw-off points via a pressurised connection
- Variable temperature selection
- Press the reset button to reset the high limit safety cut-out
- Power cable with standard plug
- Suitable for all standard pressure fittings
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These pressure-tested, unvented small water heaters supply DHW to one or more draw-off points with a low demand. The appliances for undersink installation can be combined with all commercially available pressure taps. • The appropriate safety assembly is necessary for installation.

Convenience features • The small water heaters offer a demand-dependent solution for decentralised group supply of warm or hot water at all times. They heat the water directly at the draw-off point. This prevents energy and water losses caused by long pipe runs, as well as circulation losses. High grade thermal insulation additionally reduces energy consumption. • The temperature controller works by means of a temperature sensor immersed directly in the water. • The required temperature is variably adjusted by means of a rotary selector. • An indicator lamp shows when the small water heater is heating up. • The pressure-tested inner cylinder is made from enamelled steel.

Installation • The PROFI-RAPID installation system enables very quick wall mounting. Replacing older appliances is easy, as the design is suitable for commonly used fixing points and a universal mounting rail is included in the standard delivery. • Includes safety valve. Power cable with standard plug.

Safety • The robust copper tubular heater ensures a long service life. • The high limit safety cut-out can be reset after triggering.

		ESH 10 U-P Plus
Part number		**201397**
Specification		
Rated output 1	kW	1.8
Rated output 2	kW	2.0
Rated output 3	kW	2.2
Power supply		1/N/PE
Rated voltage 1	V	220
Rated voltage 2	V	230
Rated voltage 3	V	240
Rated current 1	A	8.3
Rated current 2	A	8.7
Rated current 3	A	9.1
Fuse protection 2	A	10
Frequency	Hz	50-60
Energy efficiency class A+ -> F		A
Standby energy consumption/24 h at 65 °C	kWh	0.36
Nominal capacity	l	10
Mixed water amount at 40 °C	l	18
Temperature setting range	°C	35 - 82
Version		Small water heater
Type		pressurised
Installation type		Undersink
With tap		-
Inner cylinder material		Steel, enamelled
Colour		white
Cable length	m	0.95
Operation		manual
Temperature limit		•
IP rating		IP24 D

next page >

		ESH 10 U-P Plus
Height	mm	506
Width	mm	296
Depth	mm	276
Weight	kg	8.00

Required accessories		
Part number		**070558**
Type		WVT-G3/8
Description		Tee
Part number		**073499**
Type		SVMT
Description		Safety assembly for small water heater, pressure-tested, undersink

Oversink

ESH O-P Plus



ESH 10 O-P Plus

Benefits

- Supplies multiple draw-off points via a pressurised connection
- Variable temperature selection
- Power cable with standard plug
- Press the reset button to reset the high limit safety cut-out
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These small water heaters provide an energy saving and efficient supply of warm or hot water to one or more draw-off points with low DHW demand. • The pressure-tested, unvented appliances can be connected to all commercially available pressure taps.

Convenience features • The small water heater for oversink installation is suitable for demand-dependent, decentralised group supply of multiple draw-off points. • The sensor immersed in the water measures the temperature precisely and quickly. • The temperature can be variably adjusted using the rotary selector. • The heat-up phase is signalled by an indicator lamp.

Efficiency • The appliance heats the water directly at the draw-off point, which saves water and energy by preventing thermal losses in the pipework. • For low energy losses, the pressure-tested, enamelled inner cylinder made of steel is equipped with high grade thermal insulation.

Installation • The PROFI-RAPID installation system enables very fast installation. The universal mounting rail compensates for any unevenness in the wall and drill hole discrepancies, and is suitable for commonly used fixing points. • The connecting cable comes fitted with a standard plug. • Installation only with the appropriate safety assembly. The matching safety valve is available as an accessory.

Safety • For a long service life, the small water heater is equipped with a robust copper tubular heater. • Safe commissioning thanks to resettable high limit safety cut-out.

		ESH 10 O-P Plus
Part number		**201398**
Specification		
Rated output 1	kW	1.8
Rated output 2	kW	2.0
Rated output 3	kW	2.2
Power supply		1/N/PE
Rated voltage 1	V	220
Rated voltage 2	V	230
Rated voltage 3	V	240
Rated current 1	A	8.3
Rated current 2	A	8.7
Rated current 3	A	9.1
Fuse protection 2	A	10
Frequency	Hz	50-60
Energy efficiency class A+ -> F		A
Standby energy consumption/24 h at 65 °C	kWh	0.34
Nominal capacity	l	10
Mixed water amount at 40 °C	l	18
Temperature setting range	°C	35 - 82
Version		Small water heater
Type		pressurised
Installation type		Oversink
With tap		-
Inner cylinder material		Steel, enamelled
Colour		white
Cable length	m	0.95
Operation		manual
Temperature limit		•
Temperature selection	°C	35

next page >

		ESH 10 O-P Plus
IP rating		IP24 D
Height	mm	506
Width	mm	296
Depth	mm	276
Weight	kg	8.00

Oversink

Accessories
Accessories 72

SVMT




Benefits
› For the connection of pressure taps

Description • The safety assembly in a brass casing with chrome finish is suitable for pressure-tested, unvented, undersink small water heaters. • Standard delivery includes the pressure limiter, a water control valve and the drain outlet with non-return valve.

SVMT

		SVMT
Part number		**073499**
Specification		
Max. permissible pressure	MPa	1.00
Safety valve response pressure	MPa	0.70
Pressure reducing valve		•
Drip water connection		•
Installation type		Surface-mounted

WVT



Description • The water manifold is combined with the SVMT safety assembly to be able to connect a second commercially available pressure tap.

WVT-G3/8

		WVT-G3/8
Part number		**070558**
Specification		
Water connection		G 3/8 A

SRT



SRT 2

Benefits
› The safety assembly is used as fuse protection for unvented DHW cylinders

Description • This safety assembly for surface mounting of unvented wall mounted cylinders and pressurised small water heaters can be installed horizontally or vertically.

		SRT 2
Part number		**230764**
Specification		
Max. permissible pressure	MPa	0.60
Pressure reducing valve		-
Drip water connection		•
Installation type		Surface-mounted
Safety valve	bar	6

ST GP



ST GP 1/2”

Benefits
› The safety valve is used as fuse protection for unvented DHW cylinders

Description • Safety valve for wall and floor mounted cylinders.

		ST GP 1/2“	ST GP 3/4“
Part number		**073945**	**073946**
Specification			
Max. permissible pressure	MPa	0.60	0.60
Water connection		G 1/2	G 3/4

Application areas

Nominal capacity



	L	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
SHZ 30 LCD																											
SHZ 50 LCD																											
SHZ 80 LCD																											
SHZ 100 LCD																											
SHZ 120 LCD																											
SHZ 150 LCD																											




	L	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
SH 30 S electronic																											
SH 50 S electronic																											
SH 80 S electronic																											
SH 100 S electronic																											
SH 120 S electronic																											
SH 150 S electronic																											




	L	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
PSH 30 Universal EL																											
PSH 50 Universal EL																											
PSH 80 Universal EL																											
PSH 100 Universal EL																											
PSH 120 Universal EL																											
PSH 150 Universal EL																											

Application areas














Application areas



	l	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
PSH 80 WE-L										■																	
PSH 80 WE-R										■																	
PSH 120 WE-L														■													
PSH 120 WE-R														■													
PSH 150 WE-L																	■										
PSH 150 WE-R																	■										
PSH 200 WE-L																					■						
PSH 200 WE-R																					■						



	l	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250
PSH 80 WE-H										■																	
PSH 120 WE-H														■													
PSH 150 WE-H																	■										
PSH 200 WE-H																					■						

Pressurised
- **SHZ LCD** 78
- **SH S electronic** 80
- **PSH Universal EL** 82
- **PSH Trend** 83
- **PSH Classic** 85

Instantaneous water cylinder operation
- **SHD** 86

With tubular indirect coil
- **PSH WE** 88
- **PSH WE-H** 90

SHZ LCD



SHZ 30 LCD

Benefits

- Precise temperature adjustment via LCD screen and buttons
- Power saving operation thanks to the three selectable ECO functions
- The maintenance-free self-regulating impressed current anode ensures corrosion protection
- Currently available mixed water amount is displayed on the LCD screen
- At times of increased DHW demand, a boost function is available
- Automatic scale build-up indicator
- Repair work simplified by integral fault display
- Increased photovoltaic self-consumption through integral control for targeted use of electricity from photovoltaic systems, integrated as standard
- Suitable for single or dual circuit operation (connected to off-peak economy tariff) and for manual rapid heat-up operation
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Quick and easy installation using mounting bracket and drilling template

Application • These wall mounted cylinders are suitable for DHW supply to multiple draw-off points (individual and group supply) e.g. in the bathroom and kitchen simultaneously. • Pressure-tested appliance for use with all commercially available pressure taps. Non-pressurised option for supplying one draw-off point. • Suitable for dual circuit operation; single-circuit or manual rapid heat-up operation also possible.

Convenience features • Electronic closed-loop control guarantees precise temperature setting via operating buttons. • The illuminated LCD screen shows the set temperature, available mixed water amount, energy consumption, status and service messages. • ECO functions for energy savings. • Rapid heat-up button for increased convenience during periods of higher DHW demand. This can also be activated via an external remote button. • Adjustable temperature limit.

Efficiency • ECO modes can be individually selected for economical operation. An energy consumption display indicates the cumulative energy consumption. The intelligent ECO Dynamic function additionally saves energy while ensuring a high level of hot water convenience. • Low energy losses due to high grade thermal insulation. • Optional reverse control (activated via DIP switch) is possible in off-peak economy tariff operation (dual circuit) to further reduce costs and take full advantage of the enable times offered by the power supply utility. • Design for recycling, for environmentally responsible sorting of the various components.

Installation • Selectable connected load with removable strain relief for simplified installation. • Straightforward replacement of all standard wall mounted cylinders. Installation template for marking the holes to be drilled and for pre-installation of the water connections. The universal wall mounting bracket enables quick and straightforward wall mounting. Also suitable for installation in corners. • Recessed grips provide a secure hold when carrying the wall mounted cylinder. • Standard delivery includes caps for the mounting bracket and spacers for protruding walls. • Suitable for installation in systems with plastic, copper or stainless steel pipework. • The output and operating mode can be selected and adjusted via two triple setting DIP switches. • The automatic display indicates the level of scale build-up on the flanged immersion heater. The flanged immersion heater with unmistakable electrical flange mount connector is easy to remove. • Hoseproof. • Drainage facility via drain valve with hose connection. Large flanged aperture for effective and convenient descaling.

Safety • Universal copper flanged immersion heater suitable for single circuit, dual circuit or manual rapid heat-up operation. • Maintenance-free corrosion protection via the automatically regulated titanium impressed current anode. • Steel inner cylinder with special „anticor“ enamel coating for a long service life. • Anti-scalding protection and childproofing thanks to adjustable temperature limit and screen locking option. • Automatic frost protection monitors the water temperature and protects the cylinder under cold conditions.

		SHZ 30 LCD	SHZ 50 LCD	SHZ 80 LCD	SHZ 100 LCD	SHZ 120 LCD	SHZ 150 LCD
Part number		**231251**	**231252**	**231253**	**231254**	**231255**	**231256**
Specification							
Connected load ~ 230 V	kW	1-4	1-4	1-4	1-4	1-4	1-4
Connected load ~ 400 V	kW	1-6	1-6	1-6	1-6	1-6	1-6
Power supply		1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE
Rated voltage	V	230/400	230/400	230/400	230/400	230/400	230/400
Frequency	Hz	50/60	50/60	50/60	50/60	50/60	50/60
Load profile		S	M	M	L	XL	XL
Energy efficiency class A+ -> F		A	B	B	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	0.46	0.54	0.67	0.86	0.99	1.16
Nominal capacity	l	30	50	80	100	120	150
Mixed water amount at 40 °C	l	74	121	197	220	291	355
Temperature setting range	°C	20-85	20-85	20-85	20-85	20-85	20-85
Max. flow rate	l/min	18	18	18	18	18	18

next page >

		SHZ 30 LCD	SHZ 50 LCD	SHZ 80 LCD	SHZ 100 LCD	SHZ 120 LCD	SHZ 150 LCD
Colour		white	white	white	white	white	white
IP rating		IP25	IP25	IP25	IP25	IP25	IP25
Height	mm	770	740	1050	1050	1210	1445
Width	mm	410	510	510	510	510	510
Depth	mm	420	510	510	510	510	510
Weight	kg	22.90	27.60	37.80	39.50	42.40	52.00
Required accessories							
Part number		**230764**	**230764**	**230764**	**230764**	**230764**	**230764**
Type		SRT 2	SRT 2	SRT 2	SRT 2	SRT 2	SRT 2
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested

SH S electronic



SH 30 S electronic

Benefits
- Variable temperature setting via rotary selector
- High quality magnesium anode for optimised cylinder protection
- Electronic heat content indicator via LED indicator in the user interface
- Hot water round the clock in efficient single circuit operation
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Quick and easy installation using mounting bracket and drilling template

Application • These wall mounted cylinders supply DHW conveniently and energy efficiently to multiple draw-off points, e.g. individual or group supply to the bathroom and kitchen. • The pressure-tested, unvented appliances can be combined with all commercially available pressure taps. • If only one draw-off point is used, the appliance can also be used with a non-pressurised (vented) connection.

Convenience features • The temperature can be variably adjusted and limited in three stages. • The heat-up phase is visually indicated. • Seven LED fields on the user interface indicate the usable heat content.

Efficiency • Low energy losses thanks to high grade thermal insulation.

Installation • The integral recessed grips facilitate handling of the wall mounted cylinder. • Quick and straightforward replacement of all standard wall mounted cylinders thanks to the well planned design. • The installation template supplied can be used to mark drill holes and pre-install the water connections. • The universal wall mounting bracket allows both corner and wall installation. Standard delivery includes mounting bracket caps and spacers for protruding walls. • Selectable terminals with removable strain relief for simplified installation. • The appliance is suitable for installation in systems with plastic, copper or stainless steel pipework. • The large flanged aperture allows effective and convenient descaling of the wall mounted cylinder. The electric flanged immersion heater is easy to remove and is fitted with a reverse polarity-protected electrical flange mount connector. • The appliance is drained via a drain valve with hose connection. • The design allows environmentally responsible sorting and recycling of the individual components.

Safety • The universal flanged immersion heater is suitable for single circuit operation. • The steel inner cylinder with special „anticor“ directly applied enamel coating on the inside helps to ensure a long service life. • The high grade magnesium anode offers additional corrosion protection. Its consumption is indicated via the user interface. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing. The appliance is hoseproof to protection rating IP 25.

		SH 30 S electronic	SH 50 S electronic	SH 80 S electronic	SH 100 S electronic	SH 120 S electronic	SH 150 S electronic
Part number		**073047**	**073048**	**073049**	**073050**	**073051**	**073052**
Specification							
Connected load ~ 230 V	kW	1-4	1-4	1-4	1-4	1-4	1-4
Connected load ~ 400 V	kW	3-6	3-6	3-6	3-6	3-6	3-6
Power supply		1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE
Rated voltage	V	230/400	230/400	230/400	230/400	230/400	230/400
Frequency	Hz	50	50	50	50	50	50
Load profile		S	M	M	L	L	XL
Energy efficiency class A+ -> F		B	C	C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	0.46	0.54	0.67	0.86	0.99	1.10
Nominal capacity	l	30	50	80	100	120	150
Mixed water amount at 40 °C	l	50	80	122	133	182	229
Temperature setting range	°C	35-82	35-82	35-82	35-82	35-82	35-82
Max. flow rate	l/min	18	18	18	18	18	18
Colour		white	white	white	white	white	white
IP rating		IP25	IP25	IP25	IP25	IP25	IP25
Height	mm	770	740	1050	1050	1210	1445
Width	mm	410	510	510	510	510	510
Depth	mm	420	510	510	510	510	510
Weight	kg	23.10	28.00	38.00	40.80	45.50	53.30

next page >

		SH 30 S electronic	SH 50 S electronic	SH 80 S electronic	SH 100 S electronic	SH 120 S electronic	SH 150 S electronic
Required accessories							
Part number		**230764**	**230764**	**230764**	**230764**	**230764**	**230764**
Type		SRT 2	SRT 2	SRT 2	SRT 2	SRT 2	SRT 2
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested

PSH Universal EL



PSH 30 Universal EL

Benefits

- Electronic display and buttons for temperature adjustment accurate to the degree
- Power saving operation thanks to the three selectable ECO functions
- High quality magnesium anode for optimised cylinder protection
- At times of increased DHW demand, a boost function is available
- Choice of vertical or horizontal installation
- Repair work simplified by integral fault display
- Protected ceramic heating element can be replaced without the appliance first having to be drained
- Suitable for single or dual circuit operation (connected to off-peak economy tariff) and for manual rapid heat-up operation
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These unvented, pressure-tested wall mounted cylinders supply DHW simultaneously to multiple draw-off points, e.g. the bathroom and kitchen. • The appliance can be combined with all commercially available pressure taps. • The appliance can be used in dual circuit operation with an off-peak economy tariff connection; otherwise single circuit or manual rapid heat-up operation is also possible.

Convenience features • Electronic closed-loop control guarantees precise temperature setting via the operating buttons. • The LCD screen indicates the set temperature, status and service, as required. • A maximum temperature limit can be set. • The rapid heat-up button (boost function) provides additional convenience for increased DHW demand.

Efficiency • The intelligent ECO Dynamic function adapts automatically to individual demand, which saves additional energy. • The high grade thermal insulation protects against heat loss. • Reverse control during off-peak economy tariff operation (dual circuit) saves on costs. This is activated via a DIP switch and takes full advantage of the off-peak periods offered by the power supply utility. It also ensures a consistently high level of hot water convenience. • The individual components are designed for environmentally responsible sorting and recycling.

Installation • Quick and straightforward wall mounting is ensured with the integral wall mounting bracket. • The connected load is selectable. • Straightforward replacement of all standard wall mounted cylinders. • The output and operating mode can be adjusted via 2 triple setting DIP switches. • The ceramic heating element has no contact with the DHW because it is in an enamelled protective pipe. This enables a „dry“ replacement of the heating element. • The cylinder is drained via a shut-off valve with hose connection. • The large flanged aperture allows effective and convenient descaling.

Safety • High corrosion protection is provided by the magnesium anode and the steel inner cylinder with special „anticor“ directly applied enamel coating on the inside. • The anti-scalding protection also acts as childproofing. • The screen locking function prevents the set maximum temperature from being changed. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing. • The appliance is hoseproof.

		PSH 30 Universal EL	PSH 50 Universal EL	PSH 80 Universal EL	PSH 100 Universal EL	PSH 120 Universal EL	PSH 150 Universal EL
Part number		**231150**	**231151**	**231152**	**231153**	**231649**	**231154**
Specification							
Connected load ~ 230 V	kW	2.6	3	3	3	3	3
Power supply		1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	V	230	230	230	230	230	230
Frequency	Hz	50/60	50/60	50/60	50/60	50/60	50/60
Load profile		S	M	M	L	XL	XL
Energy efficiency class A+ -> F		B	B	B	C	C	C
Nominal capacity	l	30	50	80	100	120	150
Temperature setting range	°C	7-85	7-85	7-85	7-85	7-85	7-85
Max. flow rate	l/min	23.5	23.5	23.5	23.5	23.5	23.5
Colour		white	white	white	white	white	white
IP rating		IP25	IP25	IP25	IP25	IP25	IP25
Height	mm	696	951	893	1045	1200	1435
Width	mm	380	380	475	475	475	475
Depth	mm	392	392	492	492	492	492
Weight	kg	22.00	28.00	34.00	38.00	43.00	52.00

Safety valve with non-return valve

PSH Trend



PSH 30 Trend

Benefits
- Variable temperature setting via rotary selector
- High quality magnesium anode for optimised cylinder protection
- Visual monitoring of water temperature via temperature display
- Optimised cylinder protection with special CoPro enamel coating
- Durable, low-scaling stainless steel heating element
- Low energy losses thanks to high grade thermal insulation
- Easy handling due to distinctive recessed grips on the appliance
- Easy replacement of old appliances thanks to universal wall mounting
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These wall mounted cylinders can supply DHW simultaneously to multiple draw-off points, e.g. the bathroom and kitchen. The unvented, pressure-tested appliances offer convenient and energy saving single circuit operation. • The wall mounted cylinders can be used with commercially available pressure taps.

Convenience features • The temperature can be variably adjusted. • The heat-up phase is indicated by an LED.

Efficiency • The high grade thermal insulation protects against heat loss. • The individual components are designed for environmentally responsible sorting and recycling.

Installation • Quick and straightforward wall mounting with the integral wall mounting bracket. Existing wall mounted cylinders can be easily replaced. Suitable for installation in systems with plastic, copper or stainless steel pipework. • The large flanged aperture allows effective and convenient descaling. • The stainless steel flanged immersion heater can be easily replaced.

Safety • The magnesium sacrificial anode provides additional corrosion protection. • The steel inner cylinder with special „anticor“ directly applied enamel coating on the inside helps to ensure a long service life. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing. • The hoseproof appliance carries the VDE/GS and EMI symbols.

		PSH 30 Trend	PSH 50 Trend	PSH 80 Trend	PSH 100 Trend
Part number		**232080**	**232081**	**232082**	**232083**
Specification					
Connected load ~ 230 V	kW	2	2	2	2
Power supply		1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	V	220-240	220-240	220-240	220-240
Frequency	Hz	50/60	50/60	50/60	50/60
Load profile		S	M	M	L
Energy efficiency class A+ -> F		C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	0.53	0.73	0.79	0.98
Nominal capacity	l	30	50	80	100
Mixed water amount at 40 °C	l	52	99	142	186
Temperature setting range	°C	30-75	30-75	30-75	30-75
Max. flow rate	l/min	23.5	23.5	23.5	23.5
Colour		white	white	white	white
IP rating		IP25	IP25	IP25	IP25
Height	mm	642	897	871	1025
Width	mm	405	405	510	510
Depth	mm	410	410	520	520
Weight	kg	16.40	21.40	28.20	33.60

		PSH 120 Trend	PSH 150 Trend	PSH 200 Trend
Part number		**232084**	**232085**	**232086**
Specification				
Connected load ~ 230 V	kW	2	2	2
Power supply		1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	V	220-240	220-240	220-240

next page >

Pressurised

		PSH 120 Trend	PSH 150 Trend	PSH 200 Trend
Frequency	Hz	50/60	50/60	50/60
Load profile		L	L	XL
Energy efficiency class A+ -> F		C	C	C
Standby energy consumption/24 h at 65 °C	kWh	1.15	1.33	1.61
Nominal capacity	l	120	150	192
Mixed water amount at 40 °C	l	224	288	351
Temperature setting range	°C	30-75	30-75	30-75
Max. flow rate	l/min	23.5	23.5	23.5
Colour		white	white	white
IP rating		IP25	IP25	IP25
Height	mm	1178	1410	1715
Width	mm	510	510	510
Depth	mm	520	520	520
Weight	kg	39.10	46.20	56.30

(Product: 232080, 232082, 232083, 232084, 232085, 232086)
(Product: 232081)

PSH Classic



PSH 50 Classic

Benefits
- Variable temperature setting via rotary selector
- High quality magnesium anode for optimised cylinder protection
- Visual monitoring of water temperatures via temperature curve display
- Hot water round the clock in efficient single circuit operation
- Low energy losses thanks to high grade thermal insulation
- Optimised cylinder protection with special CoPro enamel coating
- Quick and easy installation using the universal wall mounting bracket
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These wall mounted cylinders in a cylindrical casing supply DHW to multiple draw-off points, e.g. individual or group supply to the bathroom and kitchen. • The pressure-tested, unvented appliances are used in single circuit operation and combined with commercially available pressure taps.

Convenience features • The preferred temperature can be variably adjusted and heat-up operation is visually indicated. • The current water temperature can be conveniently read from the front of the appliance.

Efficiency • The high grade thermal insulation made of insulation foam ensures low energy losses. • Thanks to the design for recycling, environmentally responsible sorting of the various components is possible.

Installation • Straightforward replacement of all standard wall mounted cylinders. Quick and straightforward wall mounting thanks to the universal mounting bracket. • The appliance can be connected to systems with plastic, copper or stainless steel pipework. • The copper flanged immersion heater can be easily removed.

Safety • The high grade magnesium anode and the steel inner cylinder with special &anticor directly applied enamel coating protect the cylinder against corrosion. • The automatic frost protection monitors the water temperature and protects the cylinder against frost. • The wall mounted cylinder is splashproof.

		PSH 50 Classic	PSH 80 Classic	PSH 100 Classic	PSH 120 Classic	PSH 150 Classic	PSH 200 Classic
Part number		**235960**	**235961**	**235962**	**235963**	**235964**	**235965**
Specification							
Connected load ~ 230 V	kW	1.8	1.8	1.8	1.8	1.8	1.8
Power supply		1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency	Hz	50/60	50/60	50/60	50/60	50/60	50/60
Load profile		M	M	L	L	L	XL
Energy efficiency class A+ -> F		C	C	C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	0.96	1.22	1.47	1.73	2.05	2.45
Nominal capacity	l	53	80	100	120	150	192
Mixed water amount at 40 °C	l	82	125	168	219	270	347
Temperature setting range	°C	30-70	30-70	30-70	30-70	30-70	30-70
Max. flow rate	l/min	23.5	23.5	23.5	23.5	23.5	23.5
Colour		white	white	white	white	white	white
IP rating		IP24	IP24	IP24	IP24	IP24	IP24
Height	mm	609	810	964	1117	1349	1704
Width	mm	475	475	475	475	475	475
Depth	mm	483	483	483	483	483	483
Weight	kg	19.00	28.00	33.00	39.00	46.00	56.00

Safety valve (Product: 235960) , 235961, 235962, 235963, 235964, 235965)

Instantaneous water cylinder operation

SHD



SHD 30 S

Benefits

- Instantaneous water cylinder operation: standard heating and automatically increased output for large draw-off volumes
- Variable temperature setting via rotary selector
- Simple maintenance with LED signal anode in the user interface
- At times of increased DHW demand, a boost function is available
- Can be used individually in single circuit operation, dual circuit operation (off-peak tariff connection) and instantaneous water cylinder operation
- Thermal insulation with very low energy losses
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Quick and easy installation using mounting bracket and drilling template

Application • These wall mounted cylinders supply DHW conveniently and energy efficiently to multiple draw-off points, e.g. individual or group supply to the bathroom and kitchen. • The pressure-tested appliances can be combined with all commercially available pressure taps. • The powerful instantaneous water cylinders can be used either in single circuit operation, or in dual circuit operation if there is an existing off-peak economy tariff connection.

Convenience features • In order to automatically heat the water directly in instantaneous water cylinder operation, an increased heating output is made available when the water draw-off rate is high. • Variable temperature setting. • A visual display indicates when the appliance is heating up. • A button for rapid heat-up (boost function) is provided for high demand in dual circuit operation.

Efficiency • For the lowest possible energy losses, the wall mounted cylinder is equipped with high grade thermal insulation. Particularly economical operation is achieved by using favourable electricity tariffs. An off-peak economy tariff connection is possible. • Design for recycling allows environmentally responsible sorting of the various components.

Installation • Recessed grips provide a secure hold when carrying the appliance. • Selectable connected load for simplified installation. • Straightforward replacement of all standard wall mounted cylinders. Rapid and straightforward wall mounting is facilitated with the universal wall mounting bracket. Installation template supplied for marking the holes to be drilled and for pre-installation of the water connections. • Also suitable for installation in corners. • Suitable for installation in systems with plastic, copper or stainless steel pipework. • The flanged immersion heater can be easily removed. • The cylinder contents are drained via a drain valve with hose connection. • The large flanged aperture allows effective and convenient descaling.

Safety • The special flanged immersion heater is suitable for instantaneous water cylinders for single or dual circuit operation. • The high grade signal anode can be replaced without removing the flange, and its consumption is displayed on the user interface. • The special „anticor“ directly applied enamel coating in the steel inner cylinder ensures a long service life. • Automatic frost protection monitors the water temperature and protects the cylinder at low temperatures. • The appliance is hoseproof.

		SHD 30 S	SHD 100 S
Part number		**073059**	**073060**
Specification			
Connected load ~ 400 V	kW	3,4/20,4	3,4/20,4
Power supply		3/PE	3/PE
Rated voltage	V	400	400
Frequency	Hz	50	50
Load profile		S	L
Energy efficiency class A+ -> F		B	C
Standby energy consumption/24 h at 65 °C	kWh	0.46	0.86
Nominal capacity	l	30	100
Mixed water amount at 40 °C	l	50	133
Temperature setting range	°C	35-85	35-85
Max. flow rate	l/min	18	18
Colour		white	white
IP rating		IP25	IP25
Height	mm	770	1050
Width	mm	410	510
Depth	mm	420	510
Weight	kg	24.30	40.10

next page >

		SHD 30 S	SHD 100 S
Required accessories			
Part number		**230764**	**230764**
Type		SRT 2	SRT 2
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested

PSH WE



PSH 80 WE-L

Benefits

- Variable temperature setting ensures a high level of convenience
- Visual monitoring of water temperatures via temperature curve display
- A DHW circulation connection increases hot water convenience in longer pipe networks
- Durable, low-scaling stainless steel heating element
- Personalised hot water convenience thanks to connection for heat exchanger and electric heating element
- Easy to transport and install with ergonomic recessed grips on the appliance
- Quick and easy installation using the universal wall mounting bracket
- Safety valve 6.7 bar with non-return valve included in the standard delivery
- Versions for connection to the tubular heat exchanger either on left or right available for easy integration

Application • These vertical wall mounted combi cylinders supply DHW to multiple draw-off points, e.g. individual and group supply to the bathroom and kitchen. The wall mounted combi cylinders are equipped with a stainless steel electric tubular heater. A tubular indirect coil is also integrated, for example for connecting the wall mounted cylinder to a central heating system. • The pressure-tested, unvented appliance is suitable for all commercially available pressure taps.

Convenience features • The temperature is variably adjusted and heat-up operation is visually indicated. • The current water temperature can be checked on the temperature curve display.

Efficiency • The high grade thermal insulation ensures low energy losses. • Particularly economical operation is possible if the integral cylinder is connected to the heating system via the built-in tubular indirect coil. • Design for recycling allows environmentally responsible sorting of the various components.

Installation • Recessed grips on the appliance ensure safe handling. • Straightforward replacement of all standard wall mounted cylinders. The universal mounting bracket enables quick and straightforward wall mounting. • The integral cylinder can be installed in systems with plastic, copper or stainless steel pipework. • The flanged immersion heater is easy to remove and is equipped with a second sensor well for external control of the heat generator. The large flanged aperture enables convenient descaling. • The DHW circulation connection increases hot water convenience in longer pipe networks. • The connection to the tubular indirect coil is on the left or right, depending on the model.

Safety • The high grade protective anode and the steel inner cylinder with special „anticor“ directly applied enamel coating protect against corrosion. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing at low temperatures.

		PSH 80 WE-L	PSH 80 WE-R	PSH 120 WE-L	PSH 120 WE-R
Part number		**236230**	**236231**	**236232**	**236233**
Specification					
Connected load ~ 230 V	kW	2	2	2	2
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	V	220-240	220-240	220-240	220-240
Frequency	Hz	50/60	50/60	50/60	50/60
Standby power consumption/24 h at 65 °C	kWh	0.893	0.893	1.19	1.19
Energy efficiency class A+ -> F		B	B	B	B
Nominal capacity	l	79	79	120	120
Mixed water amount at 40 °C	l	128	128	209	209
Surface area, heat exchanger	m²	0.60	0.60	0.60	0.60
Temperature setting range	°C	5-80	5-80	5-80	5-80
Min./max. conductivity, DHW	µS/cm	100-1500	100-1500	100-1500	100-1500
Max. flow rate	l/min	23.5	23.5	23.5	23.5
Colour		white	white	white	white
IP rating		IP25	IP25	IP25	IP25
Height	mm	871	871	1178	1178
Depth	mm	520	520	520	520
Weight, empty	kg	37.20	37.20	48.10	48.10

		PSH 150 WE-L	PSH 150 WE-R	PSH 200 WE-L	PSH 200 WE-R
Part number		**236234**	**236235**	**236236**	**236237**

next page >

		PSH 150 WE-L	PSH 150 WE-R	PSH 200 WE-L	PSH 200 WE-R
Specification					
Connected load ~ 230 V	kW	2	2	2	2
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	V	220-240	220-240	220-240	220-240
Frequency	Hz	50/60	50/60	50/60	50/60
Standby power consumption/24 h at 65 °C	kWh	1.426	1.426	1.803	1.803
Energy efficiency class A+ -> F		C	C	C	C
Nominal capacity	l	151	151	191	191
Mixed water amount at 40 °C	l	278	278	395	395
Surface area, heat exchanger	m²	0.60	0.60	0.60	0.60
Temperature setting range	°C	5-80	5-80	5-80	5-80
Min./max. conductivity, DHW	µS/cm	100-1500	100-1500	100-1500	100-1500
Max. flow rate	l/min	23.5	23.5	23.5	23.5
Colour		white	white	white	white
IP rating		IP25	IP25	IP25	IP25
Height	mm	1410	1410	1715	1715
Depth	mm	520	520	520	520
Weight, empty	kg	55.20	55.20	65.30	65.30

Safety valve (Product: 236230) , 236231, 236232, 236233, 236234, 236235, 236236, 236237)

PSH WE-H



PSH 80 WE-H

Benefits

- Variable temperature setting ensures a high level of convenience
- A DHW circulation connection increases hot water convenience in longer pipe networks
- Durable, low-scaling stainless steel heating element
- Personalised hot water convenience thanks to connection for heat exchanger and electric heating element
- Visual monitoring of water temperatures via temperature curve display
- Easy to transport and install with ergonomic recessed grips on the appliance
- Wall mounting bracket for horizontal installation
- Safety valve 6.7 bar with non-return valve included in the standard delivery

Application • These horizontal wall mounted combi cylinders supply DHW simultaneously to multiple draw-off points – e.g. individual or group supply to the bathroom and kitchen. • The wall mounted combi cylinders are equipped with a stainless steel electric tubular heater. The integral tubular indirect coil allows connection to a central heating system. • The pressure-tested appliance can be combined with all commercially available pressure taps.

Convenience features • The preferred temperature can be variably adjusted and easily checked using the temperature curve display. • A visual display indicates when the appliance is heating up.

Efficiency • Low energy losses due to high grade thermal insulation. • The integral cylinder operates extremely economically, because it is connected to the heating system via the integral tubular indirect coil. • The design for recycling ensures that the various components can be sorted in an environmentally responsible way.

Installation • The integral recessed grips facilitate handling. • Straightforward replacement of all standard wall mounted cylinders. Quick and straightforward wall mounting thanks to the universal wall mounting bracket. • Suitable for installation in systems with plastic, copper or stainless steel pipework. • The easy-to-remove flanged immersion heater is equipped with a second sensor well for external control of the heat generator. • The large flanged aperture allows effective and convenient descaling. • The DHW circulation connection increases hot water convenience in longer pipe networks.

Safety • The high grade magnesium anode and the steel inner cylinder with special „anticor“ directly applied enamel coating protect against corrosion for a long service life. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing.

		PSH 80 WE-H	PSH 120 WE-H	PSH 150 WE-H	PSH 200 WE-H
Part number		**236238**	**236239**	**236240**	**236241**
Specification					
Connected load ~ 230 V	kW	2	2	2	2
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	V	220-240	220-240	220-240	220-240
Frequency	Hz	50/60	50/60	50/60	50/60
Standby power consumption/24 h at 65 °C	kWh	1.298	1.691	1.973	2.31
Energy efficiency class A+ -> F		C	C	C	C
Nominal capacity	l	79	120	151	191
Mixed water amount at 40 °C	l	137	181	270	313
Surface area, heat exchanger	m²	0.60	0.60	0.60	0.60
Temperature setting range	°C	5-80	5-80	5-80	5-80
Min./max. conductivity, DHW	µS/cm	100–1500	100–1500	100–1500	100–1500
Max. flow rate	l/min	23.5	23.5	23.5	23.5
Colour		white	white	white	white
IP rating		IP25	IP25	IP25	IP25
Width	mm	871	1178	1410	1715
Depth	mm	538	538	538	538
Weight, empty	kg	42.20	54.10	61.20	72.50

Safety valve (Product: 236238) , 236239, 236240, 236241)

Safety assemblies
Accessories 92

Safety assemblies

SRT



SRT 2

Benefits

› The safety assembly is used as fuse protection for unvented DHW cylinders

Description • This safety assembly for surface mounting of unvented wall mounted cylinders and pressurised small water heaters can be installed horizontally or vertically.

		SRT 2
Part number		**230764**
Specification		
Max. permissible pressure	MPa	0.60
Pressure reducing valve		-
Drip water connection		•
Installation type		Surface-mounted
Safety valve	bar	6

ST GP



Benefits

› The safety valve is used as fuse protection for unvented DHW cylinders

Description • Safety valve for wall and floor mounted cylinders.

ST GP 1/2"

		ST GP 1/2“	ST GP 3/4“
Part number		**073945**	**073946**
Specification			
Max. permissible pressure	MPa	0.60	0.60
Water connection		G 1/2	G 3/4

Floor mounted cylinder
Application areas

Nominal capacity



	L	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
SHW 200 S						■	■															
SHW 300 S								■	■													
SHW 400 S										■	■											



	L	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
SHW 200 ACE						■	■															
SHW 300 ACE								■	■													
SHW 400 ACE										■	■											



	L	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
SHO AC 600 6/12 kW														■	■							
SHO AC 600 7,5 kW														■	■							
SHO AC 1000 9/18 kW																					■	■
SHO AC 1000 12 kW																					■	■



	L	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
SB 302 S								■	■													
SB 402 S										■	■											



	L	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
SB 602 AC														■	■							
SB 1002 AC																					■	■

Electric floor mounted cylinders, pressurised
- **SHW S** 96
- **SHW ACE** 98
- **SHO AC** 100

Floor mounted combi cylinders, pressurised
- **SB S** 102
- **SB AC** 103

Electric floor mounted cylinders, pressurised

SHW S



SHW 200 S

Benefits

- Variable temperature setting via rotary selector
- Simple maintenance due to signal anode with display element
- Water temperature monitored by thermometer
- Improved comfort/convenience with DHW circulation connection
- Universal flanged immersion heater for single/dual circuit operation with a selectable connected load
- Extremely economical due to favourable electricity tariffs (optional off-peak tariff connection)
- Complete cylinder casing with plastic jacket, cover and fascia
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Compensation for uneven floors via height-adjustable feet

Application • These floor mounted cylinders are suitable for family houses and apartment buildings with a high DHW demand and a high draw-off rate. Water can be supplied to multiple draw-off points simultaneously (group supply). • The unvented, pressure-tested appliances can be used with all commercially available pressure taps. • The flanged immersion heater is suitable for single circuit operation or cost efficient dual circuit operation with an off-peak economy tariff connection.

Convenience features • The required water temperature can be variably adjusted and is maintained at the selected temperature, depending on the controller. The maximum temperature limit can be set manually. • A „rapid heat-up“ button provides additional convenience for increased DHW demand. • The individual components are designed for environmentally responsible sorting and recycling.

Efficiency • The high grade thermal insulation protects the steel inner cylinder with directly applied foam insulation against heat loss.

Installation • Selectable connected load. • The water connection is suitable for pipework made from copper, plastic, stainless steel or zinc-plated steel. • Standard delivery includes a multi-directional stainless steel cold water inlet pipe for easy-to-install cold water connection. • A DHW circulation connection increases hot water convenience in longer pipe networks. • The height-adjustable feet compensate for unevenness in the floor. • The copper flanged immersion heater is easy to replace.

Safety • The floor mounted cylinders are splashproof. • The magnesium sacrificial anode with visible replacement signal ensures optimum corrosion protection. • The steel inner cylinder with special „anticor“ directly applied enamel coating on the inside helps to ensure a long service life. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing.

		SHW 200 S	SHW 300 S	SHW 400 S
Part number		**182120**	**182121**	**182122**
Specification				
Connected load ~ 230 V	kW	2-4	2-4	2-4
Connected load ~ 400 V	kW	2-6	2-6	2-6
Power supply		1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Rated voltage	V	230/400	230/400	230/400
Frequency	Hz	50/60	50/60	50/60
Load profile		XL	XL	XL
Energy efficiency class A+ -> F		C	C	C
Standby energy consumption/24 h at 65 °C	kWh	1.40	1.80	2.10
Nominal capacity	l	200	300	400
Mixed water amount at 40 °C	l	318	447	639
Temperature setting range	°C	35-82	35-82	35-82
Max. flow rate	l/min	30	38	45
Max. permissible pressure	MPa	0.60	0.60	0.60
Flanged immersion heater version		universal	universal	universal
Colour		pure white/basalt grey	pure white/basalt grey	pure white/basalt grey
IP rating		IP24	IP24	IP24
Water connection		G 1 A	G 1 A	G 1 A
Height	mm	1578	1593	1763
Width	mm	630	700	750
Depth	mm	730	815	865
Weight, empty	kg	65	77	90

next page >

Electric floor mounted cylinders, pressurised

		SHW 200 S	SHW 300 S	SHW 400 S
Required accessories				
Part number		**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested
Part number		**074371**	**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve	Pressure reducing valve
Part number		**074373**		
Type		SV 1/2 6 bar		
Description		Safety valve for DHW cylinder		
Part number			**074374**	**074374**
Type			SV 3/4 6 bar	SV 3/4 6 bar
Description			Safety valve for DHW cylinder	Safety valve for DHW cylinder

Electric floor mounted cylinders, pressurised

SHW ACE



SHW 200 ACE

Benefits

- Variable temperature setting via rotary selector
- High grade protective anode to protect cylinder from corrosion
- Water temperature monitored by thermometer
- Improved comfort/convenience with DHW circulation connection
- Efficient single circuit operation with selectable connected load
- Plastic jacket to protect the cylinder
- The steel inner cylinder features a special directly applied enamel coating for a long service life

Application • These floor mounted cylinders supply DHW to detached houses and apartment buildings with high DHW demand and a high draw-off rate. • The unvented, pressure-tested appliances also provide a group supply to multiple DHW draw-off points. They can be used with all commercially available pressure taps, and are suitable for single circuit operation.

Convenience features • The temperature is variably selected and maintained at the level set on the controller. • A temperature limit can be set if required.

Efficiency • Low heat losses due to high grade thermal insulation in the form of efficient directly applied foam. • Optimised design for recycling, with the ability to separate the various components and reusable materials.

Installation • Selectable connected load. • The water connection is suitable for pipework made from copper, plastic, stainless steel or zinc-plated steel. • The integral DHW circulation connection increases hot water convenience in longer pipe networks. • The copper flanged immersion heater is easy to replace. • The floor mounted cylinder is splashproof.

Safety • The high quality signal anode with consumption indicator ensures comprehensive corrosion protection. The steel inner cylinder with special „anticor“ directly applied enamel coating is distinguished by its long service life. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing.

		SHW 200 ACE	SHW 300 ACE	SHW 400 ACE
Part number		**070074**	**070075**	**070076**
Specification				
Connected load ~ 230 V	kW	2-6	2-6	2-6
Connected load ~ 400 V	kW	4-6	4-6	4-6
Power supply		1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Rated voltage	V	230/400	230/400	230/400
Frequency	Hz	50/60	50/60	50/60
Load profile		XL	XL	XL
Energy efficiency class A+ -> F		C	C	C
Standby energy consumption/24 h at 65 °C	kWh	1.90	2.30	2.60
Nominal capacity	l	200	300	400
Mixed water amount at 40 °C	l	317	490	618
Temperature setting range	°C	35-82	35-82	35-82
Max. flow rate	l/min	30	38	45
Max. permissible pressure	MPa	0.60	0.60	0.60
Flanged immersion heater version		Single circuit	Single circuit	Single circuit
Colour		white	white	white
Water connection		G 1	G 1	G 1
Height	mm	1578	1593	1763
Width	mm	550	650	700
Depth	mm	690	790	840
Weight, empty	kg	54	67	85
Required accessories				
Part number		**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested
Part number		**074371**	**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve	Pressure reducing valve

next page >

Electric floor mounted cylinders, pressurised

		SHW 200 ACE	SHW 300 ACE	SHW 400 ACE
Part number		**074373**		
Type		SV 1/2 6 bar		
Description		Safety valve for DHW cylinder		
Part number			**074374**	**074374**
Type			SV 3/4 6 bar	SV 3/4 6 bar
Description			Safety valve for DHW cylinder	Safety valve for DHW cylinder

Electric floor mounted cylinders, pressurised

SHO AC



SHO AC 600 6/12 kW

Benefits

- Variable temperature setting via rotary selector
- Simple maintenance due to signal anode with display element
- Water temperature monitored by thermometer
- Improved comfort/convenience with DHW circulation connection
- Flanged immersion heater suitable for single circuit operation or dual circuit/single circuit operation, depending on type
- Extremely economical due to favourable electricity tariffs (optional off-peak tariff connection)
- The steel inner cylinder features a special directly applied enamel coating for a long service life

Application • These floor mounted cylinders have been developed for a very high DHW demand and draw-off rate. They are suitable for DHW supply to multiple draw-off points (individual and group supply) in residential, commercial and industrial buildings. • The pressure-tested, unvented appliances can be connected to all commercially available pressure taps. • The flanged immersion heater can be used for single circuit or dual circuit operation, depending on the model.

Convenience features • The required water temperature can be variably adjusted and is maintained at the selected temperature, depending on the controller. The maximum temperature limit can be set manually. • The individual components are designed for environmentally responsible sorting and recycling.

Efficiency • Thanks to the optional retrofittable thermal insulation, the floor mounted cylinder achieves very good efficiency values and the standby energy consumption is reduced.

Installation • The connected load of these splashproof appliances varies by type. • The water connection is suitable for pipework made from copper, plastic, stainless steel or zinc-plated steel. • A DHW circulation connection increases hot water convenience in longer pipe networks. • Individual heating elements can be easily replaced.

Safety • The magnesium sacrificial anode with visible replacement signal provides additional corrosion protection. • The steel inner cylinder with special „anticor“ directly applied enamel coating on the inside helps to ensure a long service life. • Automatic frost protection monitors the water temperature and prevents the cylinder from freezing.

		SHO AC 600 6/12 kW	SHO AC 600 7,5 kW	SHO AC 1000 9/18 kW	SHO AC 1000 12 kW
Part number		**003352**	**001414**	**003353**	**001415**
Specification					
Connected load ~ 400 V	kW	6-12	7,5	9/18	12
Power supply		3/N/PE	3/PE	3/N/PE	3/PE
Rated voltage	V	400	400	400	400
Frequency	Hz	50	50/60	50	50
Load profile		XL	XL	XL	XL
Energy efficiency class A+ -> F		C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	2.90	2.90	3.70	3.70
Nominal capacity	l	600	600	1000	1000
Mixed water amount at 40 °C	l	1134	835	1829	1533
Temperature setting range	°C	35-85	35-85	35-85	35-85
Max. flow rate	l/min	40	40	45	45
Max. permissible pressure	MPa	0.60	0.60	0.60	0.60
Flanged immersion heater version		universal	universal	universal	universal
Colour		black	black	black	black
IP rating		IP24	IP24	IP24	IP24
Water connection		G 2 A / G 1 1/2 A	G 2 A / G 1 1/2 A	G 2 A / G 1 1/2 A	G 2 A / G 1 1/2 A
Height	mm	1685	1685	2525	2525
Width	mm	750	750	750	750
Depth	mm	1000	1000	1000	1000
Weight, empty	kg	161	160	232	230
Required accessories					
Part number		**074370**	**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested

next page >

Electric floor mounted cylinders, pressurised

		SHO AC 600 6/12 kW	SHO AC 600 7,5 kW	SHO AC 1000 9/18 kW	SHO AC 1000 12 kW
Part number		**074371**	**074371**	**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1	DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve	Pressure reducing valve	Pressure reducing valve
Part number		**074374**	**074374**	**074374**	**074374**
Type		SV 3/4 6 bar	SV 3/4 6 bar	SV 3/4 6 bar	SV 3/4 6 bar
Description		Safety valve for DHW cylinder	Safety valve for DHW cylinder	Safety valve for DHW cylinder	Safety valve for DHW cylinder
Recommended accessories					
Part number		**236077**	**236077**		
Type		WDS 600	WDS 600		
Description		Thermal insulation, floor mounted cylinder	Thermal insulation, floor mounted cylinder		
Part number				**236078**	**236078**
Type				WDS 1000	WDS 1000
Description				Thermal insulation, floor mounted cylinder	Thermal insulation, floor mounted cylinder

Floor mounted combi cylinders, pressurised

SB S



SB 302 S

Benefits

- Connection according to individual requirements through the two flanged apertures
- Simple maintenance due to signal anode with display element
- Visual monitoring of water temperature via temperature display
- Complete cylinder casing with plastic jacket, cover and fascia
- The steel inner cylinder features a special directly applied enamel coating for a long service life

Application • These floor mounted cylinders ensure the supply of DHW in family houses, apartment buildings and commercial premises with a high DHW demand and a high draw-off rate. Their large nominal capacity and pressure-tested, unvented operation enable them to supply DHW to multiple draw-off points simultaneously.

Convenience features • The flanged apertures are equipped with dust caps, and are fitted with either an electric flanged immersion heater or a blank flange.

Safety • The high grade protective anode and steel inner cylinder with special „anticor“ directly applied enamel coating protect against corrosion and ensure a long service life.

		SB 302 S	SB 402 S
Part number		**185354**	**185355**
Specification			
Energy efficiency class A+ -> F		C	C
Standby losses S	W	79	94
Nominal capacity	l	300	400
Colour		pure white/basalt grey	pure white/basalt grey
Number of flanged apertures		2	2
Water connection		G 1 A	G 1 A
Height	mm	1585	1755
Width	mm	700	750
Depth	mm	700	750
Immersion depth	mm	530	580
Weight, empty	kg	101	119
Flange diameter	mm	210	210
Required accessories			
Part number		**074370**	**074370**
Type		ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested
Part number		**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve
Part number		**074374**	**074374**
Type		SV 3/4 6 bar	SV 3/4 6 bar
Description		Safety valve for DHW cylinder	Safety valve for DHW cylinder
Part number		**074375**	**074375**
Type		SV 3/4 10 bar	SV 3/4 10 bar
Description		Safety valve for DHW cylinder	Safety valve for DHW cylinder
Recommended accessories			
Part number		**071330**	**071330**
Type		FCR 21/60	FCR 21/60
Description		Flanged immersion heater	Flanged immersion heater
Part number		**071331**	**071331**
Type		FCR 21/120 E	FCR 21/120 E
Description		Flanged immersion heater	Flanged immersion heater
Part number		**076102**	**076102**
Type		B21	B21
Description		Blank flange, floor mounted cylinder	Blank flange, floor mounted cylinder

Floor mounted combi cylinders, pressurised

SB AC



SB 602 AC

Benefits
- Connection according to individual requirements through the two flanged apertures
- Simple maintenance due to signal anode with display element
- The steel inner cylinder features a special directly applied enamel coating for a long service life
- Visual monitoring of water temperature via temperature display

Application • These floor mounted cylinders are suitable for providing DHW in family houses, apartment buildings and commercial premises with a high DHW demand and offer a high draw-off rate. They can supply DHW to multiple draw-off points simultaneously.

Convenience features • An electric flanged immersion heater or a blank flange can be fitted in the flanged apertures, which are equipped with dust protection caps.

Safety • The high grade protective anode and the steel inner cylinder with special „anticor“ directly applied enamel coating protect against corrosion and ensure a long service life.

		SB 602 AC	SB 1002 AC
Part number		**071554**	**071282**
Specification			
Standby losses S	W	108	146
Nominal capacity	l	600	1000
Water connection		G 2 A / G 1 1/2 A	top/bottom: G 2 / G 1 1/2
Height	mm	1685	2525
Width	mm	750	750
Depth	mm	800	800
Weight, empty	kg	154	212
Required accessories			
Part number		**074370**	**074370**
Type		ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested
Part number		**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve
Part number		**074374**	**074374**
Type		SV 3/4 6 bar	SV 3/4 6 bar
Description		Safety valve for DHW cylinder	Safety valve for DHW cylinder
Part number		**074375**	**074375**
Type		SV 3/4 10 bar	SV 3/4 10 bar
Description		Safety valve for DHW cylinder	Safety valve for DHW cylinder
Recommended accessories			
Part number		**000694**	**000694**
Type		FCR 28/120 E	FCR 28/120 E
Description		Flanged immersion heater	Flanged immersion heater
Part number		**000695**	**000695**
Type		FCR 28/180 E	FCR 28/180 E
Description		Flanged immersion heater	Flanged immersion heater
Part number		**071332**	**071332**
Type		FCR 28/120	FCR 28/120
Description		Flanged immersion heater	Flanged immersion heater
Part number		**071333**	**071333**
Type		FCR 28/180	FCR 28/180
Description		Flanged immersion heater	Flanged immersion heater
Part number		**076103**	**076103**
Type		B28	B28
Description		Blank flange, floor mounted cylinder	Blank flange, floor mounted cylinder

next page >


Floor mounted combi cylinders, pressurised

		SB 602 AC	SB 1002 AC
Part number		**234503**	**234503**
Type		FCR 28/120 CrNi	FCR 28/120 CrNi
Description		Flanged immersion heater	Flanged immersion heater
Part number		**236079**	
Type		WDS 602	
Description		Thermal insulation, floor mounted cylinder	
Part number			**236080**
Type			WDS 1002
Description			Thermal insulation, floor mounted cylinder

Electric threaded immersion heaters and flanged immersion heaters
Accessories 106
Safety assemblies
Accessories 108
Thermal insulation
Accessories 110

Electric threaded immersion heaters and flanged immersion heaters

FCR



Benefits

- Replaceable copper heating element
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

Description • The flanged immersion heaters are suitable for horizontal installation in unvented DHW cylinders with flange connectors to DIN 4805. • The temperature can be variably adjusted. It is possible to limit the temperature. • Please note the details supplied by the cylinder manufacturer, as well as DIN 4753 and DIN 4751.

FCR 21/60

		FCR 21/60	FCR 21/120 E	FCR 28/120	FCR 28/120 E
Part number		**071330**	**071331**	**071332**	**000694**
Specification					
Connected load ~ 230 V	kW	2-4	4		
Connected load ~ 400 V	kW	2-6	8/12	6/12	12
Power supply		1/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/PE	3/PE	3/PE
Rated voltage	V	230/400	230/400	400	400
Coil voltage	V	230	230	230	400
Frequency	Hz	50/60	50/60	50	50
Version		Dual/single circuit	Single circuit	Dual/single circuit	Single circuit
Integral contactor		X	-	X	X
IP rating		IP24	IP24	IP24	IP24
Immersion depth	mm	400	400	450	325
Flange diameter	mm	210	210	280	280

		FCR 28/120 CrNi	FCR 28/180	FCR 28/180 E
Part number		**234503**	**071333**	**000695**
Specification				
Connected load ~ 400 V	kW	6/12	9/18	18
Power supply		3/PE	3/PE	3/PE
Rated voltage	V	400	400	400
Coil voltage	V	230	230	400
Frequency	Hz	50	50	50
Version		Dual/single circuit	Dual/single circuit	Single circuit
Integral contactor		X	X	X
IP rating		IP24	IP24	IP24
Immersion depth	mm	450	450	325
Flange diameter	mm	280	280	280

(Product: 000694)

Temperature controller with frost protection setting (external), temperature limit possible, integral pushbutton for rapid heat-up, high limit safety cut-out, flange gasket, protective cover with two cable entries. (Product: 071330)

Temperature controller with frost protection setting, high limit safety cut-out, flange gasket, protective cover with two cable entries. (Product: 000694) , 000695)

(Product: 000694)

Electric threaded immersion heaters and flanged immersion heaters

BGC



Benefits
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

Application • This threaded immersion heater is suitable for sealed unvented heating systems and DHW heating systems. • The temperature can be variably adjusted; temperature limitation is possible. • The integral temperature controller is equipped with a high limit safety cut-out.

BGC 6 kW 500 mm ET

		BGC 6 kW 500 mm ET	BGC/45	BGC 2/60
Part number		**003769**	**075115**	**232030**
Specification				
Connected load ~ 230 V	kW	2-5,7	2-5,7	2-5,7
Connected load ~ 400 V	kW	6	6	6
Power supply		1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE
Rated voltage	V	230/400	230/400	230/400
Frequency	Hz	50/60	50/60	50/60
Version		Universal flange	Universal flange	Universal flange
IP rating		IP44	IP44	IP44
Immersion depth	mm	500	455	480

BG



Benefits
- Ideal for sealing the floor mounted cylinder if not all flanged apertures are used

Description • Blank flanges for sealing flanged apertures, enamel coated on the inside.

B21

		B21	B28
Part number		**076102**	**076103**
Specification			
Flange diameter	mm	210	280

Gaskets, screws with insulating sleeves and cover with thermal insulation.

Safety assemblies

ZH1



Benefits
- Maximum safety evidenced by DVGW certification mark
- Long service life and reliability thanks to the use of high quality components

Description • The safety assembly is suitable for combination with pressure-tested electric and integral cylinders. • Standard delivery includes a shut-off valve, non-return valve with service valve, pressure gauge connection, diaphragm safety valve and drain outlet. • To ensure that no waste water is sucked back, a pipe break is integrated into the drain outlet of the safety valve. • With its threaded fitting, the safety valve can be rotated, repositioned or replaced to match it to different installation situations. • The safety assembly enables angled or straight-through installation in horizontal and vertical pipework. • In vertical pipework, install the safety assembly only in a bottom to top flow direction. • A pressure reducing valve can be retrofitted if required.

ZH 1

		ZH 1
Part number		**074370**
Specification		
Safety valve response pressure	MPa	0.60
Pressure reducing valve		-
Drip water connection		•
Water connection		G 1 A
Installation type		Surface-mounted
Safety valve	bar	6

DMV/ZH 1




Benefits
- Reduced inlet pressure through additional pressure reducing valve

Description • Pressure reducing valve to supplement the safety assembly for pressure-tested electric and integral cylinders.

DMV/ZH 1

		DMV/ZH 1
Part number		**074371**
Specification		
Pressure reducing valve		•
Pressure reducing valve setting range	MPa	0,15 - 0,60
Water connection		G 1 A
Installation type		Surface-mounted

SV



SV 1/2 6 bar

Benefits
› The safety valve is used as fuse protection for unvented DHW cylinders

Description • Diaphragm safety valve with brass casing for pressurised DHW cylinders.

		SV 1/2 6 bar	SV 3/4 6 bar	SV 3/4 10 bar
Part number		**074373**	**074374**	**074375**
Specification				
Safety valve response pressure	MPa	0.60	0.60	1.00
Water connection		G 1/2	G 3/4	G 3/4

Thermal insulation

WDS



WDS 600

Benefits
- Two insulation semi-shells to make it easier to match the shape
- Graphite inserts for best insulation properties
- Low energy losses thanks to high grade thermal insulation

Application • This high grade thermal insulation, with sections for insulating the bottom and the cover, is suitable for floor mounted cylinders. • The insulation can be optimally fitted to the cylinder thanks to the wedge-shaped cut-outs in the side insulation sections. • The thermal insulation is easy to attach thanks to the integral zips.

		WDS 600	WDS 602	WDS 1000	WDS 1002
Part number		**236077**	**236079**	**236078**	**236080**
Specification					
Standby energy consumption/24 h at 65 °C	kWh	2.30	2.60	3.20	3.50
Height	mm	1850	1850	2690	2690
Thickness	mm	100	100	100	100

Compact DHW heat pumps 115

DHW heat pump accessories 127

SHP-I 300 H Plus

Place of Installation

Outdoor	**O**
Indoor	**I**

Type

Storage heat pump	**SHP**

Volumen

200 Liter	**20**
300 Liter	**30**

Defrosting

Active	**1**
Passive	**0**

Classification

Trend
Plus
Premium

Function

Flexible air mode	**F**
Heat exchanger	**H**

Application areas

Application limit heat source for heat pump operation



	°C	-10	-5	0	5	10	15	20	25	30	35	40	45
SHP-F 300 X Premium													
SHP-F 300 Premium													
SHP-F 220 Premium													



	°C	-10	-5	0	5	10	15	20	25	30	35	40	45
WWK 302													
WWK 302 H													
WWK 222 H													
WWK 222													



	°C	-10	-5	0	5	10	15	20	25	30	35	40	45
SHP-O 300 Plus													
SHP-O 200 Plus													



	°C	-10	-5	0	5	10	15	20	25	30	35	40	45
SHP-O 301 Premium													
SHP-O 201 Premium													



	°C	-10	-5	0	5	10	15	20	25	30	35	40	45
SHP-I 300 H Plus													
SHP-I 300 Plus													
SHP-I 200 Plus													

4

Floorstanding

SHP-F 220/300 (X) PREMIUM	116
WWK 222/302 (H)	118
SHP-O Plus	120
SHP-O Premium	122
SHP-I Plus	124

SHP-F 220/300 (X) PREMIUM



SHP-F 300 X Premium

Benefits

- Fully wired compact series for recirculation air operation or air duct/outdoor air operation
- Hygienic DHW heating and very high mixed water volumes with up to 65 °C in pure heat pump operation
- Categorised in the highest possible energy efficiency class for water heaters
- Maximum flexibility regarding positioning and installation in the room, with air routing optionally to the side and/or from above
- Permanently high efficiency and safety across the entire service life of the appliance, due to spring-loaded roll-bond heat exchanger
- Reduced operating costs via intelligent interface to increase consumption of on-site photovoltaic energy
- Highly reliable and cost saving due to the impressed current anode integrated as standard
- Display of the currently available mixed water amount via the LCD screen
- Very quiet operation due to sound-insulated compressor and positioning away from the air flow
- „X“ version thanks to additional smooth tube indirect coil can be combined with a solar thermal system or an oil, gas or solid fuel boiler (incl. 2 sensor wells giving a choice of heat generator integration) (Product: 238632)

Application • This compact DHW heat pump supplies DHW efficiently to multiple draw-off points. • The appliance is suitable for recirculation air and air duct operation even at low supply air temperatures. • Highly flexible positioning, because the air duct can be connected on the side or at the top (accessory required).

Convenience features • The demanding draw-off profiles ensure very high hot water convenience. High temperatures are possible in heat pump-only mode, which makes efficient and hygienic DHW heating possible. • High operating convenience. The electronic controller is equipped with an LCD screen, which displays the currently available mixed water amount. • Quiet operation thanks to compressor being sound-insulated from the air stream. • Reliable and cost saving due to the factory-fitted integral impressed current anode.

Combination options • To support the targeted increase of self-consumption, an intelligent interface for communication with suitable photovoltaic systems is integrated as standard. • The 300 litre model is equipped with an integral smooth tube indirect coil in the X version. The appliance can also be combined with a solar thermal system or an oil, gas or solid fuel boiler.

Efficiency • All appliances are noted for their high quality, reliable equipment and for their energy rating in what is currently the highest possible energy efficiency class. The spring-loaded roll-bond heat exchanger also plays a role in this, ensuring safety and efficiency over the entire service life of the appliance.

		SHP-F 300 X Premium	SHP-F 300 Premium	SHP-F 220 Premium
Part number		**238632**	**238631**	**238630**
Specification				
Energy efficiency class, DHW heating (outdoor air) A+ -> F		A+	A+	A+
Energy efficiency class, DHW heating (indoor air) A+ -> F		A+	A+	A+
Nominal load profile (EN 16147)		XL	XL	L
Height x diameter	mm	1905 x 690	1905 x 690	1501 x 690
Weight	kg	156	135	120
Nominal capacity	l	291	302	220
COP (EN 16147 / A20)		3,75	3,75	3,28
COP (EN 16147 / A7)		3,22	3,22	3,07
Nominal DHW temperature (EN 16147)	°C	55	55	55
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	l	399	422	284
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A7)	l	394	422	267
Indoor sound power level with 4 m air duct (EN 12102)	dB(A)	52	52	52

next page >

		SHP-F 300 X Premium	SHP-F 300 Premium	SHP-F 220 Premium
Indoor sound power level without air duct (EN 12102)	dB(A)	60	60	60
Min./max. application limits, heat source for heat pump operation	°C	-8/+42	-8/+42	-8/+42
Max. DHW temperature with heat pump	°C	65	65	65
Power supply		1/N/PE ~ 230 V 50 Hz	1/N/PE ~ 230 V 50 Hz	1/N/PE ~ 230 V 50 Hz
Auxiliary heater power consumption	kW	1.50	1.50	1.50
Max. mixed water amount at 40 °C	l	440	465	330
Surface area, heat exchanger	m²	1.30		
Required accessories				
Part number		**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested
Recommended accessories				
Part number		**159320**	**159320**	**159320**
Type		LWF N 160	LWF N 160	LWF N 160
Description		Plug-in connector	Plug-in connector	Plug-in connector
Part number		**234022**	**234022**	**234022**
Type		LSWP 160-4 AL	LSWP 160-4 AL	LSWP 160-4 AL
Description		Air hose	Air hose	Air hose
Part number		**234108**	**234108**	**234108**
Type		BS LSWP 160-4 AL	BS LSWP 160-4 AL	BS LSWP 160-4 AL
Description		fixing clip	fixing clip	fixing clip
Part number		**234505**	**234505**	**234505**
Type		AWG 160 R	AWG 160 R	AWG 160 R
Description		Wall outlet	Wall outlet	Wall outlet
Part number		**236899**	**236899**	**236899**
Type		LUS 221/301	LUS 221/301	LUS 221/301
Description		Air diverter hood set	Air diverter hood set	Air diverter hood set

Energy efficiency class in accordance with EU Regulation no. 812/2013Energy efficiency class in accordance with EU Regulation no. 812/2013, rating from September 2017. Highest possible energy rating A until September 2017.Nominal data to EN 16147 - A15 = heat source, recirculation air / A7 = heat source, outdoor air (indoor installation) (Product: 238632, 238631, 238630)

WWK 222/302 (H)



WWK 302

Benefits

- Compact series specially developed for outdoor installation
- Also suitable for indoor installation (recirculation air mode)
- High available mixed water amount and hygienic DHW temperatures > 61 °C in heat pump mode
- Categorised in the highest possible energy efficiency class for water heaters
- Permanently high efficiency and safety across the entire service life of the appliance, due to spring-loaded roll-bond heat exchanger
- Reduced operating costs via intelligent interface to increase consumption of on-site photovoltaic energy
- Display of the currently available mixed water amount via the LCD screen
- Highly reliable and cost saving due to the impressed current anode integrated as standard
- Very quiet operation due to sound-insulated compressor and positioning away from the air flow
- Includes temperature and pressure safety valve (T&P valve)
- Integral emergency/auxiliary heater included as standard (Product: 232905, 233209)

Application • This compact DHW heat pump is installed outdoors and efficiently supplies DHW to multiple draw-off points. • Can also be installed indoors in recirculation air mode. • Quick and easy installation: no settings necessary; the DHW setpoint is preset.

Convenience features • The robust appliance is noted for its long service life in outdoor installations. Contributing to this are the stove enamelled metal casing and the refrigerant circuit assemblies which are insulated from the air stream. • The sophisticated draw-off profiles ensure a very high level of hot water convenience. • Heat pump-only mode enables very high volumes of mixed water to be achieved, in addition to hygiene-promoting water temperatures. • The electronic controller shows the currently available amount of mixed water on an LCD screen. The display is protected by a weatherproof cover. • Quiet operation thanks to compressor being sound-insulated from the air stream. • Reliable and cost saving due to the factory-fitted integral impressed current anode. A temperature and pressure safety valve (T&P valve) is included in the standard delivery.

Efficiency • Both sizes have energy efficiency class A. Contributing to this is the spring-loaded roll-bond heat exchanger which ensures efficiency and safety throughout the entire service life of the appliance.

		WWK 302	WWK 302 H	WWK 222 H	WWK 222
Part number		**231211**	**232905**	**233209**	**231209**
Specification					
Energy efficiency class, DHW heating (indoor air) A+ -> F		A	A	A+	A+
Nominal load profile (EN 16147)		XL	XL	L	L
Height x diameter	mm	1905 x 690	1905 x 690	1501 x 690	1501 x 690
Weight	kg	135	135	120	120
Nominal capacity	l	302	302	220	220
COP (EN 16147 / A20)		2,91	2,91	2,92	2,92
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	l	457	457	322	322
Average sound pressure level at 1 m distance, free field	dB(A)	45	45	45	45
Sound power level (EN 12102)	dB(A)	56	56	56	56
Min./max. application limits, heat source for heat pump operation	°C	-5/+42	-5/+42	-5/+42	-5/+42
Max. DHW temperature with emergency/auxiliary heater	°C	63	63	63	63
Max. DHW temperature with heat pump	°C	65	65	65	65
Power supply		1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Safety valve connection		Rp 3/4	Rp 3/4	Rp 3/4	Rp 3/4

next page >

		WWK 302	WWK 302 H	WWK 222 H	WWK 222
Required accessories					
Part number		**074370**	**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested

Energy efficiency class in accordance with EU Regulation no. 812/2013

SHP-O Plus



SHP-O 300 Plus

Benefits

- DHW heat pump installed outdoors for recirculation air mode
- Especially environmentally responsible thanks to natural refrigerant R290
- Convenient control via the MyStiebel app
- Easier access to the necessary appliance components thanks to optimised device design
- Fast and straightforward remote maintenance thanks to an integral connection with the Servicewelt
- Straightforward combination with a photovoltaic system for utilising self-generated electricity (SG Ready – 4 operating states)
- Fast heating via electric immersion heater if even greater convenience is required
- Time saving PV installation thanks to integral cable ducts
- Low running costs thanks to advanced heat pump technology

Application • This energy efficient DHW heat pump is suitable for convenient central DHW heating. • It is used in family houses and supplies DHW independently of the heating system. The heat pump uses the ambient heat of the surroundings.

Convenience features • The slim, aesthetic design fits perfectly into any setting. • High temperatures are possible in heat pump-only mode, thus ensuring efficient and hygienic DHW heating. • Control is easy via three buttons for quick access to boost, pairing and emergency modes. In addition, five status LEDs provide information on the current appliance status. • Extended functions are available via app. Thanks to the WLAN connection, the heat pump can be controlled from anywhere via smartphone or tablet. The app boosts operating convenience with a multitude of setting options and functions. • The hot water boost function in the app increases the level of convenience for a limited time, for example when guests are visiting. • Very quiet operation, as there is no compressor in the air flow of the heat pump. The appliance is also optimised for recirculation air mode. The axial fan and omission of a duct connection further cut noise emissions. • Futureproof, eco-friendly operation through the natural refrigerant R290. • To be able to use self-generated solar power for DHW heating, the integral smart interface communicates with suitable photovoltaic installations. • The heat pump can be combined with solar thermal systems or with oil or gas boilers. A version with integral heat exchanger is available for this.

Service • The appliance casing consists of three parts to allow quick access to all relevant components. This cuts servicing times and simplifies the replacement of various components. • The fault message is relayed via the app, from which a qualified contractor can be contacted directly or emergency mode activated. With integration in the STIEBEL ELTRON Servicewelt, qualified contractors can access the appliance remotely. • The heat pump runtimes are recorded via the app for optimum tracking.

Efficiency • As the (microchannel) condenser is located directly on the cylinder, the heat pump offers greater efficiency than conventional hot water generators. • Charge level matching: To enhance hot water convenience without the need for higher temperatures, users can set the minimum stored mixed water amount themselves.

Installation • The appliance is designed specifically for outdoor installation. After filling the heat pump cylinder, all that's left is to set the required DHW temperature. • Connection to a photovoltaic system is easy thanks to the appliance's optimised design. The integral cable ducts save installation time. • The appliance casing consists of three parts to allow quick access to all relevant components. This cuts servicing times and simplifies the replacement of various components. • The fault message is relayed via the app, from which a qualified contractor can be contacted directly or emergency mode activated. With integration in the STIEBEL ELTRON Servicewelt, qualified contractors can access the appliance remotely. • The heat pump runtimes are recorded via the app for optimum tracking.

GERMAN DESIGN AWARD GOLD 2025 · DESIGN AWARD 2025 · reddot winner 2025

		SHP-O 300 Plus	SHP-O 200 Plus
Part number		**204473**	**204472**
Specification			
Energy efficiency class, DHW heating (indoor air) A+ -> F		A+	A+
Nominal load profile (EN 16147)		XL	L
Height x diameter	mm	1903 x 650	1478 x 650
Weight	kg	116	100
Nominal capacity	l	300	200
COP (EN 16147 / A20)		4,21	4,27

next page >

		SHP-O 300 Plus	SHP-O 200 Plus
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	l	415	267
Sound power level (EN 12102)	dB(A)	58,2	58,2
Min./max. application limits, heat source for heat pump operation	°C	+6/+43	+6/+43
Max. DHW temperature with emergency/auxiliary heater	°C	65	65
Max. DHW temperature with heat pump	°C	65	65
Power supply		1/N/PE 220-240 V 50 Hz	1/N/PE 220-240 V 50 Hz
Auxiliary heater power consumption	kW	1.5	1.5
Safety valve connection		R 1/2	R 1/2
Required accessories			
Part number		**074370**	**074370**
Type		ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested
Recommended accessories			
Part number		**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve

SHP-O Premium



SHP-O 301 Premium

Benefits

- DHW heat pump installed outdoors for recirculation air mode
- Centralised DHW heating even at very low outside temperatures
- Can be used regardless of the installed heating system
- High hot water convenience thanks to second immersion heater integrated as standard
- Sustainable and futureproof thanks to natural refrigerant R290
- Intelligent control via app on smartphone or tablet
- Hygiene program and timer function optimise the domestic hot water experience
- Rapid support in the event of service thanks to remote maintenance option
- Highest efficiency in its class (coefficient of performance according to EN 16147 A20/W10-53 °C)
- Low operating costs due to DHW temperatures of up to 65 °C in pure heat pump operation

Application • This energy efficient DHW heat pump is suitable for centralised DHW heating even at very low outside temperatures. • It is used in family houses and offers a very high degree of DHW convenience, independently of the heating system. The heat pump uses the available heat.

Convenience features • The slim, aesthetic design fits perfectly into any setting. • High temperatures are possible in heat pump-only mode, thus ensuring efficient and hygienic DHW heating. • A very high level of DHW convenience is achieved thanks to the second electric immersion heater integrated as standard. This can be controlled externally (e.g. by the power supply utility). • Control of the heat pump is easy via three buttons for quick access to BOOST, pairing and emergency modes. In addition, five status LEDs provide information on the current appliance status. • Extended functions are available via app. Thanks to the WLAN connection, the heat pump can be controlled from anywhere via smartphone or tablet. The app boosts operating convenience with a multitude of setting options and functions. • The hot water boost function in the app increases the level of convenience for a limited time, for example when guests are visiting. • Very quiet operation, as there is no compressor in the air flow of the heat pump. The appliance is also optimised for recirculation air mode. The axial fan and omission of a duct connection further cut noise emissions. • Futureproof, eco-friendly operation through the natural refrigerant R290. • To be able to use self-generated solar power for DHW heating, the integral smart interface communicates with suitable photovoltaic installations. • The heat pump can be combined with solar thermal systems or with oil or gas boilers. A version with integral heat exchanger is available for this.

Service • The appliance casing consists of three parts to allow quick access to all relevant components. This cuts servicing times and simplifies the replacement of various components. • The fault message is relayed via the app, from which a qualified contractor can be contacted directly or emergency mode activated. With integration in the STIEBEL ELTRON Servicewelt, qualified contractors can access the appliance remotely. • The heat pump runtimes are recorded via the app for optimum tracking.

Efficiency • As the (microchannel) condenser is located directly on the cylinder, the heat pump offers greater efficiency than conventional hot water generators. • Charge level matching: To enhance hot water convenience without the need for higher temperatures, users can set the minimum stored mixed water amount themselves.

Installation • The appliance is designed specifically for outdoor installation. At the installation site, the heat pump is simply connected with the standard mains plug. After filling the heat pump DHW cylinder, all that's left is to set the required DHW temperature. • Connection to a photovoltaic system is easy thanks to the appliance's optimised design. The integral cable ducts save installation time. • The appliance casing consists of three parts to allow quick access to all relevant components. This cuts servicing times and simplifies the replacement of components. • The fault message is relayed via the app, from which a qualified contractor can be contacted directly or emergency mode activated. With integration in the STIEBEL ELTRON Servicewelt, qualified contractors can access the appliance remotely. • The heat pump runtimes are recorded via the app for optimum tracking.

GERMAN DESIGN AWARD GOLD 2025

reddot winner 2025

		SHP-O 301 Premium	SHP-O 201 Premium
		NEW	NEW
Part number		**207265**	**207264**
Specification			
Nominal load profile (EN 16147)		XL	L
Height x diameter	mm	1903 x 650	1478 x 650
Weight	kg	116	100

next page >

		SHP-O 301 Premium	SHP-O 201 Premium
Nominal capacity	l	300	200
COP (EN 16147 / A20)		4,21	4,27
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	l	415	267
Sound power level (EN 12102)	dB(A)	58,2	58,2
Min./max. application limits, heat source for heat pump operation	°C	-10/+43	-10/+43
Max. DHW temperature with emergency/auxiliary heater	°C	75	75
Max. DHW temperature with heat pump	°C	65	65
Power supply		1/N/PE 220-240 V 50 Hz	1/N/PE 220-240 V 50 Hz
Auxiliary heater power consumption	kW	1.5	1.5
Safety valve connection		R 1/2	R 1/2
Required accessories			
Part number		**074370**	**074370**
Type		ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested
Recommended accessories			
Part number		**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve

SHP-I Plus



SHP-I 300 H Plus

Benefits

- DHW heat pump installed indoors for recirculation air mode
- Especially environmentally responsible thanks to natural refrigerant R290
- Intuitive operation using rotary selector or via app
- Easier access to the necessary appliance components thanks to optimised device design
- Fast and straightforward remote maintenance thanks to an integral connection with the Servicewelt
- Straightforward combination with a photovoltaic system for utilising self-generated electricity (SG Ready – 4 operating states)
- There are no special requirements for the installation site, due to the small amount of refrigerant
- Mains plug supplied as standard for straightforward, quick installation
- Time saving PV installation thanks to integral cable ducts
- Low running costs thanks to advanced heat pump technology

Application • This energy efficient DHW heat pump is suitable for convenient central DHW heating. • It is used in family houses and supplies DHW independently of the heating system. The heat pump uses the ambient heat in the installation room (e.g. waste heat from the heating system, freezer or tumble dryer).

Convenience features • The slim, aesthetic design is perfect for any installation room. • High temperatures are possible in heat pump-only mode, thus ensuring efficient and hygienic DHW heating. • It is very easily controlled by means of a rotary selector and three buttons for quick access to boost, pairing and emergency modes. In addition, five status LEDs provide information on the current appliance status. • Extended functions are available via app. Thanks to the WLAN connection, the heat pump can be controlled from anywhere via smartphone or tablet. The app boosts operating convenience with a multitude of setting options and functions. • The hot water boost function in the app increases the level of convenience for a limited time, for example when guests are visiting. • The heat pump dehumidifies and cools the air in the installation room. • Very quiet operation, as there are no components in the air flow of the heat pump. The appliance is also optimised for recirculation air mode. The axial fan and omission of a duct connection further cut noise emissions. • Futureproof, eco-friendly operation through the natural refrigerant R290. • To be able to use self-generated solar power for DHW heating, the integral smart interface communicates with suitable photovoltaic installations. • The heat pump can be combined with solar thermal systems or with oil, gas or solid fuel boilers. A version with integral heat exchanger and 300 litres capacity is available for this.

Service • The appliance casing consists of three parts to allow quick access to all relevant components. This cuts servicing times and simplifies the replacement of various components. • The fault message is relayed via the app, from which a qualified contractor can be contacted directly or emergency mode activated. With integration in the STIEBEL ELTRON Servicewelt, qualified contractors can access the appliance remotely. • The heat pump runtimes are recorded via the app for optimum tracking.

Efficiency • As the (microchannel) condenser is located directly on the cylinder, the heat pump offers greater efficiency than conventional hot water generators. • Charge level matching: To enhance hot water convenience without the need for higher temperatures, users can set the minimum stored mixed water amount themselves.

Installation • In the installation room, the heat pump is simply connected with the standard mains plug. After filling the heat pump cylinder, all that's left is to set the required DHW temperature. • Connection to a photovoltaic system is easy thanks to the appliance's optimised design. The integral cable ducts save installation time.

		SHP-I 300 H Plus	SHP-I 300 Plus	SHP-I 200 Plus
		DISCONT. PRODUCT	DISCONT. PRODUCT	DISCONT. PRODUCT
Part number		**204478**	**204476**	**204474**
Specification				
Energy efficiency class, DHW heating (indoor air) A+ -> F		A+	A+	A+
Nominal load profile (EN 16147)		XL	XL	L
Height x diameter	mm	1903 x 650	1903 x 650	1478 x 650
Weight	kg	123	110	95
Nominal capacity	l	294	300	200
COP (EN 16147 / A20)		4,34	4,21	4,27

next page >

		SHP-I 300 H Plus	SHP-I 300 Plus	SHP-I 200 Plus
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	l	390	415	267
Min./max. application limits, heat source for heat pump operation	°C	+6/+43	+6/+43	+6/+43
Max. DHW temperature with heat pump	°C	65	65	65
Power supply		1/N/PE 230-240 V ~50 Hz	1/N/PE 230-240 V ~50 Hz	1/N/PE 230-240 V ~50 Hz
Auxiliary heater power consumption	kW	1.50	1.50	1.50
Surface area, heat exchanger	m²	0.90		
Required accessories				
Part number		**074370**	**074370**	**074370**
Type		ZH 1	ZH 1	ZH 1
Description		Safety assembly, pressure-tested	Safety assembly, pressure-tested	Safety assembly, pressure-tested
Recommended accessories				
Part number		**074371**	**074371**	**074371**
Type		DMV/ZH 1	DMV/ZH 1	DMV/ZH 1
Description		Pressure reducing valve	Pressure reducing valve	Pressure reducing valve

Energy efficiency class in accordance with EU Regulation no. 812/2013

4

Installation accessories
Accessories 128

ZH1



Benefits
› Maximum safety evidenced by DVGW certification mark
› Long service life and reliability thanks to the use of high quality components

Description • The safety assembly is suitable for combination with pressure-tested electric and integral cylinders. • Standard delivery includes a shut-off valve, non-return valve with service valve, pressure gauge connection, diaphragm safety valve and drain outlet. • To ensure that no waste water is sucked back, a pipe break is integrated into the drain outlet of the safety valve. • With its threaded fitting, the safety valve can be rotated, repositioned or replaced to match it to different installation situations. • The safety assembly enables angled or straight-through installation in horizontal and vertical pipework. • In vertical pipework, install the safety assembly only in a bottom to top flow direction. • A pressure reducing valve can be retrofitted if required.

ZH 1

		ZH 1
Part number		**074370**
Specification		
Safety valve response pressure	MPa	0.60
Pressure reducing valve		-
Drip water connection		•
Water connection		G 1 A
Installation type		Surface-mounted
Safety valve	bar	6

AWG



Benefits
› Highly convenient thanks to extremely quiet weather grille with very low pressure drop

Description • The thermally insulating wall outlet made of EPS is designed for the connection of an air duct. • To reliably prevent run marks on the external wall, the weather grille made of painted sheet steel has a drip edge. • If outdoor air is used as a heat source, no additional thermal insulation measures are needed for the pipe. This allows straightforward installation with small dimensions.

AWG 160 R

		AWG 160 R
Part number		**234505**
Specification		
Max. air flow rate	m³/h	350
Width of surround for weather grille	mm	220
Connection diameter	mm	160
Outer pipe diameter	mm	200
Pipe length	mm	545
Weight	kg	0.50
Wall outlet material		EPS (grey)
Weather grille material		Painted sheet steel (silver grey)
Condensation limit at: temperature inside pipe / temperature around the pipe / relative humidity around the pipe		-20 °C / 20 °C / 60 %

LUS



Benefits
› Maximum flexibility thanks to horizontal or vertical air routing

Description • With the air diverter kit, the factory-fitted horizontal air routing on a DHW heat pump can be switched to vertical. This choice between vertical or horizontal air routing allows greater flexibility in the installation room.

LUS 221/301

		LUS 221/301
Part number		**236899**
Specification		
Connection		DN 160
Diameter		160 mm

LSWP AL



Benefits
› Thermally insulated air hose
› Hose ends for connection, can be shaped into ovals
› Length: 400 cm

Description • The thermally insulated air hose is suitable for outdoor and exhaust air ducting. • The outside and inside are made from aluminium and polyester laminate. The inside is reinforced with a wire spiral. An intermediate layer of mineral wool provides thermal insulation.

LSWP 160-4 AL

		LSWP 160-4 AL
Part number		**234022**
Specification		
Nominal diameter	mm	160
Length	mm	4000
Thermal insulation thickness	mm	50
Colour of air hose		Aluminium-coloured outer sheath
Required accessories		
Part number		**234108**
Type		BS LSWP 160-4 AL
Description		fixing clip

BS LSWP AL



Benefits
› Stainless steel clip for DN 160 and DN 200
› Stainless steel

Description • Fixing clip to DIN 3017. The band is made from stainless steel and the closure from hardened galvanised steel.

BS LSWP 160-4 AL

		BS LSWP 160-4 AL
Part number		**234108**

Water filter 133

Water pumps and filters

5

Filter cartridges
- Sediment 13“ 134
- Activated carbon block 13“ 135
- Ultra filtration 13“ 136
- Silver GAC & mineral balls 13“ 137
- Stiebel House PS cartridge 138
- Stiebel House ACB cartridge 139
- SNOW DUAL FILTER CARTRIDGE 140
- SNOW RO FILTER CARTRIDGE 141
- SNOW PRO DUAL FILTER CARTRIDGE 142
- SNOW PRO RO FILTER CARTRIDGE 143

Drinking water filter
- SNOW 144
- SNOW PRO 145

Filter cartridges

Sediment 13“



Sediment Filter 13” (EX)

Benefits

- Durable PP surface with 1 micron pore size for efficient pre-filter removal functions
- Hygienic encapsulated cartridge
- “Push & click” system for easy filter replacement

Application • First stage sediment filter cartridge used with Stream and Stream 5S drinking water filters.

Convenience features • The filter medium is made from durable polypropylene with a large surface area for outstanding filtration performance.

Replacement• The “push & click” function makes filter replacement as simple as pushing a button and changing the cartridge. A “click” sound signals that the filter has been inserted properly into the adaptor.

Safety & Quality • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter• Polypropylene, 1 µm. Reduces silt, rust, sediment and larger particles.

		Sediment Filter 13“ (EX)
Part number		**230875**
Specification		
Length of filter medium	Inches	13
Filtration stages		1
Filter stage 1		Sediment filter - 1 µm

Activated carbon block 13“



Activated carbon block 13” (EX)

Benefits
- Large carbon surface area for efficient particle removal
- High quality carbon material for better taste and filtration performance
- Strict quality control in both temperature and material ensures optimum performance of the carbon block
- Hygienic encapsulated cartridge
- “Push & click” system for easy filter replacement

Application • Second stage sediment filter cartridge used with Stream and Stream 5S drinking water filters.

Convenience features • This filter medium is made from coconut shells and delivers outstanding filtration performance. • The activated carbon reduces herbicides, pesticides and turbidity, adsorbs chlorine, VOCs and TTHMs, and is also able to remove heavy metals such as lead and mercury.

Replacement • The “push & click” function makes filter replacement as simple as pushing a button and changing the cartridge. A “click” sound signals that the filter has been inserted properly into the adaptor.

Safety & Quality • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter• Activated carbon block, 0.5 µm. • Reduces unpleasant tastes and odours, chlorine, trihalomethanes, VOCs and heavy metals (lead, copper, aluminium, selenium, zinc, iron).

5

		Activated carbon block 13“ (EX)
Part number		**230877**
Specification		
Length of filter medium	Inches	13
Filtration stages		1
Filter stage 2		Activated carbon block - 0.5 µm

Ultra filtration 13“



Ultrafiltration 13” (EX)

Benefits
- High quality Ultra-filtration from hollow fiber membrane for 100% bacterial removal and no waste water, no electricity needed
- Hygienically encapsulated cartridge
- “Push & click” system for easy filter replacement“

Application • Third stage filter cartridge used with Stream and Stream 5S drinking water filters.

Convenience features • Ultrafiltration (UF) membrane with microporous hollow fibre structure works as an efficient filter to remove 100 % of bacteria, particles down to 0.01 microns and some viruses.

Replacement • The “push & click” function makes filter replacement as simple as pushing a button and changing the cartridge. A “click” sound signals that the filter has been inserted properly into the adaptor.

Safety & Quality • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter • Ultrafiltration hollow fibre, 0.01 – 0.1 µm. • 100 % bacteria removal. • Removes cysts, bacteria, some viruses and algae.

		Ultrafiltration 13“ (EX)
Part number		**230879**
Specification		
Length of filter medium	Inches	13
Filtration stages		1
Filter stage 3		Ultra filtration (hollow fibre) - 0.1-0.01 µm

Silver GAC & mineral balls 13“



SILVER GAC & MINERAL BALLS 13” (EX)

Benefits
- A large volume of high-grade carbon powder improves the taste of the water in the last stage
- Antibacterial silver ions provide double protection of the water filter
- Hygienic encapsulated cartridge
- “Push & click” system for easy filter replacement

Application • Fourth and fifth-stage filter cartridge used with Stream and Stream 5S drinking water filters.

Convenience features • This filter medium is made from coconut shells and delivers outstanding filtration performance. • Antibacterial carbon powder prevents harmful contaminants from entering and keeps the filter cartridge constantly fresh. • Oxidation Reduction Potential (ORP) mineral ceramic balls slightly reduce the ORP value, which antioxidises the water to increase our natural metabolism.

Replacement • The “push & click” function makes filter replacement as simple as pushing a button and changing the cartridge. A “click” sound signals that the filter has been inserted properly into the adaptor.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter• 2 stages of carefully selected filter media are combined in one single filter cartridge.

1. ORP mineral balls. Reduce the ORP content of tap water

2. Post-carbon filter with silver ions. Improves the taste of the water; silver ions added to the carbon prevent the growth of bacteria inside the filter.

5

		SILVER GAC & MINERAL BALLS 13“ (EX)
Part number		**239935**
Specification		
Length of filter medium	Inches	13
Filtration stages		2.0
Filter stage 4		Activated carbon powder in granulated form
Filter stage 5		Mineral ceramic balls

Stiebel House PS cartridge



Stiebel House PS cartridge (EX)

Benefits
- Improves water quality by removing contaminants
- Durable and porous pleated filter media
- Indirectly improves the water flow as less clogging occurs, therefore less maintenance is needed for sanitary fittings
- Reduces limescale deposits with anti-limescale balls, for gleaming sanitary fittings
- Silverlite stone increases the safety of the whole filter system
- Suitable for use with various water sources

Application • 3-stage filter cartridge used with the Stiebel House PS-2.

Convenience features • The cartridge consists of durable pleated polypropylene with a large surface area, with Silverlite stone and anti-limescale balls for outstanding filtration performance. • Improves the water quality by removing dirt and contaminants (sand, soil, algae, etc.) from the inlet water with extra large, tightly pleated and durable filter media. • Less clogging of point-of-use filters and sanitary fittings (shower units, tap outlets, etc.). • Indirectly improves the water flow as less clogging occurs, therefore less maintenance is needed for sanitary fittings. • The growth of bacteria in the filter system is prevented thanks to silver ions. • Reduces limescale deposits with anti-limescale balls, for gleaming sanitary fittings and kitchenware. • Silverlite stone increases the safety of the whole filter system. It contains silver ions and several minerals to prevent the growth of bacteria inside the filter system and contamination from outside the filter.

Installation • The Stiebel House PS-2 filter cartridge can be changed conveniently using the wrench that comes with the original purchase.

Safety • The anti-limescale filter media are certified as safe for drinking water by NSF International with NSF Mark 60 for material safety.

Filter • 3 stages of carefully selected filter media.

1. Polypropylene pleated sediment, range 1 – 10 µm: Reduces silt, rust, sediment and particles larger than its pore size.

2. Silverlite stone: The insoluble Silverlite stone consists of CaO, SiO2, AlO3, MgO and MnO, and is coated with silver ions. It has a strong antibacterial effect and prohibits germs from entering the filter media.

3. Anti-limescale balls: Reduce limescale deposits in the inlet water

		Stiebel House PS cartridge (EX)
Part number		**239933**
Specification		
Length of filter medium	Inches	20
Filter stage 1		Sediment - 10 µm
Filter stage 2		Silverlite stone
Filter stage 3		NSF 60 certified anti-hardness polyphosphate crystal balls

Stiebel House ACB cartridge



Stiebel House ACB cartridge (EX)

Benefits
- Improves water quality by removing contaminants
- Improves water taste and odour by reducing chlorine, heavy metals and bacteria
- Indirectly improves the water flow as less clogging occurs, therefore less maintenance is needed for sanitary fittings
- Antibacterial silver ions provide double protection of the water filter
- Suitable for use with various water sources

Application • 2-stage filter cartridge used with the Stiebel House ACB-2.

Convenience features • The filter medium is made from coconut shells and silver ions. It improves the water quality and taste by reducing dirt particles, chlorine, heavy metals and some bacteria. • Delivers cleaner and safer drinking water with reduced odours. • Reduces allergies caused by chlorine and its harmful compounds for healthier fresh water usage. • Less clogging of point-of-use filters and sanitary fittings (shower units, tap outlets, etc.). • Indirectly improves the water flow as less clogging occurs, therefore less maintenance is needed for sanitary fittings. • Silverlite stone increases the safety of the whole filter system. It contains silver ions to prevent the growth of bacteria inside the filter system.

Installation • The Stiebel House ACB-2 filter cartridge can be changed conveniently using the wrench that was supplied with the original purchase.

Safety • The Stiebel House ACB-2 is tested by SGS

Filter • 2 stages of carefully selected filter media.

1. Activated carbon block, 5 µm: Reduces dirt particles, chlorine, heavy metals and some bacteria to give clearer, cleaner and safer outlet water.

2. Silverlite stone: Silver ions prevent the growth of bacteria inside the filter system

		Stiebel House ACB cartridge (EX)
Part number		**239934**
Specification		
Length of filter medium	Inches	20
Filtration stages		2.0
Filter stage 1		Activated carbon block with antibacterial silver media - 5 µm

Filter cartridges

SNOW DUAL FILTER CARTRIDGE



SNOW DUAL FILTER CARTRIDGE (EX)

APPLICATION: 4-in-1 filter cartridge for use for Snow RO drinking water filter.

EQUIPMENT & CONVENIENCE: This filter medium is made from polypropylene fibre and coconut shells and delivers outstanding filtration performance. The dual sediment and activated carbon block reduces sediments, herbicides, pesticides and turbidity, adsorbs chlorine, VOCs and TTHMs, and is also able to remove heavy metals such as lead and mercury.

REPLACEMENT: The “twist” function makes filter replacement as simple twist and changing the cartridge.

SAFETY & QUALITY: The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

		SNOW DUAL FILTER CARTRIDGE (EX)
		NEW
Part number		**206463**
Specification		
Filtration stages		4
Filter stage 1		Pleated sediment - 5 µm
Filter stage 2		Carbon fibre
Filter stage 3		Pleated sediment - 5 µm

SNOW RO FILTER CARTRIDGE



SNOW RO FILTER CARTRIDGE (EX)

Application • Fifth stage filter cartridge used with Snow RO drinking water filters.

Convenience features • This filter medium is made from thin-film composite membrane with pore sizes down to 0.0001 µm and delivers outstanding filtration performance.

Replacement • The “twist” function makes filter replacement as simple twist and changing the cartridge.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter • EFRO RO membrane 0.0001 µm: Removes bacteria, viruses, cysts and algae. Removes heavy metals (lead, copper, aluminium, selenium, zinc, iron), salt and calcium hardness.

		SNOW RO FILTER CARTRIDGE (EX)
		NEW
Part number		**206461**
Specification		
Length of filter medium	Inches	12
Filtration stages		1
Filter stage 1		100 GPD RO membrane 0.0001 µm

SNOW PRO DUAL FILTER CARTRIDGE



SNOW PRO DUAL FILTER CARTRIDGE (EX)

Application • 4-in-1 filter cartridge for Snow PRO drinking water filter.

Convenience features • This filter medium is made from polypropylene fibre and coconut shells and delivers outstanding filtration performance. The dual sediment and activated carbon block reduce sediments, herbicides, pesticides and turbidity, adsorb chlorine, VOCs and TTHMs, and remove heavy metals such as lead and mercury.

Replacement • Twist" function for easy filter replacement, no tools required.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

		SNOW PRO DUAL FILTER CARTRIDGE (EX)
		NEW
Part number		**207813**
Specification		
Filtration stages		4
Filter stage 1		Pleated sediment - 5 µm
Filter stage 2		Carbon fibre
Filter stage 3		Pleated sediment - 5 µm

SNOW PRO RO FILTER CARTRIDGE



SNOW PRO RO FILTER CARTRIDGE (EX)

Application • Fifth stage filter cartridge for Snow PRO drinking water filters

Convenience features • This filter medium is made from thin-film composite membrane with pore sizes down to 0.0001 µm and delivers outstanding filtration performance.

Replacement • "Twist" function for easy filter replacement, no tools required.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

Filter • EFRO RO membrane 0.0001 µm: Removes bacteria, viruses, cysts and algae. Removes heavy metals (lead, copper, aluminium, selenium, zinc, iron), salt and calcium hardness.

		SNOW PRO RO FILTER CARTRIDGE (EX)
		NEW
Part number		**207814**
Specification		
Length of filter medium	Inches	11
Filtration stages		1
Filter stage 1		100 GPD RO membrane 0.0001 µm

SNOW



SNOW (EX)

Benefits

- The powerful 100 GPD RO membrane provides high and consistent flow to fill up the tank faster
- High efficiency RO membrane reduces the ratio of wastewater to 40% of the feedwater
- Saves space while maintaining maximum filtration performance
- Filter lifetime LED indicator alerts when the cartridge is due for replacement
- The most compact and lightweight RO water purifier on the market
- Installation with 60 % less pipework than traditional models.

Application • The Snow is a reverse osmosis (RO) water filter that purifies water from the municipal supply to instantly deliver clean, fresh drinking water.

Convenience features • The powerful 100 GPD RO membrane provides filtered water with consistently high flow up to 100 gallons per day to fill up the tank faster. The high efficiency RO membrane limits the ratio of wastewater to 40% of the feedwater. This prevents early clogging of the RO filter and improves the lifetime of all filter cartridges as less feedwater needs to pass through. One of the most compact and lightweight RO water purifier on the market. The compact dimensions and stable base allow safe and steady installation in limited spaces. When the filter cartridge is due for replacement, the user is notified with light and audible alarm. “Twist & done” function for easy filter replacement, no tools required. German engineering with 60 % less pipework than traditional models. The “automatic water shut-off” function prevents water leakage and damge to the cartridges when removed from the head adapter or is not inserted properly, Making filter replacment safe and easy.

Installation • For installation under the sink or wall-mounted.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

		SNOW (EX)
		NEW
Part number		**206462**
Specification		
Height	mm	36
Width	mm	14
Depth	mm	37.5
Weight	kg	5.15
Filtration stages		5
Filter stage 1		Pleated sediment - 5 µm
Filter stage 2		Carbon fibre
Filter stage 3		Pleated sediment - 5 µm
Draw-off option		Swan neck tap
Colour		white
Maximum water pressure	bar	4
Electrical connection		1/N/PE~220-240 V
Installation type		Undersink
Temperature range	°C	4 - 35

SNOW PRO



SNOW PRO (EX)

Benefits

- The powerful RO membrane with 600 gallons per day provides filtered water with consistently high flow directly to the faucet without the need for a storage tank
- LED filter lifetime indicator consisting of a light and an audible alarm alerts the user when the cartridge is due for replacement.
- 6-stage filtration in 2 cartridges provide a good tasting and safe drinking water source
- High efficiency RO membrane reduces the ratio of wastewater to 40% of the feed water.
- "Twist" system for filter replacement without tools
- Compact and lightweight design for space saving installation

Application • The Snow Pro is a tankless reverse osmosis (RO) water filter that purifies water from the municipal supply to instantly deliver clean, fresh drinking water.

Convenience features • The powerful 600 GPD RO membrane provides filtered water with consistently high flow directly to the faucet without the need for a storage tank. The high efficiency RO membrane limits the ratio of wastewater to 40% of the feedwater. This prevents early clogging of the RO filter and improves the lifetime of all filter cartridges as less feedwater needs to pass through. One of the most compact and lightweight RO water purifiers on the market. The compact dimensions and stable base allow safe and steady installation in limited spaces. When the filter cartridge is due for replacement, the user is notified with light and audible alarm. "Twist" function for easy filter replacement, no tools required. German engineering with 60 % less pipework than traditional models. Filter replacement is made safe and easy thanks to the "automatic water shut-off" function, which prevents water leakage and damage to the cartridges when removing from or inserting to the head adapter.

Installation • Under the sink or wall-mounted.

Safety • The filter is encapsulated inside the cartridge which provides protection against contamination from the outside, for example during filter replacement and cleaning.

		SNOW PRO (EX)
		NEW
Part number		**207812**
Specification		
Height	mm	135
Width	mm	368
Depth	mm	376
Weight	kg	5.15
Filtration stages		6
Filter stage 1		Sediment - 5 µm
Filter stage 2		Carbon fibre
Filter stage 3		Sediment - 5 µm
Filter stage 4		Granulated activated carbon
Filter stage 5		600 GPD tankless RO membrane – up to 0.0001 µm
Filter stage 6		Activated carbon block
Max. flow rate	l/min	4.5*
Draw-off option		Swan neck tap
Colour		white
Maximum water pressure	bar	4
Electrical connection		1/N/PE~220-240 V
Installation type		Undersink
Nominal flow rate	l/min	1.6
Temperature range	°C	4 - 38

Drinking water filter

Air source heat pumps, outdoor installation – inverter		151
Air source heat pumps, outdoor installation – Fixspeed		215
Accessories for air source heat pumps installed outdoors		231
Air source heat pumps, indoor installation – inverter		253
Accessories for air source heat pumps installed indoors		267

HP A-O 07.1 CS Premium

Place of installation

Outdoor	**O**
Indoor	**I**

Device type

Heat pump **HP**

Version counter

.1

Source

Air	**A**
Ground	**G**
Water	**W**

Classification

Trend
Plus
Premium

Heat output

at A-7/W35 or B0/W35 integer

Function

Duo (Integral DHW cylinder)	**D**
Cooling	**C**
Free field	**F**
Corner installation	**E**
Single Phase	**S**
Sound-optimized	**dB**


Application areas




Heating

Cooling






















Air source heat pumps, outdoor installation – inverter

Inverter

- HPA-O Plus 152
- HPA-O W Plus 159
- HPA-O Plus + HSBC 200 166
- HPA-O W Plus + HSBC 200 167
- HPA-O Plus + HSBC 200 S 168
- HPA-O W Plus + HSBC 200 S 170
- HPA-O Plus + HSBC 300 171
- HPA-O W Plus + HSBC 300 172
- HPA-O Plus + HM Trend 174
- HPA-O W Plus + HM Trend 174
- HPA-O Plus + HMS Trend 175
- HPA-O W Plus + HMS Trend 176
- HPA-O Trend 177
- HPA-O Trend + HSBC 200 184
- HPA-O Trend + HSBC 200 S 185
- HPA-O Trend + HSBC 300 186
- HPA-O Trend + HM Trend 187
- HPA-O Trend + HMS Trend 188
- HPA-O 05.1/07.1 CS Premium 189
- HPA-O 7-13 Premium 195
- HPA-O 7-13 C Premium 199
- HPA-O 3-8 Plus 205
- HPA-O CS Plus flex Set 208
- HPA-O Plus compact Set 1.1 209
- HPA-O Plus compact D Set 1.1 210
- WPL 19/24 A 211

HPA-O Plus



HPA-O 05.2 Plus HC 230

Benefits

- Air source heat pump installed outdoors for modernisation and new build
- Also suitable for densely built-up areas due to very low operating noise
- Low costs thanks to R290 refrigerant circuit remaining efficient all year round, as well as optimally matched components
- Compact mono block version in a timeless design
- Efficient cooling possible thanks to circuit reversal
- Many solutions for different applications possible with flexible installation options and customised accessories
- Multi stage safety concept for the R290 refrigerant circuit

Application • Air source heat pump with inverter technology and all-in-one design for universal use in modernisation and new build. Compact mono block version for siting outdoors. Thanks to minimal operating noise, it is also suitable for densely built-up areas. Low operating costs through high efficiency all year round. • Indoor units with different storage volumes are available depending on the DHW demand. The system delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal. • The WPM heat pump manager controls the system reliably and efficiently with a connection to the STIEBEL ELTRON Servicewelt. • Cascade solution of up to six heat pumps possible. • Extended, three-stage safety concept for reliable protection of the heating circuit against refrigerant ingress.

Convenience features • Very quiet operation is made possible by the encapsulated refrigerant circuit and acoustically isolated compressor. Contributing to the low sound power level are the modulating fans and the wide gaps between the evaporator fins which reduce air resistance. • Very low operating noise and therefore free choice of installation location. Additional, dB-precise and demand-orientated sound limitation with silent mode. • High DHW temperatures are assured without the need for electric backup, even in the winter; this is because the heat pump works with high flow temperatures all year round. • The consistent design delivers a timeless and high quality aesthetic.

Installation • Easier transport and placement thanks to the innovative carrying concept, compact dimensions and low weight. • Quick installation thanks to integral anti-vibration mount, no additional components required. • Easy access to the electrical connection panel at the side, secure connection thanks to spring terminal technology. • Siting and connection of the components is supported and simplified by coordinated accessories in the product range.

Efficiency • The refrigerant circuit works with the eco-friendly and futureproof refrigerant R290. In combination with the optimally and generously matched components, efficient operation is possible all year round. • Further increase in system efficiency by optimising the number of defrosting processes with demand-dependent control and natural defrosting without using the compressor.

		HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
		NEW	NEW	NEW	NEW	NEW
Part number		**207429**	**207430**	**207432**	**207433**	**207435**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
SCOP 35 °C (EN 14825)		5.35	5.09	4.96	4.96	4.89
SCOP 55 °C (EN 14825)		4.07	4.02	3.99	3.99	4.01
Heating output at A7/W35 (EN 14511)	kW	2.77	3.05	4.32	4.32	5.79
Heating output at A2/W35 (EN 14511)	kW	3.14	3.29	4.09	4.09	4.82
Heating output at A-7/W35 (EN 14511)	kW	5.22	7.09	10.07	10.07	13.15
COP at A7/W35 (EN 14511)		5.48	5.50	5.40	5.40	5.41
COP at A2/W35 (EN 14511)		4.72	4.57	4.54	4.54	4.41
COP at A-7/W35 (EN 14511)		3.47	3.25	3.15	3.15	3.11
Max. cooling capacity at A35/W7	kW	4.50	6.51	9.33	9.33	10.09
Cooling capacity at A35/W18 partial load (EN 14511)	kW	3.15	3.15	4.29	4.29	5.81

next page >

		HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
Max. cooling capacity at A35/ W18	kW	4.96	6.98	10.51	10.51	12.95
Energy efficiency ratio at A35/ W7 max.		3.29	2.97	2.76	2.76	3.14
Energy efficiency ratio at A35/ W18 partial load (EN 14511)		5.29	5.29	5.46	5.46	5.41
Energy efficiency ratio at A35/ W18 max.		4.87	4.28	4.01	4.01	4.11
Sound power level (EN 12102)	dB(A)	43	43	46	46	45
Min./max. application limits for heat source	°C	-25 / 40	-25 / 40	-25 / 40	-25 / 40	-25 / 40
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	960	960	1144	1144	1365
Width	mm	1170	1170	1170	1170	1170
Depth	mm	727	727	727	727	727
Weight	kg	144	145	166	166	205
Rated voltage, compressor	V	230	230	230	400	400
Refrigerant		R290	R290	R290	R290	R290
Colour		Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021
Recommended accessories						
Part number		**206780**	**206780**	**206780**	**206780**	**206780**
Type		ISG Connect	ISG Connect	ISG Connect	ISG Connect	ISG Connect
Description		Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility
Part number		**207711**	**207711**	**207711**	**207711**	**207711**
Type		AHP-SB.1	AHP-SB.1	AHP-SB.1	AHP-SB.1	AHP-SB.1
Description		Cover	Cover	Cover	Cover	Cover
Part number		**207713**	**207713**			
Type		AHP-WB.1	AHP-WB.1			
Description		Wind protection of the heat pump for installation in open spaces	Wind protection of the heat pump for installation in open spaces			
Part number		**207715**	**207715**	**207715**	**207715**	**207715**
Type		AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1
Description		Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground
Part number		**207716**	**207716**	**207716**	**207716**	**207716**
Type		AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207717**	**207717**	**207717**	**207717**	**207717**
Type		AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207718**	**207718**	**207718**	**207718**	**207718**
Type		AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207719**	**207719**	**207719**	**207719**	**207719**
Type		AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207720**	**207720**	**207720**	**207720**	**207720**
Type		AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207721**	**207721**	**207721**	**207721**	**207721**
Type		AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200
Description		Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies

next page >


		HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
Part number		**207723**	**207723**	**207723**	**207723**	**207723**
Type		AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1
Description		Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps
Part number		**207724**	**207724**	**207724**	**207724**	**207724**
Type		AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4
Description		Downward connection set	Downward connection set	Downward connection set	Downward connection set	Downward connection set
Part number		**207727**	**207727**	**207727**	**207727**	**207727**
Type		AHP-TB 420	AHP-TB 420	AHP-TB 420	AHP-TB 420	AHP-TB 420
Description		Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct
Part number		**207728**	**207728**	**207728**	**207728**	**207728**
Type		AHP-TB 710	AHP-TB 710	AHP-TB 710	AHP-TB 710	AHP-TB 710
Description		Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct
Part number		**207731**	**207731**	**207731**	**207731**	**207731**
Type		AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1
Description		Condensate pan	Condensate pan	Condensate pan	Condensate pan	Condensate pan
Part number		**207732**	**207732**	**207732**	**207732**	**207732**
Type		AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1
Description		Floor bracket	Floor bracket	Floor bracket	Floor bracket	Floor bracket
Part number		**207733**	**207733**	**207733**	**207733**	**207733**
Type		AGC-CB.1	AGC-CB.1	AGC-CB.1	AGC-CB.1	AGC-CB.1
Description		Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)
Part number		**207735**	**207735**	**207735**	**207735**	**207735**
Type		AHP-CB.1	AHP-CB.1	AHP-CB.1	AHP-CB.1	AHP-CB.1
Description		Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet
Part number		**207737**	**207737**	**207737**	**207737**	**207737**
Type		AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1
Description		stand bracket	stand bracket	stand bracket	stand bracket	stand bracket
Part number		**207738**	**207738**	**207738**	**207738**	**207738**
Type		AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8
Description		Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base
Part number		**207891**	**207891**	**207891**	**207891**	**207891**
Type		AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**207892**	**207892**	**207892**	**207892**	**207892**
Type		AWM-CB.1	AWM-CB.1	AWM-CB.1	AWM-CB.1	AWM-CB.1
Description		Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set
Part number		**207894**	**207894**	**207894**	**207894**	**207894**
Type		AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1
Description		Ball siphon	Ball siphon	Ball siphon	Ball siphon	Ball siphon
Part number				**208679**	**208679**	
Type				AHP-WB.2	AHP-WB.2	
Description				Wind protection of the heat pump for installation in open spaces	Wind protection of the heat pump for installation in open spaces	
Part number						**208680**
Type						AHP-WB.3
Description						Wind protection of the heat pump for installation in open spaces

next page >


		HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
Part number		**208702**	**208702**	**208702**	**208702**	**208702**
Type		WK 3	WK 3	WK 3	WK 3	WK 3
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**232805**	**232805**	**232805**	**232805**	**232805**
Type		HM Trend	HM Trend	HM Trend	HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
Part number		**233826**	**233826**	**233826**	**233826**	**233826**
Type		HMS Trend	HMS Trend	HMS Trend	HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
DHW cylinder						
Part number		**203801**	**203801**	**203801**	**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Part number						**221360**
Type						SBB 301 WP
Description						DHW cylinder
Part number		**229980**	**229980**	**229980**		
Type		SBS 601 W	SBS 601 W	SBS 601 W		
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder		
Part number					**229981**	**229981**
Type					SBS 801 W	SBS 801 W
Description					Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	**233510**	**233510**	**233510**
Type		HSBC 200	HSBC 200	HSBC 200	HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Buffer cylinder						
Part number		**205295**	**205295**	**205295**	**205295**	**205295**
Type		SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation

Inverter

HPA-O 13.2 Plus HC 400




HPA-O 05.2 Plus HC 230
HPA-O 07.2 Plus HC 230




Inverter

HPA-O 10.2 Plus HC 400



		HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
b01 Entry electrical cables		•	•	•	•	•
d45 Condensate drain		•	•	•	•	•
e01 Heating flow - male thread		G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4
e02 Heating return - male thread		G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4
g01 Air intake		•	•	•	•	•
g02 Air discharge		•	•	•	•	•

HPA-O W Plus



HPA-O 05.2 W Plus HC 230

Benefits
- Air source heat pump installed outdoors for modernisation and new build
- Also suitable for densely built-up areas due to very low operating noise
- Low costs thanks to R290 refrigerant circuit remaining efficient all year round, as well as optimally matched components
- Compact mono block version in a timeless design
- Efficient cooling possible thanks to circuit reversal
- Many solutions for different applications possible with flexible installation options and customised accessories
- Multi stage safety concept for the R290 refrigerant circuit

Application • Air source heat pump in a white finish with inverter technology and all-in-one design for universal use in modernisation and new build. Compact mono block version for siting outdoors. Thanks to minimal operating noise, it is also suitable for densely built-up areas. Low operating costs through high efficiency all year round. • Indoor units with different storage volumes are available depending on the DHW demand. The system delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal. • The WPM heat pump manager controls the system reliably and efficiently with a connection to the STIEBEL ELTRON Servicewelt. • Cascade solution of up to six heat pumps possible. • Extended, three-stage safety concept for reliable protection of the heating circuit against refrigerant ingress.

Convenience features • Very quiet operation is made possible by the encapsulated refrigerant circuit and acoustically isolated compressor. Contributing to the low sound power level are the modulating fans and the wide gaps between the evaporator fins which reduce air resistance. • Very low operating noise and therefore free choice of installation location. Additional, dB-precise and demand-orientated sound limitation with silent mode. • High DHW temperatures are assured without the need for electric backup, even in the winter; this is because the heat pump works with high flow temperatures all year round. • The consistent design delivers a timeless and high quality aesthetic.

Installation • Easier transport and placement thanks to the innovative carrying concept, compact dimensions and low weight. • Quick installation thanks to integral anti-vibration mount, no additional components required. • Easy access to the electrical connection panel at the side, secure connection thanks to spring terminal technology. • Siting and connection of the components is supported and simplified by coordinated accessories in the product range.

Efficiency • The refrigerant circuit works with the eco-friendly and futureproof refrigerant R290. In combination with the optimally and generously matched components, efficient operation is possible all year round. • Further increase in system efficiency by optimising the number of defrosting processes with demand-dependent control and natural defrosting without using the compressor.

		HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
		NEW	NEW	NEW	NEW	NEW
Part number		**208431**	**208432**	**208433**	**208434**	**208435**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
SCOP 35 °C (EN 14825)		5.35	5.09	4.96	4.96	4.89
SCOP 55 °C (EN 14825)		4.07	4.02	3.99	3.99	4.01
Heating output at A7/W35 (EN 14511)	kW	2.77	3.05	4.32	4.32	5.79
Heating output at A2/W35 (EN 14511)	kW	3.14	3.29	4.09	4.09	4.82
Heating output at A-7/W35 (EN 14511)	kW	5.22	7.09	10.07	10.07	13.15
COP at A7/W35 (EN 14511)		5.48	5.50	5.40	5.40	5.41
COP at A2/W35 (EN 14511)		4.72	4.57	4.54	4.54	4.41
COP at A-7/W35 (EN 14511)		3.47	3.25	3.15	3.15	3.11
Max. cooling capacity at A35/W7	kW	4.50	6.51	9.33	9.33	10.09
Cooling capacity at A35/W18 partial load (EN 14511)	kW	3.15	3.15	4.29	4.29	5.81

next page >

Inverter

		HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
Max. cooling capacity at A35/W18	kW	4.96	6.98	10.51	10.51	12.95
Energy efficiency ratio at A35/W7 max.		3.29	2.97	2.76	2.76	3.14
Energy efficiency ratio at A35/W18 partial load (EN 14511)		5.29	5.29	5.46	5.46	5.41
Energy efficiency ratio at A35/W18 max.		4.87	4.28	4.01	4.01	4.11
Sound power level (EN 12102)	dB(A)	43	43	46	46	45
Min./max. application limits for heat source	°C	-25 / 40	-25 / 40	-25 / 40	-25 / 40	-25 / 40
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	960	960	1144	1144	1365
Width	mm	1170	1170	1170	1170	1170
Depth	mm	727	727	727	727	727
Weight	kg	144	145	166	166	205
Rated voltage, compressor	V	230	230	230	400	400
Refrigerant		R290	R290	R290	R290	R290
Colour		Signal white RAL 9003	Signal white RAL 9003	Signal white RAL 9003	Signal white RAL 9003	Signal white RAL 9003
Recommended accessories						
Part number		**206780**	**206780**	**206780**	**206780**	**206780**
Type		ISG Connect	ISG Connect	ISG Connect	ISG Connect	ISG Connect
Description		Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility
Part number		**207710**	**207710**	**207710**	**207710**	**207710**
Type		AHP-TW 710	AHP-TW 710	AHP-TW 710	AHP-TW 710	AHP-TW 710
Description		Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)
Part number		**207712**	**207712**	**207712**	**207712**	**207712**
Type		AHP-SW.1	AHP-SW.1	AHP-SW.1	AHP-SW.1	AHP-SW.1
Description		Cover (white)	Cover (white)	Cover (white)	Cover (white)	Cover (white)
Part number		**207715**	**207715**	**207715**	**207715**	**207715**
Type		AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1
Description		Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground
Part number		**207716**	**207716**	**207716**	**207716**	**207716**
Type		AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207717**	**207717**	**207717**	**207717**	**207717**
Type		AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207718**	**207718**	**207718**	**207718**	**207718**
Type		AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207719**	**207719**	**207719**	**207719**	**207719**
Type		AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207720**	**207720**	**207720**	**207720**	**207720**
Type		AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207721**	**207721**	**207721**	**207721**	**207721**
Type		AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200
Description		Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies

next page >

		HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
Part number		**207723**	**207723**	**207723**	**207723**	**207723**
Type		AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1
Description		Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps
Part number		**207724**	**207724**	**207724**	**207724**	**207724**
Type		AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4
Description		Downward connection set	Downward connection set	Downward connection set	Downward connection set	Downward connection set
Part number		**207730**	**207730**	**207730**	**207730**	**207730**
Type		AHP-TW 420	AHP-TW 420	AHP-TW 420	AHP-TW 420	AHP-TW 420
Description		Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)	Telescopic casing (white)
Part number		**207731**	**207731**	**207731**	**207731**	**207731**
Type		AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1
Description		Condensate pan	Condensate pan	Condensate pan	Condensate pan	Condensate pan
Part number		**207732**	**207732**	**207732**	**207732**	**207732**
Type		AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1
Description		Floor bracket	Floor bracket	Floor bracket	Floor bracket	Floor bracket
Part number		**207734**	**207734**	**207734**	**207734**	**207734**
Type		AGC-CW.1	AGC-CW.1	AGC-CW.1	AGC-CW.1	AGC-CW.1
Description		Floor bracket casing set (white)	Floor bracket casing set (white)	Floor bracket casing set (white)	Floor bracket casing set (white)	Floor bracket casing set (white)
Part number		**207736**	**207736**	**207736**	**207736**	**207736**
Type		AHP-CW.1	AHP-CW.1	AHP-CW.1	AHP-CW.1	AHP-CW.1
Description		Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet
Part number		**207737**	**207737**	**207737**	**207737**	**207737**
Type		AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1
Description		stand bracket	stand bracket	stand bracket	stand bracket	stand bracket
Part number		**207738**	**207738**	**207738**	**207738**	**207738**
Type		AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8
Description		Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base
Part number		**207891**	**207891**	**207891**	**207891**	**207891**
Type		AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**207893**	**207893**	**207893**	**207893**	**207893**
Type		AWM-CW.1	AWM-CW.1	AWM-CW.1	AWM-CW.1	AWM-CW.1
Description		Wall mounting bracket casing set (white)	Wall mounting bracket casing set (white)	Wall mounting bracket casing set (white)	Wall mounting bracket casing set (white)	Wall mounting bracket casing set (white)
Part number		**207894**	**207894**	**207894**	**207894**	**207894**
Type		AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1
Description		Ball siphon	Ball siphon	Ball siphon	Ball siphon	Ball siphon
Part number		**208658**	**208658**			
Type		AHP-WW.1	AHP-WW.1			
Description		Wind protection of the heat pump for installation in open spaces (white)	Wind protection of the heat pump for installation in open spaces (white)			
Part number				**208681**	**208681**	
Type				AHP-WW.2	AHP-WW.2	
Description				Wind protection of the heat pump for installation in open spaces (white)	Wind protection of the heat pump for installation in open spaces (white)	
Part number						**208682**
Type						AHP-WW.3
Description						Wind protection of the heat pump for installation in open spaces (white)


6

next page >

Inverter


		HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
Part number		**208702**	**208702**	**208702**	**208702**	**208702**
Type		WK 3	WK 3	WK 3	WK 3	WK 3
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**232805**	**232805**	**232805**	**232805**	**232805**
Type		HM Trend	HM Trend	HM Trend	HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
Part number		**233826**	**233826**	**233826**	**233826**	**233826**
Type		HMS Trend	HMS Trend	HMS Trend	HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
DHW cylinder						
Part number		**203801**	**203801**	**203801**	**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Part number		**229980**	**229980**	**229980**	**229980**	**229980**
Type		SBS 601 W	SBS 601 W	SBS 601 W	SBS 601 W	SBS 601 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	**233510**	**233510**	**233510**
Type		HSBC 200	HSBC 200	HSBC 200	HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Buffer cylinder						
Part number		**205295**	**205295**	**205295**	**205295**	**205295**
Type		SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation

HPA-O 13.2 W Plus HC 400




Inverter

HPA-O 05.2 W Plus HC 230
HPA-O 07.2 W Plus HC 230



Inverter

HPA-O 10.2 W Plus HC 400



		HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
b01 Entry electrical cables		•	•	–	•	•
d45 Condensate drain		•	•	–	•	•
e01 Heating flow - male thread		G 1 1/4	G 1 1/4		G 1 1/4	G 1 1/4
e02 Heating return - male thread		G 1 1/4	G 1 1/4		G 1 1/4	G 1 1/4
g01 Air intake		•	•	–	•	•
g02 Air discharge		•	•	–	•	•

HPA-O Plus + HSBC 200



HPA-O 05.2 Plus HC 230 + HSBC 200

Benefits

- Set consisting of an air source heat pump installed outdoors from the HPA-O Plus range and integral cylinder
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for standard requirements in family houses when it comes to DHW convenience, heating output and heating distribution systems. • This set consists of an HSBC 200 integral cylinder and an HPA-O Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent, all-in-one design ensures a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • It is therefore possible to connect a direct heating circuit or, optionally, a second heating circuit with mixer with accessories, without additional external components. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 Plus HC 230 + HSBC 200	HPA-O 07.2 Plus HC 230 + HSBC 200	HPA-O 10.2 Plus HC 230 + HSBC 200	HPA-O 10.2 Plus HC 400 + HSBC 200	HPA-O 13.2 Plus HC 400 + HSBC 200
		NEW	NEW	NEW	NEW	NEW
Part number		**208560**	**207962**	**208561**	**207961**	**207963**



Set components		**HPA-O 05.2 Plus HC 230 + HSBC 200**	**HPA-O 07.2 Plus HC 230 + HSBC 200**	**HPA-O 10.2 Plus HC 230 + HSBC 200**	**HPA-O 10.2 Plus HC 400 + HSBC 200**	**HPA-O 13.2 Plus HC 400 + HSBC 200**
1	Type	HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	152	152	152	152	152

next page >

Set components		HPA-O 05.2 Plus HC 230 + HSBC 200	HPA-O 07.2 Plus HC 230 + HSBC 200	HPA-O 10.2 Plus HC 230 + HSBC 200	HPA-O 10.2 Plus HC 400 + HSBC 200	HPA-O 13.2 Plus HC 400 + HSBC 200
2	Type	HSBC 200	HSBC 200	HSBC 200	HSBC 200	HSBC 200
	Qty	1	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346	346	346

Further information about the Set components can be found under the relevant product.

HPA-O W Plus + HSBC 200



HPA-O 05.2 W Plus HC 230 + HSBC 200

Benefits
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for standard requirements in family houses when it comes to DHW convenience, heating output and heating distribution systems. • This set consists of an HSBC 200 integral cylinder and an HPA-O W Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent, all-in-one design ensures a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • It is therefore possible to connect a direct heating circuit or, optionally, a second heating circuit with mixer with accessories, without additional external components. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 W Plus HC 230 + HSBC 200	HPA-O 07.2 W Plus HC 230 + HSBC 200	HPA-O 10.2 W Plus HC 230 + HSBC 200	HPA-O 10.2 W Plus HC 400 + HSBC 200	HPA-O 13.2 W Plus HC 400 + HSBC 200
		NEW	NEW	NEW	NEW	NEW
Part number		208576	208392	208393	208394	208395



Set components		HPA-O 05.2 W Plus HC 230 + HSBC 200	HPA-O 07.2 W Plus HC 230 + HSBC 200	HPA-O 10.2 W Plus HC 230 + HSBC 200	HPA-O 10.2 W Plus HC 400 + HSBC 200	HPA-O 13.2 W Plus HC 400 + HSBC 200
1	Type	HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	159	159	159	159	159
2	Type	HSBC 200	HSBC 200	HSBC 200	HSBC 200	HSBC 200
	Qty	1	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346	346	346

Further information about the Set components can be found under the relevant product.

HPA-O Plus + HSBC 200 S



HPA-O 05.2 Plus HC 230 + HSBC 200 S

Benefits

- Set consisting of an air source heat pump installed outdoors from the HPA-O Plus range and integral cylinder
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance

Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for standard requirements in family houses when it comes to DHW convenience, heating output and heating distribution systems. • This set consists of an HSBC 200 S integral cylinder and an HPA-O Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.


Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent, all-in-one design ensures a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • It is therefore possible to connect a direct heating circuit or, optionally, a second heating circuit with mixer with accessories, without additional external components. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 Plus HC 230 + HSBC 200 S	HPA-O 07.2 Plus HC 230 + HSBC 200 S	HPA-O 10.2 Plus HC 230 + HSBC 200 S
		NEW	NEW	NEW
Part number		**208718**	**208719**	**208720**

Inverter



Set components		HPA-O 05.2 Plus HC 230 + HSBC 200 S	HPA-O 07.2 Plus HC 230 + HSBC 200 S	HPA-O 10.2 Plus HC 230 + HSBC 200 S
1	Type	HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	152	152	152
2	Type	HSBC 200 S	HSBC 200 S	HSBC 200 S
	Qty	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346

Further information about the Set components can be found under the relevant product.

HPA-O W Plus + HSBC 200 S



HPA-O 05.2 W Plus HC 230 + HSBC 200 S

Benefits
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for standard requirements in family houses when it comes to DHW convenience, heating output and heating distribution systems. • This set consists of an HSBC 200 S integral cylinder and an HPA-O W Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent, all-in-one design ensures a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • It is therefore possible to connect a direct heating circuit or, optionally, a second heating circuit with mixer with accessories, without additional external components. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 W Plus HC 230 + HSBC 200 S	HPA-O 07.2 W Plus HC 230 + HSBC 200 S	HPA-O 10.2 W Plus HC 230 + HSBC 200 S
		NEW	NEW	NEW
Part number		**208721**	**208722**	**208723**



Set components		**HPA-O 05.2 W Plus HC 230 + HSBC 200 S**	**HPA-O 07.2 W Plus HC 230 + HSBC 200 S**	**HPA-O 10.2 W Plus HC 230 + HSBC 200 S**
1	Type	HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	159	159	159
2	Type	HSBC 200 S	HSBC 200 S	HSBC 200 S
	Qty	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346

next page >

Further information about the Set components can be found under the relevant product.

HPA-O Plus + HSBC 300



HPA-O 05.2 Plus HC 230 + HSBC 300

Benefits

- Set consisting of an air source heat pump installed outdoors from the HPA-O Plus range and integral cylinder
- Tailored to the usual requirements of a family house with increased hot water convenience
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and repeatable installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for the usual requirements of a family house with increased DHW convenience. • This set consists of an HSBC 300 integral cylinder and an HPA-O Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent design makes for a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 Plus HC 230 + HSBC 300	HPA-O 07.2 Plus HC 230 + HSBC 300	HPA-O 10.2 Plus HC 230 + HSBC 300	HPA-O 10.2 Plus HC 400 + HSBC 300	HPA-O 13.2 Plus HC 400 + HSBC 300
		NEW	NEW	NEW	NEW	NEW
Part number		**208564**	**207966**	**208565**	**207967**	**207968**



Set components		HPA-O 05.2 Plus HC 230 + HSBC 300	HPA-O 07.2 Plus HC 230 + HSBC 300	HPA-O 10.2 Plus HC 230 + HSBC 300	HPA-O 10.2 Plus HC 400 + HSBC 300	HPA-O 13.2 Plus HC 400 + HSBC 300
1	Type	HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	152	152	152	152	152
2	Type	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
	Qty	1	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	344	344	344	344	344
3	Type	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8
	Qty	1	1	1	1	1
		Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater
	Page	353	353	353	353	353

Further information about the Set components can be found under the relevant product.

HPA-O W Plus + HSBC 300



HPA-O 05.2 W Plus HC 230 + HSBC 300

Benefits
- Tailored to the usual requirements of a family house with increased hot water convenience
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance

Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and repeatable installation in new build or modernisation. • The air source heat pump installed outdoors is suitable for use in modernisation and new build. Thanks to minimal operating noise, it is also suitable for use in densely built-up areas. • Optimum set for the usual requirements of a family house with increased DHW convenience. • This set consists of an HSBC 300 integral cylinder and an HPA-O W Plus air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.


Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent design makes for a timeless and high quality aesthetic. • Very low operating noise and therefore free choice of installation location – even quieter thanks to silent mode with the option of limiting sound propagation as required. High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In combination with the optimally matched components, highly efficient operation is possible all year round. In addition, effective insulation of the integral cylinder minimises standby losses.

		HPA-O 05.2 W Plus HC 230 + HSBC 300	HPA-O 07.2 W Plus HC 230 + HSBC 300	HPA-O 10.2 W Plus HC 230 + HSBC 300	HPA-O 10.2 W Plus HC 400 + HSBC 300	HPA-O 13.2 W Plus HC 400 + HSBC 300
		NEW	NEW	NEW	NEW	NEW
Part number		**208396**	**208397**	**208398**	**208399**	**208400**

Inverter



Set components		HPA-O 05.2 W Plus HC 230 + HSBC 300	HPA-O 07.2 W Plus HC 230 + HSBC 300	HPA-O 10.2 W Plus HC 230 + HSBC 300	HPA-O 10.2 W Plus HC 400 + HSBC 300	HPA-O 13.2 W Plus HC 400 + HSBC 300
1	Type	HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	159	159	159	159	159
2	Type	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
	Qty	1	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	344	344	344	344	344
3	Type	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8
	Qty	1	1	1	1	1
		Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater
	Page	353	353	353	353	353

Further information about the Set components can be found under the relevant product.

HPA-O Plus + HM Trend



Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O Plus series in combination with the HM Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

HPA-O 05.2 Plus HC 230 + HM Trend

		HPA-O 05.2 Plus HC 230 + HM Trend	HPA-O 07.2 Plus HC 230 + HM Trend	HPA-O 10.2 Plus HC 230 + HM Trend	HPA-O 10.2 Plus HC 400 + HM Trend	HPA-O 13.2 Plus HC 400 + HM Trend
		NEW	NEW	NEW	NEW	NEW
Part number		**208407**	**208218**	**208408**	**208219**	**208220**

Set components		HPA-O 05.2 Plus HC 230 + HM Trend	HPA-O 07.2 Plus HC 230 + HM Trend	HPA-O 10.2 Plus HC 230 + HM Trend	HPA-O 10.2 Plus HC 400 + HM Trend	HPA-O 13.2 Plus HC 400 + HM Trend
1	Type	HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230	HPA-O 10.2 Plus HC 400	HPA-O 13.2 Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	152	152	152	152	152
2	Type	HM Trend	HM Trend	HM Trend	HM Trend	HM Trend
	Qty	1	1	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O W Plus + HM Trend



Benefits

- Suitable for new build and modernisation projects
- Depending on the cylinder, also suitable for higher DHW demand
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder
- Can be combined with any cylinder range

Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O W Plus series with white casing in combination with the HM Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

HPA-O 05.2 W Plus HC 230 + HM Trend

		HPA-O 05.2 W Plus HC 230 + HM Trend	HPA-O 07.2 W Plus HC 230 + HM Trend	HPA-O 10.2 W Plus HC 230 + HM Trend	HPA-O 10.2 W Plus HC 400 + HM Trend	HPA-O 13.2 W Plus HC 400 + HM Trend
		NEW	NEW	NEW	NEW	NEW
Part number		**208414**	**208415**	**208416**	**208417**	**208418**

Set components		HPA-O 05.2 W Plus HC 230 + HM Trend	HPA-O 07.2 W Plus HC 230 + HM Trend	HPA-O 10.2 W Plus HC 230 + HM Trend	HPA-O 10.2 W Plus HC 400 + HM Trend	HPA-O 13.2 W Plus HC 400 + HM Trend
1	Type	HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230	HPA-O 10.2 W Plus HC 400	HPA-O 13.2 W Plus HC 400
	Qty	1	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	159	159	159	159	159
2	Type	HM Trend	HM Trend	HM Trend	HM Trend	HM Trend
	Qty	1	1	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O Plus + HMS Trend



HPA-O 05.2 Plus HC 230 + HMS Trend

Benefits
- Suitable for new build and modernisation projects
- Depending on the cylinder, also suitable for higher DHW demand
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder
- Can be combined with any cylinder range

Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O Plus series in combination with the HMS Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

		HPA-O 05.2 Plus HC 230 + HMS Trend	HPA-O 07.2 Plus HC 230 + HMS Trend	HPA-O 10.2 Plus HC 230 + HMS Trend
		NEW	NEW	NEW
Part number		**208728**	**208729**	**208730**

Set components		HPA-O 05.2 Plus HC 230 + HMS Trend	HPA-O 07.2 Plus HC 230 + HMS Trend	HPA-O 10.2 Plus HC 230 + HMS Trend
1	Type	HPA-O 05.2 Plus HC 230	HPA-O 07.2 Plus HC 230	HPA-O 10.2 Plus HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	152	152	152
2	Type	HMS Trend	HMS Trend	HMS Trend
	Qty	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O W Plus + HMS Trend



HPA-O 05.2 W Plus HC 230 + HMS Trend

Benefits
- Suitable for new build and modernisation projects
- Depending on the cylinder, also suitable for higher DHW demand
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder
- Can be combined with any cylinder range


Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O W Plus series with white casing in combination with the HMS Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

		HPA-O 05.2 W Plus HC 230 + HMS Trend	HPA-O 07.2 W Plus HC 230 + HMS Trend	HPA-O 10.2 W Plus HC 230 + HMS Trend
		NEW	NEW	NEW
Part number		**208731**	**208732**	**208733**

Set components		HPA-O 05.2 W Plus HC 230 + HMS Trend	HPA-O 07.2 W Plus HC 230 + HMS Trend	HPA-O 10.2 W Plus HC 230 + HMS Trend
1	Type	HPA-O 05.2 W Plus HC 230	HPA-O 07.2 W Plus HC 230	HPA-O 10.2 W Plus HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	159	159	159
2	Type	HMS Trend	HMS Trend	HMS Trend
	Qty	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O Trend



HPA-O 07.2 Trend HC 230

Benefits

- Air source heat pump installed outdoors for modernisation and new build
- Compact design for small wall clearances and flexible positioning
- Low costs and high living comfort through efficient R290 refrigeration circuit
- Efficient cooling possible thanks to circuit reversal
- Multi stage safety concept for the R290 refrigerant circuit
- Many solutions for different applications possible with flexible installation options and customised accessories

Application • Air source heat pump for all year round sustainable living comfort with both underfloor heating and radiator heating. Perfectly tuned for the ideal harmony between of outlay, efficiency and noise. Mono block version for siting outdoors. Compact heat pump for small wall clearances enables versatile positioning. • Indoor units with different storage volumes are available depending on the DHW demand. The system delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal. • Cascade solution of up to six heat pumps possible. • Extended, three-stage safety concept for reliable protection of the heating circuit against refrigerant ingress.

Convenience features • Quiet operation is made possible by the encapsulated refrigerant circuit and acoustically isolated compressor. Additional, dB-precise and demand-orientated sound limitation with silent mode. • High DHW temperatures are assured without the need for electric backup, even in the winter; this is because the heat pump works with high flow temperatures all year round.

Installation • Easier transport and placement thanks to the innovative carrying concept, compact dimensions and low weight. • Quick installation thanks to integral anti-vibration mount, no additional components required. • Easy access to the electrical connection panel at the side, secure connection thanks to spring terminal technology. • Siting and connection of the components is supported and simplified by coordinated accessories in the product range.

Efficiency • The refrigerant circuit works with the eco-friendly and futureproof refrigerant R290. • Further increase in system efficiency by optimising the number of defrosting processes with demand-dependent control and natural defrosting without using the compressor.

GERMAN DESIGN AWARD WINNER 2025
207420, 207422, 207425, 207426

reddot winner 2025
207420, 207422, 207425, 207426

207420, 207422, 207425, 207426

6

		HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400	HPA-O 17.2 Trend HC 400
		NEW	NEW	NEW	NEW	NEW
Part number		**207420**	**207422**	**207424**	**207425**	**207426**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A++	A+++	A+++	A+++
SCOP 35 °C (EN 14825)		4.67	4.59	4.65	4.65	4.55
SCOP 55 °C (EN 14825)		3.83	3.79	3.85	3.85	3.83
Heating output at A7/W35 (EN 14511)	kW	2.91	4.26	5.56	5.56	7.96
Heating output at A2/W35 (EN 14511)	kW	4.24	5.87	4.09	7.45	10.29
Heating output at A-7/W35 (EN 14511)	kW	6.92	9.49	12.47	12.47	17.36
COP at A7/W35 (EN 14511)		5.44	5.40	5.36	5.36	5.29
COP at A2/W35 (EN 14511)		4.02	3.96	4.54	3.91	3.91
COP at A-7/W35 (EN 14511)		2.84	2.80	2.75	2.75	2.62
Max. cooling capacity at A35/W7	kW	6.04	8.27	9.56	9.56	9.75
Cooling capacity at A35/W18 partial load (EN 14511)	kW	3.35	3.96	4.29	4.99	7.13

next page >

		HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400	HPA-O 17.2 Trend HC 400
Max. cooling capacity at A35/W18	kW	6.66	8.94	11.49	11.49	15.55
Energy efficiency ratio at A35/W7 max.		2.80	2.52	2.70	2.70	3.16
Energy efficiency ratio at A35/W18 partial load (EN 14511)		5.18	5.24	5.45	4.81	5.13
Energy efficiency ratio at A35/W18 max.		3.70	3.65	3.61	3.60	3.75
Sound power level (EN 12102)	dB(A)	44	46	49	49	52
Min./max. application limits for heat source	°C	-25 / 40	-25/40	-25 / 40	-25 / 40	-25 / 40
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	960	960	1144	1144	1365
Width	mm	1170	1170	1170	1170	1170
Depth	mm	727	727	727	727	727
Weight	kg	149	150	176	176	209
Rated voltage, compressor	V	230	230	230	400	400
Refrigerant		R290	R290	R290	R290	R290
Colour		Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021
Recommended accessories						
Part number		**206780**	**206780**	**206780**	**206780**	**206780**
Type		ISG Connect	ISG Connect	ISG Connect	ISG Connect	ISG Connect
Description		Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility	Internet Service Gateway with SG Ready and §14a Compatibility
Part number		**207711**	**207711**	**207711**	**207711**	**207711**
Type		AHP-SB.1	AHP-SB.1	AHP-SB.1	AHP-SB.1	AHP-SB.1
Description		Cover	Cover	Cover	Cover	Cover
Part number		**207713**	**207713**			
Type		AHP-WB.1	AHP-WB.1			
Description		Wind protection of the heat pump for installation in open spaces	Wind protection of the heat pump for installation in open spaces			
Part number		**207715**	**207715**	**207715**	**207715**	**207715**
Type		AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1	AHP-WO.1
Description		Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground	Wall outlet above ground
Part number		**207716**	**207716**	**207716**	**207716**	**207716**
Type		AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1	AHP-WU.1
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207717**	**207717**	**207717**	**207717**	**207717**
Type		AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2	AHP-WU.2
Description		Wall outlet	Wall outlet	Wall outlet	Wall outlet	Wall outlet
Part number		**207718**	**207718**	**207718**	**207718**	**207718**
Type		AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5	AWU-HS 2.5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207719**	**207719**	**207719**	**207719**	**207719**
Type		AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5	AWU-HS 5
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207720**	**207720**	**207720**	**207720**	**207720**
Type		AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10	AWU-HS 10
Description		Hose assembly	Hose assembly	Hose assembly	Hose assembly	Hose assembly
Part number		**207721**	**207721**	**207721**	**207721**	**207721**
Type		AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200	AHS-SI 200
Description		Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies

next page >

		HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400	HPA-O 17.2 Trend HC 400
Part number		**207723**	**207723**	**207723**	**207723**	**207723**
Type		AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1	AHP-CS.1
Description		Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps	Crossover lifting straps
Part number		**207724**	**207724**	**207724**	**207724**	**207724**
Type		AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4	AHP-FH 25-0.4
Description		Downward connection set	Downward connection set	Downward connection set	Downward connection set	Downward connection set
Part number		**207727**	**207727**	**207727**	**207727**	**207727**
Type		AHP-TB 420	AHP-TB 420	AHP-TB 420	AHP-TB 420	AHP-TB 420
Description		Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct
Part number		**207728**	**207728**	**207728**	**207728**	**207728**
Type		AHP-TB 710	AHP-TB 710	AHP-TB 710	AHP-TB 710	AHP-TB 710
Description		Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct	Dark grey telescopic duct
Part number		**207731**	**207731**	**207731**	**207731**	**207731**
Type		AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1	AHP-DT.1
Description		Condensate pan	Condensate pan	Condensate pan	Condensate pan	Condensate pan
Part number		**207732**	**207732**	**207732**	**207732**	**207732**
Type		AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1	AHP-GC.1
Description		Floor bracket	Floor bracket	Floor bracket	Floor bracket	Floor bracket
Part number		**207733**	**207733**	**207733**	**207733**	**207733**
Type		AGC-CB.1	AGC-CB.1	AGC-CB.1	AGC-CB.1	AGC-CB.1
Description		Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)	Floor bracket casing set (anthracite)
Part number		**207735**	**207735**	**207735**	**207735**	**207735**
Type		AHP-CB.1	AHP-CB.1	AHP-CB.1	AHP-CB.1	AHP-CB.1
Description		Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet	Casing for heat pump feet
Part number		**207737**	**207737**	**207737**	**207737**	**207737**
Type		AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1	AHP-SC.1
Description		stand bracket	stand bracket	stand bracket	stand bracket	stand bracket
Part number		**207738**	**207738**	**207738**	**207738**	**207738**
Type		AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8	AHP-DS 0.8
Description		Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base	Sound attenuation base
Part number		**207891**	**207891**	**207891**	**207891**	**207891**
Type		AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1	AHP-WM.1
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**207892**	**207892**	**207892**	**207892**	**207892**
Type		AWM-CB.1	AWM-CB.1	AWM-CB.1	AWM-CB.1	AWM-CB.1
Description		Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set	Wall mounting bracket casing set
Part number		**207894**	**207894**	**207894**	**207894**	**207894**
Type		AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1	AHP-BS.1
Description		Ball siphon	Ball siphon	Ball siphon	Ball siphon	Ball siphon
Part number				**208679**	**208679**	
Type				AHP-WB.2	AHP-WB.2	
Description				Wind protection of the heat pump for installation in open spaces	Wind protection of the heat pump for installation in open spaces	
Part number						**208680**
Type						AHP-WB.3
Description						Wind protection of the heat pump for installation in open spaces


next page >

Inverter

		HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400	HPA-O 17.2 Trend HC 400
Part number		**208702**	**208702**	**208702**	**208702**	**208702**
Type		WK 3	WK 3	WK 3	WK 3	WK 3
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
Part number		**232805**	**232805**	**232805**	**232805**	**232805**
Type		HM Trend	HM Trend	HM Trend	HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
Part number		**233826**	**233826**	**233826**	**233826**	**233826**
Type		HMS Trend	HMS Trend	HMS Trend	HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
DHW cylinder						
Part number		**203801**	**203801**	**203801**	**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Part number					**221360**	
Type					SBB 301 WP	
Description					DHW cylinder	
Part number		**229981**	**229981**	**229981**	**229981**	**229981**
Type		SBS 801 W	SBS 801 W	SBS 801 W	SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	**233510**	**233510**	**233510**
Type		HSBC 200	HSBC 200	HSBC 200	HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Buffer cylinder						
Part number		**205295**	**205295**	**205295**	**205295**	**205295**
Type		SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool	SBP 200 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation


Inverter

HPA-O 17.2 Trend HC 400




Inverter

HPA-O 07.2 Trend HC 230
HPA-O 10.2 Trend HC 230



HPA-O 13.2 Trend HC 400



		HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400	HPA-O 17.2 Trend HC 400
a10 Appliance - height	mm			1,144		
a20 Appliance - width	mm			1,170		
b01 Entry electrical cables		•	•	–	•	•
d45 Condensate drain		•	•	–	•	•
e01 Heating flow - male thread		G 1 1/4	G 1 1/4		G 1 1/4	G 1 1/4
e02 Heating return - male thread		G 1 1/4	G 1 1/4		G 1 1/4	G 1 1/4
g01 Air intake		•	•	–	•	•
g02 Air discharge		•	•	–	•	•

Inverter

HPA-O Trend + HSBC 200



HPA-O 07.2 Trend HC 230 + HSBC 200

Benefits

- Set consisting of an air source heat pump installed outdoors from the HPA-O Trend range and integral cylinder
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • Set tailored to the usual requirements in family houses for DHW convenience, heating output and heating distribution with underfloor heating or radiators. • This set consists of an HPA-O Trend air source heat pump and an integral cylinder with DHW cylinder and 100 litre buffer cylinder. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The compact heat pump for small wall clearances enables versatile positioning. • The consistent design ensures a timeless and high quality aesthetic. • The entire system is controlled via an integral controller or conveniently via app. The high level of integration makes it easy to achieve a tidy installation. • High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • Siting of the heat pump and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The heat pump's refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In addition, low standby losses arise thanks to effective insulation of the integral cylinder.

		HPA-O 07.2 Trend HC 230 + HSBC 200	HPA-O 10.2 Trend HC 230 + HSBC 200	HPA-O 13.2 Trend HC 230 + HSBC 200	HPA-O 13.2 Trend HC 400 + HSBC 200
		NEW	NEW	NEW	NEW
Part number		**208558**	**207959**	**208559**	**207960**



Set components		HPA-O 07.2 Trend HC 230 + HSBC 200	HPA-O 10.2 Trend HC 230 + HSBC 200	HPA-O 13.2 Trend HC 230 + HSBC 200	HPA-O 13.2 Trend HC 400 + HSBC 200
1	Type	HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400
	Qty	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	177	177	177	177
2	Type	HSBC 200	HSBC 200	HSBC 200	HSBC 200
	Qty	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346	346

Further information about the Set components can be found under the relevant product.

HPA-O Trend + HSBC 200 S



HPA-O 07.2 Trend HC 230 + HSBC 200 S

Benefits
- Set consisting of an air source heat pump installed outdoors from the HPA-O Trend range and integral cylinder
- Tailored to the usual requirements of a family house
- Control via MyStiebel app possible


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • Set tailored to the usual requirements in family houses for DHW convenience, heating output and heating distribution with underfloor heating or radiators. • This set consists of an HPA-O Trend air source heat pump and an integral cylinder HSBC 200 S.

Convenience features • The compact heat pump for small wall clearances enables versatile positioning. • The consistent design ensures a timeless and high quality aesthetic. • The entire system is controlled via an integral controller or conveniently via app. The high level of integration makes it easy to achieve a tidy installation. • High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • Siting of the heat pump and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The heat pump's refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In addition, low standby losses arise thanks to effective insulation of the integral cylinder.

		HPA-O 07.2 Trend HC 230 + HSBC 200 S	HPA-O 10.2 Trend HC 230 + HSBC 200 S	HPA-O 13.2 Trend HC 230 + HSBC 200 S
		NEW	NEW	NEW
Part number		**208736**	**208716**	**208717**



Set components		**HPA-O 07.2 Trend HC 230 + HSBC 200 S**	**HPA-O 10.2 Trend HC 230 + HSBC 200 S**	**HPA-O 13.2 Trend HC 230 + HSBC 200 S**
1	Type	HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	177	177	177
2	Type	HSBC 200 S	HSBC 200 S	HSBC 200 S
	Qty	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder
	Page	346	346	346

Further information about the Set components can be found under the relevant product.

HPA-O Trend + HSBC 300



HPA-O 07.2 Trend HC 230 + HSBC 300

Benefits
- Set consisting of an air source heat pump installed outdoors from the HPA-O Trend range and integral cylinder
- Tailored to the usual requirements of a family house with increased hot water convenience
- Control via MyStiebel app possible
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance


Application • This universally applicable combination of space saving indoor unit and mono block heat pump enables quick and consistent installation in new build or modernisation. • The air source heat pump installed outdoors for all year round sustainable living comfort with both underfloor heating and radiator heating. • Set tailored to the usual requirements of a family house with increased DHW convenience. • This set consists of an HSBC 300 integral cylinder and an HPA-O Trend air source heat pump. • The set delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal.

Convenience features • The entire system is controlled via an integral controller, or conveniently by app. • The consistent design makes for a timeless and high quality aesthetic. Thanks to the high level of integration, it is easy to achieve a tidy installation. • Compact heat pump with small wall clearances enables versatile positioning. • High flow temperatures and monovalent DHW heating are possible even at low outside temperatures.

Installation • The system can be installed with just two modules. This saves time during installation and provides planning assurance in advance. • Siting and connection of the set components is supported and simplified by coordinated accessories.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R290. In addition, low standby losses arise thanks to effective insulation of the integral cylinder.

		HPA-O 07.2 Trend HC 230 + HSBC 300	HPA-O 10.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 400 + HSBC 300
		NEW	NEW	NEW	NEW
Part number		**208562**	**207964**	**208563**	**207965**



Set components		HPA-O 07.2 Trend HC 230 + HSBC 300	HPA-O 10.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 400 + HSBC 300
1	Type	HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400
	Qty	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	177	177	177	177
2	Type	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
	Qty	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	344	344	344	344

next page >

Set components		HPA-O 07.2 Trend HC 230 + HSBC 300	HPA-O 10.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 230 + HSBC 300	HPA-O 13.2 Trend HC 400 + HSBC 300
3	Type	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8	AHP-BH 8.8
	Qty	1	1	1	1
		Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater	Wall mounted module with integral emergency/auxiliary heater
	Page	353	353	353	353

Further information about the Set components can be found under the relevant product.

HPA-O Trend + HM Trend



HPA-O 07.2 Trend HC 230 + HM Trend

Benefits
- The air source heat pump is ideally suited to new builds
- Depending on the cylinder, also suitable for higher DHW demand
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder
- Can be combined with any cylinder range

Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O Trend series in combination with the HM Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

		HPA-O 07.2 Trend HC 230 + HM Trend	HPA-O 10.2 Trend HC 230 + HM Trend	HPA-O 13.2 Trend HC 230 + HM Trend	HPA-O 13.2 Trend HC 400 + HM Trend
		NEW	NEW	NEW	NEW
Part number		**208405**	**208221**	**208406**	**208222**

Set components		HPA-O 07.2 Trend HC 230 + HM Trend	HPA-O 10.2 Trend HC 230 + HM Trend	HPA-O 13.2 Trend HC 230 + HM Trend	HPA-O 13.2 Trend HC 400 + HM Trend
1	Type	HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230	HPA-O 13.2 Trend HC 400
	Qty	1	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	177	177	177	177
2	Type	HM Trend	HM Trend	HM Trend	HM Trend
	Qty	1	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O Trend + HMS Trend



HPA-O 07.2 Trend HC 230 + HMS Trend

Benefits
- The air source heat pump is ideally suited to new builds
- Depending on the cylinder, also suitable for higher DHW demand
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder
- Can be combined with any cylinder range

Application • Set consisting of an air source heat pump with output-dependent control from the HPA-O Trend series in combination with the HMS Trend hydraulic module. The set serves as the sole heat generator for new build and modernisation. • The hydraulic module used is suitable for simple hydraulic connection of mono block heat pumps to the heating system and the DHW cylinder. The heat pump manager integrated in the hydraulic module enables fully automatic, weather-compensated control of the heating system. • Furthermore, a high efficiency circulation pump and an expansion vessel in the hydraulic module are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

		HPA-O 07.2 Trend HC 230 + HMS Trend	HPA-O 10.2 Trend HC 230 + HMS Trend	HPA-O 13.2 Trend HC 230 + HMS Trend
		NEW	NEW	NEW
Part number		**208725**	**208726**	**208727**

Set components		**HPA-O 07.2 Trend HC 230 + HMS Trend**	**HPA-O 10.2 Trend HC 230 + HMS Trend**	**HPA-O 13.2 Trend HC 230 + HMS Trend**
1	Type	HPA-O 07.2 Trend HC 230	HPA-O 10.2 Trend HC 230	HPA-O 13.2 Trend HC 230
	Qty	1	1	1
		Air source heat pump installed outdoors	Air source heat pump installed outdoors	Air source heat pump installed outdoors
	Page	177	177	177
2	Type	HMS Trend	HMS Trend	HMS Trend
	Qty	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340

Further information about the Set components can be found under the relevant product.

HPA-O 05.1/07.1 CS Premium



HPA-O 05.1 CS Premium

Benefits

- The air source heat pump for heating and cooling is installed outdoors
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Suitable for energy modernisation projects, as the high supply flow temperature is available all year round
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Futureproof and eco-friendly refrigerant with high efficiency
- High efficiency and low operating costs all year round, thanks to optimally matched components
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump with output-dependent control and inverter technology is designed as a compact mono block appliance for outdoor installation. It delivers the required heating output, ensures a reliable supply of domestic hot water and can be used for efficient cooling through circuit reversal. • A flow temperature of up to 75 °C is available for heating mode and DHW heating. Protection against legionella is ensured without the need for an electric auxiliary heater. • The heat pump can also be used to heat older buildings via radiators, as a flow temperature of 55 °C can still be achieved even when there is a heavy frost (-25 °C outside temperature).

Convenience features • Very quiet operation is made possible by the encapsulated refrigerant circuit and acoustically isolated compressor. Contributing to the low sound power level are the modulating fan and the wide gaps between the evaporator fins which reduce air resistance. • High DHW temperatures are assured without the need for electric backup, even in the winter; this is because the heat pump works with high flow temperatures all year round. • The system can be integrated into a home network and controlled from a mobile device. For this, the on-site heat pump manager is combined with the Internet Service Gateway. With integral heat and electricity metering via refrigerant circuit data. • Mono energetic operation is possible thanks to the integral electric emergency/auxiliary heater. • The enamelled, corrosion-protected metal casing is made from hot-dip galvanised, powder coated sheet steel. Fan grille, recessed grips and cover are made from weatherproof and UV-resistant plastic.

Efficiency • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R454C. When combined with the optimally matched components, highly efficient operation is possible all year round. This efficiency is helped by demand-dependent defrosting via circuit reversal and the heating of the condensate pan via the refrigerant circuit. The hydrophilic coating on the fan nozzle prevents ice from forming, meaning that no electric heating is required.

Installation • The integral anti-vibration mount enables the heat pump to be connected directly to the heating system. • Simplified installation thanks to pivoting electrical connection panel. • Quick access to the condensate pan is possible via the cleaning aperture on the back of the casing.



202666, 202668



202666, 202668


		HPA-O 05.1 CS Premium	HPA-O 07.1 CS Premium
Part number		**202666**	**202668**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++
SCOP 35 °C (EN 14825)		4.70	4.88
Heating output at A7/W35 (EN 14511)	kW	3.31	3.31
Heating output at A2/W35 (EN 14511)	kW	3.19	4.30
Heating output at A-7/W35 (EN 14511)	kW	4.97	6.87
COP at A7/W35 (EN 14511)		5.42	5.42
COP at A2/W35 (EN 14511)		4.60	4.30
COP at A-7/W35 (EN 14511)		3.45	2.93
Max. cooling capacity at A35/W7	kW	4.73	7.30
Cooling capacity at A35/W18 partial load (EN 14511)	kW	3.37	4.94
Max. cooling capacity at A35/W18	kW	6.86	10.15

next page >

		HPA-O 05.1 CS Premium	HPA-O 07.1 CS Premium
Energy efficiency ratio at A35/ W7 max.		2.86	2.35
Energy efficiency ratio at A35/ W18 partial load (EN 14511)		4.35	4.28
Energy efficiency ratio at A35/ W18 max.		3.84	2.87
Sound power level (EN 12102)	dB(A)	48	48
Min./max. application limits for heat source	°C	-25/40	-25/40
Max. application limit on the heating side	°C	75	75
Height	mm	900	900
Width	mm	1270	1270
Depth	mm	593	593
Weight	kg	135	135
Rated voltage, compressor	V	230	230
Rated voltage, emergency/auxiliary heater	V	230	230
Refrigerant		R454C	R454C
Colour		white	white
Required accessories			
Part number		**236000**	**236000**
Type		WPM international	WPM international
Description		Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**
Type		HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module
Part number		**232964**	**232964**
Type		SK 1	SK 1
Description		T-support	T-support
Part number		**233622**	**233622**
Type		AS-WP 1	AS-WP 1
Description		Hydraulic connection set	Hydraulic connection set
Part number		**233623**	**233623**
Type		AS-WP 2	AS-WP 2
Description		Hydraulic connection set	Hydraulic connection set
Part number		**233826**	**233826**
Type		HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module
Part number		**234722**	**234722**
Type		WK 2	WK 2
Description		Wall mounting bracket	Wall mounting bracket
DHW cylinder			
Part number		**202926**	**202926**
Type		HSBB 180 Plus	HSBB 180 Plus
Description		Integral cylinder	Integral cylinder
Part number		**202927**	**202927**
Type		HSBC 180 Plus	HSBC 180 Plus
Description		Integral cylinder	Integral cylinder
Part number		**203082**	**203082**
Type		HSBC 180 S Plus	HSBC 180 S Plus
Description		Integral cylinder	Integral cylinder


next page >


		HPA-O 05.1 CS Premium	HPA-O 07.1 CS Premium
Part number		**203084**	**203084**
Type		HSBB 180 S Plus	HSBB 180 S Plus
Description		Integral cylinder	Integral cylinder
Part number		**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder
Part number		**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder
Part number		**229980**	**229980**
Type		SBS 601 W	SBS 601 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**
Type		HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder
Part number		**234801**	**234801**
Type		HSBC 200 S	HSBC 200 S
Description		Integral cylinder	Integral cylinder
Buffer cylinder			
Part number		**205295**	**205295**
Type		SBP 200 Plus cool	SBP 200 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation




		HPA-O 05.1 CS Premium	HPA-O 07.1 CS Premium
d45 Condensate drain - diameter	mm	29.6	29.6
d47 Drain		•	•
e01 Heating flow - connection type		Plug-in connection	Plug-in connection
e01 Heating flow - diameter	mm	28	28
e02 Heating return - connection type		Plug-in connection	Plug-in connection
e02 Heating return - diameter	mm	28	28
g01 Air intake		•	•
g02 Air discharge		•	•


Minimum clearance diagram




≥300
≥300
D0000078119.ai


≥250
≥250
2
≥300
1
≥300
2
D0000078120.ai

Inverter



HPA-O 7-13 Premium



HPA-O 10 Premium

Benefits

- The air source heat pump for heating is installed outdoors
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Even at low outside temperatures, the enhanced vapour injection/enhanced saturated vapour injection of the heat pump achieves a high flow temperature
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- High efficiency and low operating costs all year round, thanks to optimally matched components
- Low operating costs as mono mode DHW heating is possible
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump with output-dependent control and inverter technology is installed outdoors. The compact mono block design is also suitable for use in modernised older buildings thanks to the demand-dependent high flow temperatures.

Convenience features • Very quiet operation thanks to encapsulated refrigerant circuit and acoustically isolated compressor. Contributing to the low sound power level are the modulating fan and the wide gaps between the evaporator fins which reduce air resistance. The combined enhanced vapour injection/enhanced saturated vapour injection cools the scroll compressor at low outside temperatures, which enables a higher heating output/flow temperature to be achieved. • When combined with the Internet Service Gateway, the integral heat pump manager controls the system in the home network or with a mobile device. With integral heat and electricity metering via refrigerant circuit data. • The electric emergency/auxiliary heater enables mono energetic operation. The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R410A. • The enamelled, corrosion-protected metal casing is made from hot-dip galvanised, powder coated sheet steel. Fan grille, recessed grips and cover are made from weatherproof and UV-resistant plastic.

Efficiency • The waste heat from the inverter is used to raise the return temperature. In addition, the overall efficiency of the system is increased by on-demand defrosting through circuit reversal and heating of the condensate pan by the refrigerant circuit. • The hydrophilic coating on the fan nozzle prevents ice from forming, meaning that no electric heating is required.

Installation • Integral anti-vibration mounts for direct connection to the heating system. • The pivoting electrical connection panel makes installation easier. The condensate pan can be easily reached through the cleaning aperture on the back of the casing.


		HPA-O 10 Premium	HPA-O 13 Premium	HPA-O 13 S Premium
Part number		**238978**	**238982**	**238980**
Specification				
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++	A++
SCOP 35 °C (EN 14825)		4.70	4.63	4.39
Heating output at A7/W35 (EN 14511)	kW	7.84	7.84	8.00
Heating output at A2/W35 (EN 14511)	kW	8.33	8.33	8.33
Heating output at A-7/W35 (EN 14511)	kW	9.54	12.86	12.86
COP at A7/W35 (EN 14511)		5.09	5.09	4.82
COP at A2/W35 (EN 14511)		4.14	4.14	4.14
COP at A-7/W35 (EN 14511)		3.26	2.93	2.98
Sound power level (EN 12102)	dB(A)	55	55	55
Min./max. application limits for heat source	°C	-20 / 40	-20 / 40	-20 / 40
Max. application limit on the heating side	°C	65	65	65
Height	mm	1045	1045	1045
Width	mm	1490	1490	1490
Depth	mm	593	593	593

next page >

		HPA-O 10 Premium	HPA-O 13 Premium	HPA-O 13 S Premium
Weight	kg	175	175	175
Rated voltage, compressor	V	400	400	230
Rated voltage, emergency/auxiliary heater	V	400	400	230
Refrigerant		R410A	R410A	R410A
Colour			white	
Required accessories				
Part number		**236000**	**236000**	**236000**
Type		WPM international	WPM international	WPM international
Description		Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure
Recommended accessories				
Part number		**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**	**232805**
Type		HM Trend	HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module
Part number		**232964**	**232964**	**232964**
Type		SK 1	SK 1	SK 1
Description		T-support	T-support	T-support
Part number		**233622**	**233622**	**233622**
Type		AS-WP 1	AS-WP 1	AS-WP 1
Description		Hydraulic connection set	Hydraulic connection set	Hydraulic connection set
Part number		**233623**	**233623**	**233623**
Type		AS-WP 2	AS-WP 2	AS-WP 2
Description		Hydraulic connection set	Hydraulic connection set	Hydraulic connection set
Part number		**233826**	**233826**	**233826**
Type		HMS Trend	HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module
Part number		**234722**	**234722**	**234722**
Type		WK 2	WK 2	WK 2
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
DHW cylinder				
Part number		**203801**	**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder	Integral cylinder
Part number		**221360**	**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder
Part number		**221361**	**221361**	**221361**
Type		SBB 302 WP	SBB 302 WP	SBB 302 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder
Part number		**229981**	**229981**	**229981**
Type		SBS 801 W	SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	**233510**
Type		HSBC 200	HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder	Integral cylinder
Part number		**234801**	**234801**	**234801**
Type		HSBC 200 S	HSBC 200 S	HSBC 200 S
Description		Integral cylinder	Integral cylinder	Integral cylinder


next page >


		HPA-O 10 Premium	HPA-O 13 Premium	HPA-O 13 S Premium
Buffer cylinder				
Part number		**205296**	**205296**	**205296**
Type		SBP 400 Plus cool	SBP 400 Plus cool	SBP 400 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation





		HPA-O 10 Premium	HPA-O 13 Premium	HPA-O 13 S Premium
d45 Condensate drain - diameter	mm	22	22	22
d47 Drain		•	•	•
e01 Heating flow - connection type		Plug-in connection	Plug-in connection	Plug-in connection
e01 Heating flow - diameter	mm	28	28	28
e02 Heating return - connection type		Plug-in connection	Plug-in connection	Plug-in connection
e02 Heating return - diameter	mm	28	28	28
g01 Air intake		•	•	•
g02 Air discharge		•	•	•

Minimum clearance diagram









HPA-O 7-13 C Premium



HPA-O 10 C Premium

Benefits

- The air source heat pump for heating and cooling is installed outdoors
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Even at low outside temperatures, the enhanced vapour injection/enhanced saturated vapour injection of the heat pump achieves a high flow temperature
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Improved room climate in summer with active cooling using circuit reversal
- High efficiency and low operating costs all year round, thanks to optimally matched components
- Low operating costs as mono mode DHW heating is possible
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump with output-dependent control and inverter technology is designed as a compact mono block appliance for outdoor installation. • It delivers the required heating output, ensures a reliable supply of DHW and can be used for efficient cooling through circuit reversal. • Its high flow temperatures mean that it can be used for heating and DHW in new and modernised buildings.

Convenience features • Quiet operation is ensured by the encapsulated refrigerant circuit and acoustically isolated compressor. Contributing to the low sound power level are the modulating fan and the wide gaps between the evaporator fins, which reduce air resistance. • The combined enhanced vapour injection/enhanced saturated vapour injection cools the scroll compressor at low outside temperatures and ensures that the maximum flow temperature is achieved all year round. • The system can be incorporated into a smart home network and controlled via a mobile device if the on-site heat pump controller is combined with the Internet Service Gateway. • With integral heat and electricity metering via refrigerant circuit data. • The electric emergency/auxiliary heater enables mono energetic operation. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with eco-friendly, futureproof refrigerant R410A. • The corrosion-protected metal casing is made from hot-dip galvanised, powder coated sheet steel. • Fan grille, recessed grips and cover are made from weatherproof and UV-resistant plastic.

Efficiency • The waste heat from the inverter is used to raise the temperature in the return. This increases the energy efficiency of the overall system. This is further aided by on-demand defrosting through circuit reversal and heating of the condensate pan by the refrigerant circuit. • Demand-dependent, energy efficient defrosting through circuit reversal.

Installation • The integral anti-vibration mount enables the heat pump to be connected directly to the heating system. • The pivoting electrical connection panel makes installation easier. • The condensate pan can be easily reached through a cleaning aperture on the back of the casing.

		HPA-O 10 C Premium	HPA-O 13 CS Premium	HPA-O 13 C Premium
Part number		**238979**	**238981**	**238983**
Specification				
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++	A++
SCOP 35 °C (EN 14825)		4.87	4.53	4.76
Heating output at A7/W35 (EN 14511)	kW	7.84	8.00	7.84
Heating output at A2/W35 (EN 14511)	kW	8.33	8.33	8.33
Heating output at A-7/W35 (EN 14511)	kW	9.54	12.86	12.86
COP at A7/W35 (EN 14511)		5.09	4.82	5.09
COP at A2/W35 (EN 14511)		4.14	4.14	4.14
COP at A-7/W35 (EN 14511)		3.26	2.98	2.93
Max. cooling capacity at A35/W7	kW	11.49	14.88	14.88
Cooling capacity at A35/W18 partial load (EN 14511)	kW	6.76	6.76	6.76
Max. cooling capacity at A35/W18	kW	15.26	17.06	17.06


next page >

Inverter

		HPA-O 10 C Premium	HPA-O 13 CS Premium	HPA-O 13 C Premium
Energy efficiency ratio at A35/W7 max.		2.53	2.38	2.38
Energy efficiency ratio at A35/W18 partial load (EN 14511)		3.76	3.76	3.76
Energy efficiency ratio at A35/W18 max.		3.12	2.83	2.83
Sound power level (EN 12102)	dB(A)	55	55	55
Min./max. application limits for heat source	°C	-20/40	-20 / 40	-20 / 40
Max. application limit on the heating side	°C	65	65	65
Height	mm	1045	1045	1045
Width	mm	1490	1490	1490
Depth	mm	593	593	593
Weight	kg	175	175	175
Rated voltage, compressor	V	400	230	400
Rated voltage, emergency/auxiliary heater	V	400	230	400
Refrigerant		R410A	R410A	R410A
Colour				white
Required accessories				
Part number		**236000**	**236000**	**236000**
Type		WPM international	WPM international	WPM international
Description		Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure
Recommended accessories				
Part number		**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**	**232805**
Type		HM Trend	HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module
Part number		**232964**	**232964**	**232964**
Type		SK 1	SK 1	SK 1
Description		T-support	T-support	T-support
Part number		**233622**	**233622**	**233622**
Type		AS-WP 1	AS-WP 1	AS-WP 1
Description		Hydraulic connection set	Hydraulic connection set	Hydraulic connection set
Part number		**233623**	**233623**	**233623**
Type		AS-WP 2	AS-WP 2	AS-WP 2
Description		Hydraulic connection set	Hydraulic connection set	Hydraulic connection set
Part number		**233826**	**233826**	**233826**
Type		HMS Trend	HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module	Hydraulic module
Part number		**234722**	**234722**	**234722**
Type		WK 2	WK 2	WK 2
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket
DHW cylinder				
Part number		**203801**	**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder	Integral cylinder
Part number		**221360**	**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder
Part number		**221361**	**221361**	**221361**
Type		SBB 302 WP	SBB 302 WP	SBB 302 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder


next page >


		HPA-O 10 C Premium	HPA-O 13 CS Premium	HPA-O 13 C Premium
Part number		**229981**	**229981**	**229981**
Type		SBS 801 W	SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	**233510**
Type		HSBC 200	HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder	Integral cylinder
Part number		**234801**	**234801**	**234801**
Type		HSBC 200 S	HSBC 200 S	HSBC 200 S
Description		Integral cylinder	Integral cylinder	Integral cylinder
Buffer cylinder				
Part number		**205296**	**205296**	**205296**
Type		SBP 400 Plus cool	SBP 400 Plus cool	SBP 400 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation




		HPA-O 10 C Premium	HPA-O 13 CS Premium	HPA-O 13 C Premium
d45 Condensate drain - diameter	mm	29.6	22	22
d47 Drain		•	•	•
e01 Heating flow - connection type		Plug-in connection	Plug-in connection	Plug-in connection
e01 Heating flow - diameter	mm	28	28	28
e02 Heating return - connection type		Plug-in connection	Plug-in connection	Plug-in connection
e02 Heating return - diameter	mm	28	28	28
g01 Air intake		•	•	•
g02 Air discharge		•	•	•


Minimum clearance diagram




≥300
≥300
D0000078119.ai


≥250
≥250
2
≥300
1
≥300
2
D0000078120.ai

Inverter



HPA-O 3-8 Plus



HPA-O 4 CS Plus

Benefits

- The air source heat pump for heating and cooling new-builds is installed outdoors
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Reduced space requirement in installation room thanks to compact outdoor unit combined with various indoor modules
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Freezing up of the compressor and blocking of the condensate drain are prevented by means of an „anti-block condensate“ (ABC design)
- Can be integrated into the home network and operated via a smartphone
- High hot water convenience with large mixed water amount due to high flow temperature
- Straightforward hydraulic connection due to integral anti-vibration mounts
- The air source heat pump is ideally suited to new builds

Application • This air source heat pump with output-dependent control and inverter technology is designed as a compact mono block appliance for outdoor installation. • The heat pump can be used in new build and buildings with a low system temperature for heating and DHW operation as well as for efficient cooling. • To ensure simple and space saving installation in the building, the heat pump is supplied in a set with compact and ideally matched indoor units.

Convenience features • Quiet operation thanks to the encapsulated refrigerant circuit and acoustically isolated compressor. With integral heat and electricity metering via refrigerant circuit data.

Efficiency • The waste heat from the inverter raises the return temperature which, together with demand-dependent defrosting by circuit reversal, significantly increases the overall efficiency of the system.

Installation • Thanks to the integral anti-vibration mounts, the heat pump can be connected directly to the heating system. Extensive accessories are available for both floor or wall mounted installations. This ensures that any condensate can drip off easily. • The electrical connection panel is easy to access, without having to open the unit.

		HPA-O 4 CS Plus	HPA-O 6 CS Plus	HPA-O 8 CS Plus
Part number				
Specification				
Energy efficiency class, heat pump W35 A+++ -> D		A++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+	A++	A++
SCOP 35 °C (EN 14825)		4.15	4.50	4.61
SCOP 55 °C (EN 14825)				3.29
Heating output at A7/W35 (EN 14511)	kW	2.73	4.86	4.86
Heating output at A2/W35 (EN 14511)	kW	2.58	5.30	5.30
Heating output at A-7/W35 (EN 14511)	kW	3.96	6.00	7.80
COP at A7/W35 (EN 14511)		4.70	4.76	4.76
COP at A2/W35 (EN 14511)		3.64	3.80	3.80
COP at A-7/W35 (EN 14511)		2.73	2.98	2.91
Max. cooling capacity at A35/W7	kW	3.00	5.00	6.00
Cooling capacity at A35/W18 partial load (EN 14511)	kW	1.50	2.50	3.00
Max. cooling capacity at A35/W18	kW	3.00	5.00	6.00
Energy efficiency ratio at A35/W7 max.		1.62	1.73	1.73
Energy efficiency ratio at A35/W18 partial load (EN 14511)		3.56	3.28	3.28

next page >


Inverter

		HPA-O 4 CS Plus	HPA-O 6 CS Plus	HPA-O 8 CS Plus
Energy efficiency ratio at A35/W18 max.		3.12	2.88	2.88
Sound power level (EN 12102)	dB(A)	52	57	57
Min./max. application limits for heat source	°C	-20...40	-20...40	-15...40
Max. application limit on the heating side	°C	60	60	60
Height	mm	740	812	812
Width	mm	1022	1152	1152
Depth	mm	524	524	524
Weight	kg	62	91	91
Rated voltage, compressor	V	230	230	230
Rated voltage, emergency/auxiliary heater	V			230
Refrigerant		R410A	R410A	R410A

Recommended accessories				
Part number		**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**236693**	**236693**	**236693**
Type		SK 2	SK 2	SK 2
Description		T-support	T-support	T-support
Part number		**238686**	**238686**	**238686**
Type		WK 1.1	WK 1.1	WK 1.1
Description		Wall mounting bracket	Wall mounting bracket	Wall mounting bracket


Only available in the set.

The necessary T-support or wall mounting bracket is available as an accessory



		HPA-O 4 CS Plus	HPA-O 6 CS Plus	HPA-O 8 CS Plus
a10 Appliance - height	mm	740	812	812
a20 Appliance - width	mm	1,022	1,152	1,152
b01 Entry electrical cables		•	•	•
d45 Condensate drain		•	•	•
e01 Heating flow - diameter	mm	22	22	22
e02 Heating return - diameter	mm	22	22	22
g01 Air intake		•	•	•
g02 Air discharge		•	•	•

Minimum clearance diagram




HPA-O CS Plus flex Set



Benefits


- The air source heat pump is ideally suited to new builds
- Depending on the cylinder, also suitable for higher DHW demand
- Can be combined with any cylinder range
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Hydraulic module with all relevant heating components including heat pump manager for integrating the heat pump and cylinder



HPA-O 4 CS Plus flex Set

Application • Mono block heat pump with output-dependent control, in combination with a hydraulic module. • This configuration makes it possible to meet different hot water convenience requirements through free combination with DHW cylinders. • The hydraulic connection can be achieved by flexibly adding buffer cylinders. • The following components are already integrated: a highly efficient circulation pump for the heating and DHW sides, electric emergency/auxiliary heater, heating expansion vessel, safety valve, quick-action air vent valve, 3/2-way diverter valve and the heat pump manager for controlling the system.

		HPA-O 4 CS Plus flex Set	HPA-O 4 CS Plus flex Set S	HPA-O 6 CS Plus flex Set	HPA-O 6 CS Plus flex Set S	HPA-O 8 CS Plus flex Set	HPA-O 8 CS Plus flex Set S
Part number		**239052**	**238989**	**239053**	**238990**	**239054**	**238991**



Set components		HPA-O 4 CS Plus flex Set	HPA-O 4 CS Plus flex Set S	HPA-O 6 CS Plus flex Set	HPA-O 6 CS Plus flex Set S	HPA-O 8 CS Plus flex Set	HPA-O 8 CS Plus flex Set S
1	Type	HPA-O 4 CS Plus	HPA-O 4 CS Plus	HPA-O 6 CS Plus	HPA-O 6 CS Plus	HPA-O 8 CS Plus	HPA-O 8 CS Plus
	Qty	1	1	1	1	1	1
		Air source heat pump	Air source heat pump	Air source heat pump	Air source heat pump	Air source heat pump	Air source heat pump
	Page	205	205	205	205	205	205
2	Type	HM Trend	HMS Trend	HM Trend	HMS Trend	HM Trend	HMS Trend
	Qty	1	1	1	1	1	1
		Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module	Hydraulic module
	Page	340	340	340	340	340	340
3	Type	AS-HM Trend	AS-HM Trend	AS-HM Trend	AS-HM Trend	AS-HM Trend	AS-HM Trend
	Qty	1	1	1	1	1	1
		Hydraulic module connection set	Hydraulic module connection set	Hydraulic module connection set	Hydraulic module connection set	Hydraulic module connection set	Hydraulic module connection set
	Page	342	342	342	342	342	342

Further information about the Set components can be found under the relevant product.
The necessary T-support or wall mounting bracket is available as an accessory. More details regarding set contents can be found under the relevant product
The necessary plinth or wall mounting bracket is available as an accessory (Product: 238989, 238990, 238991)

HPA-O Plus compact Set 1.1




Benefits

- The air source heat pump is ideally suited to new builds
- Cost optimised solution with all required system components incl. DHW cylinder
- Small footprint as just one indoor and outdoor unit is required
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- Compact DHW cylinder with integral hydraulic components including heat pump manager for heat pumps and heating circuit connection in a single casing

Application • This mono block heat pump with output-dependent control is equipped with a DHW cylinder and all hydraulic components for the heating installation. • Standard delivery also includes: circulation pump, 3/2-way diverter valve, safety valve and electric emergency/auxiliary heater. • Control is provided by the integral heat pump manager.

HPA-O 6 CS Plus compact Set 1.1

		HPA-O 6 CS Plus compact Set 1.1	HPA-O 6 CS Plus compact Set S 1.1	HPA-O 8 CS Plus compact Set 1.1	HPA-O 8 CS Plus compact Set S 1.1
Part number		**204269**	**204272**	**204270**	**204273**



Set components		HPA-O 6 CS Plus compact Set 1.1	HPA-O 6 CS Plus compact Set S 1.1	HPA-O 8 CS Plus compact Set 1.1	HPA-O 8 CS Plus compact Set S 1.1
1	Type	HPA-O 6 CS Plus	HPA-O 4 CS Plus	HPA-O 8 CS Plus	HPA-O 8 CS Plus
	Qty	1	1	1	1
		Air source heat pump	Air source heat pump	Air source heat pump	Air source heat pump
	Page	205	205	205	205
2	Type	HSBB 180 Plus	HSBB 180 S Plus	HSBB 180 Plus	HSBB 180 S Plus
	Qty	1	1	1	1
		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page	349	349	349	349

Further information about the Set components can be found under the relevant product.
The necessary T-support or wall mounting bracket is available as an accessory.

HPA-O Plus compact D Set 1.1




HPA-O 3 CS Plus compact D Set 1.1

Benefits

- The air source heat pump is ideally suited to new builds
- Thanks to flow separation, the heating system can be integrated easily and very safely
- Small footprint as just one indoor and outdoor unit is required
- The mono block heat pump is installed outdoors and its variable speed compressor ensures perfectly matched heating output
- DHW cylinder and buffer cylinder with integral hydraulic components including heat pump manager for heat pumps and heating circuit connection in a single casing

Application • This mono block heat pump with output-dependent control has a highly integrated indoor unit to minimise the installation area. • The following components are integrated: DHW cylinder, parallel buffer cylinder, cylinder charging pump, circulation pump, 3/2-way diverter valve, safety valve and electric emergency/auxiliary heater. The heat pump manager, which controls the appliance, is also built in.

		HPA-O 3 CS Plus compact D Set 1.1	HPA-O 6 CS Plus compact D Set 1.1	HPA-O 6 CS Plus compact D Set S 1.1	HPA-O 8 CS Plus compact D Set 1.1	HPA-O 8 CS Plus compact D Set S 1.1
Part number		**204282**	**204275**	**204279**	**204276**	**204280**



Set components		HPA-O 3 CS Plus compact D Set 1.1	HPA-O 6 CS Plus compact D Set 1.1	HPA-O 6 CS Plus compact D Set S 1.1	HPA-O 8 CS Plus compact D Set 1.1	HPA-O 8 CS Plus compact D Set S 1.1
1	Type	HSBC 180 Plus	HPA-O 6 CS Plus	HPA-O 6 CS Plus	HPA-O 8 CS Plus	HPA-O 8 CS Plus
	Qty	1	1	1	1	1
		Integral cylinder	Air source heat pump	Air source heat pump	Air source heat pump	Air source heat pump
	Page	348	205	205	205	205
2	Type		HSBC 180 Plus	HSBC 180 S Plus	HSBC 180 Plus	HSBC 180 S Plus
	Qty		1	1	1	1
			Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
	Page		348	348	348	348

Further information about the Set components can be found under the relevant product.
The necessary T-support or wall mounting bracket is available as an accessory.

WPL 19/24 A



WPL 19 A Set

Benefits

- The air source heat pump for heating older buildings is installed outdoors
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Even at low outside temperatures, the enhanced vapour injection/enhanced saturated vapour injection of the heat pump achieves a high flow temperature
- Optimised for replacement of 13/18/23 E air source heat pumps installed outdoors
- Because of the high flow temperature all year round, also suitable for modernisation projects and for DHW heating
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Can be integrated into the home network and operated via a smartphone
- High efficiency and low operating costs all year round, thanks to optimally matched components
- Low operating costs as mono mode DHW heating is possible

Application • This compact air source heat pump with output-dependent control and inverter technology is designed for outdoor installation, including installation in open spaces. • It can be used in modernisation projects as flow temperatures of up to 65 °C are available all year round for room heating and DHW heating.

Convenience features • The encapsulated refrigerant circuit and acoustically isolated compressor make very quiet operation possible. The modulating fan and the wide gaps between the evaporator fins, which create low air resistance, also help to minimise the sound power level. • With integral heat and electricity metering via refrigerant circuit data. • Mono energetic operation possible with electric emergency/auxiliary heater. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.

Efficiency • The heat pump delivers a high flow temperature all year round according to demand, as the combined enhanced vapour injection/enhanced saturated vapour injection cools the scroll compressor at low outside temperatures. This allows operation without an electric emergency/auxiliary heater. • The waste heat from the inverter is used to raise the return temperature. In addition, demand-dependent defrosting through circuit reversal and heating of the condensate pan by the refrigerant circuit increase the overall efficiency of the system.

Installation • The heat pump, with integral anti-vibration mounts, is directly connected to the heating system.




		WPL 19 A Set	WPL 24 A Set
Part number		**236412**	**236413**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++
SCOP 35 °C (EN 14825)		4.44	4.45
SCOP 55 °C (EN 14825)		3.64	3.53
Heating output at A7/W35 (EN 14511)	kW	6.70	7.41
Heating output at A2/W35 (EN 14511)	kW	7.41	9.04
Heating output at A-7/W35 (EN 14511)	kW	9.91	13.45
COP at A7/W35 (EN 14511)		4.99	4.72
COP at A2/W35 (EN 14511)		4.12	4.00
COP at A-7/W35 (EN 14511)		3.32	3.00
Sound power level (EN 12102)	dB(A)	59	59
Min./max. application limits for heat source	°C	-20/40	-20/40
Max. application limit on the heating side	°C	65	65
Height	mm	1434	1434
Width	mm	1240	1240
Depth	mm	1280	1280
Weight	kg	279	279
Rated voltage, compressor	V	400	400

next page >


Inverter

		WPL 19 A Set	WPL 24 A Set
Rated voltage, emergency/auxiliary heater	V	400	400
Refrigerant		R410A	R410A
Colour		white	white
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**
Type		HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module
Part number		**233826**	**233826**
Type		HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module
DHW cylinder			
Part number		**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder
Part number		**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder
Part number		**229981**	**229981**
Type		SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**
Type		HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder
Part number		**234801**	**234801**
Type		HSBC 200 S	HSBC 200 S
Description		Integral cylinder	Integral cylinder



		WPL 19 A Set	WPL 24 A Set
g01 Air intake		•	•
g02 Air discharge		•	•
i21 Entry supply line		•	•

Minimum clearance diagram




Application areas





Heating

Cooling









Air source heat pumps, outdoor installation – Fixspeed

Fixspeed
- **WPL 47/57** 216
- **WPL 13-23 E** 219
- **WPL 13-23 cool** 225

Fixspeed

WPL 47/57



WPL 47 Set A

Benefits

- The air source heat pump for heating is installed outdoors
- Low installed height
- With integral heat and electricity meters
- Electronic expansion valve
- Suitable for cascade connection with high output demand
- Suitable for use in residential and commercial buildings due to high output
- Extremely versatile due to cascade control and dual mode integration
- High reliability thanks to robust single compressor design

Application • This air source heat pump is installed outdoors. It is suitable as a standalone appliance due to its high output of up to 24 kW. In a cascade, the appliance is suitable for apartment buildings and commercial applications up to 144 kW. • The casing design allows flexible installation, even in open spaces.

Convenience features • Quiet operation is ensured by the encapsulated refrigerant circuit and acoustically isolated compressor. The wide gaps between the evaporator fins enable low air resistance. In combination with the modulating fan, this results in a low sound power level. • In combination with the Internet Service Gateway (optional accessory), the heat pump controller (accessory) can be used to control the system in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • Fault messages can be processed externally via a 230 V signal. • Can be integrated into a building automation system if required using a software extension. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R407C. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.


Efficiency • Demand-dependent, energy efficient defrosting through circuit reversal. • To enable efficient defrosting, the refrigerant circuit heats the condensate pan.

		WPL 47 Set A	WPL 57 Set A
Part number		**228836**	**228837**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A++	A+
Energy efficiency class, heat pump W55 A+++ -> D		A+	A+
Heating output at A7/W35 (EN 14511)	kW	26.83	31.01
Heating output at A2/W35 (EN 14511)	kW	24.82	29.81
Heating output at A-7/W35 (EN 14511)	kW	21.68	24.02
COP at A7/W35 (EN 14511)		3.94	3.59
COP at A2/W35 (EN 14511)		3.43	3.30
COP at A-7/W35 (EN 14511)		3.05	2.84
SCOP 35 °C (EN 14825)		3.79	3.42
Sound power level (EN 12102)	dB(A)	69	69
Min./max. application limits for heat source	°C	-20 / 40	-20 / 40
Max. application limit on the heating side	°C	60	60
Height	mm	1485	1485
Width	mm	1860	1860
Depth	mm	2040	2040
Weight	kg	540	600
Rated voltage, compressor	V	400	400
Rated voltage, emergency/auxiliary heater	V	400	400

next page >

Fixspeed


		WPL 47 Set A	WPL 57 Set A
Rated voltage, control unit	V	230	230
Refrigerant		R407C	R407C
Colour		white	white
Required accessories			
Part number		**236000**	**236000**
Type		WPM international	WPM international
Description		Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
DHW cylinder			
Part number		**229981**	**229981**
Type		SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Part number		**229982**	**229982**
Type		SBS 1001 W	SBS 1001 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Buffer cylinder			
Part number		**185459**	**185459**
Type		SBP 700 E	SBP 700 E
Description		Buffer cylinder	Buffer cylinder
Part number		**203765**	**203765**
Type		STH 720 Plus	STH 720 Plus
Description		Buffer cylinder	Buffer cylinder
Part number		**227564**	**227564**
Type		SBP 1000 E	SBP 1000 E
Description		Buffer cylinder	Buffer cylinder



Fixspeed

		WPL 47 Set A	WPL 57 Set A
g01 Air intake		•	•
g02 Air discharge		•	•
i21 Entry supply line		•	•

Minimum clearance diagram



Fixspeed

WPL 13-23 E



WPL 13 E

Benefits

- Air source heat pump for heating
- High heating output at low outside temperatures through enhanced vapour injection
- Higher COP through optimised refrigerant circuit
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump for heating and DHW can be installed either outdoors or indoors as a mono block. Features enhanced vapour injection.

Convenience features • Quiet operation thanks to twin anti-vibration compressor mounts. • The enhanced vapour injection cools the scroll compressor at low outside temperatures, which achieves a higher heating output. • In combination with the Internet Service Gateway, the on-site heat pump controller can be used to control the system in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • An electric emergency/auxiliary heater enables mono energetic operation. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R407C. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.

Efficiency • Time optimised and energy efficient defrosting through circuit reversal with a 4/2-way valve. • For efficient defrosting, the refrigerant circuit heats the condensate pan.

		WPL 13 E	WPL 18 E	WPL 23 E
Part number		**227756**	**227757**	**227758**
Specification				
Energy efficiency class, heat pump W35 A+++ -> D		A++	A++	A+
Energy efficiency class, heat pump W55 A+++ -> D		A+	A+	A+
Heating output at A7/W35 (EN 14511)	kW	8.93	12.90	16.56
Heating output at A2/W35 (EN 14511)	kW	8.09	11.30	15.73
Heating output at A-7/W35 (EN 14511)	kW	6.77	9.72	13.21
COP at A7/W35 (EN 14511)		4.35	4.46	3.99
COP at A2/W35 (EN 14511)		3.76	3.73	3.62
COP at A-7/W35 (EN 14511)		3.20	3.27	3.14
SCOP 35 °C (EN 14825)		3.85	4.00	3.775
Sound power level (EN 12102)	dB(A)	64	65	65
Sound power level, outdoor installation (EN 12102)	dB(A)	64	65	65
Min./max. application limits for heat source	°C	-20...40	-20...40	-20...40
Max. application limit on the heating side	°C	60	60	60
Height	mm	1116	1116	1116
Width	mm	784	784	784
Depth	mm	1182	1182	1182
Weight	kg	205	212	211
Rated voltage, compressor	V	400	400	400
Rated voltage, emergency/auxiliary heater	V	400	400	400
Rated voltage, control unit	V	230	230	230
Refrigerant		R407C	R407C	R407C
Colour		white	white	

next page >


Fixspeed

		WPL 13 E	WPL 18 E	WPL 23 E
Required accessories				
Part number		**074412**	**074412**	**074412**
Type		ZVK WPL 13/18/23 I	ZVK WPL 13/18/23 I	ZVK WPL 13/18/23 I
Description		Casing components for indoor installation	Casing components for indoor installation	Casing components for indoor installation
Part number		**074413**	**074413**	**074413**
Type		ZVK WPL 13/18/23 A	ZVK WPL 13/18/23 A	ZVK WPL 13/18/23 A
Description		Casing components for outdoor installation	Casing components for outdoor installation	Casing components for outdoor installation
Part number		**201721**	**201721**	**201721**
Type		LSWP 560-3 SG	LSWP 560-3 SG	LSWP 560-3 SG
Description		Thermally and sound insulated air hose	Thermally and sound insulated air hose	Thermally and sound insulated air hose
Part number		**233837**	**233837**	**233837**
Type		AWG 560 H-SR	AWG 560 H-SR	AWG 560 H-SR
Description		External wall outlet, thermally insulated	External wall outlet, thermally insulated	External wall outlet, thermally insulated
Recommended accessories				
Part number		**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**	
Type		HM Trend	HM Trend	
Description		Hydraulic module	Hydraulic module	
Part number		**233826**	**233826**	
Type		HMS Trend	HMS Trend	
Description		Hydraulic module	Hydraulic module	
DHW cylinder				
Part number		**203801**	**203801**	
Type		HSBC 300 cool	HSBC 300 cool	
Description		Integral cylinder	Integral cylinder	
Part number		**221360**		
Type		SBB 301 WP		
Description		DHW cylinder		
Part number			**221361**	**221361**
Type			SBB 302 WP	SBB 302 WP
Description			DHW cylinder	DHW cylinder
Part number				**221362**
Type				SBB 401 WP SOL
Description				DHW cylinder
Part number		**229981**	**229981**	**229981**
Type		SBS 801 W	SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**	
Type		HSBC 200	HSBC 200	
Description		Integral cylinder	Integral cylinder	
Part number		**234801**	**234801**	
Type		HSBC 200 S	HSBC 200 S	
Description		Integral cylinder	Integral cylinder	


The housing required for indoor or outdoor installation is available as an accessory.

Wall outlets and air hoses for indoor installation must be ordered separately and are available as accessories in various versions. Preliminary specification (Product: 227756, 227758)


Fixspeed



Fixspeed


d44
d44
800
1260
d44
1240
g02
619
g01
158
442
b01
195
133
e02
233
e01
D0000016755.ai


Fixspeed



		WPL 13 E	WPL 18 E	WPL 23 E
b01 Entry electrical cables		•	•	•
d44 Outlet condensate drain		•	•	•
e01 Heating flow - male thread		G 1 1/4 A	G 1 1/4 A	G 1 1/4 A
e02 Heating return - male thread		G 1 1/4 A	G 1 1/4 A	G 1 1/4 A
g01 Air intake		•	•	•
g02 Air discharge		•	•	•
i21 Entry supply line		•	•	•

Fixspeed

Minimum clearance diagram



Fixspeed

WPL 13-23 cool



WPL 18 cool

Benefits

- Air source heat pump for heating and cooling
- High heating output at low outside temperatures through enhanced vapour injection
- Higher COP through optimised refrigerant circuit
- Active cooling through circuit reversal
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump with enhanced vapour injection can be installed as a mono block both outdoors and indoors. • The heat pump can be used for heating and DHW operation, as well as for efficient cooling through circuit reversal.

Convenience features • Quiet operation is ensured by twin anti-vibration compressor mounts. • The enhanced vapour injection cools the scroll compressor at low outside temperatures, which achieves a higher heating output. • The built-in 4/2-way valve allows the refrigerant circuit to be switched from heating to cooling mode. • In combination with the Internet Service Gateway, the on-site heat pump controller can be used to control the system in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • An electric emergency/auxiliary heater enables mono energetic operation. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R407C. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.

Efficiency • Time optimised and energy efficient defrosting through circuit reversal with a 4/2-way valve. • For efficient defrosting, the refrigerant circuit heats the condensate pan.

		WPL 18 cool	WPL 23 cool
Part number		**223401**	**223402**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A++	A+
Energy efficiency class, heat pump W55 A+++ -> D		A+	A+
Heating output at A7/W35 (EN 14511)	kW	12.30	14.45
Heating output at A2/W35 (EN 14511)	kW	11.30	14.14
Heating output at A-7/W35 (EN 14511)	kW	9.72	12.27
COP at A7/W35 (EN 14511)		4.30	3.52
COP at A2/W35 (EN 14511)		3.70	3.23
COP at A-7/W35 (EN 14511)		3.20	2.91
SCOP 35 °C (EN 14825)		4.075	3.475
Sound power level (EN 12102)	dB(A)	65	65
Sound power level, outdoor installation (EN 12102)	dB(A)	65	65
Min./max. application limits for heat source	°C	-20...40	-20...40
Max. application limit on the heating side	°C	60	60
Height	mm	1116	1116
Width	mm	784	784
Depth	mm	1182	1182
Weight	kg	214	220
Rated voltage, compressor	V	400	400
Rated voltage, emergency/auxiliary heater	V	400	400
Rated voltage, control unit	V	230	230
Refrigerant		R407C	R407C
Colour		white	


next page >

Fixspeed


		WPL 18 cool	WPL 23 cool
Required accessories			
Part number		**074412**	**074412**
Type		ZVK WPL 13/18/23 I	ZVK WPL 13/18/23 I
Description		Casing components for indoor installation	Casing components for indoor installation
Part number		**074413**	**074413**
Type		ZVK WPL 13/18/23 A	ZVK WPL 13/18/23 A
Description		Casing components for outdoor installation	Casing components for outdoor installation
Part number		**201721**	**201721**
Type		LSWP 560-3 SG	LSWP 560-3 SG
Description		Thermally and sound insulated air hose	Thermally and sound insulated air hose
Part number		**233837**	**233837**
Type		AWG 560 H-SR	AWG 560 H-SR
Description		External wall outlet, thermally insulated	External wall outlet, thermally insulated
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
Part number		**232805**	
Type		HM Trend	
Description		Hydraulic module	
Part number		**233826**	
Type		HMS Trend	
Description		Hydraulic module	
DHW cylinder			
Part number		**221361**	**221361**
Type		SBB 302 WP	SBB 302 WP
Description		DHW cylinder	DHW cylinder
Part number			**221362**
Type			SBB 401 WP SOL
Description			DHW cylinder
Buffer cylinder			
Part number		**205296**	**205296**
Type		SBP 400 Plus cool	SBP 400 Plus cool
Description		Buffer cylinder suitable for cooling operation	Buffer cylinder suitable for cooling operation

The housing required for indoor or outdoor installation is available as an accessory. Wall outlets and air hoses for indoor installation must be ordered separately and are available as accessories in various versions.


Fixspeed



Fixspeed


d44
d44
800
1260
d44
1240
g02
619
g01
158
442
b01
195
133
e02
233
e01
D0000016755.ai


Fixspeed



		WPL 18 cool	WPL 23 cool
b01 Entry electrical cables		•	•
d44 Outlet condensate drain		•	•
e01 Heating flow - male thread		G 1 1/4 A	G 1 1/4 A
e02 Heating return - male thread		G 1 1/4 A	G 1 1/4 A
g01 Air intake		•	•
g02 Air discharge		•	•
i21 Entry supply line		•	•

Fixspeed

Minimum clearance diagram



Installation accessories
Accessories 232

AHP-DT.1




Benefits
- Condensate pan for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant
- Reliable condensate drainage even during frost periods thanks to integral electric auxiliary heater
- Operating costs kept to a minimum due to intelligent control by the heat pump depending on defrost cycles and outside temperature
- Connection of the condensate line with standard plastic pipe

Description • Condensate pan for air source heat pumps with R290 refrigerant, all output sizes. • Condensate pan for retrofitting for a routed condensate drain. Used for controlled condensate drainage into a drainage system or gravel bed, for example. • Easy installation possible with floorstanding heat pump outdoor unit. • Integral electrical heating for connection within the heat pump.

AHP-DT.1

		AHP-DT.1
		NEW
Part number		**207731**
Specification		
Connection		DN 50
Height	mm	75
Width	mm	816
Length	mm	164

AHP-BS.1



Benefits
- Ball siphon for the condensate line to the domestic waste water or inside the house
- Suitable connection for the condensate line
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Ball siphon for use in the condensate line. This must be used if the condensate is discharged into the domestic waste water pipe or routed inside the house. • The ball siphon guarantees a seal even if the siphon dries out. • Suitable for combination with the AHP-DT.1 condensate pan

AHP-BS.1

		AHP-BS.1
		NEW
Part number		**207894**
Specification		
Connection		DN 40
Height	mm	90
Width	mm	120
Depth	mm	150

AHP-CB.1



Benefits
- Casing for the feet of our heat pumps with R290 refrigerant
- Elegant cover over screws and screw connections to the substrate and beneath the heat pump
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Casing in unit colour for the feet of our heat pumps with R290 refrigerant to create a rounded aesthetic. Made of sheet steel, powder coated and stove-enamelled.

AHP-CB.1

		AHP-CB.1
		NEW
Part number		**207735**
Specification		
Height	mm	50
Width	mm	1168
Depth	mm	728
Weight	kg	4
Colour		Dark grey RAL 7021

AHP-CW.1

Benefits
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant
- Casing for the feet of our heat pumps with R290 refrigerant
- Elegant cover over screws and screw connections to the substrate and beneath the heat pump

Description • Casing in unit colour for the feet of our heat pumps with R290 refrigerant to create a rounded aesthetic. Made of sheet steel, powder coated and stove-enamelled.

AHP-CW.1

		AHP-CW.1
		NEW
Part number		**207736**
Specification		
Height	mm	50
Width	mm	1168
Depth	mm	728
Weight	kg	4
Colour		signal white, RAL 9003

AHP-GC.1



Benefits
- Sturdy floor bracket made of powder coated and stove-enamelled steel
- Air inlet raised to 40 cm for reliable operation when sited in snowy regions
- Guide for easy heat pump positioning
- Can be used with and without condensate pan
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Floor bracket for our air source heat pumps with R290 refrigerant, all output sizes for elevated siting of the outdoor unit. The feet are height-adjustable and can be bolted to the substrate. Siting on strip foundations or paved surfaces possible. • AGC-CB casing available as an accessory for the floor bracket.

AHP-GC.1

		AHP-GC.1
		NEW
Part number		**207732**
Specification		
Height	mm	250
Width	mm	1118
Depth	mm	700
Weight	kg	13,5
Weight load	kg	250
Recommended accessories		
Part number		**207733**
Type		AGC-CB.1
Description		Floor bracket casing set (anthracite)
Part number		**207734**
Type		AGC-CW.1
Description		Floor bracket casing set (white)

AGC-CB



Benefits
- Sheet steel casing for floor bracket for a rounded and all-in-one look
- No visible pipes or cables under the heat pump
- Particularly tidy appearance with connection cables laid in the ground
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Casing for the floor bracket AHP-GC.1 for air source heat pumps with R290 refrigerant, all output sizes. In a dark grey finish to create a high quality look.

AGC-CB.1

		AGC-CB.1
		NEW
Part number		**207733**

next page >

		AGC-CB.1
Specification		
Height	mm	375
Width	mm	1168
Depth	mm	728
Weight	kg	13,4
Colour		Dark grey RAL 7021

AGC-CW



Benefits
- Sheet steel casing for floor bracket for a rounded and all-in-one look
- No visible pipes or cables under the heat pump
- Particularly tidy appearance with connection cables laid in the ground
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Casing for the floor bracket AHP-GC.1 for air source heat pumps with R290 refrigerant, all output sizes. In a white finish to create a high quality look.

AGC-CW.1

		AGC-CW.1
		NEW
Part number		**207734**
Specification		
Height	mm	375
Width	mm	1168
Depth	mm	728
Weight	kg	13,4
Colour		signal white, RAL 9003

AHP-WM.1



Benefits
- Wall mounting bracket including anti-vibration mounts for the installation of a heat pump with R290 refrigerant
- High quality look with mounting behind the heat pump to reduce visible parts
- Can be used with and without condensate pan

Description • Wall mounting bracket for installing a heat pump with R290 refrigerant on a wall. Use for space saving installation or siting on uneven terrain. • Integral anti-vibration mount to minimise vibration transmission from the heat pump to the building structure.

AHP-WM.1

		AHP-WM.1
		NEW
Part number		**207891**

next page >

		AHP-WM.1
Specification		
Height	mm	250
Width	mm	700
Depth	mm	750
Recommended accessories		
Part number		**207892**
Type		AWM-CB.1
Description		Wall mounting bracket casing set
Part number		**207893**
Type		AWM-CW.1
Description		Wall mounting bracket casing set (white)

AWM-CB.1



Benefits
- Casing of the wall mounting bracket and heat pump feet for an all-in-one look
- Covering the connection area behind the heat pump and the connection lines

Description • Wall mounting bracket casing set for heat pumps with R290 refrigerant. Essential parts of the wall mounting bracket in dark grey finish. For creating a high quality appearance at the installation site. Suitable accessories for the AHP-WM.1 wall mounting bracket.

AWM-CB.1

		AWM-CB.1
		NEW
Part number		**207892**
Specification		
Height	mm	350
Width	mm	1200
Depth	mm	500
Weight	kg	9
Colour		Dark grey RAL 7021

AWM-CW



Benefits
- Casing of the wall mounting bracket and heat pump feet for an all-in-one look
- Covering the connection area behind the heat pump and the connection lines

Description • Wall mounting bracket casing set for heat pumps with R290 refrigerant. Essential parts of the wall mounting bracket in a white finish. For creating a high quality appearance at the installation site. Suitable accessories for the AHP-WM.1 wall mounting bracket.

AWM-CW.1

		AWM-CW.1
		NEW
Part number		**207893**
Specification		
Height	mm	350
Width	mm	1200
Depth	mm	500
Weight	kg	9
Colour		signal white, RAL 9003

AHP-SC.1



Benefits
- Stainless steel bracket for concreting in with elevated siting of a heat pump
- Quick assembly with integral installation aid for aligning the bracket parts to each other
- Siting of the heat pump possible with only minimal changes to the substrate
- Can be used with and without condensate pan
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Stainless steel bracket for concreting in with elevated siting of the heat pump. No strip foundation or surface foundation required. Can be used on uneven substrate.

AHP-SC.1

		AHP-SC.1
		NEW
Part number		**207737**
Specification		
Height	mm	950
Width	mm	60
Depth	mm	750
Weight	kg	6,7

One pair for siting a heat pump.

WK 3



Benefits
- Wall mounting bracket including anti-vibration mounts for the installation of a heat pump with R290 refrigerant
- High quality look with mounting behind the heat pump to reduce visible parts
- Can be used with and without condensate pan

Description • Wall mounting bracket for installing a heat pump with R290 refrigerant on a wall. Use for space saving installation or siting on uneven terrain. • Integral anti-vibration mount to minimise vibration transmission from the heat pump to the building structure.

WK 3

		WK 3
		NEW
Part number		**208702**
Specification		
Support length	mm	900
Weight	kg	13,4
Version		Wall mounting bracket
Application		Heat pump
Adjustable slope		-
Quantity		2

AHP-DS 0.8



Benefits
- Anti-vibration mounts for easy siting of a heat pump on paved surfaces or compacted substrates without special preparation of the substrate
- Flat roof installation with no damage to the roof cladding
- Reduction of vibration transmission to the substrate
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Anti-vibration mounts for siting a heat pump on compacted or paved surfaces. The bracket can be bolted to both the heat pump and the substrate. When siting on flat roofs, it is recommended to attach the unit to additional ballast such as concrete slabs. • Recommended for combination with the AHP-DT.1 condensate pan.

AHP-DS 0.8

		AHP-DS 0.8
		NEW
Part number		**207738**
Specification		
Height	mm	90
Width	mm	160
Weight	kg	8,1

AHP-FB 25-0.4



Benefits
- High quality appearance of the connection lines routed downwards inside the heat pump
- Simplified connection thanks to extending hoses
- Quick connection to the heat pump for fast installation
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Flexible corrugated hoses for connecting the hydraulic connection lines downwards inside the heat pump. The hoses are extendible so that a simple connection to the supply line from the bottom is possible. • The standard delivery includes two corrugated hoses with suitable insulation and a cover plate for the connection area behind the heat pump.

AHP-FH 25-0.4

		AHP-FH 25-0.4
		NEW
Part number		**207724**
Specification		
Connection, heating and source side		G 1
Length	m	0,4
Colour		Dark grey RAL 7021

AHP-FW 25-0.4



Benefits
- Optimised for air source heat pumps with R290 refrigerant
- Quick connection to the heat pump for fast installation
- Suitable for all performance classes of air source heat pumps with R290 refrigerant
- Simplified connection thanks to extending hoses
- High quality appearance of the connection lines routed downwards inside the heat pump

Description • Flexible corrugated hoses for connecting the hydraulic connection lines downwards inside the heat pump. The hoses are extendible so that a simple connection to the supply line from the bottom is possible. • The standard delivery includes two corrugated hoses with suitable insulation and a cover plate for the connection area behind the heat pump.

AHP-FW 25-0.4

		AHP-FW 25-0.4
		NEW
Part number		**208863**
Specification		
Connection, heating and source side		G 1
Length	m	0,4
Colour		signal white, RAL 9003

AHP-TB



Benefits
- Telescopic duct for covering and protecting the wall outlet and supply lines from the weather
- Flexible use thanks to stepless length adjustment
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Telescopic duct for covering the heat pump connection pipes when laid straight to the rear. Available in two lengths for bridging wall clearances from 250 to 700 mm. • High quality weather protection and cover for the wall outlet. Can be attached both to the heat pump and to the house wall. Dark grey finish. • Can be combined with the AHP-WO.1 above-ground wall outlet.

AHP-TB 420

		AHP-TB 420	AHP-TB 710
		NEW	NEW
Part number		**207727**	**207728**
Specification			
Height	mm	240	240
Width	mm	229	229
Depth	mm	230 - 420	380 - 710
Min. installation length, cover	mm	230	380
Max. installation length, cover	mm	420	710
Colour		Dark grey RAL 7021	Dark grey RAL 7021

AHP-TW



Benefits
- Telescopic duct for covering and protecting the wall outlet and supply lines from the weather
- Flexible use thanks to stepless length adjustment
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Telescopic duct for covering the heat pump connection pipes when laid straight to the rear. Available in two lengths for bridging wall clearances from 250 to 700 mm. • High quality weather protection and cover for the wall outlet. Can be attached both to the heat pump and to the house wall. White finish. • Can be combined with the AHP-WO.1 above-ground wall outlet

AHP-TW 420

		AHP-TW 420	AHP-TW 710
		NEW	NEW
Part number		**207730**	**207710**
Specification			
Height	mm	240	240
Width	mm	229	229
Depth	mm	230 - 420	380 - 710
Min. installation length, cover	mm	230	380
Max. installation length, cover	mm	420	710
Colour		signal white, RAL 9003	signal white, RAL 9003

AHP-SB.1



AHP-SB.1

Benefits
- Cover for supply lines behind the heat pump if the connection lines are routed directly downwards
- Aesthetically high quality weather protection and cover in matching appliance colour
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Cover for the supply lines behind the heat pump. For use with floorstanding heat pumps with pipe routing behind the heat pump directly downwards.

		AHP-SB.1
		NEW
Part number		**207711**
Specification		
Height	mm	322
Width	mm	198
Depth	mm	236
Colour		Dark grey RAL 7021

AHP-SW


AHP-SW.1

Benefits
- Cover for supply lines behind the heat pump if the connection lines are routed directly downwards
- Aesthetically high quality weather protection and cover in matching appliance colour
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Cover for the supply lines behind the heat pump. For use with floorstanding heat pumps with pipe routing behind the heat pump directly downwards.

		AHP-SW.1
		NEW
Part number		**207712**
Specification		
Height	mm	322
Width	mm	198
Depth	mm	236
Colour		signal white, RAL 9003

AHP-WB.1-3



AHP-WB.1

Benefits
- Wind protection for a heat pump in wind-exposed locations
- Optimised for air source heat pumps with R290 refrigerant
- No wall is required behind the heat pump

Description • Wind protection for heat pump installations in open spaces and other locations exposed to wind, such as flat roof installations. Installation in front of a wall surface is therefore not necessary. • The wind protection is attached to the heat pump.

		AHP-WB.1	AHP-WB.2	AHP-WB.3
		NEW	NEW	NEW
Part number		**207713**	**208679**	**208680**
Specification				
Height	mm	780	964	1185
Width	mm	803	803	803
Depth	mm	274	274	274
Weight	kg	11	13	15
Colour		Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021

AHP-WW

AHP-WW.1

Benefits
- Wind protection for a heat pump in wind-exposed locations
- Optimised for air source heat pumps with R290 refrigerant
- No wall is required behind the heat pump

Description • Wind protection for heat pump installations in open spaces and other locations exposed to wind, such as flat roof installations. Installation in front of a wall surface is therefore not necessary. • The wind protection is attached to the heat pump.

		AHP-WW.1	AHP-WW.2	AHP-WW.3
		NEW	NEW	NEW
Part number		**208658**	**208681**	**208682**
Specification				
Height	mm	780	964	1185
Width	mm	803	803	803
Depth	mm	274	274	274
Weight	kg	11	13	15
Colour		signal white, RAL 9003	signal white, RAL 9003	signal white, RAL 9003

AHP-WO.1



Benefits
- Wall outlet for easy installation of the connection lines of an air source heat pump with R290 refrigerant
- Protection against splashed water, rain and the penetration of gases inside buildings
- For creating a high quality look with minimum outlay
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Wall outlet for above-ground supply and return lines and two empty conduits for the power supply. • Set consisting of 4 pairs of insulation semi-shells and two empty conduits including gas-tight rubber end caps. Create an above-ground wall outlet quickly, by drilling 4 holes with a 50 mm diameter and pressing the covers into the gap between the house wall and the pipe. • Can be combined with the AHP-TB telescopic duct with straight pipe routing behind the heat pump.

AHP-WO.1

		AHP-WO.1
		NEW
Part number		**207715**
Specification		
Application		Heat pump

AHP-WU.1



Benefits
- Suitable for new build and modernisation projects
- Can be combined with KG/HT pipe DN200
- For integration in black waterproofing
- Water pressure-tight up to 1.5 bar

Description • Wall outlet for underground supply and return lines of heat pumps installed outdoors with black waterproofing. Also with two empty conduits for the power supply. • Set consists of a 0.5 metre DN200 pipe with pressure-resistant solid wall material, single sided plug-in sleeve with foil flange and a permanently elastic and highly adhesive PU sealant that can also be used on damp surfaces. • Water pressure-tight up to 1.5 bar. Suitable for integration into black waterproofing („black tank“) with bitumen and reactive waterproofing, welded membrane, concrete and masonry.

AHP-WU.1

		AHP-WU.1
		NEW
Part number		**207716**
Specification		
Length	mm	590
Diameter	mm	200
Application		Connection system
Required accessories		
Part number		**207718**
Type		AWU-HS 2.5
Description		Hose assembly
Part number		**207719**
Type		AWU-HS 5
Description		Hose assembly

next page >

		AHP-WU.1
Part number		**207720**
Type		AWU-HS 10
Description		Hose assembly
Recommended accessories		
Part number		**207721**
Type		AHS-SI 200
Description		Sealing insert for combination with the hose assemblies

AHP-WU.2




AHP-WU.2

Benefits
- Suitable for new build and modernisation projects
- Can be combined with KG/HT pipe DN200
- For embedding in waterproof concrete or in pipe liners set in concrete
- Water pressure-tight up to 3 bar

Description • Wall outlet for underground supply and return pipes for heat pumps installed outdoors with concrete walls („white tank“) or pipe liners set in concrete. Also with two empty conduits for the power supply. • With sealing insert for combination with KG/HT pipe DN200. Suitable for core holes or pipe liners with an inner diameter of 250 mm. • Easy installation thanks to torque control via the nuts. Closure of the annular space between the KG/HT pipe and bore/pipe liner. • Water pressure-tight up to 3 bar.

		AHP-WU.2
		NEW
Part number		**207717**
Specification		
Length	mm	80
Diameter	mm	250
Application		Connection system
Required accessories		
Part number		**207718**
Type		AWU-HS 2.5
Description		Hose assembly
Part number		**207719**
Type		AWU-HS 5
Description		Hose assembly
Part number		**207720**
Type		AWU-HS 10
Description		Hose assembly
Recommended accessories		
Part number		**207721**
Type		AHS-SI 200
Description		Sealing insert for combination with the hose assemblies

AWU-HS




Benefits
- Suitable for new build and modernisation projects
- Can be combined with freely routed KG/HT pipe DN200
- Easy insertion thanks to friction-optimised casing

Description • Hose assembly consisting of supply and return line made of trimmable corrugated stainless steel pipe for connecting heat pumps installed outdoors. Also with two empty conduits for the power supply. • Optimised for use in KG/HT pipe DN200. Retrospective insertion into pipes with 3x 45° bends is simple. High quality insulation made of weather- and UV-resistant EPDM. • Ideally suited for combination with the underground wall outlets and the sealing package.

AWU-HS 2.5

		AWU-HS 2.5	AWU-HS 5	AWU-HS 10
		NEW	NEW	NEW
Part number		**207718**	**207719**	**207720**
Specification				
For pressure hose size DN		25	25	25
Length	m	2,5	5	10
Thermal insulation thickness	mm	100	100	100
External diameter incl. insulation	mm	320	320	320
Required accessories				
Part number		**207716**	**207716**	**207716**
Type		AHP-WU.1	AHP-WU.1	AHP-WU.1
Description		Wall outlet	Wall outlet	Wall outlet
Part number		**207717**	**207717**	**207717**
Type		AHP-WU.2	AHP-WU.2	AHP-WU.2
Description		Wall outlet	Wall outlet	Wall outlet
Recommended accessories				
Part number		**207721**	**207721**	**207721**
Type		AHS-SI 200	AHS-SI 200	AHS-SI 200
Description		Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies	Sealing insert for combination with the hose assemblies

AHS-SI 200



Benefits
- Suitable for new build and modernisation projects
- Secure sealing against gas and water in outdoor areas
- Air exchange in the KG/HT pipe prevented to avoid condensate formation

Description • Sealing insert for combination with the AWU-HS hose assemblies in KG/HT pipe. The set consists of sealing inserts optimised for the 4 pipes in the hose assembly. • Retrospective installation is also possible thanks to the split sealing surface. Easy installation thanks to torque control via the nuts. • Reliably prevents the ingress of water, gas and animals, for example, through the installed KG/HT pipe in outdoor areas. • The gasket on the inside prevents air exchange for the avoidance of condensation.

AHS-SI 200

		AHS-SI 200
		NEW
Part number		**207721**
Specification		
Length	mm	65
Diameter	mm	191
Application		Connection system
Recommended accessories		
Part number		**207716**
Type		AHP-WU.1
Description		Wall outlet
Part number		**207717**
Type		AHP-WU.2
Description		Wall outlet
Part number		**207718**
Type		AWU-HS 2.5
Description		Hose assembly
Part number		**207719**
Type		AWU-HS 5
Description		Hose assembly
Part number		**207720**
Type		AWU-HS 10
Description		Hose assembly

AHP-CM 2-6



AHP-CM 2

Benefits
- Cascade module for air source heat pumps installed outdoors with R290 refrigerant
- Simplified and minimised opening through the building envelope
- Reduced effort during design and installation

Description • Cascade module for air source heat pump cascades installed outdoors. Designed as a flow and return collector installed outdoors for clear and simple routing of supply and return lines into the building with only 2 pipes. This reduces the effort required for installation and keeps the wall outlet as small as possible. • All-in-one design in keeping with the heat pump aesthetic for a harmonious overall system look. This cascade module is the ideal addition to cascades of the latest generation heat pumps.

		AHP-CM 2	AHP-CM 3	AHP-CM 4	AHP-CM 5	AHP-CM 6
		NEW	NEW	NEW	NEW	NEW
Part number		**208660**	**208040**	**208009**	**208010**	**208011**
Specification						
Max. permissible pressure	MPa	0.30	0.30	0.30	0.30	0.30
Min. application limit on heating side	°C	7	7	7	7	7
Max. application limit on the heating side	°C	75	75	75	75	75
Max. permissible flow rate, heat pump	m³/h	3	3	3	3	3
Max. permissible flow rate, heating side	m³/h	18	18	18	18	18
Frequency	Hz	50	50	50	50	50
Rated voltage, control unit	V	230	230	230	230	230
Phases, control unit		1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Control unit fuse protection	A	1 x B16	1 x B16	1 x B16	1 x B16	1 x B16
Power consumption	W		261	348	435	522
Power consumption, circulation pump	W	87	87	87	87	87
Circulation pump type		2x Para 25-180/9-87	3x Para 25-180/9-87	4x Para 25-180/9-87	5x Para 25-180/9-87	6x Para 25-180/9-87
IP rating		IP14B	IP14B	IP14B	IP14B	IP14B
Height	mm	1365	1365	1365	1365	1365
Width	mm	1170	1170	1170	1170	1170
Depth	mm	727	727	727	727	727
Weight	kg	135	145	150	155	160
Connection		DN 32	DN 32	DN 32	DN 32	DN 32
Connection, heating flow/return		DN65	DN65	DN65	DN65	DN65
Connection type		Permanent connection	Permanent connection	Permanent connection	Permanent connection	Permanent connection
Suitable for		outside	outside	outside	outside	outside

AHP-CS




Description • For the safe transport of heavy STIEBEL ELTRON appliances. Thanks to the crossover lifting straps, two people can lift heavy appliances ergonomically and effortlessly. • Particularly suitable for transporting heat pumps and indoor units – even in confined spaces. The appliances can be held upright and moved close to the ground.

AHP-CS.1

		AHP-CS.1
		NEW
Part number		**207723**
Specification		
Weight load	kg	600

AS WP



Benefits
- Hydraulic connection set
- White painted cover

Description • The connection set for supply lines from the ground is supplied with a painted cover that protects against the elements.

AS-WP 1

		AS-WP 1	AS-WP 2
Part number		**233622**	**233623**
Specification			
Connection		32 x 2.9 mm	G 1 1/4

WK




Benefits
› Includes ribbon heater to keep condensate connection free from frost (Product: 234722)

Description • The wall mounting brackets are made of corrosion-protected, zinc-plated steel. • Height-adjustable wall rails; the heat pump can be aligned with the aid of these appliance rails. • The set consists of two wall mounting brackets, which are supplied including anti-vibration mounts.

WK 2

		WK 2
Part number		**234722**
Specification		
Support length	mm	900
Weight	kg	13.4
Weight load	kg	200
Version		Wall mounting bracket
Application		Heat pump
Adjustable slope		-
Quantity		2
Heated length	mm	2000
Connecting of connecting cable	mm	2000

WK 1.1



Benefits
› 2 wall mounting brackets for installing a heat pump including anti-vibration mounts
› Weight load max. 120 kg
› Support length: 750 mm
› Corrosion protection thanks to zinc-plated steel

Description • The wall mounting brackets are made of corrosion-protected, zinc-plated steel. • Height-adjustable wall rails; the heat pump can be aligned with the aid of these appliance rails. • The set consists of two wall mounting brackets, which are supplied including anti-vibration mounts.

WK 1.1

		WK 1.1
Part number		**238686**
Specification		
Support length	mm	750
Weight	kg	8.5
Weight load	kg	120
Version		Wall mounting bracket
Application		Heat pump
Adjustable slope		-
Quantity		2

next page >

SK 1



Benefits
- T-support for heat pumps
- Set with 2 robust brackets
- Load bearing capacity 175 kg each

Description • The stainless steel support in a T-shape for outdoor installation is set in concrete. • The set comprises two supports including anti-vibration mounts and a self-limiting heating cable to keep the condensate pipework frost-free. • An installation aid for a defined clearance dimension is also supplied.

SK 1

		SK 1
Part number		**232964**
Specification		
Height	mm	950
Weight load	kg	175
Version		T-support
Application		Heat pump
Adjustable slope		-
Quantity		2
Heated length	mm	1000
Connecting of connecting cable	mm	2000

SK 2



Benefits
- Set with 2 robust brackets
- Powder coated in white
- Height: 303 mm, width: 450 mm

Description • The powder coated bracket allows the heat pump to be secured to a strip foundation. • The set consists of two supports incl. the screws for securing the heat pump.

SK 2

		SK 2
Part number		**236693**
Specification		
Height	mm	303
Width	mm	450
Weight load	kg	91

Standard delivery includes: 2 pce, incl. screws for securing the heat pump to the bracket.

HZB-1/2



Benefits
- Robust ribbon heater
- Zinc-plated copper wires as earth conductors
- Full-surface protective aluminium jacket

Description • The heating cable keeps the condensate drain of air source heat pumps frost-free. Self-limiting and flexible. • Two copper wires serve as the supply cable. • The outer sheath is made of UV and moisture-resistant TPE-O. • Available as HZB-1 (length: 1 m) and HZB-2 (length: 2 m).

HZB-1

		HZB-1	HZB-2
Part number		**232978**	**232979**
Specification			
Rated output per metre at 10 °C outdoor air temperature	W	10	10
Heated length	mm	1000	2000
Rated voltage	V	230	230
Power supply		1/N/PE	1/N/PE
Min. handling/installation temperature	°C	-45	-45
Max. ambient temperature	°C	65	65
Min. bending radius	cm	2.50	2.50

ZVK-WPL A



Benefits
- Complete set for a heat pump located outdoors
- Colour: white

Description • The corrosion-protected sheet metal casing for outdoor air source heat pumps is made of hot-dip galvanised and powder coated sheet steel.

ZVK WPL 13/18/23 A


		ZVK WPL 13/18/23 A
Part number		**074413**
Specification		
Height	mm	750
Width	mm	1350
Depth	mm	1350
Weight	kg	150
Colour		white


Application areas

Heating


Cooling











Air source heat pumps, indoor installation – inverter

Inverter

WPL ICS classic 254
WPL 19/24 I 258
WPL 19/24 IK 262

WPL ICS classic



WPL 17 ICS classic

Benefits

- Heating and cooling of new builds with an air source heat pump installed indoors.
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Suitable for densely built-up areas, as it is installed indoors and so produces virtually no sound emissions outdoors
- Straightforward connection: air hoses with quick-fit adaptors reduce installation effort
- Improved room climate in summer with active cooling using circuit reversal
- Easy and time saving installation with high level of integration
- Can be integrated into the home network and operated via a smartphone

Application • This air source heat pump with output-dependent control and inverter technology is installed indoors. The system is suitable for heating and DHW operation, but can also be used for efficient cooling through circuit reversal. The heat pump is used in new build or buildings with a low system temperature.

Convenience features • Very quiet operation is made possible by the encapsulated refrigerant circuit and acoustically isolated compressor. • The integral heat pump manager provides fully automatic control of the heating system with weather compensation. • In combination with the optional Internet Service Gateway, the system can be controlled in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • The integral circulation pump is controlled automatically with reference to the flow and return temperatures. • The following components are integrated as standard: the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the diverter valve for DHW heating and the safety valve with drain pipe. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R410A.

Efficiency • To raise the return temperature, the waste heat from the inverter is used, which increases the overall efficiency of the system. Demand-dependent, energy efficient defrosting through circuit reversal.

Installation • Thanks to the integral anti-vibration mount, the heat pump can be connected directly to the heating system. • As the flexible air hoses are preassembled and equipped with quick-fit adaptors, installation work is simplified. The air hoses are connected at the top of the appliance; manual trimming or sealing is not necessary.






		WPL 17 ICS classic
Part number		**236376**
Specification		
Energy efficiency class, heat pump W35 A+++ -> D		A++
Energy efficiency class, heat pump W55 A+++ -> D		A++
Heating output at A7/W35 (EN 14511)	kW	4.27
Heating output at A2/W35 (EN 14511)	kW	5.02
Heating output at A-7/W35 (EN 14511)	kW	8.02
COP at A7/W35 (EN 14511)		4.74
COP at A2/W35 (EN 14511)		3.83
COP at A-7/W35 (EN 14511)		2.63
Cooling capacity at A35/W18 partial load (EN 14511)	kW	3.60
Max. cooling capacity at A35/W18	kW	6.00
Energy efficiency ratio at A35/W18 partial load (EN 14511)		2.78
Energy efficiency ratio at A35/W18 max.		1.83
SCOP 35 °C (EN 14825)		4.25
Sound power level (EN 12102)	dB(A)	51
Min./max. application limits for heat source	°C	-20/35

next page >

		WPL 17 ICS classic
Max. application limit on the heating side	°C	60
Height	mm	1381
Width	mm	874
Depth	mm	874
Weight	kg	175
Refrigerant		R410A
Required accessories		
Part number		**205786**
Type		AWG 315 SR.2
Description		Thermally insulated external wall air outlet
Part number		**238565**
Type		LSWP 315-2 SG Set
Description		Thermally insulated air hose with 2 EPS quick-fit adaptors
Recommended accessories		
Part number		**229336**
Type		ISG web
Description		Internet Service Gateway
DHW cylinder		
Part number		**221360**
Type		SBB 301 WP
Description		DHW cylinder
Part number		**229981**
Type		SBS 801 W
Description		Instantaneous water cylinder
Part number		**236684**
Type		HSBC 200 L
Description		Integral cylinder
Part number		**238826**
Type		HSBC 300 L cool
Description		Integral cylinder
Buffer cylinder		
Part number		**205295**
Type		SBP 200 Plus cool
Description		Buffer cylinder suitable for cooling operation


The air routing accessories required for the air intake/air discharge are available in various lengths under accessories.

Inverter




		WPL 17 ICS classic
b01 Entry electrical cables		•
d44 Outlet condensate drain - diameter	mm	22
e01 Heating flow - diameter	mm	22
e02 Heating return - diameter	mm	22
g01 Air intake - nominal diameter		DN 315
g02 Air discharge - nominal diameter		DN 315

Minimum clearance diagram



WPL 19/24 I



WPL 19 I Set

Benefits

- The air source heat pump is suitable for heating older buildings
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Even at low outside temperatures, the enhanced vapour injection/enhanced saturated vapour injection of the heat pump achieves a high flow temperature
- Optimised for replacement of 13/18/23 E air source heat pumps that are installed indoors
- Because of the high flow temperature all year round, also suitable for modernisation projects and for DHW heating
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Can be integrated into the home network and operated via a smartphone
- Low operating costs as mono mode DHW heating is possible
- Suitable for densely built-up areas, as it is installed indoors and so produces virtually no sound emissions outdoors

Application • This air source heat pump with output-dependent control and inverter technology is installed indoors. Due to the low noise emissions, the appliance is also suitable for densely built-up areas. The heat pump can be used in modernisation projects as flow temperatures of up to 65 °C are available all year round for room heating and DHW heating.

Convenience features • Very quiet operation is ensured by the encapsulated refrigerant circuit and acoustically isolated compressor. The modulating fan and the wide gaps between the evaporator fins, which create low air resistance, also help to minimise the sound power level. • With integral heat and electricity metering via refrigerant circuit data. • Mono energetic operation is possible with the electric emergency/auxiliary heater. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.

Efficiency • The heat pump delivers high flow temperatures all year round according to demand, as the combined enhanced vapour injection/enhanced saturated vapour injection cools the scroll compressor at low outside temperatures. This allows operation without an electric emergency/auxiliary heater. • The waste heat from the inverter is used to raise the return temperature, which increases the overall efficiency of the system. This is further aided by demand-dependent defrosting through circuit reversal and heating of the condensate pan by the refrigerant circuit.


Installation • The heat pump, with integral anti-vibration mounts, is directly connected to the heating system.

		WPL 19 I Set	WPL 24 I Set
Part number		**235193**	**235194**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++
Heating output at A7/W35 (EN 14511)	kW	6.70	7.41
Heating output at A2/W35 (EN 14511)	kW	7.41	9.04
Heating output at A-7/W35 (EN 14511)	kW	9.91	13.45
COP at A7/W35 (EN 14511)		4.99	4.72
COP at A2/W35 (EN 14511)		4.12	4.00
COP at A-7/W35 (EN 14511)		3.32	3.00
SCOP 35 °C (EN 14825)		4.44	4.45
Sound power level (EN 12102)	dB(A)	54	54
Min./max. application limits for heat source	°C	-20/40	-20/40
Max. application limit on the heating side	°C	65	65
Height	mm	1182	1182
Width	mm	800	800
Depth	mm	1240	1240

next page >


		WPL 19 I Set	WPL 24 I Set
Weight	kg	289	289
Weight (standard appliance)	kg	201	201
Refrigerant		R410A	R410A
SCOP 55 °C (EN 14825)	°C	3.64	3.53
Required accessories			
Part number		**233837**	**233837**
Type		AWG 560 H-SR	AWG 560 H-SR
Description		External wall outlet, thermally insulated	External wall outlet, thermally insulated
Part number		**234647**	**234647**
Type		LSWP 560-4 S	LSWP 560-4 S
Description		Thermally and sound insulated air hose	Thermally and sound insulated air hose
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
Part number		**232805**	**232805**
Type		HM Trend	HM Trend
Description		Hydraulic module	Hydraulic module
Part number		**233826**	**233826**
Type		HMS Trend	HMS Trend
Description		Hydraulic module	Hydraulic module
DHW cylinder			
Part number		**203801**	**203801**
Type		HSBC 300 cool	HSBC 300 cool
Description		Integral cylinder	Integral cylinder
Part number		**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder
Part number		**229981**	**229981**
Type		SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Part number		**233510**	**233510**
Type		HSBC 200	HSBC 200
Description		Integral cylinder	Integral cylinder
Part number		**234801**	**234801**
Type		HSBC 200 S	HSBC 200 S
Description		Integral cylinder	Integral cylinder

Wall outlets must be ordered separately and are available as accessories in various versions.
The air hoses required are available as accessories.



		WPL 19 I Set	WPL 24 I Set
b01 Entry electrical cables		•	•
d44 Outlet condensate drain		•	•
e01 Heating flow - diameter	mm	28	28
e02 Heating return - diameter	mm	28	28
g01 Air intake		•	•
g02 Air discharge		•	•

Minimum clearance diagram



WPL 19/24 IK



WPL 19 IK Set

Benefits

- The air source heat pump is suitable for heating older buildings
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Even at low outside temperatures, the enhanced vapour injection/enhanced saturated vapour injection of the heat pump achieves a high flow temperature
- Because of the high flow temperature all year round, also suitable for modernisation projects and for DHW heating
- Quiet operation thanks to encapsulated refrigerant circuit and variable matched fan speed
- Low operating costs as mono mode DHW heating is possible
- Can be integrated into the home network and operated via a smartphone
- Suitable for densely built-up areas, as it is installed indoors and so produces virtually no sound emissions outdoors

Application • This output-controlled air source heat pump with inverter technology is installed indoors and is also suitable for densely built-up areas due to its low noise emissions. Can be used for modernisation, since it provides a flow temperature of up to 65 °C all year round for heating operation and DHW heating.

Convenience features • Very quiet operation due to the encapsulated refrigerant circuit and acoustically isolated compressor. The modulating fan and the wide gaps between the evaporator fins, which create low air resistance, also help to minimise the sound power level. • With integral heat and electricity metering via refrigerant circuit data. • Mono energetic operation possible with emergency/auxiliary heater. • The metal casing is corrosion-protected. It is made from hot-dip galvanised, powder coated sheet steel, with an alpine white stove enamel finish.

Efficiency • High flow temperature all year round according to demand, as the combined enhanced vapour injection/enhanced saturated vapour injection cools the scroll compressor at low outside temperatures. This allows operation without an auxiliary heater. • The waste heat from the inverter is used to raise the return temperature. In addition, the overall efficiency of the system is increased by on-demand defrosting through circuit reversal and heating of the condensate pan by the refrigerant circuit. • The hydrophilic coating on the fan nozzle prevents ice from forming, meaning that no electric heating is required.

Installation • The heat pump, with integral anti-vibration mounts, is directly connected to the heating system. • Quick corner installation thanks to the supplied compact air handling module WPIC with pre-installed air hoses on the air intake and discharge, controller and hydraulic components.





		WPL 19 IK Set	WPL 24 IK Set
Part number		**235878**	**235879**
Specification			
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++
Heating output at A7/W35 (EN 14511)	kW	6.70	7.41
Heating output at A2/W35 (EN 14511)	kW	7.41	9.04
Heating output at A-7/W35 (EN 14511)	kW	9.91	13.45
COP at A7/W35 (EN 14511)		4.99	4.72
COP at A2/W35 (EN 14511)		4.12	4.00
COP at A-7/W35 (EN 14511)		3.32	3.00
SCOP 35 °C (EN 14825)		4.44	4.45
Sound power level (EN 12102)	dB(A)	52	51
Min./max. application limits for heat source	°C	-20/40	-20/40
Max. application limit on the heating side	°C	65	65
Height	mm	1820	1820
Width	mm	800	800
Depth	mm	1240	1240


next page >

		WPL 19 IK Set	WPL 24 IK Set
Weight	kg	373	373
Weight (standard appliance)	kg	201	201
Weight (compact air handling module)	kg	80	80
Refrigerant		R410A	R410A
SCOP 55 °C (EN 14825)	°C	3.64	3.53
Required accessories			
Part number		**233837**	**233837**
Type		AWG 560 H-SR	AWG 560 H-SR
Description		External wall outlet, thermally insulated	External wall outlet, thermally insulated
Recommended accessories			
Part number		**229336**	**229336**
Type		ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway
DHW cylinder			
Part number		**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder
Part number		**229981**	**229981**
Type		SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder
Part number		**238826**	**238826**
Type		HSBC 300 L cool	HSBC 300 L cool
Description		Integral cylinder	Integral cylinder

Standard delivery includes: air handling module WPIC


Wall outlets must be ordered separately and are available as accessories in various versions. Wall outlets must be ordered separately and are available as accessories in various versions. (Product: 235878, 235879)

Inverter



		WPL 19 IK Set	WPL 24 IK Set
b01 Entry electrical cables		•	•
c11 Safety assembly		•	•
e01 Heating flow - male thread		G 1 1/4 A	G 1 1/4 A
e02 Heating return - male thread		G 1 1/4 A	G 1 1/4 A
e22 Cylinder flow - male thread		G 1 1/4 A	G 1 1/4 A
e23 Cylinder return - male thread		G 1 1/4 A	G 1 1/4 A
g01 Air intake		•	•
g02 Air discharge		•	•

Minimum clearance diagram



Accessories
Accessories 268

ZSA



Benefits
- Quick-fit adaptor for air hoses
- Straightforward connection to the heat pump
- Standard delivery: quick-fit adaptor, fixing screws, hose clips

Description • The quick-fit adaptor made of EPS is used to install air hoses on the air connections of the unit.

ZSA 315

		ZSA 315
Part number		**236934**
Specification		
Length	mm	150.00
Nominal diameter	mm	315
Version		Quick-fit adaptor

Standard delivery includes: quick-fit adaptor, fixing screws, hose clips for the internal and external hose.

AWG WP




Benefits
- Condensate run marks on the wall face are prevented by a wide drip edge on the frame
- Integral rodent guard prevents small animals and leaves getting in
- Good protection from weather and low pressure losses, thanks to optimised fin geometry

Description • The thermally insulated wall outlet is suitable for routing the air ducts of indoor air source heat pumps and integral systems. • The length can be adjusted to suit the wall thickness thanks to telescopic technology.

AWG 560 H-SR

		AWG 560 H-SR	AWG 560 H-GL
Part number		**233837**	**232956**
Specification			
Height	mm	490	490
Width	mm	897	897
Depth	mm	627	627
Nominal diameter	mm	560	560
Wall thickness	mm	280 - 500	280 - 500
Min. outlet aperture	mm	830x430	830x430
Max. air flow rate	m³/h	3500	3500
Colour		silver-metallic	RAL 9006
Material		Sheet steel	Sheet steel
Version		Horizontal weather grille painted in metallic silver	Horizontal with grey painted weather grille

LLB AWG



Benefits
› Quick and easy to install


Description • The aluminium air deflector is installed in a light well to deflect the exhaust air from the building away from the external wall. This reduces the formation of moisture from condensation. • The width of the air deflector can be adjusted to the light well.

LLB AWG 315 L

		LLB AWG 315 L	LLB AWG 560 L
Part number		**232341**	**232342**
Specification			
Height	mm	128	128
Length	mm	900	1,500
Colour		Aluminium	Aluminium

6

SAPL



Description • The thermally insulated SAPL hose connecting plate is mounted on standard basement windows. • The standard delivery includes a collar and hose clips to join the hose to the hose connecting plate.

SAP-O DN 560

		SAP-O DN 560
Part number		**003478**
Specification		
Height	mm	780
Width	mm	1200
Air connection	mm	560

LSWP




Benefits
- Good sound insulation thanks to a 50 mm layer of acoustic insulating material
- Prevents condensation forming on the outer cover

Description • The thermally and sound insulated flexible air hose is suitable for routing the outdoor and exhaust air to/from an air source heat pump installed indoors. • The outside is made of aluminium laminate and the inside of polypropylene cloth. The intermediate layer, made of mineral wool, provides sound and thermal insulation. The hose ends can be shaped into ovals for easier fitting.

LSWP 560-3 SG

		LSWP 560-3 SG	LSWP 560-4 S
Part number		**201721**	**234647**
Specification			
Nominal diameter	mm	560	560
Length	mm	3000	4000
Thermal insulation thickness	mm	50	50
Colour of air hose		Grey outer sheath	Aluminium-coloured outer sheath

LSWP 315 SG Set



Benefits
- Flexible air hose with quick-fit adaptor
- For connection of outdoor and exhaust air with air source heat pumps
- Sound absorbent and thermal insulating covering
- Quick and straightforward installation

Description • This flexible air hose for outdoor and exhaust air ducting is heat and sound insulated. • Easy connection to the AWG or WPL thanks to the prefitted quick-fit adaptors. • The hose is covered with a sound absorbing, thermal insulation layer. The outside is made of aluminium laminate and the inside of polypropylene cloth. The intermediate layer, made of mineral wool, provides sound and thermal insulation. • A quick-fit adaptor made of EPS is ready mounted and sealed at both ends.

LSWP 315-2 SG Set

		LSWP 315-2 SG Set
Part number		**238565**
Specification		
Nominal diameter	mm	315
Length	mm	2000
Thermal insulation thickness	mm	50
Colour of air hose		grey

PK 10



Benefits
- Condensate pump with overheating protection and automatic restart
- For wall or ceiling mounting if the fall for the condensate drain is not sufficient
- Alarm contact as either N/C or N/O contact

Description • The condensate pump for indoor heat pumps and ventilation units has an integral condensate container. The appliance can be installed horizontally on the floor or on the wall. • The integral alarm contact can be used to activate an indicator lamp or warning tone, or to switch the connected main appliance. An additional float prevents the collecting vessel from overflowing. • Pressure hose and power cable are included in the standard delivery.

PK 10

		PK 10
Part number		**229286**
Specification		
Max. delivery volume	l/h	500
Max. delivery head	m	5
Height	mm	171
Width	mm	279
Depth	mm	130
Weight	kg	2
Electrical connection		1/N/PE~230 V
Power consumption	W	70

5 m pressure hose, power cable and alarm connection cable (Product: 229286)

ZVK-WPL I



Benefits
- Complete set for a heat pump located outdoors
- Colour: white

Description • The corrosion-protected sheet metal casing for indoor air source heat pumps is made of hot-dip galvanised and powder coated sheet steel.

ZVK WPL 13/18/23 I

		ZVK WPL 13/18/23 I
Part number		**074412**
Specification		
Height	mm	1182
Width	mm	1240
Depth	mm	800
Weight	kg	85
Colour		white

Ground source heat pumps – inverter 277

Ground source heat pumps – Fixspeed 307


Accessories for ground source heat pumps 319


Application areas




Heating

Cooling
















Application areas














Application areas

Inverter

HPG-I 04-15 DS Premium	278
HPG-I 04-15 DCS Premium	282
WPE-I 07.1-12.1 Plus HW (400)	286
WPE-I 07.1-17.1 Plus H (230)	289
HPG-I 04-15 CS Premium	293
HPG-I 04-15 S Premium	297
WPE-I 33-87 H 400 Premium	301

HPG-I 04-15 DS Premium



HPG-I 04 DS Premium

Benefits

- High hot water convenience and mono mode heating thanks to high flow temperatures of up to 75 °C
- Pressure monitoring in the heat source circuit with integral brine pressure switch
- Quick, space saving installation thanks to built-in DHW cylinder and high level of integration
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Very quiet operation thanks to the intelligent sound prevention concept including a number of anti-vibration mounts
- Futureproof and eco-friendly refrigerant with high efficiency
- Easy to transport as the refrigerant circuit and cylinder module can be separated from one another and are fitted with integral carrying handles

Application • This compact ground source heat pump with output-dependent control and inverter technology is installed indoors. • The appliance is equipped with an integral DHW cylinder. • The DHW cylinder is built into the casing and ready for operation. • Can be used in mono mode to provide heating and DHW in new and modernised buildings thanks to demand-dependent flow temperatures all year round. The system is also suitable for apartment buildings, depending on the heat load of the building. • A high level of integration enables the heat pump to be installed directly, requiring a small installation area thanks to the compact design.

Convenience features • Heat pump operation is particularly quiet due to the encapsulated refrigerant circuit and acoustically isolated compressor. • The high flow temperature of up to 75 °C as a heating output is ensured by the consistent source temperature. • If the on-site heat pump controller is combined with the Internet Service Gateway, the system can be integrated into a smart home network and controlled via a mobile device. • Heat and electricity metering via integral refrigerant circuit data. • Control of the heating system is fully automatic and subject to the outside temperature. • One high efficiency circulation pump is built in for the brine side and one for the heating side. • Also integrated as standard are an electric emergency/auxiliary heater for mono energetic operation, a pasteurisation heat-up function, the diverter valve for DHW heating and a safety valve with drain pipe. • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R454C, which has excellent properties in heat pump application. • The corrosion-protected casing is made from hot-dip galvanised, powder coated sheet steel.

Efficiency • Thanks to the energy saving inverter technology and integral recuperator, the heat pump works extremely efficiently all year round.


Installation • No special safety precautions are required when siting. The installation room must be of a minimum size. • Straightforward to install as the refrigerant circuit can be easily separated from the cylinder module. Both parts also have integral carrying handles. • The internal pressure hoses enable simple direct hydraulic connection to the heating and source side.

		HPG-I 04 DS Premium	HPG-I 06 DS Premium	HPG-I 08 DS Premium	HPG-I 12 DS Premium	HPG-I 15 DS Premium
Part number		**202622**	**202623**	**202624**	**202625**	**202626**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	1,96	2,37	2,78	4,19	5,18
Cylinder volume V	l	175	175	175	162	162
Heating output at B0/W35 (min./max.)	kW	1,0-4,2	1,0-6,6	1,0-7,6	2,1-12,7	2,1-14,8
COP at B0/W35 (EN 14511)		4.60	4.60	4.67	5.01	4.86
SCOP 35 °C (EN 14825)		5.07	5.20	5.12	5.59	5.44
Sound power level (EN 12102)	dB(A)	43-46	43-48	43-48	43-49	43-49
Height	mm	1937	1937	1937	1937	1937
Width	mm	600	600	600	600	600
Depth	mm	703	703	703	703	703
Nominal capacity	l	175	175	175	162	162
Weight	kg	265	265	265	275	275
Rated voltage, compressor	V	230	230	230	230	230
Rated voltage, emergency/auxiliary heater	V	230	230	230	230	230

next page >


		HPG-I 04 DS Premium	HPG-I 06 DS Premium	HPG-I 08 DS Premium	HPG-I 12 DS Premium	HPG-I 15 DS Premium
Refrigerant		R454C	R454C	R454C	R454C	R454C
Surface area, heat exchanger	m²	2.10	2.10	2.10	3.50	3.50
Energy efficiency class, DHW heating with load profile XL A+ -> F		A	A	A	A	A
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit

Inverter


f02
e01
c01
f01
e02
c06
1940
719
20-40
600
401
c12
b01
c10
1600
1154
499
429
359
289
174
104
D0000094961.ai

		HPG-I 04 DS Premium	HPG-I 06 DS Premium	HPG-I 08 DS Premium	HPG-I 12 DS Premium	HPG-I 15 DS Premium
b01 Entry electrical cables		•	•	•	•	•
c01 Cold water inlet - diameter	mm	22	22	22	22	22
c06 DHW outlet - diameter	mm	22	22	22	22	22
c10 DHW circulation		•	•	•	•	•
c12 Safety valve drain		•	•	•	•	•
e01 Heating flow - diameter	mm	22	22	22	22	22
e02 Heating return - diameter	mm	22	22	22	22	22
f01 Heat source flow - diameter	mm	28	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28	28

Minimum clearance diagram



HPG-I 04-15 DCS Premium



HPG-I 04 DCS Premium

Benefits

- High hot water convenience and mono mode heating thanks to high flow temperatures of up to 75 °C
- Pressure monitoring in the heat source circuit with integral brine pressure switch
- Passive cooling function with minimal operating costs via a geothermal probe system
- Quick, space saving installation thanks to built-in DHW cylinder and high level of integration
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Very quiet operation thanks to the intelligent sound prevention concept including a number of anti-vibration mounts
- Futureproof and eco-friendly refrigerant with high efficiency
- Easy to transport as the refrigerant circuit and cylinder module can be separated from one another and are fitted with integral carrying handles

Application • This compact ground source heat pump with output-dependent control and inverter technology is installed indoors. It can be installed directly thanks to the high level of integration. • The DHW cylinder is built into the casing and ready for operation, as is the heat exchanger for energy efficient passive cooling via an area heating system. • Can be used in mono mode for heating and DHW operation in both new and modernised buildings thanks to high flow temperatures. • The system is also suitable for apartment buildings, depending on the heat load of the building. • Does not take up much space thanks to small installation area.

Convenience features • Very quiet operation is ensured by the encapsulated refrigerant circuit and acoustically isolated compressor. • The high flow temperature of up to 75 °C is ensured as a heating output all year round thanks to the consistent source temperature. • The integral heat pump controller ensures fully automatic control of the heating system regardless of the outside temperature. • The heat pump can be connected to the Internet Service Gateway and controlled via the home network or a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • One high efficiency circulation pump is built in for the brine side and one for the heating side. • Electric emergency/auxiliary heater for mono energetic operation and pasteurisation. • Diverter valve for DHW heating and safety valve with drain pipe. • The refrigerant circuit works with the eco-friendly, futureproof refrigerant R454C, which has excellent properties in heat pump application.

Efficiency • Thanks to the energy saving inverter technology and integral recuperator, the heat pump works very efficiently all year round.


Installation • No special safety precautions are required when siting. The installation room must be of a minimum size. • The supplied pressure hoses enable direct hydraulic connection to the heating side and source side. • The corrosion-protected casing is made from hot-dip galvanised, powder coated sheet steel. • To facilitate installation, the refrigerant circuit can be easily separated from the cylinder module, and both parts have integral carrying handles.

		HPG-I 04 DCS Premium	HPG-I 06 DCS Premium	HPG-I 08 DCS Premium	HPG-I 12 DCS Premium	HPG-I 15 DCS Premium
Part number		**202632**	**202633**	**202634**	**202635**	**202636**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	1,96	2,37	2,78	4,19	5,18
Cylinder volume V	l	175	175	175	162	162
Heating output at B0/W35 (min./max.)	kW	1,0-4,2	1,0-6,6	1,0-7,6	2,1-12,7	2,1-14,8
COP at B0/W35 (EN 14511)		4.60	4.60	4.67	5.01	4.86
Cooling capacity at B15/W23	kW	2.5	3	4	6	8
SCOP 35 °C (EN 14825)		5.07	5.20	5.12	5.59	5.44
Sound power level (EN 12102)	dB(A)	43-46	43-48	43-48	43-49	43-49
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	1937	1937	1937	1937	1937
Width	mm	600	600	600	600	600

next page >


		HPG-I 04 DCS Premium	HPG-I 06 DCS Premium	HPG-I 08 DCS Premium	HPG-I 12 DCS Premium	HPG-I 15 DCS Premium
Depth	mm	703	703	703	703	703
Nominal capacity	l	175	175	175	162	162
Weight	kg	265	265	265	275	275
Rated voltage, compressor	V	230	230	230	230	230
Rated voltage, emergency/auxiliary heater	V	230	230	230	230	230
Refrigerant		R454C	R454C	R454C	R454C	R454C
Surface area, heat exchanger	m²	2.10	2.10	2.10	3.50	3.50
Energy efficiency class, DHW heating with load profile XL A+ -> F		A	A	A	A	A
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit

Inverter


f02
e01
c01
f01
e02
c06
1940
719
20-40
600
401
c12
b01
c10
1600
1154
499
429
359
289
174
104
D0000094961.ai

		HPG-I 04 DCS Premium	HPG-I 06 DCS Premium	HPG-I 08 DCS Premium	HPG-I 12 DCS Premium	HPG-I 15 DCS Premium
b01 Entry electrical cables		•	•	•	•	•
c01 Cold water inlet - diameter	mm	22	22	22	22	22
c06 DHW outlet - diameter	mm	22	22	22	22	22
c10 DHW circulation		•	•	•	•	•
c12 Safety valve drain		•	•	•	•	•
e01 Heating flow - diameter	mm	22	22	22	22	22
e02 Heating return - diameter	mm	22	22	22	22	22
f01 Heat source flow - diameter	mm	28	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28	28

Minimum clearance diagram



WPE-I 07.1-12.1 Plus HW (400)



WPE-I 07.1 Plus HW 400

Benefits

- Ground source heat pump installed indoors with inverter technology for heating and DHW heating
- Natural, environmentally friendly and futureproof refrigerant R290
- Carefree operation with VDE-tested safety concept
- Integral low maintenance stainless steel DHW cylinder
- Active or passive cooling possible with additional components
- Minimal space requirement in the installation room thanks to integral safety valves, circulation pumps for brine and heating, diverter valve
- Optimisation according to dynamic electricity tariffs is possible
- Also suitable for modernisation projects thanks to 70 °C flow temperature
- Fast and accurate remote maintenance thanks to integration into Servicewelt

Application • This ground source heat pump with inverter technology and integral DHW cylinder is suitable for heating and optional cooling of family houses as well as for DHW heating. • Thanks to the high flow temperatures all year round, the heat pump can be used in both new build and modernisation. • The system uses the natural and futureproof refrigerant R290 for optimum environmental compatibility. • The heat pump can also be used for cooling with additional external components.

Convenience features • The heat pump in a design casing is installed indoors. • The low space requirement in the installation room is achieved by the high level of integration: The compact enclosure is equipped as standard with a controller and hydraulic components such as a diverter valve, circulation pumps (source and sink), electric emergency/auxiliary heater and safety valves (source and sink). A low-maintenance stainless steel DHW cylinder is also integrated. • Intuitive operation via the easy-to-read, colour touchscreen display. Control with mobile devices is also possible via the MyStiebel app. • The heat pump is very quiet in operation as the refrigerant circuit is mounted on an anti-vibration base plate. This minimises the transfer of structure-borne sound to the building. • Active cooling is possible through external circuit reversal; for passive cooling an additional external plate heat exchanger is required. • The heat pump can be operated without a buffer cylinder.

Efficiency • The inverter technology and speed-controlled circulation pumps ensure high efficiency and low follow-up costs. • Optimisation according to dynamic electricity tariffs is possible.

Safety • Despite the use of R290, the sophisticated safety concept only requires a vent pipe to the outside. The safety fan is already integrated into the heat pump. The 80 mm core hole can be produced out by a qualified contractor without specialised knowledge. • An accessory set with flexible pipe and wall outlet is available for easy connection of the heat pump to the vent pipe.


Installation • The heat pump is easy to transport to the installation site thanks to its low weight and ergonomic carrying concept. • The sophisticated safety concept means that only one air duct to the outside is required. No additional electronics or cables are needed. • The system's high level of integration enables quick and easy installation.

		WPE-I 07.1 Plus HW 400	WPE-I 12.1 Plus HW 400	WPE-I 07.1 Plus HW 230	WPE-I 12.1 Plus HW 230
Part number		**207180**	**207181**	**207185**	**207186**
Specification					
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	3,36	6,2	3,36	6,2
Heating output at B0/W35 (min./max.)	kW	1,4/7,0	2,7/11,6	1,4/7,0	2,7/11,6
COP at B0/W35 (EN 14511)		4.62	4.87	4.62	4.87
SCOP 35 °C (EN 14825)		5.21	5.40	5.21	5.40
Sound power level (EN 12102)	dB(A)	37	40	37	40
Height	mm	1863	1863	1863	1863
Width	mm	600	600	600	600
Depth	mm	700	700	700	700
Nominal capacity	l	184	184	184	184
Weight	kg	156	172	156	172

next page >

		WPE-I 07.1 Plus HW 400	WPE-I 12.1 Plus HW 400	WPE-I 07.1 Plus HW 230	WPE-I 12.1 Plus HW 230
Rated voltage, compressor	V	230	400	230	400
Rated voltage, emergency/auxiliary heater	V	400	400	400	400
Surface area, heat exchanger	m²	1.83	1.83	1.83	1.83
Energy efficiency class, DHW heating with load profile XL A+ -> F		A+	A+	A+	A+


Recommended accessories					
Part number		**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**207742**	**207742**	**207742**	**207742**
Type		AHP-PH	AHP-PH	AHP-PH	AHP-PH
Description		Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.
Part number		**207743**	**207743**	**207743**	**207743**
Type		AWG 80	AWG 80	AWG 80	AWG 80
Description		Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants
Part number		**207744**	**207744**	**207744**	**207744**
Type		AHP-TC	AHP-TC	AHP-TC	AHP-TC
Description		Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.
Part number		**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit



		WPE-I 07.1 Plus HW 400	WPE-I 12.1 Plus HW 400	WPE-I 07.1 Plus HW 230	WPE-I 12.1 Plus HW 230
b01 Entry electrical cables		•	•	•	•
c01 Cold water inlet - diameter	mm	22	22	22	22
c06 DHW outlet - diameter	mm	22	22	22	22
e01 Heating flow - diameter	mm	28	28	28	28
e02 Heating return - diameter	mm	28	28	28	28
e22 Cylinder flow - diameter	mm	28	28	28	28
f01 Heat source flow - diameter	mm	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28

Minimum clearance diagram

WPE-I 07.1 Plus HW 400
WPE-I 12.1 Plus HW 400



WPE-I 07.1-17.1 Plus H (230)



WPE-I 07.1 Plus H 230

Benefits

- Ground source heat pump installed indoors with inverter technology for heating and DHW heating
- Natural, futureproof and eco-friendly refrigerant R290
- Carefree operation with VDE-tested safety concept
- Cascade operation with up to six heat pumps if required
- Minimal space requirement in the installation room thanks to integral safety valves, circulation pumps for brine and heating, diverter valve
- Active or passive cooling possible with additional components
- Optimisation according to dynamic electricity tariffs is possible
- Also suitable for modernisation projects thanks to 70 °C flow temperature
- Fast and accurate remote maintenance thanks to integration into Servicewelt

Application • This ground source heat pump with inverter technology is suitable for heating and optional cooling of family houses as well as for DHW heating. • Thanks to the high flow temperatures all year round, the heat pump can be used in both new build and modernisation. • The system uses the natural and futureproof refrigerant R290 for optimum environmental compatibility. • The heat pump can also be used for cooling with additional external components. Cascade operation is possible with up to 6 appliances.

Convenience features • The heat pump in a design casing is installed indoors. • The low space requirement in the installation room is achieved by the high level of integration: The compact enclosure is equipped as standard with a controller and hydraulic components such as a diverter valve, circulation pumps (source and sink), electric emergency/auxiliary heater and safety valves (source and sink). • Intuitive operation via the easy-to-read, colour touchscreen display. Control with mobile devices is also possible via the MyStiebel app. • The heat pump is very quiet in operation as the refrigerant circuit is mounted on an anti-vibration base plate. This minimises the transfer of structure-borne sound to the building. • Active cooling is possible through external circuit reversal; for passive cooling an additional external plate heat exchanger is required. • The heat pump can be operated without a buffer cylinder.

Efficiency • The inverter technology and speed-controlled circulation pumps ensure high efficiency and low follow-up costs. • Optimisation according to dynamic electricity tariffs is possible.


Safety • Despite the use of R290, the sophisticated safety concept only requires a vent pipe to the outside. The safety fan is already integrated into the heat pump. The 80 mm core hole can be produced out by a qualified contractor without specialised knowledge. • An accessory set with flexible pipe and wall outlet is available for easy connection of the heat pump to the vent pipe.

Installation • The heat pump is easy to transport to the installation site thanks to its low weight and ergonomic carrying concept. • The sophisticated safety concept means that only one air duct to the outside is required. No additional electronics or cables are needed. • The system's high level of integration enables quick and easy installation.

		WPE-I 07.1 Plus H 230	WPE-I 12.1 Plus H 230	WPE-I 07.1 Plus H 400	WPE-I 12.1 Plus H 400	WPE-I 17.1 Plus H 400
						NEW
Part number		**207183**	**207184**	**207177**	**207178**	**207179**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	3,36	6,20	3,36	6,20	8,17
Heating output at B0/W35 (min./max.)	kW	1,4/7,0	2,7/11,6	1,4/7,0	2,7/11,6	3,7 / 16,3
COP at B0/W35 (EN 14511)		4.62	4.87	4.62	4.87	4.76
SCOP 35 °C (EN 14825)		5.21	5.40	5.21	5.40	5.36
Sound power level (EN 12102)	dB(A)	38	40	38	40	41
Height	mm	1450	1450	1450	1450	1450
Width	mm	600	600	600	600	600
Depth	mm	700	700	700	700	700
Weight	kg	111	132	111	132	150
Rated voltage, compressor	V	230	400	230	400	400

next page >

		WPE-I 07.1 Plus H 230	WPE-I 12.1 Plus H 230	WPE-I 07.1 Plus H 400	WPE-I 12.1 Plus H 400	WPE-I 17.1 Plus H 400
Rated voltage, emergency/auxiliary heater	V	400	400	400	400	400
Refrigerant		R290	R290	R290	R290	R290
Connection, heating side		28 mm	28 mm	28 mm	28 mm	28 mm
Connection, heat source side		28 mm	28 mm	28 mm	28 mm	28 mm
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	
Type		MEG 30	MEG 30	MEG 30	MEG 30	
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	
Part number		**207742**	**207742**	**207742**	**207742**	**207742**
Type		AHP-PH	AHP-PH	AHP-PH	AHP-PH	AHP-PH
Description		Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.	Pipe set for integrating external heat meters with a gauge of 130 mm.
Part number		**207743**	**207743**	**207743**	**207743**	**207743**
Type		AWG 80	AWG 80	AWG 80	AWG 80	AWG 80
Description		Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants	Extract air duct accessory set for natural refrigerants
Part number		**207744**	**207744**	**207744**	**207744**	**207744**
Type		AHP-TC	AHP-TC	AHP-TC	AHP-TC	AHP-TC
Description		Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.	Outer cover that can be attached to the top of the ground source heat pump using magnetic fixings.
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit
DHW cylinder						
Part number			**221360**		**221360**	**221360**
Type			SBB 301 WP		SBB 301 WP	SBB 301 WP
Description			DHW cylinder		DHW cylinder	DHW cylinder
Part number		**229981**	**229981**	**229981**	**229981**	**229981**
Type		SBS 801 W	SBS 801 W	SBS 801 W	SBS 801 W	SBS 801 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder




		WPE-I 07.1 Plus H 230	WPE-I 12.1 Plus H 230	WPE-I 07.1 Plus H 400	WPE-I 12.1 Plus H 400	WPE-I 17.1 Plus H 400
b01 Entry electrical cables		•	•	•	•	•
e01 Heating flow - diameter	mm	28	28	28	28	28
e02 Heating return - diameter	mm	28	28	28	28	28
e22 Cylinder flow - diameter	mm	28	28	28	28	28
f01 Heat source flow - diameter	mm	28	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28	28

D000011[illegible]

7

Minimum clearance diagram

WPE-I 07.1 Plus H 400
WPE-I 12.1 Plus H 400
WPE-I 17.1 Plus H 400



HPG-I 04-15 CS Premium



HPG-I 04 CS Premium

Benefits

- Easy and time saving installation with high level of integration
- High hot water convenience and mono mode heating thanks to high flow temperatures of up to 75 °C
- Pressure monitoring in the heat source circuit with integral brine pressure switch
- Passive cooling function with minimal operating costs via a geothermal probe system
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Very quiet operation thanks to the intelligent sound prevention concept including a number of anti-vibration mounts
- Futureproof and eco-friendly refrigerant with high efficiency

Application • This ground source heat pump with output-dependent control and inverter technology is installed indoors. The appliance requires little space thanks to the high level of integration. • The additional, integral heat exchanger ensures energy efficient passive cooling via an area heating system. • It can be used in mono mode for heating and DHW operation. • The heat pump is suitable for both new build and modernisation due to the high flow temperatures. • The heat pump can also be used for apartment buildings, depending on the heat load of the building.

Convenience features • Quiet operation thanks to encapsulated refrigerant circuit and acoustically isolated compressor. • The consistent source temperature ensures a constant heating output with high flow temperatures of up to 75 °C all year round. • The integral heat pump controller ensures fully automatic control of the heating system depending on the outside temperature. • In combination with the optional Internet Service Gateway, the system can be controlled in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • One high efficiency circulation pump and one expansion vessel are provided for the brine side, and the same for the heating side. • Integrated as standard are an electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the diverter valve for DHW heating and a safety valve with drain pipe. • The refrigerant circuit works with the eco-friendly and futureproof refrigerant R454C whose properties are optimised for use in heat pumps. • The metal casing is corrosion-protected and made from hot-dip galvanised, powder coated sheet steel.

Efficiency • The inverter and built-in recuperator ensure optimised heat pump operation and therefore maximum efficiency all year round.

Installation • Due to the integrated safety concept, no special measures are necessary during installation. Only a minimum room size must be ensured. • Internal pressure hoses enable direct hydraulic connection to the heating and brine circuits. • For easy installation, the hydraulic connections are equipped with quick-release fittings and are thermally insulated. Carrying handles on the back panel facilitate transport.




		HPG-I 04 CS Premium	HPG-I 06 CS Premium	HPG-I 08 CS Premium	HPG-I 12 CS Premium	HPG-I 15 CS Premium
Part number		**202627**	**202628**	**202629**	**202630**	**202631**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	1,96	2,37	2,78	4,19	5,18
Heating output at B0/W35 (min./max.)	kW	1,0-4,2	1,0-6,6	1,0-7,6	2,1-12,7	2,1-14,8
COP at B0/W35 (EN 14511)		4.60	4.60	4.67	5.01	4.86
Cooling capacity at B15/W23	kW		3	4		
SCOP 35 °C (EN 14825)		5.07	5.20	5.12	5.59	5.44
Sound power level (EN 12102)	dB(A)	38-40	38-43	38-45	39-46	39-47
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	1369	1369	1369	1369	1369
Width	mm	598	598	598	598	598
Depth	mm	658	658	658	695	658
Weight	kg	180	180	180	190	190
Rated voltage, compressor	V	230	230	230	230	230

next page >

Inverter


		HPG-I 04 CS Premium	HPG-I 06 CS Premium	HPG-I 08 CS Premium	HPG-I 12 CS Premium	HPG-I 15 CS Premium
Rated voltage, emergency/auxiliary heater	V	230	230	230	230	230
Refrigerant		R454C	R454C	R454C	R454C	R454C
Connection, heating side		28 mm	28 mm	28 mm	28 mm	28 mm
Connection, heat source side		28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit
DHW cylinder						
Part number		**221360**	**221360**	**221360**	**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP	SBB 301 WP	SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder	DHW cylinder	DHW cylinder
Part number		**229980**	**229980**			
Type		SBS 601 W	SBS 601 W			
Description		Instantaneous water cylinder	Instantaneous water cylinder			
Part number				**229981**	**229981**	**229981**
Type				SBS 801 W	SBS 801 W	SBS 801 W
Description				Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**236684**	**236684**	**236684**	**236684**	**236684**
Type		HSBC 200 L	HSBC 200 L	HSBC 200 L	HSBC 200 L	HSBC 200 L
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Part number		**238826**	**238826**	**238826**	**238826**	**238826**
Type		HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder


598
1343
695
1355
b01
c12
460
450
e22
497
e23
427
e02
357
e01
287
f01
171
f02
101
51
D0000344468.ai

Inverter

		HPG-I 04 CS Premium	HPG-I 06 CS Premium	HPG-I 08 CS Premium	HPG-I 12 CS Premium	HPG-I 15 CS Premium
b01 Entry electrical cables		•	•	•	•	•
c12 Safety valve drain		•	•	•	•	•
e01 Heating flow - diameter	mm	28	28	28	28	28
e02 Heating return - diameter	mm	28	28	28	28	28
e22 Cylinder flow - diameter	mm	28	28	28	28	28
e23 Cylinder return - diameter	mm	28	28	28	28	28
f01 Heat source flow - diameter	mm	28	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28	28

Minimum clearance diagram



HPG-I 04-15 S Premium



HPG-I 04 S Premium

Benefits
- Easy and time saving installation with high level of integration
- High hot water convenience and mono mode heating thanks to high flow temperatures of up to 75 °C
- Pressure monitoring in the heat source circuit with integral brine pressure switch
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Very quiet operation thanks to the intelligent sound prevention concept including a number of anti-vibration mounts
- Futureproof and eco-friendly refrigerant with high efficiency

Application • This ground source heat pump with output-dependent control and inverter technology is installed indoors. • The high level of integration simplifies installation whilst the small installation area means that it does not take up much space. • The heat pump can be used in modernisation projects as flow temperatures of up to 75 °C are available all year round for room heating and DHW heating. • Mono mode is possible for both heating and DHW heating.

Convenience features • Quiet operation due to encapsulated refrigerant circuit and acoustically isolated compressor. • Fully automatic, weather-compensated control of the heating system is assured by the integral heat pump manager. Control via the home network or from a mobile device is possible via the optional Internet Service Gateway. • Integral heat and electricity metering via refrigerant circuit data. • High level of integration: high efficiency circulation pumps and expansion vessels for the brine and heating side are included. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the diverter valve for DHW heating and a safety valve with drain pipe. • The refrigerant circuit works with the eco-friendly and futureproof refrigerant R454C whose properties are optimised for use in heat pumps. • The corrosion-protected, enamelled metal casing is made from hot-dip galvanised, powder coated sheet steel.


Efficiency • Optimum operation all year round and high efficiency are ensured by the inverter and integral recuperator.

Installation • Carrying handles are provided on the back panel for easy transport. • Apart from a minimum room size, no special safety precautions are required when siting. • Internal pressure hoses enable direct hydraulic connection to the heating and brine circuits. For easy installation, the hydraulic connections are equipped with quick-release fittings and are thermally insulated.

		HPG-I 04 S Premium	HPG-I 06 S Premium	HPG-I 08 S Premium	HPG-I 12 S Premium	HPG-I 15 S Premium
Part number		**202617**	**202618**	**202619**	**202620**	**202621**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	1,96	2,37	2,78	4,19	5,18
Heating output at B0/W35 (min./max.)	kW	1,0-4,2	1,0 - 6,6	1,0-7,6	2,1-12,7	2,1-14,8
COP at B0/W35 (EN 14511)		4.60	4.60	4.67	5.01	4.86
SCOP 35 °C (EN 14825)		5.07	5.20	5.12	5.59	5.44
Sound power level (EN 12102)	dB(A)	38-40	38-43	38-45	39-46	39-47
Max. application limit on the heating side	°C	75	75	75	75	75
Height	mm	1369	1369	1369	1369	1369
Width	mm	598	598	598	598	598
Depth	mm	658	695	695	695	695
Weight	kg	180	180	180	190	190
Rated voltage, compressor	V	230	230	230	230	230
Rated voltage, emergency/auxiliary heater	V	230	230	230	230	230

next page >


		HPG-I 04 S Premium	HPG-I 06 S Premium	HPG-I 08 S Premium	HPG-I 12 S Premium	HPG-I 15 S Premium
Refrigerant		R454C	R454C	R454C	R454C	R454C
Connection, heating side		28 mm	28 mm	28 mm	28 mm	28 mm
Connection, heat source side		28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit
DHW cylinder						
Part number		**221360**	**221360**	**221360**	**221360**	**221360**
Type		SBB 301 WP	SBB 301 WP	SBB 301 WP	SBB 301 WP	SBB 301 WP
Description		DHW cylinder	DHW cylinder	DHW cylinder	DHW cylinder	DHW cylinder
Part number		**229980**	**229980**			
Type		SBS 601 W	SBS 601 W			
Description		Instantaneous water cylinder	Instantaneous water cylinder			
Part number				**229981**	**229981**	**229981**
Type				SBS 801 W	SBS 801 W	SBS 801 W
Description				Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**236684**	**236684**	**236684**	**236684**	**236684**
Type		HSBC 200 L	HSBC 200 L	HSBC 200 L	HSBC 200 L	HSBC 200 L
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder
Part number		**238826**	**238826**	**238826**	**238826**	**238826**
Type		HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool	HSBC 300 L cool
Description		Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder	Integral cylinder


598
1343
695
1355
b01
c12
460
450
e22
497
e23
427
e02
357
e01
287
f01
171
f02
101
51
D0000344468.ai

Inverter

		HPG-I 04 S Premium	HPG-I 06 S Premium	HPG-I 08 S Premium	HPG-I 12 S Premium	HPG-I 15 S Premium
b01 Entry electrical cables		•	•	•	•	•
c12 Safety valve drain		•	•	•	•	•
e01 Heating flow - diameter	mm	28	28	28	28	28
e02 Heating return - diameter	mm	28	28	28	28	28
e22 Cylinder flow - diameter	mm	28	28	28	28	28
e23 Cylinder return - diameter	mm	28	28	28	28	28
f01 Heat source flow - diameter	mm	28	28	28	28	28
f02 Heat source return - diameter	mm	28	28	28	28	28

Minimum clearance diagram



WPE-I 33-87 H 400 Premium



WPE-I 33 H 400 Premium

Benefits
- Particularly efficient DHW heating using hot gas technology
- Inverter technology allows ideally matched heating output through the variable speed compressor
- Highly versatile, as both cascade control and dual mode integration are possible
- Intuitive operation via colour touchscreen
- Easy to integrate thanks to various BMS interfaces

Application • This ground source heat pump with output-dependent control and inverter technology is installed indoors. • The heat pump is suitable for apartment buildings and commercial premises. • With the help of additional hydraulic components, the existing source system can be used for passive and active cooling, or for simultaneous heating and cooling. • It can be used in mono mode for heating and DHW operation. • Up to 16 heat pumps can be operated in a cascade to achieve the required heating output.

Convenience features • The heat pump can be installed in different types of buildings. The integral inverter continuously adjusts the heating output to match the current energy demand, which ensures flexibility in the application range. • One high efficiency circulation pump is provided for the brine side and one for the heating side. • The hot gas technology enables simultaneous DHW heating via an additional heat exchanger. • Fully automatic, weather-compensated control of the heating system is taken care of by the integral heat pump manager with colour touchscreen. There is also optional provision for external control of the heating system via a building management system. • To minimise the transfer of structure-borne sound to the building, the refrigerant circuit is mounted on an anti-vibration base plate and its internal hydraulic connections are flexible. • The refrigerant circuit is hermetically sealed, tested for leaks at the factory and filled with safety refrigerant R410A.

Efficiency • The heat pump's all year round demand-dependent output provision is ensured by the integral inverter which also enables the system to operate very efficiently. • The hot gas technology included as standard ensures high DHW temperatures with very good efficiency and at low cost.


Installation • The vertical design means that only a small installation space is required. • The high level of integration enables quick and simplified installation, even with larger systems. The appliances are fully installed and delivered ready for operation. • Internal pressure hoses are provided for direct hydraulic connection to the heating and brine circuits.

		WPE-I 33 H 400 Premium	WPE-I 44 H 400 Premium	WPE-I 59 H 400 Premium	WPE-I 87 H 400 Premium
Part number		**201412**	**201413**	**201414**	**201415**
Specification					
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A+++	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55 A+++ -> D		A+++	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	kW	20,18	26,71	35,60	52,00
Heating output at B0/W35 (min./max.)	kW	10-33	11-44	14-59	21-87
COP at B0/W35 (EN 14511)		4.73	4.60	4.50	4.71
SCOP 35 °C (EN 14825)		5.55	5.65	5.19	5.17
Sound power level (EN 12102)	dB(A)	41-56	41-56	40 - 59	46-63
Max. application limit on the heating side	°C	65	65	65	65
Height	mm	1723	1723	1742	1742
Width	mm	692	692	900	900
Depth	mm	803	803	848	848
Weight	kg	300	300	430	550
Rated voltage, compressor	V	400	400	400	400
Refrigerant		R410A	R410A	R410A	R410A


next page >

		WPE-I 33 H 400 Premium	WPE-I 44 H 400 Premium	WPE-I 59 H 400 Premium	WPE-I 87 H 400 Premium
Connection, heating side		35 mm	35 mm	42 mm	42 mm
Connection, hot gas	mm	28	28	28	28
Connection, heat source side		42 mm	42 mm	54 mm	54 mm
Recommended accessories					
Part number		**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**201715**	**201715**	**201715**	**201715**
Type		EM 33-87	EM 33-87	EM 33-87	EM 33-87
Description		Extension module for WPMG	Extension module for WPMG	Extension module for WPMG	Extension module for WPMG
Part number		**201716**	**201716**	**201716**	**201716**
Type		HG Set 33-87	HG Set 33-87	HG Set 33-87	HG Set 33-87
Description		Hot gas set	Hot gas set	Hot gas set	Hot gas set
Part number		**201767**	**201767**	**201767**	**201767**
Type		FEG	FEG	FEG	FEG
Description		Digital remote control	Digital remote control	Digital remote control	Digital remote control
Part number		**202062**	**202062**	**202062**	**202062**
Type		EMW	EMW	EMW	EMW
Description		Extension module with wall mounted enclosure	Extension module with wall mounted enclosure	Extension module with wall mounted enclosure	Extension module with wall mounted enclosure
Part number		**202779**	**202779**	**202779**	**202779**
Type		FSHP-L45	FSHP-L45	FSHP-L45	FSHP-L45
Description		Flow switch	Flow switch	Flow switch	Flow switch
Part number		**221382**	**221382**	**221382**	**221382**
Type		DWS1	DWS1	DWS1	DWS1
Description		Brine pressure switch	Brine pressure switch	Brine pressure switch	Brine pressure switch
Part number		**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
DHW cylinder					
Part number		**229982**	**229982**	**229982**	**229982**
Type		SBS 1001 W	SBS 1001 W	SBS 1001 W	SBS 1001 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**229983**	**229983**	**229983**	**229983**
Type		SBS 1501 W	SBS 1501 W	SBS 1501 W	SBS 1501 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Buffer cylinder					
Part number		**185459**	**185459**		
Type		SBP 700 E	SBP 700 E		
Description		Buffer cylinder	Buffer cylinder		
Part number		**203765**	**203765**		
Type		STH 720 Plus	STH 720 Plus		
Description		Buffer cylinder	Buffer cylinder		
Part number				**227564**	
Type				SBP 1000 E	
Description				Buffer cylinder	
Part number					**227565**
Type					SBP 1500 E
Description					Buffer cylinder

WPE-I 33 H 400 Premium
WPE-I 44 H 400 Premium




WPE-I 59 H 400 Premium
WPE-I 87 H 400 Premium



		WPE-I 33 H 400 Premium	WPE-I 44 H 400 Premium	WPE-I 59 H 400 Premium	WPE-I 87 H 400 Premium
b02 Entry electrical cables I		•	•	•	•
b03 Entry electrical cables II		•	•	•	•
d15 Hot gas DHW flow optional - diameter	mm	28	28	28	28
d16 Hot gas DHW return optional - diameter	mm	28	28	28	28
e01 Heating flow - diameter	mm	35	35	42	42
e02 Heating return - diameter	mm	35	35	42	42
f01 Heat source flow - diameter	mm	42	42	54	54
f02 Heat source return - diameter	mm	42	42	54	54


Minimum clearance diagram

WPE-I 33 H 400 Premium
WPE-I 44 H 400 Premium



Inverter

WPE-I 59 H 400 Premium
WPE-I 87 H 400 Premium




Application areas


Heating

Cooling



















Fixspeed
WPE-I 05-10 HW 400 Plus 308
WPE-I 05-17 H 400 Plus 310
WPF 20-66 312
WPF 27 HT 316

Fixspeed

WPE-I 05-10 HW 400 Plus



WPE-I 05 HW 400 Plus

Benefits

- Compact ground source heat pump for heating and cooling
- Suitable for energy modernisation projects, as the high supply flow temperature is available all year round
- Optional active cooling by reversing the refrigerant cycle
- Easy and time saving installation with high level of integration
- Intuitive operation via colour touchscreen

Application • This compact ground source heat pump is suitable for heating family homes, and at the same time assures the supply of hot water. • The heat pump is suitable for both new build and modernisation, thanks to the high flow temperatures all year round. • Cooling is possible with additional external components.

Convenience features • The heat pump is installed indoors. • The small installation area is achieved through a high level of integration: the compact casing is equipped as standard with a controller and hydraulic components such as diverter valves and circulation pumps. • For control, an easy to read touchscreen is integrated that is intuitive to use. Visualised heating curves provide information on system performance. • The heat pump is very quiet in operation as the refrigerant circuit is mounted on an anti-vibration base plate. This minimises the transfer of structure-borne sound to the building. • The high grade stainless steel cylinder has undergone a special process for very good protection against corrosion. • Active cooling is possible through external circuit reversal; for passive cooling an additional external plate heat exchanger is required. • The heat pump can be controlled via the Internet Service Gateway (optional accessory) with the MyStiebel app on a smartphone or tablet.

Efficiency • The variable speed circulation pumps ensure efficient operation of the heat pump.

Installation • Siting is easier, as the weight of the heat pump has been significantly reduced compared to the previous model.

		WPE-I 05 HW 400 Plus	WPE-I 07 HW 400 Plus	WPE-I 10 HW 400 Plus
Part number		**205834**	**205835**	**205836**
Specification				
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++	A++
Heating output at B0/W35 (EN 14511)	kW	5,56	7,35	9,81
Heating output at B0/W55 (EN 14511)	kW	5.00	6.84	9.25
Power consumption at B0/W55 (EN 14511)	kW	1.80	2.43	3.04
COP at B0/W35 (EN 14511)		4.40	4.62	4.76
COP at B0/W55 (EN 14511)		2.78	2.81	3.04
SCOP 35 °C (EN 14825)		4.74	4.96	5.09
Sound power level (EN 12102)	dB(A)	42	42	42
Max. application limit on the heating side	°C	60	60	60
Height	mm	1860	1860	1860
Width	mm	600	600	600
Depth	mm	707	707	707
Nominal capacity	l	184	184	184
Weight	kg	148	165	170
Rated voltage, compressor	V	400	400	400
Rated voltage, emergency/auxiliary heater	V	400	400	400
Refrigerant		R452B	R452B	R452B

next page >

		WPE-I 05 HW 400 Plus	WPE-I 07 HW 400 Plus	WPE-I 10 HW 400 Plus
Surface area, heat exchanger	m²	1.83	1.83	1.83
Energy efficiency class, DHW heating with load profile XL A+ -> F		A	A	A
Recommended accessories				
Part number		**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit

Fixspeed

WPE-I 05-17 H 400 Plus



WPE-I 05 H 400 Plus

Benefits

- Compact ground source heat pump for heating
- Mono mode operation possible for heating and DHW thanks to higher flow temperatures
- High level of integration for reduced installation effort
- Simple and intuitive operation

Application • This ground source heat pump is suitable for heating family homes. • Thanks to the high flow temperatures all year round, the heat pump can be used in both new build and modernisation. • Cooling is possible with additional external components.

Convenience features • The heat pump is installed indoors. • The small installation area is achieved through a high level of integration: the compact casing is equipped as standard with a controller and hydraulic components such as diverter valves and circulation pumps. • For control, an easy to read touchscreen is integrated that is intuitive to use. Visualised heating curves provide information on system performance. • The heat pump is very quiet in operation as the refrigerant circuit is mounted on an anti-vibration base plate. This minimises the transfer of structure-borne sound to the building. • Active cooling is possible through external circuit reversal; for passive cooling an additional external plate heat exchanger is required. • The heat pump can be controlled via the Internet Service Gateway (optional accessory) with the MyStiebel app on a smartphone or tablet.

Efficiency • The variable speed circulation pumps ensure efficient operation of the heat pump.

Installation • Siting is easier, as the weight of the heat pump has been significantly reduced compared to the previous model.


		WPE-I 05 H 400 Plus	WPE-I 07 H 400 Plus	WPE-I 10 H 400 Plus	WPE-I 13 H 400 Plus	WPE-I 17 H 400 Plus
Part number		**205828**	**205829**	**205831**	**205832**	**205833**
Specification						
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++	A++	A++	A++
Heating output at B0/W35 (EN 14511)	kW	5,56	7,35	9,81	12,42	16,69
Heating output at B0/W55 (EN 14511)	kW	5.00	6.84	9.25	11.85	15.77
COP at B0/W35 (EN 14511)		4.40	4.62	4.76	4.52	4.43
COP at B0/W55 (EN 14511)		2.78	2.81	3.04	3.01	2.98
SCOP 35 °C (EN 14825)		4.74	4.96	5.09	4.94	4.79
SCOP 55 °C (EN 14825)	°C		3.7			
Sound power level (EN 12102)	dB(A)	44	44	44	46	46
Max. application limit on the heating side	°C	60	60	60	60	60
Height	mm	1430	1430	1430	1430	1430
Width	mm	600	600	600	600	600
Depth	mm	707	707	707	707	707
Weight	kg	113	125	130	135	148
Rated voltage, compressor	V	400	400	400	400	400
Rated voltage, emergency/auxiliary heater	V	400	400	400	400	400
Refrigerant		R452B	R452B	R452B	R452B	R452B
Recommended accessories						
Part number		**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium

next page >

Fixspeed

		WPE-I 05 H 400 Plus	WPE-I 07 H 400 Plus	WPE-I 10 H 400 Plus	WPE-I 13 H 400 Plus	WPE-I 17 H 400 Plus
Part number		**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
Part number		**233307**	**233307**	**233307**	**233307**	**233307**
Type		WPSF	WPSF	WPSF	WPSF	WPSF
Description		WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit	WPSF multifunction brine filling unit
DHW cylinder						
Part number				**221360**	**221360**	
Type				SBB 301 WP	SBB 301 WP	
Description				DHW cylinder	DHW cylinder	
Part number						**221361**
Type						SBB 302 WP
Description						DHW cylinder
Part number			**229981**	**229981**	**229981**	**229981**
Type			SBS 801 W	SBS 801 W	SBS 801 W	SBS 801 W
Description			Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder

Minimum clearance diagram



Fixspeed

WPF 20-66



WPF 20

Benefits

- Ground source heat pump for flexible use
- Low operating costs due to high coefficient of performance all year round
- Suitable for use in residential and commercial buildings due to high output
- Where available space is limited, two appliances can be installed one above the other
- High reliability thanks to robust single compressor design

Application • This ground source heat pump is suitable for indoor installation, or outdoor installation with weather protection. • Suitable for apartment buildings and commercial applications due to high outputs: up to 66 kW per individual appliance or up to 400 kW in a cascade. • With the help of additional hydraulic components, the existing source system can be used for passive and active cooling, or for simultaneous heating and cooling. • Optimised for space saving installation as two appliances can be installed one above the other. • Can be used in mono mode for heating and DHW operation.

Convenience features • To minimise the transfer of structure-borne sound to the building, the refrigerant circuit is mounted on an anti-vibration base plate for quiet operation. • The system can be controlled via the home network or a mobile device. This is achieved by combining the heat pump controller (accessory) with the ISG Internet Service Gateway as an optional accessory. With integral heat and electricity metering via refrigerant circuit data. • Fault messages can be processed externally via a 230 V signal. • The system can be integrated into an existing building automation system if required using a software extension. • Safety equipment is integrated, such as a high/low pressure switch and frost protection. • The metal casing is corrosion-protected. It is made from hot-dip galvanised, powder coated sheet steel.

Efficiency • The heat pump unit is equipped with a scroll compressor with a soft starter and optimised stainless steel heat exchangers for improved efficiency.

Installation • To facilitate installation in confined spaces, it is possible to reduce the standard unit to a width of 800 mm for transport. Fixing points for lifting eyes are also provided.


		WPF 20	WPF 27	WPF 35	WPF 40	WPF 52	WPF 66
Part number		**233003**	**233004**	**233005**	**233006**	**233007**	**233008**
Specification							
Energy efficiency class, heat pump W35 A+++ -> D		A+++	A+++	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++	A++	A++	A++	A++	A++
Heating output at B0/W35 (EN 14511)	kW	21,5	29,69	38,04	43,1	55,83	67,10
Heating output at B0/W55 (EN 14511)	kW	20.10	26.69	34.09	40.20	52.18	62.30
COP at B0/W35 (EN 14511)		4.66	4.85	4.78	4.67	4.81	4.56
COP at B0/W55 (EN 14511)		2.84	2.79	2.78	2.88	2.99	2.82
SCOP 35 °C (EN 14825)		5.00	5.28	5.20	5.05	5.20	4.95
Sound power level (EN 12102)	dB(A)	54	55	55	58	58	59
Max. application limit on the heating side	°C	60	60	60	60	60	60
Height	mm	1154	1154	1154	1154	1154	1154
Width	mm	1242	1242	1242	1242	1242	1242
Depth	mm	860	860	860	860	860	860
Weight	kg	345	367	391	415	539	655
Rated voltage, compressor	V	400	400	400	400	400	400
Rated voltage, emergency/auxiliary heater	V	400	400	400	400	400	400
Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A

next page >

Fixspeed

		WPF 20	WPF 27	WPF 35	WPF 40	WPF 52	WPF 66
Required accessories							
Part number		**236000**	**236000**	**236000**	**236000**	**236000**	**236000**
Type		WPM international	WPM international	WPM international	WPM international	WPM international	WPM international
Description		Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure	Heat pump manager in wall mounted enclosure
Recommended accessories							
Part number		**161696**	**161696**	**161696**	**161696**	**161696**	**161696**
Type		MEG 30	MEG 30	MEG 30	MEG 30	MEG 30	MEG 30
Description		Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium	Heat transfer medium
Part number		**221382**	**221382**	**221382**	**221382**	**221382**	**221382**
Type		DWS1	DWS1	DWS1	DWS1	DWS1	DWS1
Description		Brine pressure switch	Brine pressure switch	Brine pressure switch	Brine pressure switch	Brine pressure switch	Brine pressure switch
Part number		**222375**	**222375**				
Type		WPSB 308 E	WPSB 308 E				
Description		Brine assembly for the heat source system	Brine assembly for the heat source system				
Part number		**229336**	**229336**	**229336**	**229336**	**229336**	**229336**
Type		ISG web	ISG web	ISG web	ISG web	ISG web	ISG web
Description		Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway	Internet Service Gateway
DHW cylinder							
Part number		**229982**	**229982**	**229982**	**229982**	**229982**	**229982**
Type		SBS 1001 W	SBS 1001 W	SBS 1001 W	SBS 1001 W	SBS 1001 W	SBS 1001 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Part number		**229983**	**229983**	**229983**	**229983**	**229983**	**229983**
Type		SBS 1501 W	SBS 1501 W	SBS 1501 W	SBS 1501 W	SBS 1501 W	SBS 1501 W
Description		Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder	Instantaneous water cylinder
Buffer cylinder							
Part number		**227564**	**227564**				**227564**
Type		SBP 1000 E	SBP 1000 E				SBP 1000 E
Description		Buffer cylinder	Buffer cylinder				Buffer cylinder
Part number				**227565**	**227565**	**227565**	
Type				SBP 1500 E	SBP 1500 E	SBP 1500 E	
Description				Buffer cylinder	Buffer cylinder	Buffer cylinder	


Fixspeed



		WPF 20	WPF 27	WPF 35	WPF 40	WPF 52	WPF 66
b01 Entry electrical cables		•	•	•	•	•	•
e01 Heating flow - male thread		G 2	G 2	G 2	G 2	G 2	G 2
e02 Heating return - male thread		G 2	G 2	G 2	G 2	G 2	G 2
f01 Heat source flow - male thread		G 2	G 2	G 2	G 2	G 2	G 2
f02 Heat source return - male thread		G 2	G 2	G 2	G 2	G 2	G 2

Fixspeed

Minimum clearance diagram



Fixspeed

WPF 27 HT



WPF 27 HT

Benefits

- Ground source heat pump for flexible use
- High hot water convenience with flow temperatures of up to 75 °C
- Low operating costs due to high coefficient of performance all year round
- Suitable for use in residential and commercial buildings due to high output
- Ideal for DHW heating in a cascade of ground source heat pumps
- Where available space is limited, two appliances can be installed one above the other
- High reliability thanks to robust single compressor design

Application • This ground source heat pump is suitable for indoor installation, or outdoor installation with weather protection. • Suitable for apartment buildings and commercial applications due to high outputs: 66 kW per individual appliance or up to 400 kW in a cascade. • With additional hydraulic components, the existing source system can be used for passive and active cooling, or for simultaneous heating and cooling. • Optimised for space saving installation as two appliances can be installed one above the other. • Can be used in mono mode for heating and DHW operation.

Convenience features • To minimise the transfer of structure-borne sound to the building, the refrigerant circuit is mounted on an anti-vibration base plate for quiet operation. • The system can be controlled via the home network or a mobile device. This is achieved by combining the heat pump controller (accessory) with the Internet Service Gateway as an optional accessory. With integral heat and electricity metering via refrigerant circuit data. • Fault messages can be processed externally via a 230 V signal. • The system can be integrated into an existing building automation system if required using a software extension. • Safety equipment is integrated, such as a high/low pressure switch and frost protection. • The corrosion-protected metal casing is made from hot-dip galvanised, powder coated sheet steel.

Efficiency • The heat pump unit is equipped with a scroll compressor with soft starter and optimised stainless steel heat exchangers for improved efficiency.


Installation • To facilitate installation in confined spaces, it is possible to reduce the standard unit to a width of 800 mm for transport. In addition, there are fixing points on the standard appliance for lifting eyes.

		WPF 27 HT
Part number		**233009**
Specification		
Energy efficiency class, heat pump W35 A+++ -> D		A+++
Energy efficiency class, heat pump W55 A+++ -> D		A++
Heating output at B0/W35 (EN 14511)	kW	27,41
Heating output at B0/W55 (EN 14511)	kW	25.10
COP at B0/W35 (EN 14511)		4.34
COP at B0/W55 (EN 14511)		2.95
SCOP 35 °C (EN 14825)		4.58
Sound power level (EN 12102)	dB(A)	60
Max. application limit on the heating side	°C	75
Height	mm	1154
Width	mm	1242
Depth	mm	860
Weight	kg	409
Rated voltage, compressor	V	400
Rated voltage, emergency/auxiliary heater	V	400
Refrigerant		R134a

next page >

Fixspeed


		WPF 27 HT
Required accessories		
Part number		**236000**
Type		WPM international
Description		Heat pump manager in wall mounted enclosure
Recommended accessories		
Part number		**161696**
Type		MEG 30
Description		Heat transfer medium
Part number		**221382**
Type		DWS1
Description		Brine pressure switch
Part number		**229336**
Type		ISG web
Description		Internet Service Gateway
DHW cylinder		
Part number		**229982**
Type		SBS 1001 W
Description		Instantaneous water cylinder
Part number		**229983**
Type		SBS 1501 W
Description		Instantaneous water cylinder
Buffer cylinder		
Part number		**227564**
Type		SBP 1000 E
Description		Buffer cylinder



Fixspeed

		WPF 27 HT
b01 Entry electrical cables		•
e01 Heating flow - male thread		G 2
e02 Heating return - male thread		G 2
f01 Heat source flow - male thread		G 2
f02 Heat source return - male thread		G 2

Minimum clearance diagram



Accessories
Accessories 320

UPF



UPF 30/1-8 E

Benefits
- Electronic closed-loop control
- Insulation shell included in delivery
- with connecting cable and non-return valve (Product: 232532)

Description • Circulation pump with vapour diffusion-proof thermal insulation. Energy efficient thanks to integral electronic output control for constant or variable differential pressure. The circulation pump is suitable for operation on the heat source side of ground source heat pumps.

		UPF 30/1-8 E	UPF 40/1-8 E	UPF 50/1-12 E
Part number		**232532**	**227413**	**227414**
Specification				
Energy Efficiency Index EEI		0.23	0.23	0.23
Connection		G 2	DN 40	DN 50
Delivery head	m	8.00	8.00	12.00
Max. flow rate	m³/h	8.00	15.00	29.00
Power consumption	W	8-130	12-310	25-590
Rated voltage	V	230	230	230
Control via 0-10 V signal with IF module		-	-	-
Control via differential pressure		x	x	x
Control via PWM signal		-	-	-
Installation length (centre distance)	mm	180	220	280

WPSB



WPSB 308 E

Benefits
- Quick and straightforward installation

Description • Assembly with wall mounting bracket for the heat source system of the ground source heat pump, for quick and straightforward installation. The standard delivery includes a high efficiency brine circuit pump, including shut-off valves and insulation shell, brine-resistant diaphragm expansion vessel, pressure gauge, safety valve and drain valve.

		WPSB 308 E
Part number		**222375**
Specification		
Circulation pump type		Stratos PARA 30/1-8 E
Flow rate	m³/h	2.0
Max. delivery head	m	7.00
Safety valve	bar	2.50
Expansion vessel	l	25

WPSF



WPSF

Benefits
- Multifunction brine filling unit
- Both microbubble separator and filter already integrated
- Easily removable filter element
- Preassembled components for source side
- Microbubble separator and filter already integrated (Product: 233307)
- Filter element easy to remove (Product: 233307)
- All important components for the source side are pre-assembled (Product: 233307)

Description • This multifunction filling unit can be used for ground source heat pumps with a heating output of up to 16 kW. It is used to fill or flush the brine circuit and facilitates easy and quick installation on the heat source side. • The standard delivery includes the brine safety valve, pressure gauge, filter, quick-action air vent valve, microbubble separator and vapour diffusion-proof insulation.

		WPSF
Part number		**233307**

Specification		
Connection, heat source side		G 1 1/4 A
Safety valve response pressure	MPa	0.30
Max. application limit, heat source	°C	40
Min. application limit, heat source	°C	-5
Max. operating pressure	MPa	0.60

DWS



DWS1

Benefits
- Adjustable switching point

Description • The brine pressure switch for geothermal collectors and probes is used in accordance with VDI 4640 for leak detection. • The switching point can be set between 0.08 MPa and 0.15 MPa. • If an audible or visual signal is required, an additional appropriate signal transmitter can be installed.

		DWS1
Part number		**221382**

Included in standard delivery: pressure hose

Accessories

AG



MAG 12

Benefits
- Colour: white
- For floorstanding installation (Product: 235221)

Description • The brine-resistant diaphragm expansion vessel for ground source heat pumps has a rolling diaphragm for pressure maintenance and volume compensation for the heat source side.

		MAG 12	MAG 18	MAG 25	MAG 50
Part number		**235218**	**235219**	**235220**	**235221**
Specification					
Expansion vessel	l	12	18	25	50
Pre-charge pressure	bar	0.50	0.50	0.50	0.50

MEG



MEG 30

Benefits
- Ethylene glycol with excellent heat transfer properties
- Available in two container sizes

Description • Heat transfer medium for ground source heat pumps, to protect against frost and corrosion on the heat source side.

		MEG 30
Part number		**161696**
Specification		
Type of liquid		Ethylene glycol
Liquid content	l	30

The concentrate must be mixed with water prior to filling the heat source system. Observe the mixing ratio shown in the heat pump instructions. Heat transfer medium MEG, mix with water prior to filling into the system.
Never use potassium carbonate in connection with hemp gaskets. (Product: 161696)

SDB 40-50 G




Description • The uninsulated pressure hose for the brine flow line and the brine return line is equipped with a threaded fitting at one end, while the other end offers a locking ring fitting.

SDB 40-0.8 G

		SDB 40-0.8 G	SDB 50-0.8 G
Part number		**201713**	**201714**
Specification			
For pressure hose size DN		40	50

EM 33-87



Benefits
- Extension module for extended WPMG controller functions
- Suitable for installation in the heat pump

Description • The extension module is used for actuating other functions and integrating additional heating circuits or heat generators, for example.

EM 33-87

		EM 33-87
Part number		**201715**

EMW



Benefits
› Extension module for extended WPMG controller functions
› A wall mounted enclosure for installation direct onto the wall is included in the standard delivery

Description • The extension module is used to control extra functions, such as additional heating circuits or heat generators. The module is supplied with a wall mounted enclosure.

EMW

		EMW
Part number		**202062**
Specification		
Width	mm	300
Height	mm	180
Depth	mm	109

HG Set 33-87



Benefits
› Hot gas set

Description • The set for DHW heating via hot gas consists of a circulation pump and a line regulating valve.

HG Set 33-87

		HG Set 33-87
Part number		**201716**
Specification		
Power consumption	W	6
Rated voltage	V	230

FEG



FEG

Benefits
› Remote control for adjusting room temperature or heating circuit temperature

Description • The remote control is combined with the WPMG controller. • The integral sensor measures the room temperature in the lead room; the room temperature or set temperature can be adjusted.

		FEG
Part number		**201767**

TAF PT



TAF PT 5m

Description • The PT 1000 sensor is used in heat pump systems as an immersion or contact sensor.

		TAF PT 5m	TAF PT 2m
Part number		**235995**	**235996**
Specification			
Version		Temperature sensor	Temperature sensor
With supply line		•	•
Colour		white	white
Diameter	mm	6	6

(Product: 235995, 235996)

AF PT

AF PT

Benefits
- Outside temperature sensor for surface-mounted installation
- Weather-resistant casing
- Supply line included in delivery

Description • The outside temperature sensor in a plastic enclosure is supplied without a cable.

		AF PT
Part number		**235997**

Specification		
Version		Outside sensor
Installation type		Surface-mounted
With supply line		-
Width	mm	40
Height	mm	82
Depth	mm	38

AWG 80



AWG 80

Benefits
- Complete set for safety concept for ground source heat pumps with natural refrigerant (R290) installed indoors
- Aluminium flexible pipe set DN 80 including gaskets

Description • Accessory set consisting of DN80 wall outlet for external walls up to 550 mm wall thickness including weather grille, rodent guard, check valve and two 5 m DN80 aluminium flexible pipes. • Ideal for extract air routing for ground source heat pumps with natural refrigerant and power of less than 20 kW.

		AWG 80
Part number		**207743**

AHP-TC



Benefits
› Elegant design cover
› Easy installation thanks to magnetic fixing

Description • Outer cover conceals the pipe connections at the top of the heat pump, for visually refined installation.
• Easy installation thanks to magnetic fixing of the fascia.

AHP-TC

		AHP-TC
Part number		**207744**
Specification		
Height	mm	1450
Width	mm	600
Length	mm	700

AHP-PH




Benefits
› Accessories for installing external heat meters in ground source heat pumps

Description • Pipe set for integrating external heat meters with a gauge of 130 mm.

AHP-PH

		AHP-PH
Part number		**207742**

Control units		331
Hydraulic modules		339
Accessories for hydraulic modules		341
Integral cylinder		343
Accessories for integral cylinders		351
DHW cylinder		355
Accessories for DHW cylinders		359
Instantaneous water cylinder		361
Accessories for instantaneous water cylinders		365
Buffer cylinder		367
Accessories for buffer cylinders		375
Additional accessories		381
Heat pump accessories		385

Controller
Accessories 332
Connectivity
Accessories 334
Controller accessories
Accessories 335

WPM



WPM international

Benefits

- Heat pump manager in stylish wall mounted enclosure
- Management of a 2-stage on/off or inverter cascade for one direct heating circuit and two heating circuits with mixer
- Straightforward electrical installation thanks to RAST 5 connector technology
- Integral heat metering
- Cooling control function
- A second heat generator can be controlled
- Screed drying program
- DHW circulation pump management
- PWM circulation pump management
- 3 immersion/contact sensors and 1 outside sensor are included in the standard delivery
- Fault output 230 V
- Update via an SD card
- An internet interface is available as an option
- SG Ready (optional)
- Smart home and energy management interfaces (optional)

Description • This WPM heat pump manager is the main controller in the system. One direct heating circuit and two heating circuits with mixer can be controlled via the integral programming unit. Two heat pumps can also be operated in a cascade. • In combination with the ISG Internet Service Gateway, the heat pump can be integrated into a home network or controlled from mobile devices. • Direct connection of high efficiency circulation pumps is possible via relay outputs or PWM outputs. • The WPM also provides a fault contact for external pick-up of system faults. • A drip-proof wall mounted enclosure with large installation area provides sufficient space for the electrical connections and other components such as a top-hat rail relay. The well designed cable layout ensures easy connection.

		WPM international
Part number		**236000**
Specification		
Protection class		I
Supply voltage	V	230
IP rating		IP21
Width	mm	310
Height	mm	400
Depth	mm	100

International operating instructions
Controller, 1 AF PT outside temperature sensor, 3 TAF PT sensors (Product: 236000)

WPM Connect



WPM Connect International

Benefits
- Heat pump manager in stylish wall mounted enclosure
- Integrated WLAN and Ethernet connectivity
- Diagnosis and control via mobile devices possible
- Management of a 2-stage on/off or inverter cascade for one direct heating circuit and two heating circuits with mixer
- Straightforward electrical installation thanks to RAST 5 connector technology
- 3 immersion/contact sensors and 1 outside sensor are included in the standard delivery

Description • This WPM Connect heat pump manager is the main controller in the system. The integral programming unit is controlled via a colour touchscreen with intuitive user guidance. • One direct heating circuit and two heating circuits with mixer can be controlled via the device. Two heat pumps can also be operated in a cascade. • Thanks to the integrated WLAN and Ethernet connectivity, the installer can perform remote diagnostics just as easily as control with mobile devices via the MyStiebel app. • Highly efficient circulation pumps can be directly connected via relay outputs or PWM outputs. The heat pump manager offers integral heat metering, cooling control function, screed drying program, circulation management and circulation pump management. • The WPM also provides a fault contact for external pick-up of system faults. • A stylish drip-proof wall mounted enclosure with large installation area provides sufficient space for the electrical connections and other components such as a top-hat rail relay. The well designed cable layout ensures easy connection.

		WPM Connect International
		NEW
Part number		**207709**

WPE

WPE

Benefits
- Function extension module for the WPM heat pump manager
- Data link via the system bus
- Straightforward electrical installation thanks to RAST 5 connector technology
- The sensor is adjusted and operated via the programming unit on the WPM heat pump manager
- Management of 4 additional heat pump stages
- Two additional heating circuits with mixer can also be controlled
- Swimming pool management
- Universal differential controller
- 3 immersion/contact sensors are included in the standard delivery

Application • This WPE heat pump extension adds numerous functions to the WPM heat pump manager. It offers two additional heating circuits with mixer, a swimming pool controller and cascade control for up to six heat pumps. Two additional 0-10 V interfaces, a differential controller and switching outputs are also available. • The enclosure is installed to the right or left of the WPM and is connected to the power supply via the bus. • The module's additional functions can be set at the programming unit of the WPM.

		WPE
Part number		**234725**
Specification		
Protection class		I
Supply voltage	V	230
IP rating		IP21
Width	mm	310
Height	mm	400
Depth	mm	100
Required accessories		
Part number		**236000**
Type		WPM international
Description		Heat pump manager in wall mounted enclosure

Controller, 3 TAF PT sensors (Product: 234725)

ISG Connect



Benefits
- Browser-based operation of the heat pump in a home network
- Straightforward use of self-generated photovoltaic power by means of SG Ready function
- Output control in accordance with §14a of the German Energy Industry Act (EnWG)


Application • This ISG Connect Internet Service Gateway connects the heat pump to the home network via LAN and enables the heat pump system to be operated using a browser. • If the appliance data is also transmitted to the STIEBEL ELTRON Servicewelt (Internet Service Portal), the heat pump can be conveniently controlled from anywhere via the internet using the MyStiebel app. • The ISG Connect is a required accessory for use of the SG Ready functions. The ISG can be integrated into an existing building management system via the Modbus TCP/IP data interface. • ISG Connect enables control to an output specified by the power supply utility or energy manager (HEMS – Home Energy Management System) via relay contacts or EEBUS protocol.

ISG Connect

		ISG Connect
		NEW
Part number		**206780**

Observe the compatibility list.

ISG web



Benefits
- Browser-based operation of the heat pump in a home network
- Can be integrated into home automation systems through Modbus TCP/IP software interface fitted as standard
- Optional automation with KNX IP software extension
- Forecast-based on-site PV self-consumption facilitated by optional EMI software extension

Description • The ISG Internet Service Gateway connects the heat pump to the home network and enables the appliance to be operated using a browser. • Once enabled, appliance data is transferred to the Stiebel Eltron Internet Service Portal. • The ISG plus is a required accessory for use of the SG Ready functions of the WPM heat pump manager. The ISG can be integrated into an existing building management system via the Modbus TCP/IP data interface.

ISG web

		ISG web
Part number		**229336**
Specification		
Version		Wall mounting
10/100 Ethernet		RJ45
CAN		RJ45
RS232		RJ12
Width	mm	158
Height	mm	95
Depth	mm	37
Min./max. application range	°C	0 / 60

Observe the compatibility list.

FET



Benefits
- Data link via the system bus
- Room remote control with thermostatic function for the WPM heat pump manager
- Can be used for each of the 5 heating circuits in the WPM system
- Illuminated graphic display
- Display of time, room temperature and room humidity, along with outside temperature
- Touch-Wheel operation
- Room temperature and humidity measurement
- Simple adjustment of comfort temperature
- Energy savings with selectable eco function
- Activating a DHW charging process

FET

Description • The FET digital remote control can be used to conveniently control a heating zone. • The remote control measures the relative humidity and room temperature.

		FET
Part number		**234723**
Specification		
Width	mm	145
Height	mm	96
Depth	mm	31

TAF PT



Description • The PT 1000 sensor is used in heat pump systems as an immersion or contact sensor.

TAF PT 5m

		TAF PT 5m	TAF PT 2m
Part number		**235995**	**235996**
Specification			
Version		Temperature sensor	Temperature sensor
With supply line		•	•
Colour		white	white
Diameter	mm	6	6

(Product: 235995, 235996)

AF PT

Benefits
- Outside temperature sensor for surface-mounted installation
- Weather-resistant casing
- Supply line included in delivery

Description • The outside temperature sensor in a plastic enclosure is supplied without a cable.

AF PT

		AF PT
Part number		**235997**
Specification		
Version		Outside sensor
Installation type		Surface-mounted
With supply line		-
Width	mm	40
Height	mm	82
Depth	mm	38

AVF 6



Description • The PTC contact sensor is used as an additional sensor in a heat pump system.

AVF 6

		AVF 6
Part number		**165341**
Specification		
Version		Cable sensor
With supply line		•
Supply line length	m	2.00
Diameter	mm	6

TF 6



Benefits
› Supply line (1 m) included in the delivery
› Sensor diameter: 6 mm

Description • The TF 6 is an additional PTC immersion sensor for the heat pump system.

TF 6

		TF 6
Part number		**165342**
Specification		
Version		Temperature sensor
With supply line		•
Supply line length	m	1.00
Diameter	mm	6

Mono mode
Accessories 340

HM Trend



HM Trend

Benefits
- Time saving installation of heating components thanks to high level of integration
- Simple connection to the heat pump via water pipes
- Very good thermal insulation for heating and cooling, with main body in expanded polypropylene (EPP)

Application • This hydraulic module is suitable for simple hydraulic connection of mono block heat pumps to the heating system. The appliance is designed for heating or cooling in family houses. • The insulated, black EPP casing is mounted on the wall in the installation room to save space.


Convenience features • The fully automatic, weather-compensated control of the heating system is provided by the integral heat pump manager. In combination with the optional Internet Service Gateway, the system can be controlled in the home network or with a mobile device. • With integral heat and electricity metering via refrigerant circuit data. • High level of integration: a high efficiency circulation pump and an expansion vessel are already included for the heating circuit. Also integrated are the electric emergency/auxiliary heater for mono energetic operation and pasteurisation, the heating diverter valve for DHW heating and a safety valve with drain pipe.

		HM Trend	HMS Trend
Part number		**232805**	**233826**
Specification			
Max. permissible pressure	MPa	0.30	0.30
Min. application limit on heating side	°C	7	7
Max. application limit on the heating side	°C	75	75
External available pressure differential at 1.0 m³/h	hPa	715	715
External available pressure differential at 1.5 m³/h	hPa	661	661
External available pressure differential at 2 m³/h	hPa	468	468
External available pressure differential at 2.5 m³/h	hPa	300	300
Expansion vessel volume	l	24	24
Frequency	Hz	50	50
Rated voltage, control unit	V	230	230
Phases, control unit		1/N/PE	1/N/PE
Control unit fuse protection	A	1 x B 16	1 x B 16
Rated voltage, emergency/auxiliary heater	V	400	230
Power consumption, emergency/auxiliary heater	kW	8.80	5.90
Power consumption, circulation pump	W	3-76	3-76
Circulation pump type		Yonos PARA 25/7.5, highly efficient circulation pump	Yonos PARA 25/7.5, highly efficient circulation pump
IP rating		IP20	IP20
Height	mm	896	896
Height incl. connector block	mm	1131	1131
Width	mm	590	590
Depth	mm	405	405
Weight	kg	27	27
Connection		G 1	G 1
Connection type		Permanent connection	Permanent connection
Recommended accessories			
Part number		**232806**	**232806**
Type		ASL-HM	ASL-HM
Description		Insulated connector block	Insulated connector block
Part number		**233750**	**233750**
Type		AS-HM Trend	AS-HM Trend
Description		Hydraulic module connection set	Hydraulic module connection set

Accessories
Accessories 342

Accessories

ASL-HM



Benefits
- Thermally insulated connector block
- Simplifies installation of hydraulic module
- Expanded polypropylene casing

Description • The accessories facilitate connection of the hydraulic module to the pipework on site. • The standard delivery includes flow lines with ball valve as well as the heating and DHW return lines, encased in vapour diffusion-proof EPP.

ASL-HM

		ASL-HM
Part number		**232806**
Specification		
Height	mm	285
Width	mm	580
Depth	mm	215
Weight	kg	4.50
Connection		28 mm

AS-HM Trend



Benefits
- For connecting the hydraulic module in the Trend series
- Three ball valves with drain

Description • The accessory, featuring ball valves in the flows, simplifies connection of the hydraulic module to the on-site pipework.

AS-HM Trend

		AS-HM Trend
Part number		**233750**
Specification		
Connection		G 1 - 28 mm

With integral buffer cylinder
Accessories 344
Without integral buffer cylinder
Accessories 349

With integral buffer cylinder

HSBC 300 cool



HSBC 300 cool

Benefits

- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance
- Large area heat exchanger for high DHW demand
- Can be used for cooling via area heating system or fan coil units (condensation resistance)
- The integral WPM heat pump manager makes the system easier to install

Application • This integral cylinder is suitable for DHW heating in heat pump mode. • The appliance is prepared for the optional addition of another heating circuit. • The equipment simplifies the hydraulic connection in heating systems, as the heat pump and heating circuit flows are separated by means of an integral buffer cylinder. This means that it can be used in different heat distribution systems. • Can be used for heating and cooling in a family house (new or existing building).

Convenience features • DHW cylinder and buffer cylinder are steel cylinders with directly applied foam insulation. The DHW cylinder is equipped with an internal indirect coil and magnesium signal anode for additional corrosion protection. The two cylinders are mounted one above other to save space; practical recessed grips facilitate handling. • Space saving installation through integration of key components in a single casing: WPM heat pump manager, cylinder charging pump, circulation pump and 3/2-way diverter valve. • Easy to handle, as the DHW cylinder and the buffer cylinder can be transported separately.

Efficiency • Low standby losses as both the cylinder volume and the heat exchanger surface area are matched to requirements.

Installation • The DHW and buffer cylinders are arranged one above the other and can be separated. Two recessed grips facilitate transport to the installation site.

		HSBC 300 cool
Part number		**203801**
Specification		
Energy efficiency class A+ -> F		B
Nominal capacity, DHW cylinder	l	270
Nominal capacity, buffer cylinder	l	100
Surface area, heat exchanger	m²	3.20
Capacity, heat exchanger	l	21
Standby energy consumption/24 h at 65 °C	kWh	1.50
Height	mm	1918
Width	mm	680
Depth	mm	910
Height when tilted	mm	2123
Weight	kg	250

Recommended accessories		
Part number		**238825**
Type		HSBC 3-HKM
Description		Mixer circuit pump assembly

Availability on request

HSBC 300 (L) cool



HSBC 300 L cool

Benefits

- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance
- High level of integration for reduced installation effort
- Large cylinder volume and heat exchanger surface area for high DHW demand
- Can be used for cooling, e.g. via an area heating system or fan coil units (condensation resistance)
- Not equipped with a cylinder charging pump for combination with recommended heat pump types (Product: 238826)

Application • This integral cylinder for heat pump operation is suitable for DHW heating. Furthermore, the integral cylinder is integrated into heating systems for the hydraulic connection and is used for delivery to/separation between the heat pump and heating circuit. The appliance is suitable for heating and cooling in family houses.

Convenience features • The generously sized DHW cylinder has an enamelled steel cylinder with directly applied foam insulation. • The internal indirect coil and signal anode offer additional corrosion protection. • The integral cylinder is equipped with a circulation pump and a 3/2-way diverter valve. • The appliance can optionally be operated with a heating circuit with mixer. • The cylinder casing consists of a plastic jacket, permanently attached at the back and sides. The removable front made of sheet metal has a design cover.

Efficiency • Standby losses are low because the cylinder volume and the indirect coil surface area have been optimised.

Installation • The cylinders are arranged one above the other and can be separated. Integral recessed grips facilitate transport to the installation site.

		HSBC 300 L cool
Part number		**238826**
Specification		
Energy efficiency class A+ -> F		B
Nominal capacity, DHW cylinder	l	270
Nominal capacity, buffer cylinder	l	100
Surface area, heat exchanger	m²	3.20
Capacity, heat exchanger	l	21
Standby energy consumption/24 h at 65 °C	kWh	1.50
Height	mm	1918
Width	mm	680
Depth	mm	910
Height when tilted	mm	2123
Weight	kg	248
Recommended accessories		
Part number		**238825**
Type		HSBC 3-HKM
Description		Mixer circuit pump assembly

With integral buffer cylinder

HSBC 200



HSBC 200

Benefits

- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance
- Installation requires little effort thanks to high level of integration including WPM heat pump manager
- Can be used for cooling, for example with an area heating system
- Large area heat exchanger for high DHW demand

Application • This integral cylinder is suitable for DHW heating in heat pump mode. It is used simultaneously for the hydraulic connection of the heat pump to the heating system and for delivery to/separation between the heat pump and heating circuit. • Designed for heating and cooling in family houses.

Convenience features • DHW cylinder and buffer cylinder are enamelled steel cylinders with directly applied foam insulation. The DHW cylinder is equipped with an internal indirect coil and a signal anode for additional corrosion protection. • Space saving installation is made possible through the integration of key components in a single casing. • Standard delivery includes the WPM heat pump manager, cylinder charging pump, circulation pump and 3/2-way diverter valve. • The integral cylinder is easy to manoeuvre as the DHW cylinder and the buffer cylinder can be transported separately. • The integral cylinder can optionally be operated with a heating circuit with mixer. • The cylinder casing consists of a plastic jacket that is permanently attached at the sides and the back; the removable front has a design cover.

Efficiency • As the cylinder volume and the indirect coil surface area are optimally matched to the system, standby losses are only minimal and the DHW heating is very efficient.

Installation • The DHW and buffer cylinders are arranged one above the other during operation and can be separated for transport. Handling is made easy thanks to handle positions at top and bottom.

		HSBC 200	HSBC 200 S
Part number		**233510**	**234801**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity, DHW cylinder	l	168	168
Nominal capacity, buffer cylinder	l	100	100
Surface area, heat exchanger	m²	3.30	3.30
Capacity, heat exchanger	l	21	21
Standby energy consumption/24 h at 65 °C	kWh	1.30	1.30
Height	mm	1908	1908
Width	mm	680	680
Depth	mm	871	871
Height when tilted	mm	2107	2107
Weight	kg	203	203
Recommended accessories			
Part number		**234648**	**234648**
Type		HSBC-HKM	HSBC-HKM
Description		Mixer circuit pump assembly	Mixer circuit pump assembly

HSBC 200 L

HSBC 200 L

Benefits
- High level of integration for reduced installation effort
- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance
- Can be used for cooling, for example with an area heating system

Application • This integral cylinder for heat pump operation is suitable for DHW heating. Furthermore, the integral cylinder is integrated into heating systems for the hydraulic connection and is used for delivery to/separation between the heat pump and heating circuit. The appliance is suitable for heating and cooling in family houses.

Convenience features • DHW cylinder and buffer cylinder are enamelled steel cylinders with directly applied foam insulation. The DHW cylinder is equipped with an internal indirect coil and a signal anode for additional corrosion protection. • Space saving installation and integral circulation pump • The integral cylinder can optionally be operated with a heating circuit with mixer. • The cylinder casing consists of a plastic jacket, permanently attached at the back and sides.

Efficiency • Standby losses are low, because the cylinder volume and the indirect coil surface area are perfectly matched to the application area.

Installation • The cylinders are arranged one above the other and can be separated. Integral recessed grips facilitate transport to the installation site.

		HSBC 200 L
Part number		**236684**
Specification		
Energy efficiency class A+ -> F		B
Nominal capacity, DHW cylinder	l	180
Nominal capacity, buffer cylinder	l	100
Surface area, heat exchanger	m²	1.60
Capacity, heat exchanger	l	10
Standby energy consumption/24 h at 65 °C	kWh	1.30
Height	mm	1908
Width	mm	680
Depth	mm	800
Height when tilted	mm	2107
Weight	kg	185
Recommended accessories		
Part number		**234648**
Type		HSBC-HKM
Description		Mixer circuit pump assembly

HSBC 180 plus



HSBC 180 Plus

Benefits

- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning thanks to integration of DHW cylinder, buffer cylinder and hydraulic working parts into a single appliance
- Installation requires little effort thanks to high level of integration including WPM heat pump manager
- Can be used for cooling via area heating system or fan coil units (condensation resistance)

Application • This integral cylinder is used for DHW heating in combination with a heat pump. The appliance simplifies the hydraulic connection in heating systems, as the heat pump and heating circuit flows are separated by means of an integral buffer cylinder. • Designed for use in family houses for heating and cooling.

Convenience features • Standard delivery includes: WPM heat pump manager, cylinder charging pump, circulation pump, 3/2-way diverter valve, safety valve with drain routed out of the appliance, and electric emergency/auxiliary heater. • The DHW cylinder is an enamelled steel cylinder with directly applied foam insulation. It is equipped with an internal indirect coil and a magnesium anode for additional corrosion protection. The buffer cylinder is also a steel cylinder with directly applied foam insulation.

Application • Specific matching of the cylinder volume and the indirect coil surface area to the application ensures low standby losses.

Installation • The integral carrying aids facilitate transportation to the installation site.

		HSBC 180 Plus	HSBC 180 S Plus
Part number		**202927**	**203082**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity, DHW cylinder	l	178	178
Nominal capacity, buffer cylinder	l	80	80
Surface area, heat exchanger	m²	1.59	1.59
Capacity, heat exchanger	l	10	10
Standby energy consumption/24 h at 65 °C	kWh	1.29	1.29
Height	mm	1910	1910
Width	mm	605	605
Depth	mm	917	917
Height when tilted	mm	1986	1986
Weight	kg	134	134
Recommended accessories			
Part number		**204642**	**204642**
Type		CDT 180	CDT 180
Description		Cooling accessories	Cooling accessories

Availability on request

HSBB 180 plus



HSBB 180 Plus

Benefits
- The integral cylinder for DHW heating is combined with a heating heat pump and integrated into the heating system.
- Space saving positioning, as the DHW cylinder and hydraulic parts are integrated in a single appliance
- Can be used for cooling via area heating system or fan coil units (condensation resistance)
- Installation requires little effort thanks to high level of integration including WPM heat pump manager

Application • This integral cylinder is suitable for DHW heating. The appliance is integrated into the heating system and connects the heat pump hydraulically to the heating circuit. • The cylinder is designed for heating and cooling in the single-family house and is optimised for use with an underfloor heating system.

Convenience features • The DHW cylinder comprises an enamelled steel cylinder with foam insulation, an internal indirect coil and a magnesium anode for additional corrosion protection. Can be used for cooling via underfloor heating system or fan coil units. • Equipment includes: WPM heat pump manager, DHW/heating circuit charging pump, 3/2-way diverter valve, safety valve with drain connector, and electric emergency/auxiliary heater. • Carrying aids are integrated to simplify transport.

Efficiency • Low standby losses.

Installation • The integral carrying aids facilitate transportation to the installation site.

		HSBB 180 Plus	HSBB 180 S Plus
Part number		**202926**	**203084**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity, DHW cylinder	l	178	178
Surface area, heat exchanger	m²	1.59	1.59
Capacity, heat exchanger	l	10	10
Standby energy consumption/24 h at 65 °C	kWh	1.29	1.29
Height	mm	1300	1300
Width	mm	605	605
Depth	mm	917	917
Height when tilted	mm	1420	1420
Weight	kg	99	99
Suitable for		Heat pump	Heat pump
Recommended accessories			
Part number		**204642**	**204642**
Type		CDT 180	CDT 180
Description		Cooling accessories	Cooling accessories

Availability on request

Without integral buffer cylinder

Accessories
Accessories 352

HSBC (3)-HKM



HSBC-HKM

Benefits
- Pump assembly for an additional heating circuit with mixer
- Heating circuit connection: 22 mm
- Integral cylinder accessories

Description • The pump assembly mixer circuit adds a heating circuit with mixer to the integral cylinder. • The assembly comprises the insulated connection pipework, heating circuit pump and 3-way mixer with servomotor. It is intended for use inside the integral cylinder using the prepared connections.

		HSBC-HKM	HSBC 3-HKM
Part number		**234648**	**238825**
Specification			
Connection, heating circuit	mm	22	22

CDT



CDT 180

Benefits
- Condensate pan with condensate pump for installation in the integral cylinder
- Used for seasonal cooling below the dew point or for cooling without dew point monitoring

Description • The condensate pan with condensate pump is installed in an integral cylinder. • It needs to be used for seasonal cooling below the dew point temperature or if, for example, fan coil units provide cooling without dew point monitoring. • Without this accessory, cooling rooms is only permissible with dew point temperature monitoring. • Standard delivery includes the condensate pan with condensate pump, hose for external drainage, wiring harness for the electrical connection and installation accessories.

		CDT 180
Part number		**204642**

AHP-BH



AHP-BH 8.8

Benefits
- Wall mounted module with integral emergency/auxiliary heater
- Optimised for air source heat pumps with R290 refrigerant
- Suitable for all performance classes of air source heat pumps with R290 refrigerant

Description • Wall mounted module with integral emergency/auxiliary heater. For use with air source heat pumps with R290 refrigerant if no other emergency/auxiliary heater is available. • The module must be connected to the integral cylinder or the heat pump manager via the bus cable supplied.

		AHP-BH 8.8
		NEW
Part number		**207902**
Specification		
Phases, emergency/auxiliary heater		3 x B 16 A
Emergency/auxiliary heater fuse protection		3/N/PE
Frequency	Hz	50
Max. permissible pressure	MPa	0.3
Min. application limit on heating side	°C	18

DHW cylinder
Accessories 356

DHW cylinder

SBB 301-501 WP SOL



SBB 301 WP

Benefits

- DHW cylinders for use in combination with heating heat pumps
- Large mixed water amount due to matched inlet and outlet flow technology
- Large area heat exchanger for high DHW demand
- Installation-friendly fittings including signal anode and flexible, multi-directional cold water connection
- Additional application range thanks to integral solar indirect coil (Product: 221362, 227534)

Application • This DHW cylinder is suitable for operation with heat pumps. It can be used for DHW supply in family houses and apartment buildings, depending on the nominal capacity and the indirect coil surface area.

Convenience features • The enamelled steel cylinder with foam insulation is equipped with an inspection flange and a protective anode for additional corrosion protection. • The heat pump is connected via the internal indirect coil. A plug-in dial thermometer is included in the standard delivery. • The cylinder casing can be removed for transport to the installation site.

		SBB 301 WP	SBB 302 WP	SBB 401 WP SOL	SBB 501 WP SOL
Part number		**221360**	**221361**	**221362**	**227534**
Specification					
Energy efficiency class A+ -> F		C	C	C	
Nominal capacity	l	301	290	395	495
Surface area, heat exchanger, top	m²	3.20	4.80	4.00	5.00
Surface area, heat exchanger, bottom	m²			1.40	1.40
Standby energy consumption/24 h at 65 °C	kWh	2.10	2.10	2.40	2.40
Height	mm	1710	1710	1880	1988
Diameter incl. thermal insulation	mm	700	700	750	810
Height when tilted	mm	1,750	1,750	1,930	2,035
Weight	kg	156	184	219	260

The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors. (Product: 221362)

STD 180-520-1 Plus



STD 315-1 Plus

Benefits

- DHW cylinders for combination with heating heat pumps
- Low standby losses for efficient operation
- Protective anode for corrosion protection as standard
- Available in 300, 400 or 500 litre versions depending on the DHW demand

Application • This DHW cylinder is suitable for combination with a heating heat pump and is intended for use in family houses. • Available in 300, 400 or 500 litre versions depending on the DHW demand. • Long service life through integral corrosion protection.

		STD 315-1 Plus	STD 420-1 Plus	STD 520-1 Plus
Part number		**204784**	**204785**	**204786**
Specification				
Energy efficiency class A+ -> F		B	B	B
Nominal capacity	l	314	418	522
Surface area, heat exchanger, top	m²	2.00	2.60	3.20

next page >

DHW cylinder

		STD 315-1 Plus	STD 420-1 Plus	STD 520-1 Plus
Standby energy consumption/24 h at 65 °C	kWh	1.70	1.80	1.90
Height	mm	1619	1799	1904
Diameter incl. thermal insulation	mm	650	730	780
Height when tilted	mm	1,750	1,946	2,063
Weight	kg	111	139	182

SBB 600-1000 WP SOL



SBB 600 WP SOL

Benefits

- Additional application range thanks to integral solar indirect coil
- DHW cylinder for combination with heating heat pumps with high output
- Large heat exchanger surface area for high DHW demand through the use of twin pipe indirect coils

Application • This DHW cylinder is suitable for operation with high capacity heat pumps. The appliance is used in apartment buildings or commercial properties, depending on the capacity and surface area of the indirect coils. • Optional integration of solar thermal backup is possible.

Convenience features • The enamelled steel cylinder is equipped with a magnesium signal anode for additional corrosion protection. • Features two internal twin pipe indirect coils: the lower coil is for the solar thermal system; the upper one for the heat pump. For heat pumps with a higher output, the two indirect coils can be connected in series. • The inspection flanges are fitted with blank flanges. If required, additional heat exchangers or electric flanged immersion heaters can be fitted.

Efficiency • Low standby losses if the thermal insulation available as an accessory is used. • Good temperature stratification is ensured by matched inlet and outlet technology.

		SBB 600 WP SOL	SBB 800 WP SOL	SBB 1000 WP SOL
Part number		**235906**	**235907**	**235908**
Specification				
Height	mm	1775	1943	2153
Height when tilted	mm	1,813	1,990	2,185
Weight	kg	256	302	321
Required accessories				
Part number		**235909**		
Type		WDH 600 SBB		
Description		Thermal insulation		
Part number			**235910**	
Type			WDH 800 SBB	
Description			Thermal insulation	
Part number				**235911**
Type				WDH 1000 SBB
Description				Thermal insulation
Recommended accessories				
Part number		**232629**	**232629**	**232629**
Type		WRV 40	WRV 40	WRV 40
Description		Corrugated pipe connector for indirect coils	Corrugated pipe connector for indirect coils	Corrugated pipe connector for indirect coils

The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors.

(Product: 235906) The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors. (Product: 235907)The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors.

The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors. (Product: 235908)

DHW cylinder

Accessories
Accessories 360

Accessories

WRV 32-40



WRV 32

Benefits
- Thermally insulated corrugated pipe
- Available in two nominal diameters

Description • The corrugated pipe connector is used to connect the lower and upper indirect coils. • Standard delivery includes the threaded end and a union nut.

		WRV 32	WRV 40
Part number		**232628**	**232629**
Specification			
Nominal diameter, corrugated pipe		DN 32	DN 40
Union nut fitting connection		G 1 1/2	G2

WDH 600-1000 SBB



WDH 600 SBB

Benefits
- Composite thermal insulation made from rigid foam and fleece
- Graphite inserts for good insulation properties
- Two insulation semi-shells to make it easier to match the shape

Description • The high grade thermal insulation made from EPS rigid foam is supplied with insulated cover and floor disc. Graphite inserts in the EPS and the fleece ensure minimal heat losses. • The thermal insulation can be optimally adapted to the cylinder thanks to the wedge-shaped cut-outs and the fleece layer. The prepared adhesive joints in the wedge-shaped cut-outs also contribute to this. • The integrated quick-release hook strip makes it easier to attach the thermal insulation.

		WDH 600 SBB	WDH 800 SBB	WDH 1000 SBB
Part number		**235909**	**235910**	**235911**
Specification				
Insulation for		SBB 600 WP SOL	SBB 800 WP SOL	SBB 1000 WP SOL
Thermal insulation thickness	mm	110	110	110
Standby energy consumption/24 h at 65 °C	kWh	2.70	3.00	3.40

Instantaneous water cylinder
Accessories 362

Instantaneous water cylinder

SBS 601-1501 W (W SOL)



SBS 601 W

Benefits

- Efficient operation through inlet device for demand-dependent, zoned charging
- Highly versatile, as it can be combined with various heat generators
- Space saving combination of heating buffer cylinder and DHW heating in a single unit
- Hygienic DHW heating through instantaneous water heater principle
- Additional application range thanks to integral solar indirect coil (Product: 229984, 229985, 229986, 229987)

Application • This combination instantaneous water cylinder is suitable for DHW heating. The appliance can be used both as a buffer cylinder for hydraulic separation between the heat pump and heating circuit, as well as for storing heating energy. • The instantaneous water cylinder is suitable for family houses, as well as apartment buildings with hydraulically interconnected appliances. • Integration of solar thermal backup is possible with SOL types.

Convenience features • The steel cylinder is equipped with an integral corrugated pipe indirect coil made of stainless steel, which ensures instantaneous DHW heating. • Connectors facing the front allow system-specific hydraulic connections. • An electric threaded immersion heater can be installed via the inspection port if required.

Efficiency • Low standby losses thanks to the high grade thermal insulation available as an accessory. • Matched inlet and outlet technology with integral PRO temp-Flow inlets ensures good temperature stratification. Flow turbulence is reduced by up to 60 percent.

		SBS 601 W	SBS 601 W SOL	SBS 801 W	SBS 801 W SOL
Part number		**229980**	**229984**	**229981**	**229985**
Specification					
Nominal capacity	l	613	599	759	740
Area of DHW cylinder heat exchanger	m²	6.00	6.00	6.50	6.50
Max. recommended collector aperture area	m²		12		16
Height incl. thermal insulation	mm	1,775	1,775	1,940	1,940
Diameter incl. thermal insulation	mm	970	970	1,010	1,010
Height when tilted	mm	1,840	1,840	1,880	1,880
Weight	kg	135	180	150	195
Required accessories					
Part number		**231925**	**231925**		
Type		WDH 601 SBS	WDH 601 SBS		
Description		Thermal insulation	Thermal insulation		
Part number				**231926**	**231926**
Type				WDH 801 SBS	WDH 801 SBS
Description				Thermal insulation	Thermal insulation
Recommended accessories					
Part number		**230312**	**230312**	**230312**	**230312**
Type		ZW 1 1/4	ZW 1 1/4	ZW 1 1/4	ZW 1 1/4
Description		DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder

		SBS 1001 W	SBS 1001 W SOL	SBS 1501 W	SBS 1501 W SOL
Part number		**229982**	**229986**	**229983**	**229987**
Specification					
Nominal capacity	l	941	916	1430	1399
Area of DHW cylinder heat exchanger	m²	8.70	8.70	10.00	10.00
Max. recommended collector aperture area	m²		20		30

next page >

Instantaneous water cylinder

		SBS 1001 W	SBS 1001 W SOL	SBS 1501 W	SBS 1501 W SOL
Height incl. thermal insulation	mm	2,350	2,350	2,265	2,265
Diameter incl. thermal insulation	mm	1,010	1,010	1,220	1,220
Height when tilted	mm	2,285	2,285	2,225	2,225
Weight	kg	175	220	236	291
Required accessories					
Part number		**231927**	**231927**		
Type		WDH 1001 SBS	WDH 1001 SBS		
Description		Thermal insulation	Thermal insulation		
Part number				**231928**	**231928**
Type				WDH 1501 SBS	WDH 1501 SBS
Description				Thermal insulation	Thermal insulation
Recommended accessories					
Part number		**230312**	**230312**	**230312**	**230312**
Type		ZW 1 1/4	ZW 1 1/4	ZW 1 1/4	ZW 1 1/4
Description		DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder	DHW circulation set, instantaneous water cylinder

The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors. The max. recommended collector aperture area relates to STIEBEL ELTRON flat-plate collectors. (Product: 229984)

Instantaneous water cylinder

Accessories
Accessories 366

WDH 601-1501 SBS




WDH 601 SBS

Benefits
- Graphite inserts for good insulation properties
- Two insulation semi-shells to make it easier to match the shape
- Composite thermal insulation made from rigid foam and fleece

Description • The high grade thermal insulation made from EPS rigid foam is supplied with insulated cover and floor disc. Graphite inserts in the EPS and the fleece ensure minimal heat losses. • The thermal insulation can be optimally adapted to the cylinder thanks to the wedge-shaped cut-outs and the fleece layer. The prepared adhesive joints in the wedge-shaped cut-outs also contribute to this. • The integrated quick-release hook strip makes it easier to attach the thermal insulation.

		WDH 601 SBS	WDH 801 SBS	WDH 1001 SBS	WDH 1501 SBS
Part number		**231925**	**231926**	**231927**	**231928**
Specification					
Insulation for		SBS 601 W, W SOL	SBS 801 W, W SOL	SBS 1001 W, W SOL	SBS 1501 W, W SOL
Thermal insulation thickness	mm	110	110	110	110
Standby energy consumption/24 h at 65 °C	kWh	2.60	2.90	3.50	4.10

ZW 1 1/4



ZW 1 1/4

Benefits
- The DHW circulation set is screwed onto the DHW connector
- The set comprises a tee and a stainless steel corrugated pipe
- Length: 950 mm (Product: 230312)

Description • The DHW circulation set for instantaneous water cylinders ensures quick and straightforward connection of the DHW circulation return to the DHW connection.

		ZW 1 1/4
Part number		**230312**
Specification		
Connection		G 1 1/4
DHW circulation connection		G 1/2

Buffer cylinder
Accessories 368

Buffer cylinder

SBP 100 classic



SBP 100 classic

Benefits
- Suitable for heating and cooling operation as the impermeable complete foam insulation on the buffer cylinder makes it suitable for cooling
- Particularly space saving for use in family homes
- Floorstanding buffer cylinder for integration into the heating system

Application • This buffer cylinder provides hydraulic separation between the heat pump and heating/cooling circuit.

Convenience features • The steel cylinder with directly applied foam insulation is equipped with a protective cover and connections at the top for ventilation and draining.

Efficiency • Reduced mixing due to matched inlet and outlet technology.

		SBP 100 classic
Part number		**235200**
Specification		
Energy efficiency class A+ -> F		C
Nominal capacity	l	100
Standby energy consumption/24 h at 65 °C	kWh	1.20
Height	mm	877
Diameter	mm	510
Height when tilted	mm	968
Weight	kg	21

SBP 200-400 Plus cool



SBP 200 Plus cool

Benefits
- Connector for an electric threaded immersion heater in both the upper and lower third
- More efficient operation with inverter heat pumps
- Suitable for both heating and cooling modes
- Prepared for self-consumption of electricity from photovoltaic systems
- New appealing design

Application • This round, floorstanding buffer cylinder with its attractive design is suitable for heat pump heating systems in family houses. • It stores heat for heating operation but can also be used for cooling operation.

Convenience features • The steel cylinder with directly applied foam insulation has hydraulic connectors arranged at the front one above the other. • The buffer cylinder ensures hydraulic separation between the primary and secondary circuits. It is designed for the connection of a heat pump with high flow rates in the primary circuit. • In the upper section, there is a connector for the installation of an electric threaded immersion heater for electric reheating. In the lower section, there is another connector for an electric threaded immersion heater for charging the buffer cylinder. This can be used to increase self-consumption of electricity from a photovoltaic system, for example.

Efficiency • Low standby losses. • Prepared for self-consumption of electricity from photovoltaic system.

		SBP 200 Plus cool	SBP 400 Plus cool
Part number		**205295**	**205296**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity	l	207	415
Standby energy consumption/24 h at 65 °C	kWh	1.235	1.719
Height	mm	1510	1700
Height when tilted	mm	1637	1867

next page >

Buffer cylinder

		SBP 200 Plus cool	SBP 400 Plus cool
Recommended accessories			
Part number		**003711**	**003711**
Type		ET SBP	ET SBP
Description		Inserts	Inserts

STH 210-415 C Plus



STH 210 C Plus

Benefits

- Connector for an electric threaded immersion heater in both the upper and lower third
- More efficient operation with inverter heat pumps
- Suitable for both heating and cooling modes
- Prepared for self-consumption of electricity from photovoltaic systems
- New appealing design

Application • This round, floorstanding buffer cylinder with its attractive design is suitable for heat pump heating systems in family houses. • It stores heat for heating operation but can also be used for cooling operation.

Convenience features • The steel cylinder with directly applied foam insulation has hydraulic connectors arranged at the front one above the other. • The buffer cylinder ensures hydraulic separation between the primary and secondary circuits. It is designed for the connection of a heat pump with high flow rates in the primary circuit. • In the upper section, there is a connector for the installation of an electric threaded immersion heater for electric reheating. In the lower section, there is another connector for an electric threaded immersion heater for charging the buffer cylinder. This can be used to increase self-consumption of electricity from a photovoltaic system, for example.

Efficiency • Low standby losses. • Prepared for self-consumption from a solar PV system.

		STH 210 C Plus	STH 415 C Plus
Part number		**205369**	**205370**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity	l	207	415
Standby energy consumption/24 h at 65 °C	kWh	1.163	1.719
Height	mm	1510	1700
Height when tilted	mm	1637	1867
Recommended accessories			
Part number		**003711**	**003711**
Type		ET SBP	ET SBP
Description		Inserts	Inserts

Buffer cylinder

SBP 200-700 E (SOL)



SBP 700 E

Benefits

- Easy to transport at the installation site as the casing can be removed if necessary
- Suitable for cooling due to complete thermal foam insulation of the cylinder
- Efficient thermal insulation allows use in heating and cooling modes
- Low standby losses for efficient operation
- Buffer cylinder for heating systems with heat pumps
- Additional application range thanks to integral solar indirect coil (Product: 185460)

Application • This buffer cylinder is suitable for heat pump heating systems in family houses (depending on the nominal capacity). It can also be used in cooling mode and enables hydraulic separation between the heat pump and heating circuit, extends the operating time of the heat pump and stores heating energy. • The buffer cylinder is designed for connecting heat pumps with high flow rates on the primary side. • Integration of solar thermal backup is possible with „SOL“ types.

Convenience features • The steel cylinder with directly applied foam insulation has hydraulic connectors arranged at the front, one above the other. Connectors are provided for installing electric threaded immersion heaters. • The SOL types also have an internal indirect coil for connection to a solar thermal system. • The cylinder casing consists of a plastic outer jacket, a cylinder cover and the plinth trim.

Efficiency • Low standby losses.

		SBP 700 E	SBP 700 E SOL
Part number		**185459**	**185460**
Specification			
Energy efficiency class A+ -> F		B	B
Nominal capacity	l	720	703
Surface area, heat exchanger, bottom	m²		2
Standby energy consumption/24 h at 65 °C	kWh	2.20	2.20
Height	mm	1890	1890
Diameter incl. thermal insulation	mm	910	910
Height when tilted	mm	2000	2000
Weight	kg	185	216
Recommended accessories			
Part number		**003711**	**003711**
Type		ET SBP	ET SBP
Description		Inserts	Inserts

Buffer cylinder

STH 210-720-1 Plus



STH 720 Plus

Benefits

- Easy to transport at the installation site as the casing can be removed if necessary
- Suitable for cooling due to complete thermal foam insulation of the cylinder
- Efficient thermal insulation allows use in heating and cooling modes
- Low standby losses for efficient operation
- Buffer cylinder for heat pump heating systems

Application • These buffer cylinders are suitable for heat pump heating systems and can also be used in cooling mode. • Provides hydraulic separation between the heat pump and the heating/cooling circuit, extends heat pump runtimes and stores heating energy. • Suitable for use in family houses, depending on nominal capacity. • A threaded immersion heater can be used to increase the PV self-consumption rate. The STH 720-1 Plus appliance can also be combined with a solar thermal system.

Convenience features • The steel cylinder with directly applied foam insulation has hydraulic connectors arranged at the front, one above the other. Connectors are also provided for electric threaded immersion heaters if required. • The cylinder casing consists of the plastic outer jacket, the cylinder cover and a plinth trim.

Efficiency • Low standby losses. • The buffer cylinders are designed for connecting heat pumps with high flow rates on the primary side.

		STH 720 Plus	STH 720-1 Plus
Part number		**203765**	**203766**
Specification			
Nominal capacity	l	720	703
Surface area, heat exchanger, bottom	m²		2
Standby energy consumption/24 h at 65 °C	kWh	2.20	2.20
Height	mm	1890	1890
Diameter incl. thermal insulation	mm	910	910
Height when tilted	mm	2000	2000
Weight	kg	185	216
Recommended accessories			
Part number		**003711**	**003711**
Type		ET SBP	ET SBP
Description		Inserts	Inserts

Availability on request

Buffer cylinder

SBP 1000-1500 E SOL



SBP 1000 E

Benefits

- Buffer cylinder for heating systems with large heat pumps
- Highly versatile, as it can be combined with various heat generators
- The buffer cylinder is designed for high flow rates with suitably sized flanged connections
- Additional application range thanks to integral solar indirect coil (Product: 227566)
- Suitable in multi storey construction thanks to extremely reliable operating pressure (Product: 236569)
- Additional flanged connection for special applications (Product: 236569)

Application • This buffer cylinder is combined with heating heat pumps in a large scale system and is suitable for use in apartment buildings and commercially used buildings. The appliance enables hydraulic separation between the heat pump and heating circuit flows, extends the operating time of the heat pump and stores heating energy.

Convenience features • The steel cylinder has flange connections arranged at the front, one above the other, for the primary and secondary circuit. There is also an additional connector for combination with further heat generators. An additional indirect coil or an electric flanged immersion heater can also be fitted as required for the specific system. For this purpose, a flanged aperture sealed with a blank flange has been integrated. The SOL types are, in addition, equipped with an internal smooth tube solar indirect coil.

Efficiency • Low standby losses in conjunction with the high grade thermal insulation as an accessory. • The matched inlet and outlet technology is responsible for the good temperature stratification. • The buffer cylinder is designed for connecting heat pumps with high flow rates on the primary side.

		SBP 1000 E	SBP 1000 E SOL	SBP 1010 E	SBP 1500 E	SBP 1500 E SOL
Part number		**227564**	**227566**	**236569**	**227565**	**227567**
Specification						
Nominal capacity	l	1006	979	1006	1503	1473
Surface area, heat exchanger, bottom	m²		3.00			3.60
Max. permissible pressure	MPa	0.30	0.30	1.00	0.30	0.30
Height incl. thermal insulation	mm	2340	2340	2340	2255	2255
Diameter incl. thermal insulation	mm	1010	1010	1010	1220	1220
Height when tilted	mm	2335	2335	2335	2250	2250
Weight	kg	172	219	233	229	285
Required accessories						
Part number				**201662**		
Type				WDH 1010 SBP		
Description				Thermal insulation		
Part number		**231929**	**231929**			
Type		WDH 1000 SBP	WDH 1000 SBP			
Description		Thermal insulation	Thermal insulation			
Part number					**231930**	**231930**
Type					WDH 1500 SBP	WDH 1500 SBP
Description					Thermal insulation	Thermal insulation
Recommended accessories						
Part number		**231884**	**231884**	**231884**	**231884**	**231884**
Type		BF 80 Set	BF 80 Set	BF 80 Set	BF 80 Set	BF 80 Set
Description		Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)

Buffer cylinder

SBP 1000-1500 E cool



SBP 1000 E cool

Benefits

- Suitable for either heating or cooling operation
- Buffer cylinder for heating systems with large heat pumps
- Suitable for cooling due to combination of thermal insulation and pre-insulated cylinder
- Suitable in multi storey construction thanks to extremely reliable operating pressure (Product: 236570)

Application • This buffer cylinder is combined with heat pumps in apartment buildings or in commercial buildings. • The appliance can be used for heating and cooling. At the same time, it enables hydraulic separation between the heat pump and heating circuit flows, extends the operating time of the heat pump and stores heating energy.

Convenience features • Pre-insulated steel cylinder with flange connections arranged at the front, one above the other, for the primary and secondary circuit. Additional connectors for combining with extra heat generators. • A flanged aperture sealed with a blank flange is provided, so that the cylinder can be fitted with an additional indirect coil or electric flanged immersion heater.

Efficiency • The cooling-compatible high grade thermal insulation as an accessory, together with the insulation applied to the cylinder, result in low standby losses. This combination is an essential requirement for the buffer cylinder cooling capability. • Matched inlet and outlet technology enables good temperature stratification. • The buffer cylinder is designed for connecting heat pumps with high flow rates on the primary side.

		SBP 1000 E cool	SBP 1010 E cool	SBP 1500 E cool
Part number		**227588**	**236570**	**227589**
Specification				
Nominal capacity	l	1006	1006	1503
Max. permissible pressure	MPa	0.30	1.00	0.30
Height incl. thermal insulation	mm	2340	2340	2255
Diameter incl. thermal insulation	mm	1010	1010	1220
Height when tilted	mm	2335	2335	2250
Weight	kg	181	242	239
Required accessories				
Part number		**231921**	**231921**	
Type		WDH 1000 cool	WDH 1000 cool	
Description		Thermal insulation	Thermal insulation	
Part number				**231922**
Type				WDH 1500 cool
Description				Thermal insulation
Recommended accessories				
Part number		**231884**	**231884**	**231884**
Type		BF 80 Set	BF 80 Set	BF 80 Set
Description		Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)	Set incl. blank flange or flange adaptor DN80 for buffer cylinder (2 pce)

Buffer cylinder

Accessories
Accessories 376

WPKI 5



WPKI 5-I

Benefits
- All parts are included in the compact installation
- Straightforward connection of a heating heat pump to a 200-700 litre buffer cylinder
- Only for heat pumps WITHOUT integral heating circuit pump
- Including insulation assembly for flow/return connector (Product: 205875)
- For heating heat pumps without integral circulation pump (Product: 205875)
- Integral non-return valve (Product: 205875)

Application • This compact installation includes all the components needed for the hydraulic connection of the heating heat pump to buffer cylinders with 200 to 700 litres. • The standard delivery includes: insulation, safety valve, thermometer/pressure gauge, shut-off valves, non-return valve and the option to connect a diaphragm expansion vessel, plus the DHW heating set. • The compact installation is only suitable for heating heat pumps without an integral heating circuit pump.

		WPKI 5-I
Part number		**205875**
Specification		
Connection		G 1 1/4
Max. operating pressure	MPa	0.30
Required accessories		
Part number		**201620**
Type		UP 25/7.5 PCV
Description		Heating circuit pump

BBI 5



BBI 5-I

Benefits
- Robust complete set for straightforward installation
- With integral non-return valve
- Only for heat pumps WITHOUT integral heating circuit pump
- Integral non-return valve (Product: 205877)

Description • The DHW heating kit is suitable for the compact installation of the buffer cylinder. • Contains all required components for the hydraulic connection of the heat pump to the DHW cylinder, including the insulation.

		BBI 5-I
Part number		**205877**
Specification		
Connection		G 1 1/4 / Cu 28 x 1.5
Max. operating pressure	MPa	0.30
Required accessories		
Part number		**201620**
Type		UP 25/7.5 PCV
Description		Heating circuit pump
Part number		**205875**
Type		WPKI 5-I
Description		WPKI 5 Compact installation

WPKI 6



WPKI 6-I

Benefits
- For heat pumps WITH an integral heating circuit pump
- Straightforward connection of a heating heat pump to a 200-700 litre buffer cylinder
- All parts are included in the compact installation
- Including insulation assembly for flow/return connector (Product: 205876)
- For heating heat pumps with integral circulation pump (Product: 205876)

Description • The compact installation is suitable for the hydraulic connection of the heating heat pump (with integral heating circuit pump) to buffer cylinders with 200-700 l capacity. • All necessary components, including the insulation, are supplied.

		WPKI 6-I
Part number		**205876**
Specification		
Connection		G 1 1/4
Max. operating pressure	MPa	0.30

ET SBP



Benefits
- SBP connection accessories
- For a tight fitting pipe connection without compact installation
- Standard delivery: 4 inserts, 4 gaskets, 4 G4 union nuts

Description • The adaptor fittings with female threads are suitable for the hydraulic connection of buffer cylinders with 200-700 l capacity. • The fittings are only required if a compact installation is not used.

ET SBP

		ET SBP
Part number		**003711**

BF FG Set



BF 80 Set

Benefits
› Flange diameter DN 80
› Material: steel

Description • Blank flange or flange adaptor. The set consists of two pieces per package.

		BF 80 Set
Part number		**231884**
Specification		
Flange diameter		DN 80

incl. gasket and screws
Set consists of 2 x BF 80 (Product: 231884)

BF FG



BF 80

Description • Blank flange or flange adaptor DN 80 for buffer cylinder

		BF 80
Part number		**205090**
Specification		
Flange diameter		DN 80

incl. gasket and screws

WDH 1000-1500 SBP



WDH 1010 SBP

Benefits
- Composite thermal insulation made from rigid foam and fleece
- Graphite inserts for good insulation properties
- Two insulation semi-shells to make it easier to match the shape

Description • The high grade thermal insulation made from EPS rigid foam is supplied with insulated cover and floor disc. Graphite inserts in the EPS and the fleece ensure minimal heat losses. • The thermal insulation can be optimally adapted to the cylinder thanks to the wedge-shaped cut-outs and the fleece layer. The prepared adhesive joints in the wedge-shaped cut-outs also contribute to this. • The integrated quick-release hook strip makes it easier to attach the thermal insulation.

		WDH 1010 SBP	WDH 1000 SBP	WDH 1500 SBP
Part number		**201662**	**231929**	**231930**
Specification				
Insulation for		SBP 1010 E	SBP 1000 E and E SOL	SBP 1500 E and E SOL
Thermal insulation thickness	mm	110	110	110
Standby energy consumption/24 h at 65 °C	kWh	3.60	3.60	4.10

WDH 1000-1500 cool



WDH 1000 cool

Benefits
- Composite thermal insulation made from rigid foam and fleece
- Graphite inserts for good insulation properties
- Two insulation semi-shells to make it easier to match the shape
- A pre-insulated cylinder can be used for cooling in conjunction with this thermal insulation

Description • The high grade thermal insulation made from EPS rigid foam is supplied with insulated cover and floor disc. Graphite inserts in the EPS and the fleece ensure minimal heat losses. • The thermal insulation can be optimally adapted to the cylinder thanks to the wedge-shaped cut-outs and the fleece layer. The prepared adhesive joints in the wedge-shaped cut-outs also contribute to this. • The integrated quick-release hook strip makes it easier to attach the thermal insulation.

		WDH 1000 cool	WDH 1500 cool
Part number		**231921**	**231922**
Specification			
Insulation for		SBP 1000 E cool and SBP 1010 E cool	SBP 1500 E cool
Thermal insulation thickness	mm	110	110
Standby energy consumption/24 h at 65 °C	kWh	3.50	4.00

Electric threaded immersion heaters and flanged immersion heaters
Accessories 382

Electric threaded immersion heaters and flanged immersion heaters

BGC




Benefits
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

Application • This threaded immersion heater is suitable for sealed unvented heating systems and DHW heating systems. • The temperature can be variably adjusted; temperature limitation is possible. • The integral temperature controller is equipped with a high limit safety cut-out.

BGC 6 kW 500 mm ET

		BGC 6 kW 500 mm ET	BGC/45	BGC 2/60
Part number		**003769**	**075115**	**232030**
Specification				
Connected load ~ 230 V	kW	2-5,7	2-5,7	2-5,7
Connected load ~ 400 V	kW	6	6	6
Power supply		1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE
Rated voltage	V	230/400	230/400	230/400
Frequency	Hz	50/60	50/60	50/60
Version		Universal flange	Universal flange	Universal flange
IP rating		IP44	IP44	IP44
Immersion depth	mm	500	455	480

FCR



Benefits
- Replaceable copper heating element
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

Description • The flanged immersion heaters are suitable for horizontal installation in unvented DHW cylinders with flange connectors to DIN 4805. • The temperature can be variably adjusted. It is possible to limit the temperature. • Please note the details supplied by the cylinder manufacturer, as well as DIN 4753 and DIN 4751.

FCR 21/60

		FCR 21/60	FCR 21/120 E	FCR 28/120	FCR 28/120 E
Part number		**071330**	**071331**	**071332**	**000694**
Specification					
Connected load ~ 230 V	kW	2-4	4		
Connected load ~ 400 V	kW	2-6	8/12	6/12	12
Power supply		1/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/PE	3/PE	3/PE
Rated voltage	V	230/400	230/400	400	400
Coil voltage	V	230	230	230	400
Frequency	Hz	50/60	50/60	50	50

next page >

		FCR 21/60	FCR 21/120 E	FCR 28/120	FCR 28/120 E
Version		Dual/single circuit	Single circuit	Dual/single circuit	Single circuit
Integral contactor		X	-	X	X
IP rating		IP24	IP24	IP24	IP24
Immersion depth	mm	400	400	450	325
Flange diameter	mm	210	210	280	280

		FCR 28/120 CrNi	FCR 28/180	FCR 28/180 E
Part number		**234503**	**071333**	**000695**
Specification				
Connected load ~ 400 V	kW	6/12	9/18	18
Power supply		3/PE	3/PE	3/PE
Rated voltage	V	400	400	400
Coil voltage	V	230	230	400
Frequency	Hz	50	50	50
Version		Dual/single circuit	Dual/single circuit	Single circuit
Integral contactor		X	X	X
IP rating		IP24	IP24	IP24
Immersion depth	mm	450	450	325
Flange diameter	mm	280	280	280

(Product: 000694)

Temperature controller with frost protection setting (external), temperature limit possible, integral pushbutton for rapid heat-up, high limit safety cut-out, flange gasket, protective cover with two cable entries. (Product: 071330)

Temperature controller with frost protection setting, high limit safety cut-out, flange gasket, protective cover with two cable entries. (Product: 000694) , 000695)
(Product: 000694)

WPRB



Benefits
- Pipe assembly for WPL and WPF-M heating heat pumps
- 1 1/4 inch connection
- Length: ${att.ef001438.value} ${att.ef001438.unit} (Product: 074233)

Description • Pipe assembly for electric threaded immersion heater for electrical reheating.

WPRB

		WPRB
Part number		**074233**

DHW heating
Accessories 386
Heating system hydraulics
Accessories 388
Additional accessories
Accessories 399

UPZ



UPZ

Benefits
- Highly efficient DHW circulation pump
- Time switch included in standard delivery
- Adjustable shutdown temperature
- Low heat losses thanks to high grade insulation shell

Application • DHW circulation pump with automatic ventilation mode, suitable for detached houses and apartment buildings. • The highly efficient DHW circulation pump can be controlled via the electronic control thermostat and/or the time switch. • The pump shutdown temperature can be adjusted by means of a rotary selector – this allows the pump runtime and the electronic energy demand for DHW provision to be reduced to a minimum. • Insulation shell, time switch and non-return valve are included in the standard delivery.

		UPZ
Part number		**233719**
Specification		
Connection		G 1/2
Power consumption	W	2 - 27
Rated voltage	V	220-240
Control via 0-10 V signal with IF module		-
Control via PWM signal		-
Installation length (centre distance)	mm	65

UP B



UP 25-60-180

Benefits
- Circulation pump, DHW circuit
- 3-stage electronic control
- Inserts included in the delivery

Description • The circulation pump for the DHW circuit can be controlled electrically in three stages. • Inserts are included in the standard delivery.

		UP 25-60-180
Part number		**056899**
Specification		
Connection		G 2
Power consumption	W	46/67/93
Rated voltage	V	230
Installation length (centre distance)	mm	180

WT




Benefits
- The plate heat exchanger consists of multiple hard-soldered stainless steel plates
- For DHW heating or swimming pool water heating

Description • The plate heat exchanger comprising several hard-soldered stainless steel plates is suitable for DHW heating or swimming pool heating. • The heat exchanger is supplied with thermal insulation. • Observe application limits.

WT 30

		WT 30	WT 40
Part number		**071091**	**229338**
Specification			
Output	kW	40	50
Primary pressure drop	hPa	90	120
Secondary pressure drop	hPa	60	200
Height	mm	313	313
Width	mm	113	113
Depth	mm	173.5	219.7
Weight	kg	8.0	10.2

FS-WP



Benefits
- Easily removable filter element
- Brass body
- Can be installed vertically or horizontally
- With backflushing facility (Product: 233511)
- With a removable filter (Product: 233512)

Description • The filter to protect the heat pump against impurities is installed in the return of the heat generator.

FS-WP 22

		FS-WP 22	FS-WP 28
Part number		**233511**	**233512**
Specification			
Connection		G 1 A / Cu 22 x 1	G 1 1/4 A / Cu 28 x 1.5

MFS-WP



Benefits
- Filter set with pressure gauge
- Backflushing facility included
- Replaceable strainers in the dirt traps
- With removable filter element, pressure gauge and ball valve (Product: 235234)

Description • The filter to protect the heat pump against impurities is installed in the return of the heat generator. • The integral pressure gauge shows the system pressure.

MFS-WP 28

		MFS-WP 28
Part number		**235234**
Specification		
Connection		G 1 1/4 A / Cu 28 x 1.5

AHP-PS



AHP-PS.1

Benefits
- Sludge separator for heating systems
- Reduces energy consumption, extends the service life

Description • The sludge separator reduces energy consumption and wear in closed heating systems. It protects your heating system by removing suspended particles from the heating water. Otherwise, these particles could clog pumps, heat exchangers, and pipes, thus reducing the system's efficiency.

		AHP-PS.1	AHP-PS.2	AHP-PS.3
		NEW	NEW	NEW
Part number		**208668**	**208669**	**208670**
Specification				
Connection		DN 25	DN 32	DN 65

UP



UP 25/7.5 PCV

Benefits
- Electronically controlled circulation pump with variable differential control
- Energy efficiency index (EEI): 0.20
- Can be controlled via either a PWM signal or differential pressure (Product: 201620)
- Delivery head max. 10 m (Product: 201620, 205285, 205286, 205288, 206633)
- 0-10 V actuation possible with IF module (Product: 206633, 206636)
- Delivery head max. 12 m (Product: 206636)

Description • The heating circuit pump is particularly energy efficient, as electronic output control is integrated for pumping the heat transfer medium, as is variable differential control.

		UP 25/7.5 PCV	UP 25/1-8 PCV	UP 30/1-8 PCV	UP 30/1-10 PCV	UP 40/1-8 E	UP 50/1-12 E
Part number		**201620**	**205285**	**205286**	**205288**	**206633**	**206636**
Specification							
Energy Efficiency Index EEI		0.20	0.20	0.20	0.20	0.23	0.23
Connection		G 1 1/2	G 1 1/2	G 2	G 2	DN 40	DN 50
Delivery head	m	8.40	8.00	8.00	10.00	8.00	12.00
Max. flow rate	m³/h	4.00	9.50	9.00	10.00	15.00	29.00
Power consumption	W	10-60	200	130	200	12-310	25-590
Rated voltage	V	230	230	230	230	230	230
Control via 0-10 V signal with IF module		-	x	x	x	x	x
Control via differential pressure		x	x	x	x	x	x
Control via PWM signal		x	x	x	x	-	-
Installation length (centre distance)	mm	180	180	180	180	220	280

Standard delivery: Insulation shell (Product: 201620)

WPKI-HK



WPKI-HK DN 25

Benefits
- Pump assembly for heating circuit without mixer
- For combination with buffer cylinders

Description • The pump assembly is suitable for one heating circuit without mixer. The standard delivery includes the integral high efficiency heating circuit pump, shut-off valves with thermometer and gravity brake, including opening mechanism and the EPP complete insulation set with wall mounting bracket. • The pump assembly can be installed either directly on the buffer cylinder or on the wall.

		WPKI-HK DN 25
Part number		**206627**
Specification		
Connection, above		G 1
Connection, below		G 1 1/2 A
Circulation pump type		Wilo Para SC 25/6-43
Height	mm	383
Width	mm	250
Depth	mm	213
Energy Efficiency Index EEI		0.20
Delivery head	m	6.70
Max. flow rate	m³/h	7.80

WPKI-HKM E



WPKI-HKM E 24

Benefits
- Pump assembly for heating circuit with mixer
- Complete with built-in high efficiency pump and 24 V mixer motor
- Including thermal insulation and wall mounting bracket

Description • Pump assembly for one heating circuit with mixer. • Included in the standard delivery are the integral high efficiency pump, a 24 V mixer motor, shut-off valves and thermometers for the flow and return. Also included in the standard delivery are a gravity brake and the EPP complete insulation set with wall mounting bracket. • The pump assembly can be installed either on the buffer cylinder or on the wall.

		WPKI-HKM E 24
Part number		**206300**
Specification		
Connection, above		G 1
Connection, below		G 1 1/2 A
Circulation pump type		Wilo Para SC 25/6-43
Height	mm	383
Width	mm	250
Depth	mm	245
Energy Efficiency Index EEI		0.20
Delivery head	m	6.70
Max. flow rate	m³/h	6.00

WPKI-HKM 24



WPKI-HKM 24 DN 32

Benefits
- Including thermal insulation and wall mounting bracket
- Complete with built-in high efficiency pump and 24 V mixer motor
- Pump assembly for heating circuit with mixer

Description • Pump assembly for one heating circuit with mixer. • Included in the standard delivery are the integral high efficiency pump, a 24 V mixer motor, shut-off valves and thermometers for the flow and return. Also included in the standard delivery are a gravity brake and the EPP complete insulation set with wall mounting bracket. • The pump assembly can be installed either on the buffer cylinder or on the wall.

		WPKI-HKM 24 DN 32	WPKI-HKM 24 DN 40
Part number		**206628**	**206632**
Specification			
Connection, above		G 1 1/4 I	1 1/2 I
Connection, below		G 2 A	DN 40 PN6
Circulation pump type		Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	mm	441	811
Width	mm	250	320
Depth	mm	293	554
Energy Efficiency Index EEI		0.20	0.20
Delivery head	m	10.00	12.00
Max. flow rate	m³/h	11.40	17.70

WPKI-HKM 230



WPKI-HKM 230 DN 25

Benefits
- Heating circuit assembly with mixing valve
- Complete with high efficiency pump, shut-off valves and gravity valves
- Including thermal insulation and wall mounting bracket
- Complete with built-in high efficiency pump and 230 V mixer motor
- Pump assembly for heating circuit with mixer

Description • Pump assembly for one heating circuit with mixer. • Included in the standard delivery are the integral high efficiency pump, a 230 V mixer motor, shut-off valves and thermometers for the flow and return. Also included in the standard delivery are a gravity brake and the EPP complete insulation set with wall mounting bracket. • The pump assembly can be installed either on the buffer cylinder or on the wall.

		WPKI-HKM 230 DN 25
Part number		**206631**
Specification		
Connection, above		G 1
Connection, below		G 1 1/2 A
Circulation pump type		Wilo Para SC 25/6-43
Height	mm	383
Width	mm	250
Depth	mm	245
Energy Efficiency Index EEI		0.20
Delivery head	m	6.00
Max. flow rate	m³/h	5.70

WPKI-HKV 2



Benefits
- Straightforward installation of two pump assemblies next to each other
- Makes it easier to ensure a tidy, visually appealing installation
- EPP thermal insulation included in the delivery

Description • The manifold is suitable for the fast and visually high quality installation of up to two heating circuit pump assemblies. • The standard delivery includes the high grade EPP insulation and all required fittings for wall mounting the manifold.

WPKI-HKV 2

		WPKI-HKV 2
Part number		**206638**
Specification		
Connection		DN 25

WPKI-HKV 3



Benefits
- Straightforward installation of up to three pump assemblies next to each other
- Makes it easier to ensure a tidy, visually appealing installation
- EPP thermal insulation included in the delivery

Description • The manifold is suitable for the fast and visibly high quality installation of up to three heating circuit pump assemblies. • The standard delivery includes the high grade EPP insulation and all required fittings for wall mounting the manifold.

WPKI-HKV 3

		WPKI-HKV 3
Part number		**206637**
Specification		
Connection		DN 25

HUV



HUV 65

Benefits
- The actuator is ready for operation and mounted on the 3-way changeover valve
- Can be installed vertical to horizontal
- Maintenance-free

Description • The 3-way heating changeover valve with actuator is suitable for installation in heating systems.

		HUV 65	HUV 80
Part number		**227425**	**227426**
Specification			
Connection		DN 65	DN 80
kVS value	m³/h	58	90
IP rating		IP54	IP54
Protection class		II reinforced insulation	
Runtime		7.5 s/mm (18 mm)	7.5 s/mm (18 mm)
Weight	kg	16.30	22.50

HUV-L



HUV 1.1

Benefits
- Maintenance-free
- Can be installed vertical to horizontal

Description • The 3-way heating changeover valve with included actuator is suitable for upright or horizontal installation in central heating systems. • L-ball for leakage rate A according to DIN EN 12266. • The maintenance-free valve features short switching times and easy change of rotation direction via jumper. • The actuator is factory-matched to the valve.

		HUV 1.1	HUV 2.1
		NEW	NEW
Part number		**208004**	**208320**
Specification			
Connection		G 1 1/4	G 1 1/2
kVS value	m³/h	15.5	25
Leakage rate		A (EN 12266-1)	A (EN 12266-1)
IP rating		IP42	IP42

WPHW



WPHW 25

Benefits
- Hydraulic separation of heating circuit and heat pump
- Quick installation

Description • The low loss header provides hydraulic separation between the heat pump and the heating circuit. Standard delivery includes an air separator and a dirt trap. • The welded casing with connectors is fully insulated and equipped with automatic float air vent valves, sensor pockets for return sensors and drain valve.

		WPHW 25
Part number		**221135**
Specification		
Connection, heating system		G 1 1/2
Connection, heat pump		G 1 1/2
Flow rate	m³/h	2

HZEA



HZEA

Benefits
- Water softening device
- Ion resin cartridge incl. flat gasket included in the standard delivery
- Suitable for flow temperatures of up to max. 100 degrees Celsius
- The volume of softened water is subject to the level of hardness in the water (Product: 230013)

Description • The heating water softening device is used to fill or top up heating systems. • The fitting is installed in the cold water pipe, directly downstream of the system separator. • The water passes through an acidic and high efficiency ion exchange resin. • Depending on the system volume, the appropriate number of refill cartridges must be kept in stock for the initial filling.

		HZEA
Part number		**230013**
Specification		
Max. flow rate	m³/h	0.30

HZEN



HZEN

Benefits
- Refill cartridge for water softening device
- The volume of softened water is subject to the level of hardness in the water (Product: 230031)

Description • Replacement cartridge for the HZEA heating water softening device.

		HZEN
Part number		**230031**
Specification		
Max. permissible pressure	MPa	0.80
Weight	kg	1.20
Capacity	l x °dH	6000
Required accessories		
Part number		**230013**
Type		HZEA
Description		Heating water softening device

SD..G/GE



Benefits
- Pressure hose for flow or return line

Description • The vapour diffusion-proof pressure hoses with straight end pieces, for flow and return lines, are supplied including thermal insulation and threaded fittings.

SD 25-1 G

		SD 25-1 G	SD 25-2 GE	SD 25-2.5 GE	SD 32-0.6 G
Part number		**232976**	**233828**	**232971**	**201710**
Specification					
Connection, heating and source side		G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4
For pressure hose size DN		25	25	25	32
Length	m	1	2	2.5	
Max. operating pressure	bar	3.00	3.00	3.00	
Thermal insulation thickness	mm	19	30	30	
External diameter incl. insulation	mm	80	99	99	

next page >

		SD 32-1 G	SD 32-2 GE	SD 40-0.8 G
Part number		**232977**	**233831**	**201711**
Specification				
Connection, heating and source side		G 1 1/4	G 1 1/4	
For pressure hose size DN		32	32	40
Length	m	1	2	
Max. operating pressure	bar	3.00	3.00	
Thermal insulation thickness	mm	19	30	
External diameter incl. insulation	mm	86	106	

Without thermal insulation (Product: 201710) , 201711)

SD..E



Benefits
- Pressure hose for flow or return line
- High grade thermal insulation

Description • The vapour diffusion-proof pressure hoses with one right angle and one straight end piece for flow and return lines are supplied including thermal insulation and threaded fittings.

SD DN25-1 E

		SD DN25-1 E	SD 25-1 E	SD 32-1 E	SD DN32-1 E	SD 50-1 E
Part number		**074415**	**232965**	**232968**	**074414**	**232972**
Specification						
Connection, heating and source side		G 1 1/4	G 1 1/4	G 1 1/4	G 1 1/4	G 2
For pressure hose size DN		25	25	32	32	50
Length	m	1	1	1	1	1
Max. operating pressure	bar	2.50	2.50	2.50	2.50	2.50
Thermal insulation thickness	mm	19	30	30	19	50
External diameter incl. insulation	mm	80	99	106	86	134

SD..KE



Benefits
- Pressure hose for flow or return line
- High grade thermal insulation

Description • The vapour diffusion-proof pressure hoses (which can be trimmed), for flow and return lines, are supplied inclusive of thermal insulation and threaded fittings.

SD 25-1 KE

		SD 25-1 KE	SD 32-1 KE
Part number		**232974**	**232975**
Specification			
Connection, heating and source side		G 1 1/4	G 1 1/4
For pressure hose size DN		25	32
Length	m	1	1
Max. operating pressure	bar	2.50	2.50
Thermal insulation thickness	mm	30	30
External diameter incl. insulation	mm	99	106

SV DS



Benefits
- Available for DN 25 and DN 32
- Two-piece set

Description • Hose fitting for trimming pressure hoses with threaded fittings.

SV DS 25

		SV DS 25	SV DS 32
Part number		**003713**	**070692**

FS-HP



Benefits
› Liquid and gaseous media in the pipework are monitored by the FS-HP flow switch

Description • The FS-HP flow switch can be used to reliably monitor liquid and gaseous media in pipelines. • A connection adaptor to G 1/4“ and a five metre PUR cable with a 1/2“ plug-in connection are included in the standard delivery.

FSHP-L45

		FSHP-L45
Part number		**202779**

STB-FB



STB-FB

Benefits
- High limit safety cut-out for underfloor heating
- Setting of the maximum flow temperature
- Installation on the heating pipe

Description • The contact thermostat made of bimetal limits the maximum permissible flow temperature. A casing is included in the standard delivery.

		STB-FB
Part number		**233711**
Specification		
Temperature setting range	°C	20-90
Switching hysteresis	K	8±3
IP rating		IP30

Additional accessories

Central ventilation units 403

Accessories, central ventilation units 425

Distribution system for integral and central ventilation 437

Application areas

Air flow rate

	m³/h	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
VRC-W 450 Premium																						
VRC-W 600 Premium																						

	m³/h	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
VRC-W 450 E Premium																						
VRC-W 600 E Premium																						

	m³/h	0	50	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000
VRC-W 400																						
VRC-W 400 E																						

	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LWZ 180																																					
LWZ 280																																					

	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LWZ 180 Enthalpie																																					
LWZ 280 Enthalpie																																					



	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LWZ 70 E																																					



	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LWZ 130																																					



	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LWZ 130 Enthalpie																																					

Supply and extract air with heat recovery, wall mounting

- **VRC-W 450/600 Premium** 404
- **VRC-W 450/600 E Premium** 407
- **VRC-W 400/400 E** 410
- **LWZ 180/280** 412
- **LWZ 180/280 E** 415
- **LWZ 70 E** 417

Supply and extract air with heat recovery, ceiling mounting

- **LWZ 130** 420
- **LWZ 130 E** 422

Supply and extract air with heat recovery, wall mounting

VRC-W 450/600 Premium



VRC-W 450 Premium

Benefits

- Central supply and extract air system for optimum air quality
- Durable and hygienic polymer heat exchanger with high thermal efficiency
- Well designed condensate drain prevents water leaks even in tropical climates
- Efficient operation through by the constant flow rate fan, which ensures a balanced air flow rate
- Balanced flow rate in winter by means of integral preheating coil
- The programming unit can also be used as a remote control for ventilation regulated by the humidity sensor
- Easy electrical installation as the connection panel is readily accessible even when the appliance is closed
- Convenient CO2-controlled ventilation via the removable programming unit that can be used as a remote control

Application • This central ventilation unit is suitable for use in family houses, apartments and small commercial properties. • It is distinguished by its high air flow rate and heat recovery for ventilation.

Convenience features • The ventilation unit boasts a compact, aesthetic design with ergonomic user interface. Remote control with matrix display; eleven languages available. • Easy and convenient control of the appliance via WLAN and the MyStiebel APP for a comfortable climate. • The MyStiebel app is the platform for remote operation of many STIEBEL ELTRON appliances and systems, such as ventilation systems and heat pumps • Electric preheating via high performance heating coil. • Energy savings thanks to bypass duct with damper in the supply air line for passive cooling/heating. • Multiple sensors for temperature, humidity and CO2/VOC for zone control. • Separate filter cover. Simple filter changing thanks to individually replaceable frame filters. HEPA filter against COVID-19 and PM2.5 available as accessory. • Powder coated sheet steel casing.


Efficiency • High thermal efficiency and high moisture recovery. Energy savings with both cooling and heating functions. • High efficiency cross-countercurrent heat exchanger. • High electrical efficiency (SPI) of the integral EC fan with constant air flow rate control.

Installation • Installation in dwellings, utility rooms, basements, etc. The air connections are located at the top of the appliance and the electrical connection panel can be easily accessed. • The appliance can be converted on site for right or left-side connection in just a few simple steps, thereby offering maximum flexibility during installation. • Easy maintenance: Heat exchangers and filters can be serviced without tools.

		VRC-W 450 Premium	VRC-W 600 Premium
Part number		**204940**	**204714**
Specification			
Heat recovery level up to	%	94.5	90
Filter class		ePM1 ≥ 50 % (F7) | ISO Coarse > 60 % (G4)	ePM1 ≥ 50 % (F7) | ISO Coarse ≥ 65 % (G4)
Sound power level (EN 12102)	dB(A)	48,5	53,7
Height	mm	975	975
Width	mm	740	740
Depth	mm	655	655
Air connection diameter	mm	180	180
WLAN		802.11b/g/n/ 2.4 GHz/DHCP	802.11b/g/n/ 2.4 GHz/DHCP
Weight	kg	58.6	58.6
Rated voltage	V	230	230
Air flow rate	m³/h	110 - 450	150 - 600
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-40.35	-38.30
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-41.69	-39.99
Energy efficiency class, moderate climates, time control A+ -> G		A	A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A	A
Energy efficiency class A+ -> G		A+	A
Recommended accessories			
Part number		**206612**	**206612**
Type		FEB 2.1	FEB 2.1
Description		Control unit for central ventilation	Control unit for central ventilation


next page >

		VRC-W 450 Premium	VRC-W 600 Premium
Maintenance			
Part number		**206596**	**206596**
Type		FMK EPM1 55-2 W450/600	FMK EPM1 55-2 W450/600
Description		Filter cassette set F7, 2 pce	Filter cassette set F7, 2 pce
Part number		**206610**	**206610**
Type		FMS EPMC 65-10 W450/600	FMS EPMC 65-10 W450/600
Description		Filter mat set	Filter mat set



		VRC-W 450 Premium	VRC-W 600 Premium
a10 Appliance - height	mm	972	972
a20 Appliance - width	mm	745	745
a30 Appliance - depth	mm	655	655
b07 Electrical connection - electrical connection		•	•
d45 Condensate drain		•	•
g03 Outdoor air - diameter	mm	180	180
g04 Exhaust air - diameter	mm		180
g05 Extract air - diameter	mm	180	
g06 Supply air		–	•
g06 Supply air - diameter	mm	180	180
i13 Wall mounting bracket		•	•

Minimum clearance diagram



VRC-W 450/600 E Premium



VRC-W 450 E Premium

Benefits
- Central supply and extract air system for optimum air quality
- Durable and hygienic polymer heat exchanger with high thermal efficiency
- Moisture in the air is recovered by means of the integral enthalpy heat exchanger
- Well designed condensate drain prevents water leaks even in tropical climates
- Efficient operation through by the constant flow rate fan, which ensures a balanced air flow rate
- Balanced flow rate in winter by means of integral preheating coil
- The programming unit can also be used as a remote control for ventilation regulated by the humidity sensor
- Easy electrical installation as the connection panel is readily accessible even when the appliance is closed
- Convenient CO2-controlled ventilation via the removable programming unit that can be used as a remote control

Application • This central ventilation unit is suitable for use in family houses, apartments and small commercial properties. • It is distinguished by its high air flow rate and heat recovery for ventilation.

Convenience features • The ventilation unit boasts a compact, aesthetic design with ergonomic user interface. Remote control with matrix display; eleven languages available. • Easy and convenient control of the appliance via WLAN and the MyStiebel APP for a comfortable climate. • The MyStiebel app is the platform for remote operation of many STIEBEL ELTRON appliances and systems, such as ventilation systems and heat pumps • Electric preheating via high performance heating coil. • Energy savings thanks to bypass duct with damper in the supply air line for passive cooling/heating. • Multiple sensors for temperature, humidity and CO2/VOC for zone control. • Separate filter cover. Simple filter changing thanks to individually replaceable frame filters. HEPA filter against COVID-19 and PM2.5 available as accessory. • Powder coated sheet steel casing.

Efficiency • High thermal efficiency and high moisture recovery. Energy savings with both cooling and heating functions. • High efficiency cross-countercurrent heat exchanger. • High electrical efficiency (SPI) of the integral EC fan with constant air flow rate control.


Installation • Installation in dwellings, utility rooms, basements, etc. The air connections are located at the top of the appliance and the electrical connection panel can be easily accessed. • The appliance can be converted on site for right or left-side connection in just a few simple steps, thereby offering maximum flexibility during installation. • Easy maintenance: Heat exchangers and filters can be serviced without tools.

		VRC-W 450 E Premium	VRC-W 600 E Premium
Part number		**204941**	**204715**
Specification			
Heat recovery level up to	%	77	74.8
Filter class		ePM1 ≥ 50 % (F7) | ISO Coarse > 60 % (G4)	ePM1 ≥ 50 % (F7) | ISO Coarse ≥ 65 % (G4)
Sound power level (EN 12102)	dB(A)	48,5	53,7
Height	mm	975	975
Width	mm	740	740
Depth	mm	655	655
Air connection diameter	mm	180	180
WLAN		802.11b/g/n/ 2.4 GHz/DHCP	802.11b/g/n/ 2.4 GHz/DHCP
Weight	kg	61.2	61.2
Rated voltage	V	230	230
Air flow rate	m³/h	110 - 450	150 - 600
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-37.07	-34.99
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-38.71	-36.98
Energy efficiency class, moderate climates, time control A+ -> G		A	A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A	A
Energy efficiency class A+ -> G		A+	A

next page >


Supply and extract air with heat recovery, wall mounting

		VRC-W 450 E Premium	VRC-W 600 E Premium
Recommended accessories			
Part number		**206612**	**206612**
Type		FEB 2.1	FEB 2.1
Description		Control unit for central ventilation	Control unit for central ventilation
Maintenance			
Part number		**206596**	**206596**
Type		FMK EPM1 55-2 W450/600	FMK EPM1 55-2 W450/600
Description		Filter cassette set F7, 2 pce	Filter cassette set F7, 2 pce
Part number		**206610**	**206610**
Type		FMS EPMC 65-10 W450/600	FMS EPMC 65-10 W450/600
Description		Filter mat set	Filter mat set




		VRC-W 450 E Premium	VRC-W 600 E Premium
a10 Appliance - height	mm	972	974
a20 Appliance - width	mm	745	740
a30 Appliance - depth	mm	655	655
b07 Electrical connection - electrical connection		•	•
d45 Condensate drain		•	•
g03 Outdoor air - diameter	mm		180
g04 Exhaust air - diameter	mm		180
g05 Extract air		•	
g05 Extract air - diameter	mm	180	180
g06 Supply air		•	•
g06 Supply air - diameter	mm	180	180
i13 Wall mounting bracket		•	•

Minimum clearance diagram



Supply and extract air with heat recovery, wall mounting

VRC-W 400/400 E



VRC-W 400

Benefits

- For apartments, family houses and commercial properties with an area of up to 250 m²
- Central supply and extract air system for optimum air quality
- Efficient operation through by the constant flow rate fan, which ensures a balanced air flow rate
- Simple to control via the ergonomic programming unit
- Balanced flow rate in winter by means of integral preheating coil
- The programming unit can also be used as a remote control for ventilation regulated by the humidity sensor
- During the hot summer nights, temperature is reduced by means of the integral bypass module
- Pollutants are continuously removed from the living space
- Easy electrical installation as the connection panel is readily accessible even when the appliance is closed
- An enthalpy heat exchanger is built in for recovering moisture in the winter (Product: 203637)

Application • This central ventilation unit with heat recovery is used for ventilating family houses, large apartments and small commercial properties.

Convenience features • Contemporary design with ergonomically arranged programming unit. • The integral controller is equipped with a multifunction display and seven-day program and can also be used as a remote control. • The appliance offers a wide range of benefits: highly efficient, backwards-curved fan with constant flow rate control, highly efficient cross-countercurrent heat exchanger, electric preheating via high performance heating coil, bypass damper in the supply air duct. • The integral humidity sensor in the extract air can be used for humidity-dependent control of the air flow rate. • Easy filter change via combi filter cassette. Fine dust filters are available as an accessory. • The duplex sheet steel casing has a visible surface with alpine white powder coated finish.

Efficiency • The backwards-curved constant flow rate fans with air flow rate control ensure balanced air flow rates, thereby promoting efficient operation.

Installation • Installation in apartments, utility rooms, basement rooms, etc. • The air connections are located at the top of the unit; the electrical connection panel can be easily accessed without having to open the unit.

		VRC-W 400	VRC-W 400 E
Part number		**203636**	**203637**
Specification			
Heat recovery level up to	%	94	89
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)	ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)
Sound power level (EN 12102)	dB(A)	50	49,6
Height	mm	997	997
Width	mm	690	690
Depth	mm	534	534
Air connection diameter	mm	160	160
Weight	kg	78	80
Rated voltage	V	230	230
Air flow rate	m³/h	60-400	60-400
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-37.96	-35.33
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-40.18	-37.28
Energy efficiency class, moderate climates, time control A+ -> G		A+	A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A	A
Energy efficiency class A+ -> G		A	A
Recommended accessories			
Part number		**205018**	**205018**
Type		FEB 2.0	FEB 2.0
Description		Control unit for central ventilation	Control unit for central ventilation
Part number		**206611**	**206611**
Type		WLAN VRC .1	WLAN VRC .1
Description		WLAN function with app for central ventilation	WLAN function with app for central ventilation

next page >

		VRC-W 400	VRC-W 400 E
Service			
Part number		**240592**	**240592**
Type		Planning of ventilation technology, 3D	Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment	Engineering service: ventilation equipment
Maintenance			
Part number		**234147**	**234147**
Type		FMS G4-10 180	FMS G4-10 180
Description		Filter mat set	Filter mat set
Part number		**234148**	**234148**
Type		FMK M5-2 180	FMK M5-2 180
Description		Filter cassette set	Filter cassette set
Part number		**234208**	**234208**
Type		FMK F7-2 180	FMK F7-2 180
Description		Filter cassette set F7, 2 pce	Filter cassette set F7, 2 pce


The following are supplied with the device: Wall suspension, 2 star handles as spacers for the back of the device, condensate drain hose, hose clamp, hanging bend, 4 double nipples nominal width 160 (Product: 203636)

The following are supplied with the device: Wall suspension,2 star handles as spacers for the back of the device, Condensate drain hose, hose clamp, hanging bend, 4 double nipples nominal width 160 (Product: 203637)

STIEBEL ELTRON central ventilation unit VRC-W 400 higher air volume (400 m3/h) with heat recovery (sensible heat exchanger), bypass module, integrated preheating. (Product: 203636)


STIEBEL ELTRON central ventilation unit VRC-W 400 E higher air volume (400 m3/h) with heat recovery (enthaphy heat exchanger), bypass module, integrated preheating. (Product: 203637)

Minimum clearance diagram



Supply and extract air with heat recovery, wall mounting

LWZ 180/280



LWZ 180

Benefits

- For apartments, family houses and commercial properties with an area of up to 250 m²
- Central supply and extract air system for optimum air quality
- Efficient operation through by the constant flow rate fan, which ensures a balanced air flow rate
- Simple to control via the ergonomic programming unit
- Balanced flow rate in winter by means of integral preheating coil
- The programming unit can also be used as a remote control for ventilation regulated by the humidity sensor
- During the hot summer nights, temperature is reduced by means of the integral bypass module
- Pollutants are continuously removed from the living space
- Easy electrical installation as the connection panel is readily accessible even when the appliance is closed

Application • This central ventilation unit with heat recovery is suitable for ventilating family houses, large apartments and small commercial properties.

Convenience features • The unit is in a contemporary design with ergonomically arranged programming unit and separate filter cover panel. • The integral controller is operated via the multifunction display, which is also used to set the seven-day program. • The integral bypass damper in the supply air line prevents heat recovery from the extract air on hot summer nights. • The heating coil with electric preheating provides additional comfort by routing the supply air, which is a higher temperature, into the room. • The humidity sensor can be used for humidity-dependent control of the air flow rate.

Efficiency • The backwards-curved constant flow rate fan with air flow rate control ensures balanced air flow rates, promoting efficient operation. • The cross-countercurrent heat exchanger routes the supply and extract air streams so that they cross each other inside the unit. This extends the contact time for heat exchange, which improves the overall efficiency of the system. • The filter can be replaced easily thanks to the combi filter cassette. A fine dust filter is available as an optional accessory.

Installation • The unit can be installed in apartments, utility rooms and basement rooms. • The air connections are located at the top of the unit. • The electrical connection panel is easy to access without having to open the unit. • The ventilation unit has a duplex sheet steel casing with a powder coated finish on visible surfaces.

cool, temperate climate
CERTIFIED COMPONENT
Passive House Institute


232361

		LWZ 180	LWZ 280
Part number		**232361**	**232362**
Specification			
Heat recovery level up to	%	94	94
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)	ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)
Power consumption, fan	W	65	132
Sound power level (EN 12102)	dB(A)	43	48
Height	mm	997	997
Width	mm	690	690
Depth	mm	534	534
Air connection diameter	mm	160	160
Weight	kg	78	78
Rated voltage	V	230	230
Air flow rate	m³/h	60-250	60-350
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-39.95	-38.51

next page >


		LWZ 180	LWZ 280
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-41.58	-40.63
Energy efficiency class, moderate climates, time control A+ -> G		A	A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A	A
Energy efficiency class A+ -> G		A+	A+
Recommended accessories			
Part number		**205018**	**205018**
Type		FEB 2.0	FEB 2.0
Description		Control unit for central ventilation	Control unit for central ventilation
Part number		**206611**	**206611**
Type		WLAN VRC .1	WLAN VRC .1
Description		WLAN function with app for central ventilation	WLAN function with app for central ventilation
Service			
Part number		**240592**	**240592**
Type		Planning of ventilation technology, 3D	Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment	Engineering service: ventilation equipment
Maintenance			
Part number		**234147**	**234147**
Type		FMS G4-10 180	FMS G4-10 180
Description		Filter mat set	Filter mat set
Part number		**234148**	**234148**
Type		FMK M5-2 180	FMK M5-2 180
Description		Filter cassette set	Filter cassette set
Part number		**234208**	**234208**
Type		FMK F7-2 180	FMK F7-2 180
Description		Filter cassette set F7, 2 pce	Filter cassette set F7, 2 pce

Minimum clearance diagram



Supply and extract air with heat recovery, wall mounting

LWZ 180/280 E



LWZ 180 Enthalpie

Benefits

- An enthalpy heat exchanger is built in for recovering moisture in the winter
- For apartments, family houses and commercial properties with an area of up to 250 m²
- Central supply and extract air system for optimum air quality
- Efficient operation through by the constant flow rate fan, which ensures a balanced air flow rate
- Simple to control via the ergonomic programming unit
- Balanced flow rate in winter by means of integral preheating coil
- The programming unit can also be used as a remote control for ventilation regulated by the humidity sensor
- During the hot summer nights, temperature is reduced by means of the integral bypass module
- Pollutants are continuously removed from the living space
- Easy electrical installation as the connection panel is readily accessible even when the appliance is closed

Application • This central ventilation unit with heat recovery is suitable for ventilating family houses, large apartments and small commercial properties.

Convenience features • The unit is in a contemporary design with ergonomically arranged programming unit and separate filter cover panel. • The integral controller is operated via the multifunction display, which is also used to set the seven-day program. The display can be used as a remote control. • The integral bypass damper in the supply air line prevents heat recovery from the extract air on hot summer nights. • The heating coil with electric preheating provides additional comfort by routing the supply air, which is a higher temperature, into the room. • The unit is fitted with an enthalpy heat exchanger for moisture recovery. The humidity sensor can be used for humidity-dependent control of the air flow rate.

Efficiency • The backwards-curved constant flow rate fan with air flow rate control ensures balanced air flow rates, promoting efficient operation. • The cross-countercurrent heat exchanger routes the supply and extract air streams so that they cross each other inside the unit. This extends the contact time for heat exchange, which improves the overall efficiency of the system. • The filter can be replaced easily thanks to the combi filter cassette. A fine dust filter is available as an optional accessory.


Installation • The unit can be installed in apartments, utility rooms and basement rooms. • The air connections are located at the top of the unit. • The electrical connection panel is easy to access without having to open the unit. • The ventilation unit has a duplex sheet steel casing with a powder coated finish on visible surfaces.

		LWZ 180 Enthalpie	LWZ 280 Enthalpie
Part number		**236646**	**236647**
Specification			
Heat recovery level up to	%	89	89
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)	ePM10 ≥ 50 % (M5) | ISO Coarse ≥ 65 % (G4)
Sound power level (EN 12102)	dB(A)	43	48
Height	mm	997	997
Width	mm	690	690
Depth	mm	534	534
Air connection diameter	mm	160	160
Weight	kg	80	80
Rated voltage	V	230	230
Air flow rate	m³/h	60-250	60-350
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-37.32	-35.04
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-39.21	-37.73
Energy efficiency class, moderate climates, time control A+ -> G		A	A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A	A
Energy efficiency class A+ -> G		A+	A+

next page >

		LWZ 180 Enthalpie	LWZ 280 Enthalpie
Recommended accessories			
Part number		**205018**	**205018**
Type		FEB 2.0	FEB 2.0
Description		Control unit for central ventilation	Control unit for central ventilation
Part number		**206611**	**206611**
Type		WLAN VRC .1	WLAN VRC .1
Description		WLAN function with app for central ventilation	WLAN function with app for central ventilation
Service			
Part number		**240592**	**240592**
Type		Planning of ventilation technology, 3D	Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment	Engineering service: ventilation equipment
Maintenance			
Part number		**234147**	**234147**
Type		FMS G4-10 180	FMS G4-10 180
Description		Filter mat set	Filter mat set
Part number		**234148**	**234148**
Type		FMK M5-2 180	FMK M5-2 180
Description		Filter cassette set	Filter cassette set
Part number		**234208**	**234208**
Type		FMK F7-2 180	FMK F7-2 180
Description		Filter cassette set F7, 2 pce	Filter cassette set F7, 2 pce

Minimum clearance diagram



Supply and extract air with heat recovery, wall mounting

LWZ 70 E



LWZ 70 E

Benefits
- Central supply and extract air system for optimum air quality
- Pollutants are continuously removed from the living space
- Easy adjustment with constant flow rate fan
- High heat recovery through cross-countercurrent heat exchanger
- Easy to program using the integral programming unit

Application • This central ventilation unit with heat recovery is suitable for ventilating apartments and family houses.

Convenience features • The powder coated sheet steel casing is distinguished by its modern design with ergonomically arranged programming unit. • Highly efficient fans with constant flow rate control and the highly efficient cross-countercurrent heat exchanger are integrated into the unit. • The air flow rate can be selected in three stages. • Filters are easy to change thanks to the separate cover panel.


Efficiency • The constant flow rate fans with air flow rate control ensure balanced air flow rates, promoting efficient operation.

Installation • The ventilation unit is installed indoors, for example in the utility room. The air connections are located at the top of the unit.

		LWZ 70 E
Part number		**233851**
Specification		
Heat recovery level up to	%	90
Power consumption, fan	W	80
Sound power level (EN 12102)	dB(A)	46
Height	mm	600
Width	mm	560
Depth	mm	290
Air connection diameter	mm	125
Weight	kg	25
Rated voltage	V	230
Air flow rate	m³/h	50-180
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-35.96
Specific energy consumption in moderate climates, central demand-dependent control	kWh/(m²a)	-38.16
Energy efficiency class, moderate climates, time control A+ -> G		A
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G		A
Energy efficiency class A+ -> G		A
Recommended accessories		
Part number		**185358**
Type		FEZ
Description		Remote control
Part number		**227046**
Type		LSK 70 E
Description		Summer cassette
Part number		**234866**
Type		ZLWZ 4 S
Description		Four-stage switch
Part number		**236038**
Type		ZLWZ VHR 70 E
Description		Preheating coil


next page >

		LWZ 70 E
Service		
Part number		**240592**
Type		Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment
Maintenance		
Part number		**222446**
Type		FMS G3-10 70
Description		Filter mat set
Part number		**227660**
Type		FMK F7-2 70
Description		Filter cassette set F7, 2 pce



		LWZ 70 E
b01 Entry electrical cables		•
d45 Condensate drain - diameter	mm	13
g03 Outdoor air - nominal diameter		DN 125
g04 Exhaust air - nominal diameter		DN 125
g05 Extract air - nominal diameter		DN 125
g06 Supply air - nominal diameter		DN 125

Minimum clearance diagram



Supply and extract air with heat recovery, ceiling mounting

LWZ 130



LWZ 130

Benefits
- Central supply and extract air system for optimum air quality
- Integral electric air preheater coil
- Space saving installation in the ceiling

Application • This central ventilation unit with heat recovery is suitable for ventilating apartments and small family houses.

Convenience features • The compact design is optimised for installation in a suspended ceiling. The appliance is suitable for living spaces up to approx. 130 m2. • The hardwired controller with multifunction display can also be used as a wall mounted programming unit and is equipped with an integral humidity sensor and seven-day program. • The unit boasts the following features: efficient constant flow rate fans, electric preheating via high performance heating coil, electronic bypass. • Simple filter change, with coarse dust filter in the extract air and medium dust filter, with option of fine dust filter, in the supply air.


Efficiency • The constant flow rate fan enables a balanced air flow rate, which promotes efficient operation.

Installation • The ceiling mounted unit is installed in residential units, with the air connectors located on the right hand and left hand sides of the unit.• The electrical connection panel can be easily reached without having to open the appliance. • The EPS casing has a partial enclosure made from zinc-plated sheet steel. • Termination on the room side by means of a service flap to be installed on site.

		LWZ 130
Part number		**237805**
Specification		
Heat recovery level up to	%	94
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse > 60 % (G4)
Power consumption, fan	W	105
Sound power level (EN 12102)	dB(A)	33
Height	mm	248
Width	mm	520
Depth	mm	1113
Air connection diameter	mm	125
Weight	kg	18
Rated voltage	V	230
Air flow rate	m³/h	50-180
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-36.63
Energy efficiency class, moderate climates, time control A+ -> G		A
Energy efficiency class A+ -> G		A
Recommended accessories		
Part number		**205018**
Type		FEB 2.0
Description		Control unit for central ventilation
Part number		**206611**
Type		WLAN VRC .1
Description		WLAN function with app for central ventilation
Service		
Part number		**240592**
Type		Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment
Maintenance		
Part number		**238923**
Type		FMS G4-10 130/135
Description		Filter mat set

next page >

		LWZ 130
Part number		**238924**
Type		FMK M5-2 130/135
Description		Filter cassette set
Part number		**238925**
Type		FMK F7-2 130/135
Description		Filter cassette set F7, 2 pce



		LWZ 130
b07 Electrical connection - electrical connection		•
d45 Condensate drain - diameter	mm	16.5
g03 Outdoor air - diameter	mm	125
g04 Exhaust air - diameter	mm	125
g05 Extract air - diameter	mm	125
g06 Supply air - diameter	mm	125

Supply and extract air with heat recovery, ceiling mounting

LWZ 130 E



LWZ 130 Enthalpie

Benefits

- Central supply and extract air system for optimum air quality
- Integral electric air preheater coil
- Integral moisture recovery (on enthalpy version)
- Enthalpy version simpler to install as there is no condensate drain
- Space saving installation in the ceiling

Application • This central ventilation unit with heat recovery is suitable for ventilating apartments and small family houses.

Convenience features • The compact design is optimised for installation in a suspended ceiling. The appliance is suitable for living spaces up to approx. 130 m2. • The hardwired controller with multifunction display can also be used as a wall mounted programming unit and is equipped with an integral humidity sensor and seven-day program. • The unit is distinguished by the following features: efficient constant flow rate fans, highly efficient cross-countercurrent heat exchanger with moisture recovery, electric preheating via high performance heating coil, electronic bypass. • Simple filter change, with coarse dust filter in the extract air and medium dust filter, with option of fine dust filter, in the supply air.


Efficiency • The constant flow rate fan enables a balanced air flow rate, which promotes efficient operation.

Installation • The ceiling mounted unit is installed in residential units, with the air connectors located on the right hand and left hand sides of the unit. • The electrical connection panel is easy to access, without having to open the unit. • The EPS casing has a partial enclosure made from zinc-plated sheet steel. • Termination on the room side by means of a service flap to be installed on site.

		LWZ 130 Enthalpie
Part number		**237806**
Specification		
Heat recovery level up to	%	89
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse > 60 % (G4)
Power consumption, fan	W	105
Sound power level (EN 12102)	dB(A)	33
Height	mm	248
Width	mm	520
Depth	mm	1113
Air connection diameter	mm	125
Weight	kg	18
Rated voltage	V	230
Air flow rate	m³/h	50-180
Specific energy consumption in moderate climates, time control	kWh/(m²a)	-34.02
Energy efficiency class, moderate climates, time control A+ -> G		A
Energy efficiency class A+ -> G		A
Recommended accessories		
Part number		**205018**
Type		FEB 2.0
Description		Control unit for central ventilation
Part number		**206611**
Type		WLAN VRC .1
Description		WLAN function with app for central ventilation
Service		
Part number		**240592**
Type		Planning of ventilation technology, 3D
Description		Engineering service: ventilation equipment

next page >

		LWZ 130 Enthalpie
Maintenance		
Part number		**238923**
Type		FMS G4-10 130/135
Description		Filter mat set
Part number		**238924**
Type		FMK M5-2 130/135
Description		Filter cassette set
Part number		**238925**
Type		FMK F7-2 130/135
Description		Filter cassette set F7, 2 pce



		LWZ 130 Enthalpie
b07 Electrical connection - electrical connection		•
g03 Outdoor air - diameter	mm	125
g04 Exhaust air - diameter	mm	125
g05 Extract air - diameter	mm	125
g06 Supply air - diameter	mm	125

Supply and extract air with heat recovery, ceiling mounting

Accessories
Accessories 426
Controllers
Accessories 428
Filter
Accessories 431

LWTF 180/280




Benefits
- Moisture recovery prevents the indoor air from becoming too dry
- Improved room climate in winter
- Straightforward replacement for existing heat exchanger

Description • The enthalpy heat exchanger for the central ventilation units 180 and 280 replaces the cross-countercurrent heat exchanger in the winter months. • The highly efficient, moisture-transferring enthalpy heat exchanger is equipped with a selective plastic film membrane. The membrane recovers the moisture from the extract air and transfers it to the supply air. This increases the low relative humidity in the rooms during the winter months. • The membrane prevents the transfer of gases and impurities; it is distinguished by a long service life, high leak tightness and low pressure drop. It is antimicrobial and resistant to frost and heat.

LWTF 180/280

		LWTF 180/280
Part number		**236420**
Specification		
Height	mm	366
Width	mm	366
Depth	mm	395

LWTF W450/600



Benefits
- Enthalpy heat exchanger for W450/W600
- Moisture recovery prevents the indoor air from becoming too dry
- Improved room climate in winter
- Straightforward replacement for existing heat exchanger

Description • The enthalpy heat exchanger replaces the cross-countercurrent heat exchanger in the central ventilation unit in the winter months. • The highly efficient, moisture-transferring enthalpy heat exchanger is equipped with a selective plastic film membrane. The membrane recovers the moisture from the extract air and transfers it to the supply air. This increases the low relative humidity in the rooms during the winter months. • The membrane prevents the transfer of gases and impurities; it is distinguished by a long service life, high leak tightness and low pressure drop. It is antimicrobial and resistant to frost and heat.

LWTF W450/600

		LWTF W450/600
Part number		**359304**
Specification		
Height	mm	42
Width	mm	42
Depth	mm	39

ZLWZ VHR



Benefits
- Preheating coil for central ventilation units
- Reduces the risk of freezing
- Accessory for year-round operation of central ventilation units

Description • The electric preheating coil preheats the outdoor air in central ventilation units, in order to keep the cross-countercurrent heat exchanger frost-free in winter.

ZLWZ VHR 70 E

		ZLWZ VHR 70 E
Part number		**236038**
Specification		
Heating output	kW	1
Connection diameter	mm	160

LSK 70



Benefits
- LSK summer cassette for integral systems
- Alternative to the cross-countercurrent heat exchanger

Description • Insert module as an alternative to the cross-countercurrent heat exchanger in order to prevent heat transfer in summer.

LSK 70 E

		LSK 70 E
Part number		**227046**
Specification		
Height	mm	458
Width	mm	229
Depth	mm	283

FEB 2.0



Benefits
- Plain text display for understandable information
- Multiple languages available
- Operating mode can be switched easily via the Touch-Wheel
- Rapid ventilation function is started with action button
- Filter change and fault indicators

Description • The new FES/FEB control is combined with the central ventilation units 180/280. It enables both convenient operation and the display of system parameters specific to the living space. • Clear, understandable information via the plain text matrix display. • Customers can choose between different languages.

FEB 2.0

		FEB 2.0
Part number		**205018**
Specification		
Rated voltage	V	5
IP rating		IP22
Colour		white
Width	mm	145
Height	mm	96
Depth	mm	31

FEB controller (2.0) is converted to a matrix display with plain text (Product: 205018)

FEB 2.1




Benefits
- Control module with integral CO2/VOC sensor
- Plain text display for understandable information
- Multiple languages available
- Operating mode can be switched easily via the Touch-Wheel
- Action button starts rapid ventilation function
- Filter change and fault indicators

Description • This control (2.1) is combined with central ventilation units. It is equipped with an integral CO2/VOC sensor. The controller enables convenient operation of the ventilation unit and also displays system parameters specific to the living space. • Clear, understandable information via the plain text matrix display. • Customers can choose between different languages.

FEB 2.1

		FEB 2.1
Part number		**206612**
Specification		
Air quality sensor		CO2
Rated voltage	V	5
IP rating		IP22
Colour		white
Width	mm	145
Height	mm	96
Depth	mm	31

FEZ



Benefits
› Straightforward operation
› Filter change indicator

Description • The remote control with time switch and operating mode switch is used to control fan settings. • A rotary selector is used to switch between operating modes. • In automatic mode, time-controlled changeover between day and night mode is effected by the time switch. • The remote control has a control display and integral power reserve, and shows upcoming filter changes on a time dependent basis.

FEZ

		FEZ
Part number		**185358**
Specification		
IP rating		IP20
Width	mm	160
Height	mm	78
Depth	mm	45

ZLWZ 4 S



Benefits
› Wall switch for controlling the fan levels
› Plastic rotary knob

Description • To adjust the fan settings from the living space, the 4-stage switch with LED is used. • The switch is compatible with 70 E, 170 E Plus and 370 Plus central ventilation units, and is supplied with a power cable (1.5 m). • Installation on a surface box.

ZLWZ 4 S

		ZLWZ 4 S
Part number		**234866**

WLAN VRC .1



WLAN VRC .1

Benefits
- WLAN module for central ventilation units
- Convenient control via the MyStiebel app
- Quick and easy to install
- Strong WLAN signal for reliable connections

Description • With this module, central ventilation units can be incorporated in an existing WLAN. • All functions can be conveniently controlled from anywhere via our app. • The module is easy to install and the strong WLAN signal ensures a reliable connection.

		WLAN VRC .1
Part number		**206611**
Specification		
Installation type		Wall mounted appliance
WLAN		802.11b/g/n/ 2.4 GHz/DHCP
Supply voltage	V	5
Power consumption	W	0,8
Colour		white
Width	mm	135
Height	mm	180
Depth	mm	35
Weight	kg	0.70
Application limit	°C	0 - 45
Storage and transportation temperature	°C	-25 - +55

FMS G4-10 130



Benefits
- Fleece filter mats for replacement
- Filter class ${att.sf001226.value}
- Filter class ISO Coarse > 60 % (G4) (Product: 238923)

Description • The set contains 10 filter mats made of synthetic nonwoven fleece. No chemical binders are added. • The outstanding dust-holding capacity with little pressure drop is achieved through the progressively compressed construction and an optimised nonwoven structure.

FMS G4-10 130/135

		FMS G4-10 130/135
Part number		**238923**
Specification		
Quantity		10
Filter class		ISO Coarse > 60 % (G4)
Application		Ventilation units

FMK M5-2 130



Benefits
- Set with two high quality supply air filters
- Filter class ${att.sf001226.value}
- Filter class ePM10 ≥ 50 % (M5) (Product: 238924)

Description • The set contains two filter cassettes made of synthetic fibre fleece for the supply air. • The low pressure drop is achieved by the large, Z-pleated filter surfaces. • The sturdy frames consist of compressed filter fleece.

FMK M5-2 130/135

		FMK M5-2 130/135
Part number		**238924**
Specification		
Quantity		2
Filter class		ePM10 ≥ 50 % (M5)

FMK F7-2 130



Benefits
- Set with fine filters for ventilation systems
- Integral pull tab for easy replacement
- Filter class ${att.sf001226.value}
- Filter class ePM1 ≥ 50 % (F7) (Product: 238925)

Description • The replacement filter cassettes for supply air are made from unbreakable polyester fibres with a partially progressive structure. They are thermally bonded, temperature-resistant to 100 °C and pleated in a Z-shape. • The sturdy frame is made of moisture-resistant cardboard, with a pull tab integrated on the front.

FMK F7-2 130/135

		FMK F7-2 130/135
Part number		**238925**
Specification		
Quantity		2
Filter class		ePM1 ≥ 50 % (F7)
Application		Ventilation units

FMS G4-10 180



Benefits
- Fleece filter mats for replacement
- Filter class ISO Coarse > 60 % (G4) (Product: 234147)

Description • The set contains 10 filter mats made of synthetic nonwoven fleece. No chemical binders are added. • The outstanding dust-holding capacity with little pressure drop is achieved through the progressively compressed construction and an optimised nonwoven structure.

FMS G4-10 180

		FMS G4-10 180
Part number		**234147**
Specification		
Quantity		10
Filter class		ISO Coarse > 60 % (G4)
Application		Ventilation units

FMK M5-2 180



Benefits
› Set with two high quality supply air filters
› Filter class ePM10 ≥ 50 % (M5) (Product: 234148)

Description • The set contains two filter cassettes made of synthetic fibre fleece for the supply air. • The low pressure drop is achieved by the large, Z-pleated filter surfaces. • The sturdy frames consist of compressed filter fleece.

FMK M5-2 180

		FMK M5-2 180
Part number		**234148**
Specification		
Quantity		2
Filter class		ePM10 ≥ 50 % (M5)
Application		Ventilation units

FMK F7-2 180



Benefits
› Integral pull tab for easy replacement
› Set with fine filters for ventilation systems

Description • The replacement filter cassettes for supply air are made from unbreakable polyester fibres with a partially progressive structure. They are thermally bonded, temperature-resistant to 100 °C and pleated in a Z-shape. • The sturdy frame is made of moisture-resistant cardboard, with a pull tab integrated on the front.

FMK F7-2 180

		FMK F7-2 180
Part number		**234208**
Specification		
Quantity		2
Filter class		ePM1 ≥ 50 % (F7)
Application		Ventilation units

FMS G3



Benefits
- Fleece filter mats for replacement
- Standard delivery: 10 pce
- Filter class ISO Coarse > 45 % (G3) (Product: 222446)

Description • Set of filter mats made of synthetic nonwoven fleece. No chemical binders are added. • The outstanding dust-holding capacity with little pressure drop is achieved through the progressively compressed construction and an optimised nonwoven structure.

FMS G3-10 70

		FMS G3-10 70
Part number		**222446**
Specification		
Quantity		10
Filter class		ISO Coarse > 45 % (G3)
Application		Ventilation units

FMK F7-2 70



Benefits
- Two filter cassettes in set
- Replacement for dirty fresh air filters

Description • The replacement filter cassettes for supply air are made from unbreakable polyester fibres with a partially progressive structure. They are thermally bonded, temperature-resistant to 100 °C and pleated in a Z-shape within a sturdy frame made of moisture-resistant cardboard with a pull tab at the front.

FMK F7-2 70

		FMK F7-2 70
Part number		**227660**
Specification		
Quantity		2
Filter class		ePM1 ≥ 50 % (F7)
Application		Ventilation units

FMS EPMC 65-10 W450/600



Benefits
- G4 filter for LWZ W-450/600 (E), VRC-W 450/600 (E) and TVZ 450/600
- ISO Coarse 65 %
- Fleece filter mats for replacement
- Filter standard to ISO 16890

Description • The set contains 10 filter mats made of synthetic nonwoven fleece. No chemical binders are added. • The outstanding dust-holding capacity with little pressure drop is achieved through the progressively compressed construction and an optimised nonwoven structure.

FMS EPMC 65-10 W450/600

		FMS EPMC 65-10 W450/600
Part number		**206610**
Specification		
Quantity		10
Filter class		ISO Coarse > 60 % (G4)
Application		Ventilation units

FMK EPM1 70-2 W450/600



Benefits
- ISO ePM1 70 %
- Integral pull tab for easy replacement
- Set with fine filters for ventilation systems

Description • The replacement filter cassettes for supply air are made from unbreakable polyester fibres with a partially progressive structure. They are thermally bonded, temperature-resistant to 100 °C and pleated in a Z-shape. • The sturdy frame is made of moisture-resistant cardboard, with a pull tab integrated on the front.

FMK EPM1 55-2 W450/600

		FMK EPM1 55-2 W450/600
Part number		**206596**
Specification		
Quantity		2
Filter class		ePM1 ≥ 50 % (F7)
Application		Ventilation units

FMK EPA 12-2 W450/600



Benefits
› ISO EPA 12 filter
› Fine dust filtration up to PM 2.5 and a maximum of 99.5 %

Description: • E12 filter for various ventilation units.

FMK EPA 12-2 W450/600

		FMK EPA 12-2 W450/600
Part number		**206597**
Specification		
Quantity		2
Application		Ventilation units

LVE onfloor
Accessories 448
LVS infloor
Accessories 455
LWF system
Accessories 462

Distribution system for integral and central ventilation

Distribution system for integral and central ventilation

STIEBEL ELTRON simplifies the preparation of quotations for ventilation systems. A reliable quotation can be generated in just a few steps, which comes very close to the subsequent demand for ventilation material.

› Simple quotation preparation in just a few steps for the complete system
› Includes the ventilation unit, the external and exhaust air ducting and the complete air distribution

Procedure:
The offer can easily be determined according to square metres of living space (see example houses).
Supplementary material can be obtained from wholesalers.

Step 1
› **Selection of the suitable ventilation unit**

Step 2
› **Selection of accessories for external and exhaust air connection and air distribution connectors**

Step 3
› **Selection of the air distribution system**

STIEBEL ELTRON offers two air distribution systems:

STANDARD AIR DISTRIBUTION SYSTEM – ONFLOOR
System for routing the air ducts in the floor structure, consisting of a central air distributor, round plastic duct DN 75, flat plastic duct 130 x 52 mm and moulded parts for the construction of wall, ceiling or floor outlets.

› Central sound insulated air distributor with adjustable connectors for each line
› Ideal combination of flexible round duct (LVS) and flexible flat duct (LVE)
› Installation in the floor structure (wet or dry) and/or in walls
› Possible combinations of wall, ceiling and floor outlets

STANDARD AIR DISTRIBUTION SYSTEM – INFLOOR
System for routing the air ducts in the concrete ceiling or wooden beam layer, consisting of a central air distributor, round plastic duct DN 75 and moulded parts to accommodate the extract and supply air vents

› Central sound insulated air distributor with adjustable connectors for each line
› Few moulded parts, high stability and flexibility
› Installation in the concrete ceiling or suspended ceiling
› Position of the air outlets: ceiling

Distribution system for integral and central ventilation

Complete overview for easy quotation and calculation of standard systems for controlled mechanical ventilation

Ventilation systems consist of the ventilation unit, the accessories for the outdoor and exhaust air connection, and an air distribution system for supply and extract air in the building. The following compilation gives sample material ranges for applications in detached houses of different sizes.

Use this overview to prepare quotations and select materials for your building project. First select the ventilation unit and combine it with an air distribution system. Further information and detailed material ranges depending on house size can be found on the following pages.

	Ventilation units				
Type	LWZ 130/ LWZ 70 E	LWZ 130 Enthalpy	LWZ 180/ LWZ 180 E/ LWZ 170 E Plus	LWZ 280/ LWZ 370 P/ VRC-W400	LWZ 280 E/ VRC-W400E
Product number	237805/ 233851	237806	232361/ 236646/ 233850	203636/ 232033/ 203636	236647/ 203637
Price of the ventilation unit	On demand	On demand	On demand	On demand	On demand

Accessories for the connection of outdoor and exhaust air (unit installed on the ground floor)

Product no.	Unit price	Type	Designation	No. of units				
200205	On demand	LSWP 125-4 AL	Thermally insulated air hose, 4 m long, DN 125	1	1	1		
239139	On demand	KWG 125	Combi external wall grille	1	1	1		
239231	On demand	LWF DR 125-1 EPP	Duct insulated with EPP, DN 125, 1 m long	2	2	2		
239233	On demand	LWF DRB 125-90 EPP	Duct bend insulated with EPP, DN 125, 90°	2	2	2		
234505	On demand	AWG 160 R	Thermally insulating EPS wall outlet incl. weather grille with drip edge				2	2
239232	On demand	LWF DR 160-1 EPP	Duct insulated with EPP, DN 160, 1 m long				4	4
239235	On demand	LWF DRB 160-90 EPP	Duct bend insulated with EPP, DN 160, 90°				3	3
159320	On demand	LWF N 160	Push-fit connector DN 160				2	2
234646	On demand	LSWP 315-4 S	Thermally insulated air hose					
233836	On demand	AWG 315 SR	Wall outlet with weather grille, thermally insulated					

InFloor air distribution system | Total price InFloor

House size	Price				
Living space 50 m²	On demand	On demand			
Living space 70 m²	On demand	On demand			
Living space 100 m²	On demand	On demand			
Living space 130 m²			On demand		
Living space 160 m²			On demand		
Living space 190 m²			On demand		
Living space 220 m²				On demand	On demand
Living space 250 m²				On demand	On demand
Living space 280 m²				On demand	On demand


House size	Price				
Living space 50 m²	On demand	On demand			
Living space 70 m²	On demand	On demand			
Living space 100 m²	On demand	On demand			
Living space 130 m²			On demand		
Living space 160 m²			On demand		
Living space 190 m²			On demand		
Living space 220 m²				On demand	On demand
Living space 250 m²				On demand	On demand
Living space 280 m²				On demand	On demand

OnFloor air distribution system | Total price OnFloor

House size	Price				
Living space 50 m²	On demand	On demand			
Living space 70 m²	On demand	On demand			
Living space 100 m²	On demand	On demand			
Living space 130 m²			On demand		
Living space 160 m²			On demand		
Living space 190 m²			On demand		
Living space 220 m²				On demand	On demand
Living space 250 m²				On demand	On demand
Living space 280 m²				On demand	On demand


House size	Price				
Living space 50 m²	On demand	On demand			
Living space 70 m²	On demand	On demand			
Living space 100 m²	On demand	On demand			
Living space 130 m²			On demand		
Living space 160 m²			On demand		
Living space 190 m²			On demand		
Living space 220 m²				On demand	On demand
Living space 250 m²				On demand	On demand
Living space 280 m²				On demand	On demand

Distribution system for integral and central ventilation



	OnFloor system (sample material range)												
	Product no.	Unit price	Type	Designation	50 m²	70 m²	100 m²	130 m²	160 m²	190 m²	220 m²	250 m²	280 m²
1	159324	On demand	LWF RS 160 - 125	Reducer DN 160 to DN 125	2	2	2	2					
2	161095	On demand	LWF 125-2	Folded spiral-seam duct DN 125, 2 m long	2	2	2	2					
3	159309	On demand	LWF B 125-90	90° duct bend DN 125	3	3	3	3					
4	161096	On demand	LWF 160 - 2	Folded spiral-seam duct DN 160, 2 m long					2	2	2	2	2
5	159329	On demand	LWF B 160 - 90	90° duct bend DN 160					3	3	3	3	3
6	234493	On demand	LVS VTS 9	Sound insulating air distributor for finished walls, 9-way, adjustable					2	2	2	2	2
7	201456	On demand	LVS VTS 6	Sound insulating air distributor for finished walls, 6-way, adjustable	2	2	2	2					
8	236421	On demand	ZLVS O 75-10	O-Ring seal, 10 pce.					2	2	2	2	2
9	235058	On demand	LVS RP75 - 25	Duct pack 25 m long DN 75	1	1	1	1					
10	235059	On demand	LVS RP 75 - 50	Duct pack 50 m long DN 75					1	1	1	2	2
11	231111	On demand	LVE RP 20	Flat, flexible plastic duct, 20 m long	3	3	4	4	5	6	8	10	10
12	205364	On demand	LVE WDA 125	Wall outlet complete	4	5	6	8	7	7	8	9	9
13	239126	On demand	LVE YS	Y piece, 3 x LVE	2	2	2	2	2	2	2	3	3
14	231125	On demand	LVE FA	Floor outlet complete					4	5	5	5	6
15	231122	On demand	LVE BF 90	90° bend, complete, horizontal	1	1	1	1	3	3	3	4	4
16	206252	On demand	LVE BH 90-D	90° bend, complete, vertical					2	2	3	5	5
17	235912	On demand	LVE ÜB-U	Adaptor bend to LVS; connection from below	6	7	8	11	15	16	16	17	18
18	239130	On demand	LVE WGW 125	Slot design, painted white	4	5	6	8	7	7	8	9	9
19	231115	On demand	LVE FG	Slot design, brushed stainless steel					4	5	5	5	6
20	231113	On demand	LVE KF	Duct fixing clip, 10 pce	4	4	5	5	6	7	8	11	11
21	231112	On demand	LVE M	Female connection, 5 pce	1	1	1	1	1	1	2	2	2

Distribution system for integral and central ventilation



	InFloor system (sample material range												
	Product no.	Unit price	Type	Designation	50 m²	70 m²	100 m²	130 m²	160 m²	190 m²	220 m²	250 m²	280 m²
1	159324	On demand	LWF RS 160 - 125	Reducer DN 160 to DN 125	2	2	2	2					
2	161095	On demand	LWF 125-2	Folded spiral-seam duct DN 125, 2 m long	2	2	2	2					
3	159309	On demand	LWF B 125-90	90° duct bend DN 125	3	3	3	3					
4	161096	On demand	LWF 160 - 2	Folded spiral-seam duct DN 160, 2 m long					2	2	2	2	2
5	159329	On demand	LWF B 160 - 90	90° duct bend DN 160					3	3	3	3	3
6	234493	On demand	LVS VTS 9	Sound insulating air distributor for finished walls, 9-way, adjustable					2	2	2	2	2
7	201456	On demand	LVS VTS 6	Sound insulating air distributor for finished walls, 6-way, adjustable	2	2	2	2					
8	236421	On demand	ZLVS O 75-10	O-Ring seal, 10 pce.					2	2	2	2	2
9	235058	On demand	LVS RP75 - 25	Duct pack 25 m long DN 75		1				1	1	1	
10	235059	On demand	LVS RP 75 - 50	Duct pack 50 m long DN 75	1	1	2	3	3	3	4	4	5
11	205367	On demand	LVS WDA 125-2-75	Wall outlet complete	4	5	6	9	12	13	14	15	16
12	239130	On demand	LVE WGW 125	Air grille, slot design, painted white, 125 mm	4	5	6	9	12	13	14	15	16
13	224897	On demand	LVS M 75	Female connection DN 75, 5 pce.		1	1	1	1	1	1	1	1

Distribution system for integral and central ventilation

Distribution system for integral and central ventilation

Complete overview for easy quotation and calculation of standard systems for controlled mechanical ventilation

VVentilation systems consist of the ventilation units for the bathroom/WC and living space, as well as the corresponding accessories for the ventilation units. The following compilation gives sample material ranges for applications in detached houses and multistorey apartment buildings of different sizes.

Use this overview to prepare quotations and select materials for your building project. First select the appropriate number of extractors for your bathroom and/or WC and combine this with the number of bidirectional fans for your living space. Further information and detailed material ranges depending on house size can be found on the following pages.

Bathroom/WC – LA 100

Product no.	Unit price	Type	Designation	Living space 40 m²		60 m²		80 m²		100 m²		120 m²		140 m²	
				No. of units											
205771	On demand	LA 100 A	Decentralized ventilation unit LA 100 for surface mounting	1		1		1	2	1	2		2		2
231104	On demand	LWF W 100 VA-60	External wall outlet DN 100 for LA 100						1		1		2		2
205830	On demand	ZLA 100-H	Control module with humidity sensor for LA 100	1		1		1	1	1	1		1		1
205772	On demand	LA 100 U	Decentralized ventilation unit LA 100 for flush mounting												
205773	On demand	LA 100 UB	Decentralized ventilation unit LA 100 for flush mounting Fire protection												

Living spaces – VLR 70 L Trend EU

Product no.	Unit price	Type	Designation	No. of units											
203133	On demand	VLR 70 L Trend EU	Fan unit, inner + outer hood, telescope housing	2		2		4	2	4	4	6	4	6	4
239570	On demand	VLR 70-2 CU	Control unit for 2 units	1		1			1						
239571	On demand	VLR 70-4 CU	Control unit for up to 4 units					1		1	1		1		1
239572	On demand	VLR 70-8 CU	Control unit for up to 8 units									1		1	

Living spaces – VLR 70 S Trend EU

Product no.	Unit price	Type	Designation	No. of units											
203132	On demand	VLR 70 S Trend EU	Fan unit, inner + outer hood, telescope housing	2		2		4	2	4	4	6	4	6	4
239570	On demand	VLR 70-2 CU	Control unit for 2 units	1		1			1						
239571	On demand	VLR 70-4 CU	Control unit for up to 4 units					1		1	1		1		1
239572	On demand	VLR 70-8 CU	Control unit for up to 8 units									1		1	

Living spaces – VLR 70 L Trend EN

Product no.	Unit price	Type	Designation	No. of units											
201458	On demand	VLR 70 L Trend EN	Fan unit, inner + outer hood, telescope housing	2		2		4	2	4	4	6	4	6	4
239570	On demand	VLR 70-2 CU	Control unit for 2 units	1		1			1						
239571	On demand	VLR 70-4 CU	Control unit for up to 4 units					1		1	1		1		1
239572	On demand	VLR 70-8 CU	Control unit for up to 8 units									1		1	

Living spaces – VLR 70 S Trend EN

Product no.	Unit price	Type	Designation	No. of units											
200002	On demand	VLR 70 S Trend EN	Fan unit, inner + outer hood, telescope housing	2		2		4	2	4	4	6	4	6	4
239570	On demand	VLR 70-2 CU	Control unit for 2 units	1		1			1						
239571	On demand	VLR 70-4 CU	Control unit for up to 4 units					1		1	1		1		1
239572	On demand	VLR 70-8 CU	Control unit for up to 8 units									1		1	


Additional articles LA 60

Product no.	Unit price	Type	Designation	No. of units											
201452	On demand	LA 60 BRA	Fire protection shut-off device for LA 60	1		1		1	2	1	2		2		2
201455	On demand	FMS G2-5 LA 60	G2 filter mat set for LA 60, 5 pce	1		1		1	1	1	1		1		1

Additional/alternative articles VLR 70 L Trend EU


Product no.	Unit price	Type	Designation	No. of units											
239562	On demand	SP VLR 70 RF Coarse 30 G2-4	Filter set G2, 4 pce	1		1		1	1	1	1	1	1	1	1
239575	On demand	SP VLR 70 RF Coarse 60 G4-4	Filter set G4, 4 pce												
239576	On demand	SP VLR 70 RF ePM10 50 M5-4	Filter set M5, 4 pce												
239577	On demand	SP VLR 70 RF ePM1 50 F7-4	Filter set F7, 4 pce												
203140	On demand	Telescope (S)	Telescope housing 315 mm												

Distribution system for integral and central ventilation



	Example – material range for different house sizes for quick easy calculation													
	Product no.	Unit price	Type	Designation	40 m²	60 m²	80 m²		100 m²		120 m²		140 m²	
1	203133	On demand	VLR 70 L Trend EU	Fan unit, inner + outer hood, telescope housing	2	2	4	2	4	4	6	4	6	4
2	239570	On demand	VLR 70-2 CU	Control unit for 2 units	1	1		1						
3	239571	On demand	VLR 70-4 CU	Control unit for up to 4 units			1		1	1		1		1
4	239572	On demand	VLR 70-8 CU	Control unit for up to 8 units							1		1	
5	203132	On demand	VLR 70 S Trend EU	Fan unit, inner + outer hood, telescope housing	2	2	4	2	4	4	6	4	6	4
6	239570	On demand	VLR 70-2 CU	Control unit for 2 units	1	1		1						
7	239571	On demand	VLR 70-4 CU	Control unit for up to 4 units			1		1	1		1		1
8	239572	On demand	VLR 70-8 CU	Control unit for up to 8 units							1		1	
9	201458	On demand	VLR 70 L Trend EN	Fan unit, inner + outer hood, telescope housing	2	2	4	2	4	4	6	4	6	4
10	239570	On demand	VLR 70-2 CU	Control unit for 2 units	1	1		1						
11	239571	On demand	VLR 70-4 CU	Control unit for up to 4 units			1		1	1		1		1
12	239572	On demand	VLR 70-8 CU	Control unit for up to 8 units							1		1	
13	200002	On demand	VLR 70 S Trend EN	Fan unit, inner + outer hood, telescope housing	2	2	4	2	4	4	6	4	6	4
14	239570	On demand	VLR 70-2 CU	Control unit for 2 units	1	1		1						
15	239571	On demand	VLR 70-4 CU	Control unit for up to 4 units			1		1	1		1		1
16	239572	On demand	VLR 70-8 CU	Control unit for up to 8 units							1		1	
17	239562	On demand	SP VLR 70 RF Coarse 30 G2-4	Filter set G2, 4 pce										
18	239575	On demand	SP VLR 70 RF Coarse 60 G4-4	Filter set G4, 4 pce										
19	239576	On demand	SP VLR 70 RF ePM10 50 M5-4	Filter set M5, 4 pce										
20	239577	On demand	SP VLR 70 RF ePM1 50 F7-4	Filter set F7, 4 pce										
21	203140	On demand	Telescope (S) accessory	Telescope housing 315 mm										

Distribution system for integral and central ventilation



	Example – material range for different house sizes for quick easy calculation											
	Product no.	Unit price	Type	Designation	40 m²	60 m²	80 m²		100 m²		120 m²	140 m²
1	205771	On demand	LA 100 A	Decentralized ventilation unit LA 100 for surface mounting	1	1	1	2	1	2	2	2
2	231104	On demand	LWF W 100 VA-60	External wall outlet DN 100 for LA 60				1		1	2	2
3	231104	On demand	LWF W 100 VA-60	External wall outlet DN 100 for LA 100	1	1	1	1	1	1	1	1
4	205830	On demand	ZLA 100-H	Control module with humidity sensor for LA 100								
5	205772	On demand	LA 100 U	Decentralized ventilation unit LA 100 for flush mounting								
6	205773	On demand	LA 100 UB	Decentralized ventilation unit LA 100 for flush mounting Fire protection								
7	201452	On demand	LA 60 BRA	Fire protection shut-off device for LA 100								
8	201455	On demand	FMS G2-5 LA 60	G2 filter mat set for LA 100, 5 pce								

LVE RP



Benefits
- Flat flexible air duct made of plastic
- Internal pipe with low installed height
- Suitable for LVE onfloor
- Supplied as a 20 metre roll

Description • The flat and flexible LVE onfloor air duct made of plastic with internal pipe is distinguished by its low installed height.

LVE RP 20

		LVE RP 20
Part number		**231111**
Specification		
Height	mm	52
Width	mm	130
Length	mm	20000

LVE BF




Benefits
- Horizontal bend for the flexible air duct
- Connection on both sides via plug-in sleeves with slide-on clamps
- Suitable for LVE onfloor
- 45° angle (Product: 231121)
- 90° angle (Product: 231122)

Description • Bend for the flat and flexible LVE onfloor air distribution system made of plastic.

LVE BF 45

		LVE BF 45	LVE BF 90
Part number		**231121**	**231122**
Specification			
Height	mm	57	57
Width	mm	225	250
Length	mm	225	250

LVE BH-D



Benefits
- Set of one upward bend and two adaptors
- Universal application possibilities for LVE - onfloor
- Higher air flow rate due to optimised cross-section
- Quick, space saving installation

Description• The LVE 90 degree vertical bend is suitable for the LVE onfloor system. Two adaptors are supplied, which can be turned through 180 degrees. • Low pressure drop and minimal noise thanks to optimised cross-section. • The vertical bend is easy to clean. • The inner rib stiffens the component and separates the air streams. • Ideal for the prefabricated house sector as the compact size of maximum 86 mm enables installation at the factory. The vertical bend can be easily installed in 100 mm walls (timber frame construction). • The ribs on the back ensure secure positioning on the wall. • The vertical bend can be easily adapted to the position of the LVE pipe.

LVE BH 90-D

		LVE BH 90-D
Part number		**206252**
Specification		
Height	mm	157
Width	mm	228

Universal 90 degree vertical bend, 2 adaptors for LVE (Product: 206252)

LVE Ü 180



Benefits
- Adaptor for flexible air duct
- 180° change of direction
- Connections designed for inserts at both ends
- Suitable for LVE onfloor


Description • Adaptor for 180° change of position, for the flat and flexible LVE onfloor air distribution system made of plastic.

9

LVE Ü 180

		LVE Ü 180
Part number		**231120**
Specification		
Height	mm	69
Width	mm	144
Length	mm	64

LVE Ü 90



Benefits
- Connections designed for inserts at both ends
- Suitable for LVE onfloor
- Robust polyethylene adaptor

Description • Plastic adaptor for connecting DN 75/90 LVS pipe to the flat and flexible LVE onfloor air distribution system.

LVE Ü 90

		LVE Ü 90
Part number		**233032**
Specification		
Height	mm	95
Width	mm	144
Length	mm	100

LVE TB



Benefits
- Adaptor bend with swivelling connection adaptors for a wide range of installation situations
- 2 x LVS to 1 x LVE
- Low pressure drop
- Fewer ventilation ducts due to the reduction to one LVE duct

Description • Adaptor bend from 2 x LVS pipe to the flexible LVE onfloor air distribution system. Saves space and time during installation as the two LVS connections end in one LVE duct. There is no need for a second LVE duct. • The connection adaptors can be rotated 180 degrees to suit almost any installation situation. • The pressure drop is low due to the flow-optimised cross-section.

LVE TB 75

		LVE TB 75
Part number		**207077**
Specification		
Height	mm	171
Width	mm	228

LVE ÜB-O



Benefits
- Plastic adaptor bend
- With gasket and locking clip
- Robust polyethylene adaptor
- Connections designed for inserts at both ends
- Suitable for LVE onfloor
- Connection to the screed from above (Product: 235913)
- Connection to the screed from below (Product: 235912)

Description • The adaptor bend from a DN 75/90 LVS pipe to the flexible LVE onfloor air distribution system is made of plastic. The standard delivery includes a gasket and locking clip. • LVS connection for routing the LVE on screed.

LVE ÜB-O

		LVE ÜB-O	LVE ÜB-U
Part number		**235913**	**235912**
Specification			
Height	mm	120	120
Width	mm	144	144

LVE M



Benefits
- Connections designed for inserts at both ends
- Suitable for LVE onfloor
- Set with 5 sleeves


Description • Sleeve for the flat and flexible LVE onfloor air distribution system made of plastic.

LVE M

		LVE M	LVE RA
Part number		**231112**	**231117**
Specification			
Height	mm	55	35
Width	mm	130	
Length	mm	115	130

Push-fit adaptor for moulded parts of the flexible LVE onfloor air distribution system. (Product: 231117)

LVE YS



Benefits
- Suitable for LVE onfloor
- Divides the air flow across two ducts
- Y piece for flexible air duct (Product: 239126)
- Division of the flow across two ducts (Product: 239126)

Description • Y piece made of plastic for the flat and flexible LVE onfloor air distribution system.

LVE YS

		LVE YS
Part number		**239126**
Specification		
Height	mm	57
Width	mm	300
Length	mm	300

LVE A



Benefits
- Set of five connection adaptors
- The adaptors can be rotated 180°

Description • The set contains five connection adaptors for the LVE onfloor system. The adaptor can be rotated 180° to individually fit the LVE duct.

LVE A

		LVE A
Part number		**205366**
Specification		
Height	mm	59
Width	mm	184
Length	mm	92

LVE KF



Benefits
- 10 fixing clips made of zinc-plated steel
- Suitable for LVE onfloor
- Folded edges prevent the duct from slipping sideways
- Duct fixing sets consisting of sturdy brackets (Product: 231113)
- For fixing the flexible air duct on the unfinished concrete floor (Product: 231113)
- Suitable for impact rawl plugs (Product: 231113)

Description • The duct fixing clip consists of sturdy sheet steel brackets. It is used to secure the flexible LVE onfloor air duct to a bare concrete floor and is suitable for impact rawl plugs.

LVE KF

		LVE KF
Part number		**231113**
Specification		
Height	mm	53
Width	mm	25
Length	mm	215

LVE WDA



Benefits
- Individual fixing thanks to the rotatable connection adaptor
- Quick and straightforward installation
- Low flow velocities
- Suitable for high air flow rates

Description • The wall/ceiling diffuser is made from corrosion-resistant, odour-neutral plastic. It is equipped with a removable connection adaptor that makes it possible to connect a flexible LVE onfloor air duct. Since the connection adaptor can be rotated 180°, only one diffuser is required. • The large, aerodynamically optimised cross-section in the moulded part reduces the flow velocity and noise level, so a higher air flow rate can be achieved if required.

LVE WDA 125

		LVE WDA 125
Part number		**205364**
Specification		
Height	mm	385
Width	mm	184
Length	mm	230
Recommended accessories		
Part number		**207073**
Type		LWF SE 125
Description		Silencer element, 4 pce

WDA 125



Benefits
› Set of five wall/ceiling diffusers
› Optimized cross-section for a higher air flow rate

Description • The set comprises five wall/ceiling diffusers made from corrosion-resistant, odour-neutral plastic. With the relevant adaptors, the diffuser can be used for the LVE onfloor and LVS infloor air distribution systems. • The cross-section in the moulded part reduces the flow velocity, and a higher air flow rate can be achieved if required.

LVE-LVS WDA 125

		LVE-LVS WDA 125
Part number		**205368**
Specification		
Height	mm	85
Diameter	mm	125

5 pieces (Product: 205368)

LVS RP



Benefits
- Flexible pipes made of PE plastic (Product: 235059, 223320)
- Odour-neutral and antistatic (Product: 235059, 223320)
- Hygienically unproblematic (Product: 235059, 223320)

Description • The flexible corrugated plastic LVS pipe has corrugations on the outside and on the inside is smooth, odour-neutral and antistatic.

LVS RP 75-50

		LVS RP 75-50	LVS RP 90-25
Part number		**235059**	**223320**
Specification			
Weight	kg	17	12
Diameter	mm	75	90
Recommended accessories			
Part number		**207074**	
Type		LVS RS 75	
Description		Pipe cutter for LVS pipe DN 75	

LVS RS



Benefits
- Pipe cutter for LVS pipe DN 75
- Replaceable blade
- Rapid cutting with minimal risk of injury

Description • Handy pipe cutter with replaceable blade for LVS pipes DN 75 • The blade can be replaced with a standard cutter blade. • This handy tool allows LVS pipes to be cut quickly and cleanly. Risk of injury is reduced.

LVS RS 75

		LVS RS 75
Part number		**207074**
Specification		
Height	mm	16
Width	mm	90
Depth	mm	145

LVS VTS



Benefits
- Excellent sound attenuation at low frequencies
- Distributor plate and inspection cover can be interchanged
- Can be installed on the wall, ceiling or in a stud frame
- Air volumes can be adjusted at the distributor

Description • The sound insulated air distributor for the flexible LVS infloor and LVE onfloor air distribution systems is mounted on the wall or ceiling.

LVS VTS 6

		LVS VTS 6	LVS VTS 9
Part number		**201456**	**234493**
Specification			
Height	mm	150	250
Width	mm	500	500
Length	mm	640	1165
Insertion loss at 63 Hz	dB	3	5
Insertion loss at 125 Hz	dB	9	10
Insertion loss at 250 Hz	dB	15	10
Insertion loss at 500 Hz	dB	30	18
Insertion loss at 1000 Hz	dB	28	36
Insertion loss at 2000 Hz	dB	28	32
Insertion loss at 4000 Hz	dB	20	23
Insertion loss at 8000 Hz	dB	19	16
Required accessories			
Part number			**236421**
Type			ZLVS O 75-10
Description			O-ring set, 10 pce.

VT 14/16



Benefits
- Compact air distributor with multiple diffusers
- Good sound insulation
- Insulation material largely resistant to fungi and bacteria
- Hygiene certificate for the food industry

Description • The compact ventilation air distributors have multiple diffusers. Thanks to the special design, the air is distributed evenly so that uniform parameters are ensured for all diffusers, resulting in balanced air distribution. • The sound insulation of the air distributors reduces noise development. The insulating material has antibacterial and antifungal properties which counteract the growth of fungi and bacteria. • The air distributors have hygiene certificates which permit use in the food industry.

LVS VT 14

		LVS VT 14
Part number		**205558**

next page >

		LVS VT 14
Specification		
Height	mm	235
Width	mm	750
Length	mm	305

14 diffusers (Product: 205558)

ZLVS VTÜ



ZLVS VTÜ 75-90

Benefits
- ZLVS air distribution system accessories
- Zinc-plated sheet steel for corrosion protection

Description • Adaptor from DN 75 to DN 90 LVS.

		ZLVS VTÜ 75-90
Part number		**234494**
Specification		
Height	mm	92
Width	mm	92
Length	mm	150
Required accessories		
Part number		**236421**
Type		ZLVS O 75-10
Description		O-ring set, 10 pce.
Part number		**236422**
Type		ZLVS O 90-10
Description		O-ring set, 10 pce.

LVS WDA




Benefits
- Individual fixing thanks to the rotatable connection adaptor
- Quick and straightforward installation
- Low flow velocities
- Suitable for high air flow rates

Description • The wall/ceiling diffuser is made from corrosion-resistant, odour-neutral plastic. It is equipped with a removable connection adaptor that can be rotated 180°. • Two DN 75 connectors are provided; the corresponding LVS pipes are fixed in the adaptor with two locking pins each. • The size of the outlet connector is DN 125. • The large cross-section in the moulded part permits lower flow velocities and makes a higher air flow rate possible. • Standard delivery includes a DN 75 dummy cover, a DN 125 dummy cover and four locking pins.

LVS WDA 125-2-75

		LVS WDA 125-2-75
Part number		**205367**
Specification		
Height	mm	385
Width	mm	228
Length	mm	270.8
Recommended accessories		
Part number		**207073**
Type		LWF SE 125
Description		Silencer element, 4 pce

LVS A



Benefits
- Connection adaptor for 2 x DN 75 to the LVS infloor system
- Includes locking pins and dummy cover

Description • The connection adaptor for the LVS infloor system provides two connections for LVS pipe DN 75. • The pipes are fixed with two locking pins each. • The adaptor has a centre fixing point and side fixing tabs. • Standard delivery includes a dummy cover and four locking pins.

LVS A 2-75

		LVS A 2-75
Part number		**205365**
Specification		
Height	mm	79
Width	mm	228
Length	mm	113.7

LVS M



LVS M 75

Benefits
- Suitable for LVS infloor
- Plastic sleeve, connection for inserts at both ends
- Standard delivery: 5 pce

Description • Sleeve for the flexible LVS infloor air distribution system.

		LVS M 75
Part number		**224897**
Specification		
Length	mm	154
Diameter	mm	75

ZLVS O



ZLVS O 75-10

Benefits
- For VTS distributors and LTS diverters
- Set with 10 seal rings
- O-rings for sealing

Description • The seal ring set contains O-rings for the LVS pipe set, which can be used to seal the connections at the VTS distributor and the LVS diverter.

		ZLVS O 75-10	ZLVS O 90-10
Part number		**236421**	**236422**

LVS DA



LVS DA 75-125-2

Benefits
- Suitable for LVS infloor
- Pipe connection DN 75
- Corrosion protection thanks to zinc-plated steel

Description • Diverter to DN 100 for the flexible LVS infloor air distribution system.

		LVS DA 75-125-2
Part number		**236423**
Specification		
Height	mm	445
Width	mm	230
Length	mm	250

LVS-MSV-8-160



LVS-MSV-SB

Benefits
- Air distributor, 8-way
- Connection DN 160
- Robust plastic

Description • The air distributor for the flexible LVS air distribution system is suitable for installation in a concrete ceiling.

		LVS-MSV-SB
Part number		**232117**
Specification		
Height	mm	130
Width	mm	270
Length	mm	330

LVS-MSV-12-160



Benefits
- Connection DN 160
- Air distributor, 12-way
- Robust plastic

Description • The air distributor for the flexible LVS air distribution system is suitable for installation in a concrete ceiling.

LVS-MSV-SBA

		LVS-MSV-SBA
Part number		**232118**
Specification		
Height	mm	130
Width	mm	270
Length	mm	540

LVS AS



Benefits
- Set with 5 connectors
- Robust plastic
- Suitable for LVS infloor

Description • Connector for the flexible LVS air distribution system.

LVS AS 75

		LVS AS 75
Part number		**223318**
Specification		
Height	mm	98
Width	mm	98
Length	mm	53
Diameter	mm	75

LWF T



LWF T 160 - 160

Benefits
- Complete with 3 rolling ring seals
- Zinc-plated sheet steel for corrosion protection
- Tee for LWF air distribution system

Description • Tee for folded spiral-seam tubes made from zinc-plated sheet steel with rolling ring sealing system.

		LWF T 160 - 160
Part number		**159323**
Specification		
Installed length	mm	229
Diameter	mm	160

LWF M 100



LWF M 125

Benefits
- Suitable for LWF air distribution system
- Zinc-plated sheet steel for corrosion protection
- Robust version

Description • Connector for folded spiral-seam tubes made from zinc-plated sheet steel with rolling ring sealing system.

		LWF M 125
Part number		**159299**
Specification		
Diameter	mm	125

LWF N



LWF N 160

Benefits
- Pipe nipple for LWF air distribution system
- Zinc-plated sheet steel for corrosion protection
- Supplied with 2 rolling ring seals

Description • The push-fit connector for folded spiral-seam tubes made from zinc-plated sheet steel is equipped with a rolling ring sealing system.

		LWF N 160
Part number		**159320**
Specification		
Installed length	mm	8
Diameter	mm	160

LWF RS M/N




LWF RS 160 M - 125 N

Benefits
- Reducer for folded spiral-seam tubes in the air distribution system
- Zinc-plated sheet steel for corrosion protection
- Lip seal included in delivery

Description • The reducer for folded spiral-seam tubes of the LWF air distribution system is made of galvanised sheet steel. • The reduced side is designed as a plug-in connector with lip seal, the other side as a sleeve end.

		LWF RS 160 M - 125 N
Part number		**207509**
Specification		
Installed length	mm	66
Diameter	mm	160
Reducer diameter	mm	125

LWF F 125 - 5



Benefits
- Two-layered, flexible aluminium tube
- Length: 5 metres
- Temperature resistant to 200 degrees Celsius in continuous operation

Description • The flexible aluminium tube to DIN 24146 is folded in two layers and suitable for connecting the appliance to the pipework.

LWF F 125 - 5

		LWF F 125 - 5	LWF F 160 - 5
Part number		**159334**	**159332**
Specification			
Diameter	mm	125	160

LWF DR



Benefits
- Expanded polypropylene (EPP)
- Pipe length: 100 cm
- Pipe material prevents condensate forming

Description • The thermally insulated pipe system for outdoor air and exhaust air ducting is made of polypropylene foam – a vapour diffusion-proof, very light and self-supporting material.

LWF DR 125-1 EPP

		LWF DR 125-1 EPP	LWF DR 160-1 EPP
Part number		**239231**	**239232**
Specification			
Length	mm	1000	1000
Diameter	mm	125	160

LWF DRB



LWF DRB 125-45 EPP

Benefits
- Lightweight rigid foam duct
- Expanded polypropylene (EPP)
- Seamless finish

Description • The thermally insulated pipe system for outdoor air and exhaust air ducting is made of polyethylene foam – a vapour diffusion-proof, very light and self-supporting material.

		LWF DRB 125-45 EPP	LWF DRB 125-90 EPP	LWF DRB 160-45 EPP	LWF DRB 160-90 EPP
Part number		**239234**	**239233**	**239236**	**239235**
Specification					
Bend radius		45	90	45	90
Material		Foam	Foam	Foam	Foam

LWF DRM



LWF DRM 125 EPP

Benefits
- Expanded polypropylene (EPP)

Description • Pipe sleeve made of EPP for the sound insulated and thermally insulated rigid pipework, with flange collar push-fit connector.

		LWF DRM 125 EPP	LWF DRM 160 EPP
Part number		**239237**	**239238**
Specification			
Length	mm	85	85
Nominal diameter	mm	125	160

LWF S



Benefits
› Silencer for LWF air distribution system
› Effective sound insulation

Description • The silencer consists of an external pipe, a perforated internal pipe and two connection ends sized for nipple connectors. • The space is filled with sound-absorbing insulation material, with a fibreglass fleece between the internal pipe and the insulation to protect the air stream.

LWF S 160 - 0,9

		LWF S 160 - 0,9
Part number		**159346**
Specification		
Length	m	0.9
Nominal diameter	mm	160
External diameter	mm	280

Silencer element made from foam, 4 pce per pack (Product: 159346)

LWF SK



Benefits
› Excellent sound attenuation at low frequencies

Description • The splitter silencer consists of an external pipe, a perforated internal pipe, a baffle and two connection ends with double lip gasket. It reduces the sound levels of integral systems and air source heat pumps at the external wall grille. • The space is filled with sound-absorbing insulation material. A fibreglass fleece between the internal pipe and insulation prevents any contact between the insulating material and the air stream.

LWF SK 315 - 0,6

		LWF SK 315 - 0,6
Part number		**202933**
Specification		
Nominal diameter	mm	315
External diameter	mm	515

Splitter silencer, comprising an external pipe, a perforated internal pipe, a baffle and two connection ends with double lip seals. Suitable for use in the exhaust air of the integral systems and air/water heat pump to reduce the sound values at the outer grille. The intermediate space is filled with noise-absorbing material. A glass fibre fleece between the internal pipe and insulation prevents any contact between the insulating material and the air stream. (Product: 202933)
Silencer with baffle (Product: 202933)

LWF SE



Benefits
- Flow rate and sound attenuation can be individually adjusted
- Set with 4 silencers

Description • The silencer element for installation in the folded spiral-seam tube reduces airborne sound. • The element is made from fire-resistant and mould-resistant foam. • Both the flow rate and sound attenuation can be varied by the number of flow apertures.

LWF SE 125

		LWF SE 125
Part number		**207073**

Silencer element DN 125 made of foam, 4 pce per pack (Product: 207073)

LWF LB




Benefits
- Perforated tape made of zinc-plated steel
- Width: 16 mm
- Length: 10 metres

Description • Perforated tape for securing the air distribution system.

LWF LB 10m

		LWF LB 10m
Part number		**159348**
Specification		
Width	mm	16
Length	m	10

LWF KB



Benefits
- Grey butyl tape with high adhesive strength for sealing air duct systems
- Aluminium backed with protective foil
- 10 m per roll

Description • High quality butyl adhesive tape is used to seal joints in air duct systems. It is distinguished by its high adhesive strength.

LWF KB 10

		LWF KB 10
Part number		**227948**
Specification		
Width	mm	50
Length	m	10

LWF AVM



Benefits
- Round supply air vent made of white powder coated sheet steel
- Adjustable air flow rate
- Adjustable outlet section
- Easy installation

Description • The round and elegantly shaped vent is suitable for central extract air systems. • Easy installation in ceilings or walls with fastening springs and supplied installation supports. • The air flow rate is set easily and precisely with the rotating front panel. • Durable, robust design from powder coated, zinc-plated sheet steel.

LWF AVM 125

		LWF AVM 125
Part number		**227924**
Specification		
Max. air flow rate	m³/h	70
Connection diameter	mm	125
Air flow rate adjustable		•
Material		Steel

LWF ZVM



Benefits
- Round supply air vent made of white powder coated sheet steel
- Adjustable air flow rate
- Adjustable outlet section
- Easy installation

Description • The round and elegantly shaped vent is suitable for central supply air systems. • Easy installation in ceilings or walls with fastening springs and supplied installation supports. • The air flow rate is set easily and precisely with the rotating front panel. The air flow can be directed with the integral air outlet section. • Durable, robust design from powder coated, zinc-plated sheet steel.

LWF ZVM 125

		LWF ZVM 125
Part number		**230163**
Specification		
Max. air flow rate	m³/h	40
Connection diameter	mm	125
Air flow rate adjustable		•
Material		Sheet steel

KWG 125-160



Benefits
- Sheet steel intake/discharge grille
- Corrosion-resistant zinc plating and powder coating in silver grey
- Delivery includes pre-plumbing jig as drilling template

Description • The combined intake/discharge grille for the outdoor air and exhaust air ducting of central ventilation units with heat recovery is mounted on the external wall. The connections for exhaust air and outdoor air are arranged next to each other. • The grille is made of powder coated, zinc-plated sheet steel.

KWG 125

		KWG 125
Part number		**239139**
Specification		
Max. air flow rate	m³/h	200
Connection diameter	mm	125

WG



WG 200

Description • The stainless steel wall outlet is designed for the connection of a central ventilation unit.

		WG 200	WG 160
Part number		**205560**	**205559**
Specification			
Height	mm	253	192
Width	mm	253	192
Length	mm	62	62

Decentralised ventilation in residential buildings 473
Accessories for decentralised ventilation in residential buildings 481
Decentralised ventilation in non-residential buildings 487
Accessories for decentralised ventilation in non-residential buildings 521

Application areas

Air flow rate



	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
VLR 70 S Trend EN																																					
VLR 70 L Trend EN																																					
VLR 70 L Trend EU																																					



	m³/h	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
LA 100 A																																					
LA 100 U																																					
LA 100 UB																																					

Decentralised ventilation in residential buildings

Supply and extract air with heat recovery
VLR 70 S/L Trend 474
Extract air without heat recovery
LA 100 476
Accessories 477

VLR 70 S/L Trend



VLR 70 S Trend EN

Benefits
- Decentralised ventilation unit with heat recovery for new build and modernisation
- Rapid, hygienic cleaning thanks to aluminium heat exchanger
- Very good filter performance due to filters on the inside and outside
- No condensate run marks on the wall face
- Quick tool-free filter change and tool-free visual monitoring of the heat exchanger, due to compact design of fan unit

Application • This decentralised ventilation unit with heat recovery is used for ventilating apartments and small commercial properties.

Convenience features • Contemporary design with separate programming unit. • Thanks to the axial fan that can overcome back-pressure, use in locations exposed to the wind is possible. • The appliance is equipped with an efficient heat exchanger made of aluminium. • The external panel is watertight against heavy rain; it is made of stainless steel and powder coated. The internal panel is made of plastic. • Straightforward filter replacement with easy-to-remove fan unit. Fine dust filters are available as accessories.

Efficiency • EC fan ensures efficient operation.

Installation • The unit is installed in a round or square wall outlet. • The easily accessible mains connection is located on the inside of the fan unit.


		VLR 70 S Trend EN	VLR 70 L Trend EN	VLR 70 L Trend EU
Part number		**200002**	**201458**	**203133**
Specification				
Sound power level LW total relative to air flow rate	dB(A)	35 (20 m³/h)	35 (20 m³/h)	36 (20 m³/h)
Weight	kg	5.20	5.20	5.20
IP rating		IP21	IP21	IP21
Min. outlet aperture	mm	Ø 200, 185x185	Ø 200, 185x185	Ø 200, 185x185
Air flow rate	m³/h	20/30/40/49/70	20/30/40/49/70	20/30/40/49/70
Rated voltage	V	24	24	24
Energy efficiency class, moderate climates, central demand-dependent control A+ -> G				A+
Height	mm	285	285	285
Width	mm	360	360	360
Depth	mm	590	780	780
Required accessories				
Part number		**239570**	**239570**	**239570**
Type		VLR 70-2 CU	VLR 70-2 CU	VLR 70-2 CU
Description		Control set for VLR 70	Control set for VLR 70	Control set for VLR 70
Part number		**239571**	**239571**	**239571**
Type		VLR 70-4 CU	VLR 70-4 CU	VLR 70-4 CU
Description		Control set for VLR 70	Control set for VLR 70	Control set for VLR 70
Part number		**239572**	**239572**	**239572**
Type		VLR 70-8 CU	VLR 70-8 CU	VLR 70-8 CU
Description		Control set for VLR 70	Control set for VLR 70	Control set for VLR 70
Recommended accessories				
Part number		**237126**	**237126**	
Type		LTM TL HUMIDITY	LTM TL HUMIDITY	
Description		Humidity sensor	Humidity sensor	
Maintenance				
Part number		**239562**	**239562**	**239562**
Type		SP VLR 70 RF COARSE 30 G2-4	SP VLR 70 RF COARSE 30 G2-4	SP VLR 70 RF COARSE 30 G2-4
Description		Filter for VLR 70	Filter for VLR 70	Filter for VLR 70

next page >


		VLR 70 S Trend EN	VLR 70 L Trend EN	VLR 70 L Trend EU
Part number		**239575**	**239575**	**239575**
Type		SP VLR 70 RF COARSE 60 G4-4	SP VLR 70 RF COARSE 60 G4-4	SP VLR 70 RF COARSE 60 G4-4
Description		Filter for VLR 70	Filter for VLR 70	Filter for VLR 70
Part number		**239576**	**239576**	**239576**
Type		SP VLR 70 RF EPM10 50 M5-4	SP VLR 70 RF EPM10 50 M5-4	SP VLR 70 RF EPM10 50 M5-4
Description		Filter for VLR 70	Filter for VLR 70	Filter for VLR 70
Part number		**239577**	**239577**	**239577**
Type		SP VLR 70 RF EPM1 50 F7-4	SP VLR 70 RF EPM1 50 F7-4	SP VLR 70 RF EPM1 50 F7-4
Description		Filter for VLR 70	Filter for VLR 70	Filter for VLR 70

Blower unit, inner hood, outer hood (Product: 200002)
Only for sales outside the EU (Product: 200002)
Decentralised ventilation unit (Product: 203133)
VLR 70 L Trend EU with heat recovery (Product: 203133)

VLR 70 L Trend EU



VLR 70 L Trend EU



Extract air without heat recovery

LA 100



LA 100 A

Benefits

- Decentralised extractor for rooms with and without windows
- For use in traditional extract air areas, such as the bathroom, kitchen and WC
- Modernisation solution that is easy to install
- Ideal for combination with our decentralised ventilation units
- Energy efficient EC fan for low noise pollution at high air flow rates
- Quiet operation (Product: 205771, 205772, 205773)
- Fan unit for single ventilation units to DIN 18017-3 (Product: 205771, 205772, 205773)
- Fan unit for surface mounting (Product: 205771)
- Fan unit for flush mounting (Product: 205772, 205773)

Application • This fan unit for extractors ventilates rooms with and without external windows.

Convenience features • The casing, internal panel and filter holder are made from high quality white plastic. All appliances are equipped with a start delay and run-on time. If required, this can be extended by a humidity sensor. Subsequent extension of the control module is also possible in its installed state.

Efficiency • The fan unit has a very energy efficient and quiet fan motor.

Installation • Depending on the selected version, the appliances are suitable for installation in walls and ceilings or surface mounting. The electrical connection of the fan unit is easily accessible.

		LA 100 A	LA 100 U	LA 100 UB
Part number		**205771**	**205772**	**205773**
Specification				
Type of ventilation		Ventilation	Ventilation	Ventilation
Filter class		G3	G3	G3
Filter class		ePM10 ≥ 50 % (M5) | ISO Coarse > 45 % (G3)	ePM10 ≥ 50 % (M5) | ISO Coarse > 45 % (G3)	ePM10 ≥ 50 % (M5) | ISO Coarse > 45 % (G3)
Max. power consumption	W	15.3	15.3	15.3
Power consumption at 30 m³/h	W	2.2	2.2	2.2
Power consumption at 60 m³/h	W	4.5	4.5	4.5
Power consumption at max. flow rate	W	15.3	15.3	15.3
Sound power level LWA	dB(A)	47	47	47
Sound power level LWA at 60 m³/h	dB(A)	40	40	40
Sound power level LWA at 30 m³/h	dB(A)	33	33	33
Weight	kg	2.30	2.30	2.30
IP rating		IP X5	IP X5	IP X5
Max. air flow rate	m³/h	90	100	100
Recommended accessories				
Part number		**205830**	**205830**	**205830**
Type		ZLA 100-H	ZLA 100-H	ZLA 100-H
Description		Control module with humidity control	Control module with humidity control	Control module with humidity control
Part number		**231104**	**231104**	**231104**
Type		LWF W 100 VA - 60	LWF W 100 VA - 60	LWF W 100 VA - 60
Description		External wall outlet	External wall outlet	External wall outlet
Maintenance				
Part number		**201455**	**201455**	**201455**
Type		FMS G3-5 LA 60	FMS G3-5 LA 60	FMS G3-5 LA 60
Description		Filter mat set for extract air fan	Filter mat set for extract air fan	Filter mat set for extract air fan

ZLA100-H



Benefits
› Demand-regulated control of the fan based on the air humidity

Description • Humidity sensor for extractors LA 100 A / U / UB

ZLA 100-H

		ZLA 100-H
Part number		**205830**
Specification		
Power supply		1/N ~ 230 V 50 Hz
Width	mm	115
Height	mm	20
Depth	mm	170

LA 60/100 G-U




Benefits
› Optionally as standard or fire protection versions
› Installation accessory for decentralised ventilation unit

Description • Flush-mounted enclosure (LA 100 G-U) or flush-mounted enclosure with fire protection (LA 100 G-UB) for the installation of extractors.

LA 100 G-U

		LA 100 G-U	LA 100 G-UB
Part number		**205878**	**206247**
Specification			
Height	mm	280	255
Width	mm	295	255
Depth	mm	74	85

LA 100 G



Benefits
- Fan unit for surface mounting
- Fan unit for single ventilation units to DIN 18017-3
- Extremely quiet operation

Description • Surface-mounted enclosure for extractor LA 100 A.

LA 100 G-A

		LA 100 G-A
Part number		**205906**
Specification		
Height	mm	270
Width	mm	270
Depth	mm	136

LA 100 VE



Benefits
- Fan unit for flush mounting
- Fan unit for single ventilation units to DIN 18017-3
- Extremely quiet operation

Description • Fan unit for extractors LA 100 A / U / UB

LA 100 VE

		LA 100 VE
Part number		**205907**
Specification		
Max. power consumption	W	15.3
Height	mm	260
Width	mm	260
Depth	mm	50
Power supply		1/N 230 V 50 Hz
Air flow rate	m³/h	20/30/40/50/60/100

LWF W 100 VA - 60



Benefits
- Stainless steel with spherical protective cover
- Wall outlet DN 100
- Weather resistant

Description • Wall outlet for decentralised ventilation units.

LWF W 100 VA - 60

		LWF W 100 VA - 60
Part number		**231104**
Specification		
Length	mm	360
Material		Stainless steel
Nominal diameter	mm	100

FMS LA 60



Benefits
- High performance filters for ventilation systems
- Filter class ${att.sf001226.value}
- Filter class ISO Coarse > 45 % (G3) (Product: 201455)

Description • Set with 5 filter mats for extract air fan LA 60.

FMS G3-5 LA 60

		FMS G3-5 LA 60
Part number		**201455**
Specification		
Quantity		5
Filter class		ISO Coarse > 45 % (G3)
Application		Ventilation units

Accessories for controllers
Accessories 482
Filter
Accessories 484

Accessories for controllers

VLR 70-2/4/8 CU



Benefits
- Matched accessories for VLR 70
- Simple to control via the ergonomic programming unit
- Basic module including power supply unit and flush box (Product: 239570)
- Number of fans per control unit: max. 2 (Product: 239570)
- Number of fans per control unit: max. 4 (Product: 239571)
- Expansion set for controlling additional fan units (Product: 239571, 239572)
- Number of fans per control unit: max. 8 (Product: 239572)

Description • The control set comprises control unit, power supply unit and programming unit for controlling the ventilation units. • An LED on the control unit reminds the user to clean or replace the filter. These signals are issued according to the operating time. • The programming unit is installed in the supplied flush box. • The power supply unit is designed for top hat rail mounting.

VLR 70-2 CU

		VLR 70-2 CU	VLR 70-4 CU	VLR 70-8 CU
Part number		**239570**	**239571**	**239572**
Specification				
Number of fans per control unit		max. 2	max. 4	max. 8
Power supply		1/N 100-240 V 50/60 Hz	1/N 100-240 V 50/60 Hz	1/N 100-240 V 50/60 Hz
Width	mm	80	80	80
Height	mm	80	80	80
Depth	mm	9	9	9

User interface, control module, power supply, control panel with frame (Product: 239570)
User interface, control module, power supply, frame (Product: 239571) , 239572)

TL HDY



Benefits
- Suitable for connection to building automation system

Description • Humidity sensor for humidity-controlled operation in two different stages.

LTM TL HUMIDITY

		LTM TL HUMIDITY
Part number		**237126**
Specification		
Version		Room sensor
Measurement accuracy	% rF	5
Setting range, relative humidity	%	30-90
Measurement deviation per year	% rF	-1,5
Switching differential	% rF	6
Width	mm	76
Height	mm	76
Depth	mm	34

TL/DEZ MNT



LTM dezent APD BT

Benefits
› Installation accessory for decentralised ventilation unit

Description • Installation accessories for decentralised ventilation units

		LTM dezent APD BT
Part number		**237644**
Specification		
Height	mm	80
Width	mm	80
Depth	mm	37

SP VLR 70 RF



Benefits
- Matched accessories for VLR 70
- Different filter classes available
- 4 Filter for the Filter class G2 (Product: 239562)
- 4 Filter for the Filter class F7 (Product: 239577)

Description • Filter for VLR 70

SP VLR 70 RF COARSE 30 G2-4

		SP VLR 70 RF COARSE 30 G2-4	SP VLR 70 RF EPM1 50 F7-4
Part number		**239562**	**239577**
Specification			
Quantity		4	4
Filter class		ISO Coarse > 30 % (G2)	ePM1 ≥ 50 % (F7)
Application		Ventilation units	Ventilation units

Includes four G2 filters (Product: 239562)
Includes four F7 filters (Product: 239577)

SP VLR 70 RF COARSE 60 G4-4



Benefits
- Set with four filters
- Filter class G4


Description • Filter for VLR 70

SP VLR 70 RF COARSE 60 G4-4

		SP VLR 70 RF COARSE 60 G4-4
Part number		**239575**
Specification		
Quantity		4
Filter class		ISO Coarse > 60 % (G4)

Includes four G4 filters (Product: 239575)

SP VLR 70 RF EPM10 50 M5-4



Benefits
› Filter class M5
› Set with four filters

Description • Filter for VLR 70

SP VLR 70 RF EPM10 50 M5-4

		SP VLR 70 RF EPM10 50 M5-4
Part number		**239576**
Specification		
Quantity		4
Filter class		ePM10 ≥ 50 % (M5)

Supply and extract air with heat recovery

VRL-C 870 G Premium 488
VRL-C 870 G Trend 492
VRL-C 870 D Premium 496
VRL-C 870 D Trend 500
VRL-C 300 G Premium 504
VRL-C 300 G Trend 508
VRL-C 300 D Premium 512
VRL-C 300 D Trend 516

VRL-C 870 G Premium



Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- The supply and discharge air grilles can be adjusted to optimise air flow
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Very quick and easy installation, even in modernisation projects

VRL-C 870 G Premium

Application • Typical applications include controlled ventilation of larger spaces such as classrooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract and supply air is routed directly through the grille diffusers on the appliance.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • The equipment is fitted with motorised outdoor/exhaust air flaps to prevent uncontrolled flow of air in standby. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher-ranking building management system via BACnet, Modbus or LON interface (accessories). • The integral PCB enables easy integration of additional functions, such as smoke detectors, intermittent ventilation, minimum ventilation, external OFF and control of a hydraulic reheating coil. • With the integral reheating coil, the supply air temperature can be raised to a comfortable level. • The intelligent preheating control permanently monitors temperature and humidity levels in the appliance, reducing the demand for electrical energy to a minimum and lowering the connected load.

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. • It can be installed at various points on the ceiling of the room. • The supply air grille with adjustable air flow direction is located on the front of the appliance. • The extract air is sucked in through a grille on the right of the narrow side.

Efficiency • The combination of energy saving EC fans, intelligent control and other sensors ensures efficient operation.


		VRL-C 870 G Premium
Part number		**204132**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	147
Max. power consumption, fan	W	329
Max. power consumption	W	1,750
Power consumption, preheating coil	W	400
Power consumption, reheating coil	W	1,000
Height	mm	507
Width	mm	902
Length	mm	1,688
Air connection diameter	mm	315
Weight	kg	140

next page >

		VRL-C 870 G Premium
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	300-870
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	600
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 1
Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237629**
Type		LTM dezent BA VA 410 B
Description		External cover
Part number		**237633**
Type		LTM dezent BA VA 410 W
Description		External cover
Part number		**237672**
Type		LTM dezent 600/800 Z-PSS
Description		Mounting system for decentralised ventilation unit
Part number		**237674**
Type		LTM dezent RWA
Description		Mounting system for decentralised ventilation unit
Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237634**
Type		LTM dezent ULB-90
Description		Mounting system for decentralised ventilation unit
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units
Maintenance		
Part number		**206202**
Type		FMK M5-2 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit


next page >

		VRL-C 870 G Premium
Part number		**206203**
Type		FMK M5-10 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206204**
Type		FMK F7-2 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206205**
Type		FMK F7-10 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**237668**
Type		LTM dezent FMS F9-1
Description		Filter mat set for decentralised ventilation unit



		VRL-C 870 G Premium
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	315
g04 Exhaust air - diameter	mm	315
g05 Extract air		•
g06 Supply air		•

Minimum clearance diagram



VRL-C 870 G Trend



VRL-C 870 G Trend

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- The supply and discharge air grilles can be adjusted to optimise air flow
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as classrooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract and supply air is routed directly through the grille diffusers on the appliance.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. The temperature-dependent bypass automatically circumvents heat recovery when necessary. All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • To prevent uncontrolled air flow when the system is in standby, it is equipped with motorised outdoor air and exhaust air dampers. • In the case of fire or loss of power, the spring-loaded outdoor and exhaust air flaps seal the airways, which helps reduce the spread of fire or smoke through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances can be connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories).

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. • The direction of the air flow is determined by the adjustable supply air grille on the front of the appliance. • The extract air is sucked in through the extract air grille on the right of the narrow side.

Efficiency • The combination of energy saving EC fans, intelligent control and other sensors ensures efficient operation.

		VRL-C 870 G Trend
Part number		**204133**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	147
Max. power consumption, fan	W	329
Max. power consumption	W	1,850
Power consumption, preheating coil	W	1,500
Height	mm	507
Width	mm	902
Length	mm	1,688
Air connection diameter	mm	315
Weight	kg	140
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50

next page >

		VRL-C 870 G Trend
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	300-870
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	610
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 1

Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237629**
Type		LTM dezent BA VA 410 B
Description		External cover
Part number		**237633**
Type		LTM dezent BA VA 410 W
Description		External cover
Part number		**237672**
Type		LTM dezent 600/800 Z-PSS
Description		Mounting system for decentralised ventilation unit
Part number		**237674**
Type		LTM dezent RWA
Description		Mounting system for decentralised ventilation unit


Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units

Maintenance		
Part number		**206202**
Type		FMK M5-2 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206203**
Type		FMK M5-10 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206204**
Type		FMK F7-2 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit

next page >


		VRL-C 870 G Trend
Part number		**206205**
Type		FMK F7-10 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**237668**
Type		LTM dezent FMS F9-1
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 870 G Trend
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	315
g04 Exhaust air - diameter	mm	315
g05 Extract air		•
g06 Supply air		•

Minimum clearance diagram



VRL-C 870 D Premium



VRL-C 870 D Premium

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Connector for air duct
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as class rooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. • Air ducting is required for routing the outdoor and exhaust air. Extract air and supply air can be channelled to precise points in the room or building.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • The equipment is fitted with motorised outdoor/exhaust air flaps to prevent uncontrolled flow of air in standby. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories). • The integral PCB allows easy integration of further functions, such as smoke detectors, intermittent ventilation, minimum ventilation, external OFF and control of a hydraulic reheating coil. • With the integral reheating coil, the supply air temperature can be raised to a comfortable level. • Thanks to permanent monitoring of temperature and humidity levels by the intelligent preheating control, demand for electrical energy is reduced to a minimum and the connected load lowered.

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed at various points on the ceiling of the room. • The supply air grille on the front of the appliance can be adjusted to change the direction of the air flow. • The extract air is sucked in through the extract air grille on the right of the narrow side.

Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.

		VRL-C 870 D Premium
Part number		**204134**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	147
Max. power consumption, fan	W	329
Max. power consumption	W	1,750
Power consumption, preheating coil	W	400
Power consumption, reheating coil	W	1,000
Height	mm	507
Width	mm	902

next page >

		VRL-C 870 D Premium
Length	mm	1,688
Air connection diameter	mm	315
Weight	kg	140
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	300-870
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	610
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 1

Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237629**
Type		LTM dezent BA VA 410 B
Description		External cover
Part number		**237633**
Type		LTM dezent BA VA 410 W
Description		External cover
Part number		**237672**
Type		LTM dezent 600/800 Z-PSS
Description		Mounting system for decentralised ventilation unit
Part number		**237674**
Type		LTM dezent RWA
Description		Mounting system for decentralised ventilation unit


Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units

Maintenance		
Part number		**206202**
Type		FMK M5-2 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit

next page >


		VRL-C 870 D Premium
Part number		**206203**
Type		FMK M5-10 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206204**
Type		FMK F7-2 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206205**
Type		FMK F7-10 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**237668**
Type		LTM dezent FMS F9-1
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 870 D Premium
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	315
g04 Exhaust air - diameter	mm	315
g05 Extract air - diameter	mm	315
g06 Supply air - diameter	mm	315

Minimum clearance diagram



Supply and extract air with heat recovery

VRL-C 870 D Trend



VRL-C 870 D Trend

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Connector for air duct
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as class rooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract and supply air is routed directly through the grille diffusers on the appliance.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • The equipment is fitted with motorised outdoor/exhaust air flaps to prevent uncontrolled flow of air in standby. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories).

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. The pipe connector for the supply air line is located on the front of the appliance. Extract air is routed via the extract air connector on the right of the narrow side.

Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.

		VRL-C 870 D Trend
Part number		**204135**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	147
Max. power consumption, fan	W	329
Max. power consumption	W	1,850
Power consumption, preheating coil	W	1,500
Height	mm	507
Width	mm	902
Length	mm	1,688
Air connection diameter	mm	315
Weight	kg	140
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50

next page >

		VRL-C 870 D Trend
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	300-870
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	610
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 1

Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237629**
Type		LTM dezent BA VA 410 B
Description		External cover
Part number		**237633**
Type		LTM dezent BA VA 410 W
Description		External cover
Part number		**237672**
Type		LTM dezent 600/800 Z-PSS
Description		Mounting system for decentralised ventilation unit
Part number		**237674**
Type		LTM dezent RWA
Description		Mounting system for decentralised ventilation unit


Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units

Maintenance		
Part number		**206202**
Type		FMK M5-2 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206203**
Type		FMK M5-10 ABL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**206204**
Type		FMK F7-2 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit

next page >


		VRL-C 870 D Trend
Part number		**206205**
Type		FMK F7-10 ZUL dez. 800/870
Description		Filter mat set for decentralised ventilation unit
Part number		**237668**
Type		LTM dezent FMS F9-1
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 870 D Trend
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	315
g04 Exhaust air - diameter	mm	315
g05 Extract air - diameter	mm	315
g06 Supply air - diameter	mm	315

Minimum clearance diagram



VRL-C 300 G Premium



VRL-C 300 G Premium

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- The supply and discharge air grilles can be adjusted to optimise air flow
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as classrooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract and supply air is routed directly through the grille diffusers on the appliance.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. The temperature-dependent bypass automatically circumvents heat recovery when necessary. All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • The equipment is fitted with motorised outdoor/exhaust air flaps to prevent uncontrolled flow of air in standby. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories).

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. • The supply air grille with adjustable air flow direction is located on the front of the appliance. • The extract air is sucked in through a grille on the right of the narrow side.

Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.


		VRL-C 300 G Premium
Part number		**204140**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	67
Max. power consumption, fan	W	137
Max. power consumption	W	1,150
Power consumption, preheating coil	W	600
Power consumption, reheating coil	W	400
Height	mm	407
Width	mm	585
Length	mm	1,202
Air connection diameter	mm	200
Weight	kg	100
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE

next page >

		VRL-C 300 G Premium
Frequency	Hz	50
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	100-300
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	210
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 2
Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237627**
Type		LTM dezent 300 BA VA 320 B
Description		External cover
Part number		**237628**
Type		LTM dezent 300 BA VA 320 W
Description		External cover
Part number		**237671**
Type		LTM dezent 300 Z-PSS
Description		Mounting system for decentralised ventilation unit
Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units
Maintenance		
Part number		**206206**
Type		FMK M5-2 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206207**
Type		FMK M5-10 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206208**
Type		FMK F7-2 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206209**
Type		FMK F7-10 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit


next page >

Availability on request



		VRL-C 300 G Premium
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	200
g04 Exhaust air - diameter	mm	200
g05 Extract air		•
g06 Supply air		•

Minimum clearance diagram



VRL-C 300 G Trend



VRL-C 300 G Trend

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- The supply and discharge air grilles can be adjusted to optimise air flow
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as class rooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract and supply air is routed directly through the grille diffusers on the appliance.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • The equipment is fitted with motorised outdoor/exhaust air flaps to prevent uncontrolled flow of air in standby. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories).

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. The supply air grille on the front of the appliance can be adjusted to change the direction of the air flow. The extract air is sucked in through the extract air grille on the right of the narrow side.


Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.

		VRL-C 300 G Trend
Part number		**204141**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	67
Max. power consumption, fan	W	137
Max. power consumption	W	760
Power consumption, preheating coil	W	600
Height	mm	407
Width	mm	585
Length	mm	1,202
Air connection diameter	mm	200
Weight	kg	100
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50

next page >


		VRL-C 300 G Trend
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	100-300
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	210
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 2
Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237627**
Type		LTM dezent 300 BA VA 320 B
Description		External cover
Part number		**237628**
Type		LTM dezent 300 BA VA 320 W
Description		External cover
Part number		**237671**
Type		LTM dezent 300 Z-PSS
Description		Mounting system for decentralised ventilation unit
Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units
Maintenance		
Part number		**206206**
Type		FMK M5-2 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206207**
Type		FMK M5-10 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206208**
Type		FMK F7-2 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206209**
Type		FMK F7-10 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 300 G Trend
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	200
g04 Exhaust air - diameter	mm	200
g05 Extract air		•
g06 Supply air		•

Minimum clearance diagram



VRL-C 300 D Premium



VRL-C 300 D Premium

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Connector for air duct
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as classrooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. • Air ducting is required for routing the outdoor and exhaust air. Extract air and supply air can be channelled to precise points in the room or building.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • To prevent uncontrolled air flow when the appliance is on standby, the systems are equipped with motorised outdoor air and exhaust air dampers. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories). • The integral PCB allows easy integration of further functions, such as smoke detectors, intermittent ventilation, minimum ventilation, external OFF and control of a hydraulic reheating coil. • The integral reheating coil can raise the supply air temperature to a comfortable level. • Permanent monitoring of the temperature and humidity levels by the intelligent preheating control minimises the use of electrical energy and reduces the required connected load.

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. • The pipe connector for the supply air line is located on the front of the appliance. Extract air is routed via the extract air connector on the right of the narrow side

Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.

		VRL-C 300 D Premium
Part number		**204142**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	67
Max. power consumption, fan	W	137
Max. power consumption	W	1,150
Power consumption, preheating coil	W	600
Power consumption, reheating coil	W	400
Height	mm	407
Width	mm	585
Length	mm	1,202
Air connection diameter	mm	200
Weight	kg	100


next page >

		VRL-C 300 D Premium
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	100-300
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	210
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 2
Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237627**
Type		LTM dezent 300 BA VA 320 B
Description		External cover
Part number		**237628**
Type		LTM dezent 300 BA VA 320 W
Description		External cover
Part number		**237671**
Type		LTM dezent 300 Z-PSS
Description		Mounting system for decentralised ventilation unit
Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units
Maintenance		
Part number		**206206**
Type		FMK M5-2 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206207**
Type		FMK M5-10 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206208**
Type		FMK F7-2 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit

next page >


		VRL-C 300 D Premium
Part number		**206209**
Type		FMK F7-10 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 300 D Premium
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	200
g04 Exhaust air - diameter	mm	200
g05 Extract air - diameter	mm	200
g06 Supply air - diameter	mm	200

Minimum clearance diagram



VRL-C 300 D Trend



VRL-C 300 D Trend

Benefits

- High degree of heat recovery due to aluminium cross-countercurrent heat exchanger
- Easily installed in the ceiling thanks to the matching rail system
- Easy maintenance as the casing cover pivots open
- Flexible installation, with choice of flush or surface installation on ceiling
- Decentralised ventilation unit with heat recovery for schools, nurseries, seminar, therapy and club facilities, offices, community halls
- Integral preheater coil
- Connector for air duct
- Very quick and easy installation, even in modernisation projects

Application • Typical applications include controlled ventilation of larger spaces such as classrooms, conference rooms, sales showrooms, nurseries, restaurants and other function rooms. • The automated room ventilation improves the quality of the indoor air and reduces the level of CO2, aerosols, spores and dirt, thanks to the integral filters and heat recovery. At the same time, the high rate of air exchange reduces smells, bacteria and viruses in the indoor air. • The appliances are optimised for low-noise operation and are designed for decentralised usage directly at the point of use. Air ducting is required for routing the outdoor and exhaust air. Extract air and supply air can be channelled to precise points in the room or building.

Convenience features • Operating modes, programs and parameters can be adjusted simply and intuitively on the programming unit. The appliances are designed for straightforward and rapid servicing and are easy to maintain. • An additional sensor (accessory) measures the CO2 concentration in the indoor air and provides fully automatic control of the appliance's air flow rate until the CO2 falls below the set level again. • With the aid of a movement sensor (accessory), the appliance can switch between basic ventilation and a higher level. • The temperature-dependent bypass automatically circumvents heat recovery when necessary. • All the appliances are fitted with an electric preheating coil and can be used even when outdoor temperatures are very low with balanced supply and extract air flow rates. • To prevent uncontrolled air flow when the appliance is on standby, the systems are equipped with motorised outdoor air and exhaust air dampers. • In the case of fire or loss of power, the spring-loaded outdoor/exhaust air flaps seal the airways, which helps reduce the spread of fire or flue gas through the building. • In larger buildings, up to 20 appliances can be linked and controlled using a single programming unit. The appliances are connected to a higher ranking building management system via BACnet, Modbus or LON interface (accessories).

Installation • The appliance is designed for ceiling installation and can be built into a suspended ceiling. It can be installed in different places on the ceiling. The supply air connector is located on the front of the appliance. Extract air is routed via the extract air connector on the right of the narrow side.


Efficiency • Energy saving EC fans, in conjunction with the control unit and other sensors, ensure efficient operation.

		VRL-C 300 D Trend
Part number		**204143**
Specification		
Heat recovery level up to	%	92
Heat recovery level, nominal flow rate DIBt	%	80
Heat recovery level to DIN EN 13053		H1
Filter class, extract air		ePM 10 ≥ 50 % (M5)
Filter class, supply air		ePM1 ≥ 50 % (F7)
Rated power consumption, fan	W	67
Max. power consumption, fan	W	137
Max. power consumption	W	760
Power consumption, preheating coil	W	600
Height	mm	407
Width	mm	585
Length	mm	1,202
Air connection diameter	mm	200
Weight	kg	100
Condensate hose length	m	3
Condensate hose diameter	mm	7
Phases		1/N/PE
Frequency	Hz	50

next page >


		VRL-C 300 D Trend
Fuse protection	A	16
IP rating		IP20
Cable length	m	3
Air flow rate	m³/h	100-300
Min. ceiling clearance	mm	20
Nominal air flow rate	m³/h	210
Max. efficiency, cross-counter-current heat exchanger	%	92
Max. ambient conditions, installation room (temperature)	°C	40
Min. ambient conditions, installation room (temperature)	°C	12
SFP classification to DIN EN 13779		SFP 2
Required accessories		
Part number		**204144**
Type		ZVRL-C CU
Description		Controller for decentralised ventilation unit
Part number		**237627**
Type		LTM dezent 300 BA VA 320 B
Description		External cover
Part number		**237628**
Type		LTM dezent 300 BA VA 320 W
Description		External cover
Part number		**237671**
Type		LTM dezent 300 Z-PSS
Description		Mounting system for decentralised ventilation unit
Recommended accessories		
Part number		**237126**
Type		LTM TL HUMIDITY
Description		Humidity sensor
Part number		**237646**
Type		LTM dezent BACnet Web - Ethernet
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237648**
Type		LTM dezent Modbus RS 485 IF
Description		Interface card for connecting decentralised ventilation units to a building management system
Part number		**237649**
Type		LTM dezent CO2
Description		CO2 sensor
Part number		**237658**
Type		LTM dezent VOC
Description		VOC sensor for demand-controlled management of decentralised ventilation units
Maintenance		
Part number		**206206**
Type		FMK M5-2 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206207**
Type		FMK M5-10 ABL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206208**
Type		FMK F7-2 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit
Part number		**206209**
Type		FMK F7-10 ZUL dez. 300
Description		Filter mat set for decentralised ventilation unit

Availability on request



		VRL-C 300 D Trend
b01 Entry electrical cables		•
d45 Condensate drain		•
g03 Outdoor air - diameter	mm	200
g04 Exhaust air - diameter	mm	200
g05 Extract air - diameter	mm	200
g06 Supply air - diameter	mm	200


Minimum clearance diagram



Accessories for decentralised ventilation in non-residential buildings

Installation accessories
Accessories 522
Wall terminal
Accessories 523
Controllers and sensors
Accessories 524
Supplementary accessories
Accessories 526
Filter
Accessories 527

DEZ MG



Description • Mounting system for decentralised ventilation unit.

LTM dezent 300 ULB-90

		LTM dezent 300 ULB-90	LTM dezent ULB-90	LTM dezent 300 Z-PSS	LTM dezent 600/800 Z-PSS	LTM dezent C-PSS	LTM dezent RWA
Part number		**237626**	**237634**	**237671**	**237672**	**237673**	**237674**
Specification							
Width	mm	400	600	56	56	26	477
Length	m	1,202					

Wall terminal

ABL SL



LTM dezent 300 BA VA 320 B


Benefits

› Weather-resistant stainless steel external cover

Description • External cover for wall terminal on the façade. Mounting frame with integral drip edge and bird guard for installation on the façade. Sealing of plaster with sealing tape. Draining condensate safely in front of the plaster.

		LTM dezent 300 BA VA 320 B	LTM dezent 300 BA VA 320 W	LTM dezent BA VA 410 B	LTM dezent BA VA 410 W
Part number		**237627**	**237628**	**237629**	**237633**
Specification					
Material		Stainless steel	Stainless steel	Stainless steel	Stainless steel
Height	mm	327	327	422	422
Width	mm	324	324	423	423
Depth	mm	112	112	215	215
Colour		other	white	other	white

ZVRL-C CU



Benefits
- Convenient control of decentralised ventilation systems
- For wall mounting indoors
- Beautifully designed

Description • This digital control unit for up to 20 appliances has an integral LCD screen which displays all the relevant operating modes. • The system can be operated and programmed intuitively with just 6 buttons. This allows variable control of air flow rates and supply air temperature. • Using the bypass function, night-time cooling in the summer can be set manually or to automatic mode. • The integral time switch automatically switches between summertime and wintertime. • In addition to the monitoring, status and alarm functions (filter change warning signal), demand-dependent operation can be achieved with the aid of CO2 and VOC sensors. • The programming unit is mounted on the wall.

ZVRL-C CU

		ZVRL-C CU
Part number		**204144**
Specification		
Colour		white
Width	mm	156
Height	mm	82
Depth	mm	31

Availability on request

VOC



Benefits
- VOC sensor for decentralised ventilation units
- Reliable detection of volatile organic compounds

Description • VOC sensor for demand-controlled management of decentralised ventilation units.

LTM dezent VOC

		LTM dezent VOC
Part number		**237658**
Specification		
Width	mm	100
Height	mm	100
Depth	mm	28

CO2 S SL




LTM dezent CO2

Benefits
› CO2 sensor with adjustable switching threshold

Description • The CO2 sensor for demand-dependent, enhanced ventilation mode is supplied with a sensor and threshold switch.

		LTM dezent CO2
Part number		**237649**
Specification		
Version		Room sensor
Width	mm	80
Height	mm	100
Depth	mm	28

DEZ IF



Description • Interface cards to connect decentralised ventilation units to a building management system.

LTM dezent BACnet Web - Ethernet

		LTM dezent BACnet Web - Ethernet	LTM dezent Modbus RS 485 IF
Part number		**237646**	**237648**
Specification			
Width	mm	100	100
Height	mm	50	50
Depth	mm	5	5

FMS dez SL



LTM dezent FMS F9-1

Benefits
- High performance filters for ventilation systems
- Different filter classes available
- Filter class ePM1 ≥ 80 % (F9) (Product: 237668)
- Filter class ePM10 ≥ 50 % (M5) (Product: 206202, 206203, 206206, 206207)
- Filter class ePM1 ≥ 50 % (F7) (Product: 206204, 206205, 206208)

Description • The filter set, with particularly low pressure drop, allows high grade air filtration.

		LTM dezent FMS F9-1	FMK M5-2 ABL dez. 800/870	FMK M5-10 ABL dez. 800/870	FMK F7-2 ZUL dez. 800/870	FMK F7-10 ZUL dez. 800/870
Part number		**237668**	**206202**	**206203**	**206204**	**206205**
Specification						
Quantity		1	2	10	2	10
Filter class		ePM1 ≥ 80 % (F9)	ePM10 ≥ 50 % (M5)	ePM10 ≥ 50 % (M5)	ePM1 ≥ 50 % (F7)	ePM1 ≥ 50 % (F7)
Application		Ventilation units	Ventilation units	Ventilation units	Ventilation units	Ventilation units

		FMK M5-2 ABL dez. 300	FMK M5-10 ABL dez. 300	FMK F7-2 ZUL dez. 300	FMK F7-10 ZUL dez. 300
Part number		**206206**	**206207**	**206208**	**206209**
Specification					
Quantity		2	10	2	10
Filter class		ePM10 ≥ 50 % (M5)	ePM10 ≥ 50 % (M5)	ePM1 ≥ 50 % (F7)	ePM1 ≥ 50 % (F7)
Application		Ventilation units	Ventilation units	Ventilation units	Ventilation units

Storage heaters 531

Accessories for storage heaters 533

Application areas

Heating output



	W	820	1180	1630	1910	2400	2770
SHF 2000							
SHF 3000							
SHF 4000							
SHF 5000							
SHF 6000							
SHF 7000							

Standard storage heater
SHF 2000-7000 532

Standard storage heater

SHF 2000-7000



SHF 2000

Benefits

- For convenient, energy saving operation, C-Plus technology is used as an intelligent automatic charging system.
- Enable time for charging can be set directly on the appliance
- Integral RT controller with weekly timer and open window detection
- In timer mode, the self-learning control unit calculates the preheating time automatically
- Increased safety, as the high limit safety cut-out does not reset automatically
- The connected load can be reduced with a 3-phase connection
- Quiet crossflow fan
- As standard with fluff filter

Application • This compact storage heater is installed on the floor and is suitable as a standalone heater for apartments or commercial spaces. • The appliance is used with off-peak economy tariff models with blocking times.

Convenience features • The integral electronic charge controller with C-Plus technology charges the storage heater fully automatically and according to demand, without additional control units. • The required room temperature and the enable time for charging can be easily adjusted on the display. • In addition to the programmable weekly timer, there are two preset and one individually programmable time programs available. • In timer mode, the comfort temperature is achieved at precisely the right time thanks to the adaptive control with learning function. • In addition to the comfort temperature, it is also possible to program the setback temperature. • If required, users are able to activate a function on the appliance which detects when windows are open; this avoids unnecessary energy loss. • With three-phase connection, the connected load can be reduced in four stages. • The control input for AC signals is configured at the factory; a control input for DC signals is available as an optional accessory. • An auxiliary heater can be integrated as an option. • Integral childproofing as the programming unit can be locked. • High heat retention capacity. • The storage heater is equipped as standard with a fluff filter and operates very quietly. •

Installation • The appliance is installed directly on the floor, or off-floor on suitable floor brackets. • The single-phase or three-phase mains connection is easily accessible thanks to the hinged connection panel. A permanent control voltage is required.

Safety • Integral high limit safety cut-out.



200175, 200176,
200177, 200178,

		SHF 2000	SHF 3000	SHF 4000	SHF 5000	SHF 6000	SHF 7000
Part number		**200175**	**200176**	**200177**	**200178**	**200179**	**200180**
Specification							
Power supply		1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Frequency	Hz	50/-	50/-	50/-	50/-	50/-	50/-
Rated current	A	2,9	4,3	5,8	7,2	8,7	10,1
Rated connected load	kW	2.00	3.00	4.00	5.00	6.00	7.00
Fuse protection	A	10	10	10	16	16	16
Heating output	W	820	1180	1630	1910	2400	2770
Operating noise	dB(A)	30	32	33	34	34	34
Heat retention capacity	%	47	52	55	56	59	60
Height	mm	650	650	650	650	650	650
Width	mm	605	780	955	1130	1305	1480
Depth	mm	275	275	275	275	275	275
Weight	kg	32	40	48	56	64	72
Weight (incl. bricks)	kg	116	169	220	266	316	373
Number of brick packs		6	9	12	15	18	21
Colour		alpine white	alpine white	alpine white	alpine white	alpine white	alpine white

Core bricks included in the standard delivery.
Overall depth = 30 mm with wall clearance mesh

Control units
Accessories 534

RTA-S2



RTA-S2

Benefits
- ON/OFF switch
- Variable temperature selection via rotary selector
- Optional temperature setback via external time switch
- Adjustable range restriction so that minimum and maximum temperatures can be specified individually


Description • The room temperature controller for surface mounting has an integral bimetal controller with thermal feedback. • The controller has operating selectors. • Thanks to the integral terminal, the temperature can be lowered via an external time switch.

		RTA-S2
Part number		**231061**
Specification		
Breaking capacity	A	10
Rated voltage	V	230
Frequency	Hz	50/-
IP rating		IP30
Colour		pure white, RAL 9010
Width	mm	75
Height	mm	75
Depth	mm	26

Convectors 537

Rapid heater 545

Infrared wall mounted radiant heater 549



Application areas

Heating output

	W	500	1000	1500	2000	3000
CON 5 Premium						
CON 10 Premium						
CON 15 Premium						
CON 20 Premium						
CON 30 Premium						

	W	500	750	1000	1500	2000	2500	3000
CWM 500 P								
CWM 750 P								
CWM 1000 P								
CWM 1500 P								
CWM 2000 P								
CWM 2500 P								
CWM 3000 P								



	W	500	1000	2000
CNS 50 Trend M				
CNS 100 Trend M				
CNS 200 Trend M				



	W	2000
CNS 2000 Plus LCD Move		
CNS-B 2000 Plus LCD Move		



	W	750	1000	1500	2000	2500	3000
CWM 750 M-F							
CWM 1000 M-F							
CWM 1500 M-F							
CWM 2000 M-F							
CWM 2500 M-F							
CWM 3000 M-F							

Wall installation
- **CON Premium** 538
- **CWM P** 539
- **CNS Trend M** 541

Floorstanding appliances
- **CNS 2000 Plus LCD move** 542
- **CWM M-F** 543

CON Premium



CON 5 Premium

Benefits
- Elegant design with aluminium front
- Electronic controller with illuminated LCD screen
- Weekly timer with 3 time programs, self-learning function and open window detection
- With short-time timer
- Safety through overheating protection
- Omnipolar operating selector
- Long lasting stainless steel tubular heater with steel fins
- Cable storage at the back for the connecting cable
- During a power failure, the clock is buffered for up to 10 hours

Application • This compact, wall mounted convector is used as a standalone heater, as an efficient interim heater in spring/autumn, or simply for additional heat demand in the living space, bathroom or utility rooms. • The appliance has won the Red Dot Design Award and looks good in any setting.

Convenience features • The convector with electronic closed-loop control, easy-to-read display and simple programming is characterised by even, silent and accurate heating of the indoor air. • The required room temperature is easy to set at the programming unit. The appliance is equipped with a weekly timer with two preset time programs and one individually programmable time program. A short-time timer is also integrated. • In timer mode, the comfort temperature is achieved at precisely the right time thanks to the adaptive control with learning function. • Comfort and setback temperatures can be programmed. • The function for detecting an open window can be activated to avoid wasted energy. • The appliance features a frost protection setting and an omnipolar operating selector. • The high grade stainless steel tubular heater with aluminium coated steel fins is integrated in a robust metal casing. • The adjustable childproofing prevents unintentional or unauthorised modifications to the programming unit.

Installation • Straightforward, stable wall mounting needs one person only. The adjustable wall mounting bracket can be fitted separately from the convector. The appliance simply needs to be hooked into place.

Safety • Integral safety temperature limiter.

reddot award 2018
winner

		CON 5 Premium	CON 10 Premium	CON 15 Premium	CON 20 Premium	CON 30 Premium
Part number		**237830**	**237831**	**237832**	**237833**	**237834**
Specification						
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230	230	230	230
Voltage range	V	230	230	230	230	230
Frequency	Hz	50/-	50/-	50/-	50/-	50/-
Rated current	A	2,2	4,3	6,5	8,7	13
Connected load	W	500	1000	1500	2000	3000
Connected load	kW	0,5	1,0	1,5	2	3
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Fuse protection	A	10	10	10	16	16
Setting range	°C	5-30	5-30	5-30	5-30	5-30
IP rating		IP24	IP24	IP24	IP24	IP24
Protection class		I	I	I	I	I
Height	mm	470	470	470	470	470
Width	mm	345	470	625	780	1090
Depth	mm	126	126	126	126	126
Weight	kg	4.30	5.90	7.50	9.30	12.60
Colour		alpine white	alpine white	alpine white	alpine white	alpine white

Depth including wall mounting bracket

CWM P



CWM 500 P

Benefits
- Wall mounted convector heaters with high heating output
- Compact metal casing in a slimline design
- Electronic controller with illuminated LCD screen
- Weekly timer with 3 time programs, self-learning function and open window detection
- In timer mode, the self-learning control unit calculates the preheating time automatically
- Safety through overheating protection
- Omnipolar operating selector
- Long lasting stainless steel tubular heater with steel fins
- During a power failure, the clock is buffered for up to 10 hours

Application • This convector is suitable for use as a standalone heater, as an efficient interim heater in spring/autumn, or for additional heat demand in the living space, bathroom or utility rooms. • With its compact dimensions, it takes up very little space. • The timeless and very slimline design suits any setting.

Convenience features • The convector with electronic closed-loop control ensures even, silent and accurate heating of the indoor air. • The required room temperature is easy to set at the top mounted programming unit. • The appliance has a large and easy-to-read display with programmable weekly timer with one individually programmable and two preset time programs. • In addition to the comfort temperature, it is also possible to program the setback temperature. In timer mode, the comfort temperature is achieved at precisely the right time thanks to the adaptive control with learning function. • Omnipolar operating selector. • The high grade tubular heater made from stainless steel with aluminium coated steel fins and the robust metal casing both help to ensure a long service life. • The appliance is equipped with an integral frost protection setting.

Efficiency • Users can activate a function on the appliance which detects open windows, thereby avoiding unnecessary energy loss.

Installation • Straightforward, stable wall mounting needs one person only because the wall mounting bracket is fitted to the wall separately from the appliance and can be readjusted later. All that then remains is to hook the maintenance-free appliance into place. • The power cable is fitted with a standard plug.

Safety • Integral childproofing means that the programming unit can be locked. • Integral safety temperature limiter.

		CWM 500 P	CWM 750 P	CWM 1000 P	CWM 1500 P
Part number		**200254**	**200255**	**200256**	**200257**
Specification					
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230	230	230
Voltage range	V	230	230	230	230
Frequency	Hz	50	50	50	50
Rated current	A	2,2	3,3	4,3	6,5
Connected load	W	500	750	1000	1500
Connected load	kW	0,5	0,75	1,0	1,5
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE
Fuse protection	A	10	10	10	10
Setting range	°C	5 - 30	5 - 30	5 - 30	5 - 30
IP rating		IP24	IP24	IP24	IP24
Protection class		I	I	I	I
Height	mm	450	450	450	450
Width	mm	348	426	426	582
Depth	mm	100	100	100	100
Weight	kg	4.00	4.60	4.60	6.00
Colour		alpine white	alpine white	alpine white	alpine white

		CWM 2000 P	CWM 2500 P	CWM 3000 P
Part number		**200258**	**200259**	**200260**
Specification				
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230	~230
Voltage range	V	230	230	230

12

next page >

		CWM 2000 P	CWM 2500 P	CWM 3000 P
Frequency	Hz	50	50	50
Rated current	A	8,7	10,9	13,0
Connected load	W	2000	2500	3000
Connected load	kW	2,0	2,5	3,0
Phases		1/N/PE	1/N/PE	1/N/PE
Fuse protection	A	10	16	16
Setting range	°C	5 - 30	5 - 30	5 - 30
IP rating		IP24	IP24	IP24
Protection class		I	I	I
Height	mm	450	450	450
Width	mm	738	894	1050
Depth	mm	100	100	100
Weight	kg	7.70	9.20	10.90
Colour		alpine white	alpine white	alpine white

Depth including wall mounting bracket

CNS Trend M



CNS 50 Trend M

Benefits
- Wall mounted convector heaters with high heating output
- Compact metal casing in a slimline design
- Mechanical temperature controller
- Omnipolar operating selector
- Safety through overheating protection
- Long lasting stainless steel tubular heater with steel fins

Application • This compact, wall mounted convector can be used as a standalone heater, as an efficient interim heater in spring/autumn, or for additional heat demand in the living space, bathroom or utility rooms. • The timeless and very slimline design suits any setting.

Convenience features • The mechanically controlled convector ensures even and silent heating of the indoor air. • The required room temperature can be variably adjusted at the programming unit. • A high grade stainless steel tubular heater with steel fins is integrated in the robust metal casing. The appliance features a frost protection setting and an omnipolar operating selector.

Installation • Straightforward, stable wall mounting needs one person only: the wall mounting bracket is fitted to the wall separately from the appliance and can be adjusted later. All that remains is to hook the appliance into place.

Safety • Integral high limit safety cut-out.

		CNS 50 Trend M	CNS 100 Trend M	CNS 200 Trend M
Part number		**203638**	**203640**	**203642**
Specification				
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230	230
Frequency	Hz	50/60	50/60	50/60
Rated current	A	2,2	4,3	8,7
Connected load	W	500	1000	2000
Connected load	kW	0,5	1	2
Phases		1/N/PE	1/N/PE	1/N/PE
Fuse protection	A	10	10	10
Setting range	°C	5-35	5-35	5-35
IP rating		IP24	IP24	IP24
Protection class		I	I	I
Height	mm	450	450	450
Width	mm	348	426	738
Depth	mm	100	100	100
Weight	kg	4.00	4.60	7.70
Colour		alpine white	alpine white	alpine white

Depth including wall mounting bracket
Notice: Only for sales outside the EU. (Product: 203638) , 203640, 203642)

CNS 2000 Plus LCD move



CNS 2000 Plus LCD Move

Benefits

- Elegant freestanding convector in a timeless design casing
- High heating output despite slimline design
- Highly safe due to pendulum switch which switches the appliance off if knocked over
- Splashproof tested for use in bathrooms
- Electronic controller with illuminated LCD screen
- Safety through overheating protection
- Weekly timer with 3 time programs, self-learning function and window open detection
- Integrated handle
- Long lasting stainless steel tubular heater with steel fins
- Colour: white (similar to RAL 9003) (Product: 207060)
- Colour: (Product: 207068)

Application • This electronically controlled freestanding convector is characterised by its elegant design casing, which blends in perfectly with any living space. • The appliance is easy to program and versatile to use, for example as a booster heater, or in recreational rooms that are only used sporadically. • Suitable for the bathroom thanks to IP24 protection class (splashproof). • Thanks to the high heating output, the required heat is available quickly. • The appliances are available in different colours for optimum integration into the living space.

Convenience features • Thanks to its sophisticated and timelessly elegant design, the freestanding convector fits into any living space seamlessly. • The operating controls are integrated into the top and are easily accessible. It is simple to set your required room temperature. A large and easy-to-read display shows information about the most important settings. The programming unit can be locked to prevent unintentional changes. • A weekly time switch with two preset time programs and one individual time program is integrated. The time switch has adaptive control as a learning function for reaching the comfort temperature at exactly the right time in timer mode. • The comfort and setback temperatures can be programmed to suit individual needs. • The convector detects open windows. • The freestanding convector has a high quality, stainless steel tubular heater with steel fins in a robust metal casing.

Installation • The appliance is delivered complete with a power cable with fitted standard plug. It is equipped with stable feet; a handle makes it easy to move around. • The frost protection setting prevents frost damage at low temperatures.

Safety • The freestanding convector offers the greatest possible operational reliability thanks to the built-in pendulum switch, as it switches off automatically if it is tipped over. • IP24 protection class for use even in bathrooms. • The integral safety temperature limiter protects against overheating.

		CNS 2000 Plus LCD Move	CNS-B 2000 Plus LCD Move
Part number		**207060**	**207068**
Specification			
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230
Voltage range	V	230	230
Frequency	Hz	50/-	50/-
Rated current	A	8,7	8,7
Connected load	W	2000	2000
Connected load	kW	2	2
Phases		1/N/PE	1/N/PE
Fuse protection	A	16	16
Setting range	°C	5-30	5-30
IP rating		IP24	IP24
Protection class		I	I
Height	mm	443	443
Width	mm	738	738
Depth	mm	80	80
Weight	kg	7.90	7.90
Colour		white (similar to RAL 9003)	

Depth and height including feet with castors (Product: 207060) , 207068)

CWM M-F



CWM 750 M-F

Benefits
- Freestanding convectors with a high heating output
- Mechanical temperature controller
- For maximum operational reliability, the integral pendulum switch protects against overturning
- Handle and feet with castors
- Omnipolar operating selector
- Long lasting stainless steel tubular heater with steel fins

Application • This freestanding convector in a robust metal casing provides heat quickly when needed. The appliance is distinguished by easy handling and versatility.

Convenience features • Even and silent heating of the indoor air. • Very user friendly thanks to the top mounted operating controls. • The required room temperature is easy to set at the temperature selector. • High grade stainless steel tubular heater with steel fins. • The convector has a frost protection setting.

Installation • The appliance is delivered complete with a handle, power cable and standard plug. The feet are equipped with castors.

Safety • The integral pendulum switch ensures protection against overturning for maximum safety in operation. Additional protection against overheating is provided by the integral safety temperature limiter.

		CWM 750 M-F	CWM 1000 M-F	CWM 1500 M-F	CWM 2000 M-F	CWM 2500 M-F	CWM 3000 M-F
		DISCONT. PRODUCT		DISCONT. PRODUCT		DISCONT. PRODUCT	
Part number		**204452**	**204453**	**204454**	**204455**	**204456**	**204457**
Specification							
Power supply		1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	V	230	230	230	230	230	230
Voltage range	V	230	230	230	230	230	230
Frequency	Hz	50/60	50/60	50/60	50/60	50/60	50/60
Rated current	A	3,3	4,3	6,5	8,7	10,9	13
Connected load	W	750	1000	1500	2000	2500	3000
Connected load	kW	0,75	1	1,5	2	2,5	3
Phases		1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Fuse protection	A	10	10	10	16	16	16
Setting range	°C	5-35	5-35	5-35	5-35	5-35	5-35
IP rating		IP24	IP24	IP24	IP24	IP24	IP24
Protection class		I	I	I	I	I	I
Height	mm	546	546	546	546	546	546
Width	mm	426	426	582	738	894	1050
Depth	mm	305	305	305	305	305	305
Weight	kg	5.00	5.00	6.50	8.70	9.00	10.30
Colour		alpine white	alpine white	alpine white	alpine white	alpine white	alpine white

This product is only suitable for well insulated rooms or for occasional use.
Depth and height including feet with castors

Application areas

Heating output

	W	2000
 **CK 20 Premium**		

	W	2000
 **CK 20 Trend LCD**		

Wall installation
CK Premium 546
CK Trend LCD 547

CK Premium



CK 20 Premium

Benefits
- Elegant design with aluminium front
- Electronic controller with illuminated LCD screen
- Silent mode with a quiet heating stage and powerful rapid heat-up stage
- Weekly timer with 3 time programs, self-learning function and open window detection
- With short-time timer
- Safety through overheating protection
- Omnipolar operating selector

Application • This high quality rapid heater is suitable as a standalone heater or as a booster heater, particularly for rooms that are not heated constantly. • The wall mounted appliance heats the indoor air quickly and evenly. • The design has won the Red Dot Design Award; the appliance suits any setting.

Convenience features • The premium rapid heater with electronic closed-loop control is equipped with a large, easy-to-read display. The required room temperature can be easily adjusted at the top-mounted programming unit. • In addition to the programmable weekly timer, there are two preset and one individually programmable time programs available. • In addition to the comfort temperature, the setback temperature can also be programmed. In timer mode, the comfort temperature is achieved at precisely the right time thanks to the adaptive control with learning function. • Quiet operation in Silent Mode which features a switchable heating stage and reduced fan speed. • The elegant appliance is equipped with an aluminium front and has an integral frost protection setting.

Efficiency • To prevent unnecessary energy losses, users can activate a function that detects open windows.

Installation • Straightforward, stable wall mounting by just one person because the wall mounting bracket is fitted separately from the appliance and can be adjusted afterwards. All that then remains is to hook the maintenance-free appliance into place.

Safety • Integral childproofing as the programming unit can be locked. • The rapid heater has an integral safety temperature limiter.

reddot award 2018
winner

		CK 20 Premium
Part number		**237835**
Specification		
Power supply		1/N/PE ~ 230 V
Rated voltage	V	230
Voltage range	V	220-240
Frequency	Hz	50
Rated current	A	8,7
Connected load	W	2000
Connected load	kW	2
Phases		1/N/PE
Fuse protection	A	16
Sound pressure level	dB(A)	37/48
Setting range	°C	5-30
IP rating		IP24
Protection class		I
Height	mm	470
Width	mm	345
Depth	mm	126
Weight	kg	5.30
Colour		alpine white

Depth including wall mounting bracket

CK Trend LCD



CK 20 Trend LCD

Benefits
- Compact appliance in a plastic casing
- Electronic controller with illuminated LCD screen
- Weekly timer with 3 time programs, self-learning function and open window detection
- During a power failure, the clock is buffered for up to 10 hours
- Very high safety thanks to 3-stage overheating protection
- Fluff filter in the air intake
- Cable storage at the back for the connecting cable
- Very quiet operation

Application • This rapid heater is suitable as a standalone heater in the bathroom. The appliance can also be used as an efficient interim heater in spring/autumn and as a booster heater, for example in a guest room or recreational room. • Thanks to its compact design, the rapid heater does not take up much space. • The appliance is designed for wall mounting and heats the indoor air quickly and evenly.

Convenience features • The rapid heater with electronic closed-loop control is equipped with a large, easy-to-read display. • The required room temperature can be easily adjusted at the top-mounted programming unit. • In addition to the programmable weekly timer, there are two preset and one individually programmable time programs available. • In addition to the comfort temperature, the setback temperature is also programmable. The comfort temperature is reached at exactly the right time in timer mode. Adaptive control with a learning function is integrated for this purpose. • If required, users are able to activate a function which detects when windows are open; this avoids unnecessary energy loss. • The rapid heater has an integral fluff filter. • The casing is made from hard-wearing plastic.

Efficiency • The high quality self-limiting ceramic heating element keeps the temperature constant to save energy.

Installation • Stable wall mounting is possible with one person only: the wall mounting bracket is fitted to the wall separately from the appliance and can be readjusted later. The appliance is then simply hooked into place. • The power cable is fitted with a right angle plug as standard (not for GB). Any excess cable can be housed in the cable storage compartment on the back panel.

Safety • Integral childproofing as the programming unit can be locked. • The 3-stage safety concept includes the self-limiting ceramic heating element, the safety temperature limiter and the built-in fuse.

		CK 20 Trend LCD
Part number		**236653**
Specification		
Power supply		1/N ~ 230 V
Rated voltage	V	~230
Voltage range	V	220-240
Frequency	Hz	50/-
Rated current	A	8,7
Connected load	W	2000
Connected load	kW	2
Phases		1/N
Fuse protection	A	16
Sound pressure level	dB(A)	49
Setting range	°C	5-30
IP rating		IP24
Protection class		II
Height	mm	400
Width	mm	275
Depth	mm	131
Weight	kg	2.50
Colour		alpine white

Depth including wall mounting bracket

Application areas


Heating output

	W	1200
 IW 120		

Infrared wall mounted radiant heater

Indoor
IW 550

IW



IW 120

Benefits
- Full metal casing
- Pull-cord activation
- Display shows the switching position in the indicator window

Application • This radiant heater is suitable for heating small rooms. The appliance gives off noticeable warmth immediately without any air movement. It is particularly suitable for bathrooms, recreational rooms or wind-sheltered, covered verandas.

Convenience features • The pivoting highly polished reflector is equipped with quartz heater rods. It is operated by a pull cord.

Installation • Easy wall mounting with direct electrical connection.

		IW 120
Part number		**229339**
Specification		
Power supply		1/N/PE ~ 230 V
Rated voltage	V	230
Frequency	Hz	50/60
Rated current	A	5.2
Rated output	kW	1.2
Connected load	W	1200
Number of heating stages		3
IP rating		IPX4
Protection class		I to EN 60335
Height	mm	145
Width	mm	535
Depth	mm	85
Weight	kg	1.55
Colour		silver
Installation type		Indoor/outdoor installation

Hand dryer

Hand dryer, high speed 553

Hand dryer

Hand dryer, high speed

High speed

ULTRONIC Premium 554

ULTRONIC Plus 555

High speed

ULTRONIC Premium



ULTRONIC Premium

Benefits

- Extremely short hand drying time of less than 12 seconds
- Robust, impact-resistant casing made of brushed stainless steel
- Integral indoor air purifier with UV-C lamp and ion generator
- With HEPA filter for hygienic hand drying with clean air
- Add-on heating element for pleasant hand drying
- Silent mode with reduced fan speed
- Hygienic and energy efficient through IR proximity sensors
- Maintenance-free thanks to brushless motor
- Very long service life
- Brushed stainless steel casing (Product: 205633)

Application • This high quality, electric high speed hand dryer is distinguished by its particularly short drying time. The appliance dries hands by removing the moisture with a concentrated jet of air. • The hand dryer is ideally suited to the special demands made on washroom facilities in restaurants, commerce and public buildings.

Convenience features • Operation is contactless due to the integral infrared proximity sensors. • Additional hygiene is provided by the HEPA filter and the air purification function by UV-C light and ion generator. The appliance reliably removes dust, pollen, bacteria and viruses from the indoor air. The air purification function works cyclically, running for 1 h and being off for 1 h. • A switchable heating element increases comfort when drying hands. • Optimally suited to sanitary facilities in schools and offices thanks to silent mode. The particularly low connected load enables energy efficient and environmentally responsible operation. • The robust and impact-resistant casing is made from brushed stainless steel.

Installation • Easy installation due to separate mounting plate.

		ULTRONIC Premium
Part number		**205633**
Specification		
Power supply		1/N/PE ~ 220-240 V
Rated voltage	V	230
Frequency	Hz	50/60
Rated current	A	3,1
Rated output	W	720
Operating noise	dB(A)	76
Air speed	m/s	96
Air flow rate	m³/h	84
Drying time	s	12
IP rating		IP23
Protection class		I
Height	mm	309
Width	mm	272
Depth	mm	132
Weight	kg	4.00
Casing material		Stainless steel
Colour		Stainless steel

High speed

ULTRONIC Plus



ULTRONIC Plus

Benefits

- Extremely short hand drying time of less than 12 seconds
- Robust, impact-resistant plastic casing
- Integral indoor air purifier with UV-C lamp and ion generator
- With HEPA filter for hygienic hand drying with clean air
- Add-on heating element for pleasant hand drying
- Silent mode with reduced fan speed
- Hygienic and energy efficient through IR proximity sensors
- Maintenance-free thanks to brushless motor
- Very long service life
- Casing made of impact-resistant plastic (Product: 205632)

Application • This high quality, electric high speed hand dryer is distinguished by its particularly short drying time. The appliance dries hands by removing the moisture with a concentrated jet of air. • The hand dryer is ideally suited to the special demands made on washroom facilities in restaurants, commerce and public buildings.

Convenience features • Operation is contactless due to the integral infrared proximity sensors. • Additional hygiene is provided by the HEPA filter and the air purification function by UV-C light and ion generator. The appliance reliably removes dust, pollen, bacteria and viruses from the indoor air. The air purification function works cyclically, running for 1 h and being off for 1 h.• A switchable heating element increases your comfort during hand drying. • Optimally suited to sanitary facilities in schools and offices thanks to silent mode. The particularly low connected load enables energy efficient and environmentally responsible operation. • The robust and impact-resistant casing is made from plastic.

Installation • Easy installation due to separate mounting plate.

		ULTRONIC Plus
Part number		**205632**

Specification		
Power supply		1/N/PE ~ 220-240 V
Rated voltage	V	230
Frequency	Hz	50/60
Rated current	A	3,1
Rated output	W	720
Operating noise	dB(A)	76
Air speed	m/s	96
Air flow rate	m³/h	84
Drying time	s	12
IP rating		IP23
Protection class		I
Height	mm	309
Width	mm	272
Depth	mm	132
Weight	kg	2.80
Casing material		Plastic
Colour		signal white, RAL 9003


High speed

Engineering 559

Engineering services
Accessories 560

Engineering services

Engineering service: ventilation equipment



Planning of ventilation technology, 3D

Benefits

- System engineering and sizing of a ventilation unit and an air distribution system
- Preparation of verification of the ventilation concept as production information
- The service can be ordered online

Description • System engineering and sizing of a ventilation unit and an air distribution system is handled as part of this service. Standard delivery includes verification of the ventilation concept as production information. The service comprises the stated plans for a ventilation unit or an apartment. • Identical apartments, such as in a multi residency building, are included in the scope of performance of an engineering service.

Requirements • The engineering service can be ordered quickly, easily and digitally via the Toolbox. Alternatively, the necessary order form and the associated technical questionnaire can be obtained from the trade partner internet portal or from the contact person. • In addition to the binding order confirmation, dimensioned floor plans, views and cut-away drawings are required for further processing.

Legal information • The service cannot be refunded or offset.

		Planning of ventilation technology, 3D
Part number		**240592**

Experience service from its personal side

STIEBEL ELTRON is represented in over 120 countries worldwide
We have a policy of continuous improvement; we therefore reserve the right to alter specifications and prices without notice. The information contained in this brochure is correct at the time of going to press, but you are advised to consult your dealer or the company before purchasing. Although every care has been taken in the reproduction of product finishes in this brochure, the photographs should only be taken as a guide.

Australia
STIEBEL ELTRON Australia Pty. Ltd.
294 Salmon Street | Port Melbourne VIC 3207
info@stiebel-eltron.com.au
www.stiebel-eltron.com.au

Austria
STIEBEL ELTRON Gesellschaft mbH
Margaritenstraße 4A | 4063 Hörsching
Tel. 07221 746000
office@stiebel-eltron.at | www.stiebel-eltron.at

Belgium
STIEBEL ELTRON bv/sprl
't Hofveld 6 – D1 | 1702 Groot-Bijgaarden
Tel. 02 4232222 | Fax 02 4232212
info@stiebel-eltron.be | www.stiebel-eltron.be

China
STIEBEL ELTRON Electric Appliance Co. Ltd
C3 XEDA International Industry City
Xiqing District, Tianjin 300085
Tel. 022 83962077 | Fax 022 83962075
info@stiebel-eltron.cn

Czech Republic
STIEBEL ELTRON spol. s r.o.
Dopraváků 749/3 | 184 00 Praha 8
Tel. 02 51116111 | Fax 02 35512122
info@stiebel-eltron.cz | www.stiebel-eltron.cz

France
STIEBEL ELTRON S.A.S.
7-9 rue des Selliers | B.P. 85107 | 57073 Metz-Cédex 3
Tel. 0387 743888 | Fax 0387 749610
info@stiebel-eltron.fr | www.stiebel-eltron.fr

Hungary
STIEBEL ELTRON Kft.
Gyár u. 2 | 2040 Budaörs
Tel. 01 2506055 | Fax 01 3688097
info@stiebel-eltron.hu | www.stiebel-eltron.hu

India
STIEBEL ELTRON India pvt Ltd
710, Tower 2, World Trade Centre
Kharadi Pune | 411014 Maharashtra
Tel. 020 67480909
info@stiebel-eltron.in | www.stiebel-eltron.in

Italien
STIEBEL ELTRON ITALIA S.R.L.
Via Triumplina 92 | 25123 Brescia (BS)
www.stiebel-eltron.it

Japan
NIHON STIEBEL Co. Ltd.
Kowa Kawasaki Nishiguchi Building 8F
66-2 Horikawa-Cho Saiwai-Ku | 212-0013 Kawasaki
Tel. 044 5403200 | Fax 044 5403210
stiebel-pr@stiebel-eltron.co.jp
www.stiebel-eltron.co.jp

Netherlands
STIEBEL ELTRON Nederland B.V.
Daviottenweg 36 | 5222 BH's Hertogenbosch
Tel. 073 6230000 | Fax 073 6231141
info@stiebel-eltron.nl | www.stiebel-eltron.nl

New Zealand
STIEBEL ELTRON NZ Limited
61 Barrys Point Road | Takapuna Auckland 0622
Tel. 09486 2221
info@stiebel-eltron.co.nz | www.stiebel-eltron.co.nz

Poland
STIEBEL ELTRON Polska Sp. zo. o.o.
ul. Działkowa 2 | 02-234 Warszawa
Tel. 022 6092030 | Fax 022 6092029
biuro@stiebel-eltron.pl | www.stiebel-eltron.pl

Slovakia
STIEBEL ELTRON Slovakia, s.r.o.
Hlavná 1 | 05801 Poprad
Tel. 052 7127151 | Fax 052 7127148
info@stiebel-eltron.sk | www.stiebel-eltron.sk

South Africa
STIEBEL ELTRON Southern Africa (PYT) Ltd
30 Archimedes Rd. | Wendywood Johannesburd | 2090
Tel. 010001 8547 | Fax 087255 9288
info@stiebel-eltron.co.za | www.stiebel-eltron.co.za

Switzerland
STIEBEL ELTRON AG
Gass 8 I 5242 Lupfig
Tel. 056 4640500
info@stiebel-eltron.ch | www.stiebel-eltron.ch

Thailand
STIEBEL ELTRON Asia Ltd.
469 Moo 2, Tambol Klong-Jik
Ampur Bangpa-In | Ayutthaya 13160
Tel. 035 220088 | Fax 035 221188
info@stiebeleltronasia.com
www.stiebeleltronasia.com

United Kingdom
STIEBEL ELTRON UK Ltd.
Unit 12 Stadium Court | Stadium Road
Bromborough CH62 3RP
Tel. 0151 3462300 | Fax 0151 3342913
info@stiebel-eltron.co.uk | www.stiebel-eltron.co.uk

United States of America
STIEBEL ELTRON Inc.
17 West Street | West Hatfield, MA, 01088
Tel. 0413 2473380 | Fax 0413 2473369
info@stiebel-eltron-usa.com
www.stiebel-eltron-usa.com

Vietnam
STIEBEL ELTRON VIETNAM CO. LTD.
No. 0.03 Tower B1 | Complex Apartment Building
Lot M2 (Sarimi) | 72 Nguyen Co Thach
An Loi Dong Ward, Thu Duc City, Ho Chi Minh City
Tel. 084 1800 888822
info@stiebel-eltron.vn | www.stiebel-eltron.vn

Legal notice
In spite of the care taken in the production of this brochure, no guarantee can be given regarding the accuracy of its contents. Information about the equipment and characteristics are non-binding. The equipment features described in this brochure are not stated as agreed properties of our products. Constant product development can result in individual equipment characteristics being modified or deleted. Our experts will be happy to advise you about currently applicable equipment characteristics. Pictorial illustrations in this brochure only represent application examples. The illustrations also contain installation components, accessories and special equipment, which are not part of the standard delivery. Reproduction, even in extracts, only with the publisher's agreement.

Comfort through Technology

STIEBEL ELTRON International GmbH | Dr.-Stiebel-Straße 33 | 37603 Holzminden | Germany
Tel. +49 5531 7020 | info@stiebel-eltron.com | www.stiebel-eltron.com

Issue 11_25